

4000 Series CMOS Logic

1984




Solid State Scientific

TABLE OF CONTENTS

| | PAGE |
|--|------|
| Numerical Index | 3 |
| Functional Index | 7 |
| Family Specifications | 11 |
| 4000 Series Data | 19 |
| JEDEC Standard Specifications . . | 273 |
| CMOS Fundamentals | 277 |
| Design Information | 281 |
| Typical Package Outlines | 291 |
| Ordering Information | 299 |
| 4000 Series High Reliability | 301 |

Numerical Index




NUMERICAL DEVICE INDEX

| SSS Standard Part Number | Description | Page | SSS Standard Part Number | Description | Page |
|-----------------------------|---|------|-----------------------------|--|------|
| SCL 4000B | Dual 3-input NOR gate and inverter | 20 | SCL 4047B | Monostable/astable multivibrator | 124 |
| SCL 4001B | Quad 2-input NOR gate | 22 | SCL 4049UB | Hex inverter buffer/ level shifter | 128 |
| SCL 4001UB | Quad 2-input NOR gate (unbuffered) | 24 | SCL 4050B | Hex non-inverting buffer/ level shifter | 128 |
| SCL 4002B | Dual 4-input NOR gate | 22 | SCL 4051B | 8-channel analog multiplexer/ demultiplexer | 131 |
| SCL 4006B | 18-stage shift register | 27 | SCL 4052B | Differential 4-channel analog multiplexer/demultiplexer | 131 |
| SCL 4007UB | Dual complementary pair and inverter | 29 | SCL 4053B | Triple 2-channel analog multi- plexer/demultiplexer | 131 |
| SCL 4008B | Four-bit full adder | 32 | SCL 4060B | 14-stage binary counter and oscillator | 136 |
| SCL 4009UB | Hex inverting buffer/ level shifter | 36 | SCL 4066B | Quad analog switch | 140 |
| SCL 4010B | Hex non-inverter buffer/ level shifter | 36 | SCL 4068B | 8-input NAND gate | 39 |
| SCL 4011B | Quad 2-input NAND gate | 39 | SCL 4069UB | Hex inverter | 145 |
| SCL 4011UB | Quad 2-input NAND gate (unbuffered) | 41 | SCL 4070B | Quad 2-input exclusive- OR gate | 147 |
| SCL 4012B | Dual 4-input NAND gate | 39 | SCL 4071B | Quad 2-input OR gate | 149 |
| SCL 4013B | Dual D-type flip-flop | 44 | SCL 4072B | Dual 4-input OR gate | 149 |
| SCL 4014B | 8-stage parallel-input/serial- output shift register | 46 | SCL 4073B | Triple 3-input AND gate | 156 |
| SCL 4015B | Dual 4-stage serial-input/ parallel-output shift register | 48 | SCL 4075B | Triple 3-input OR gate | 149 |
| SCL 4016B | Quad analog switch | 50 | SCL 4076B | 4-bit D-type register w/3-state outputs | 151 |
| SCL 4017B | Decade counter w/10 outputs | 56 | SCL 4077B | Quad 2-input exclusive NOR gate | 154 |
| SCL 4018B | Presetable divide-by-N counter | 61 | SCL 4078B | 8-input NOR gate | 22 |
| SCL 4019B | Quad AND-OR select gate | 64 | SCL 4081B | Quad 2-input AND gate | 156 |
| SCL 4020B | 14-stage binary counter | 66 | SCL 4082B | Dual 4-input AND gate | 156 |
| SCL 4021B | 8-stage parallel-input/serial output shift register | 69 | SCL 4085B | Complex gate AND-OR inverter | 158 |
| SCL 4022B | Octal counter w/8 decoded outputs | 72 | SCL 4086B | Complex gate AND-OR inverter | 160 |
| SCL 4023B | Triple 3-input NAND gate | 39 | SCL 4093B | Quad 2-input NAND Schmitt trigger | 162 |
| SCL 4024B | 7-stage binary counter | 77 | SCL 4094B | 8-stage shift and store register | 165 |
| SCL 4025B | Triple 3-input NOR gate | 22 | SCL 4099B | 8-bit addressable latch | 168 |
| SCL 4026AB | Decade counter w/7 segment outputs | 80 | SCL 4160B | BCD decade counter w/ asynchronous clear | 170 |
| SCL 4027B | Dual JK-type flip-flop | 85 | SCL 4161B | 4-stage binary counter w/ asynchronous clear | 170 |
| SCL 4028B | BCD-to-decimal decoder | 87 | SCL 4162B | BCD decade counter w/ synchronous clear | 170 |
| SCL 4029B | Presetable up/down binary decade counter | 90 | SCL 4163B | 4-stage binary counter w/ synchronous clear | 170 |
| SCL 4030B | Quad 2-input exclusive OR gate | 94 | SCL 4174B | Hex D flip-flop | 175 |
| SCL 4033AB | Decade counter w/7 segment outputs | 80 | SCL 4192B | 4-bit BCD up/down counter | 178 |
| SCL 4034B | 8-stage universal bus register | 96 | SCL 4193B | 4-bit binary up/down counter | 178 |
| SCL 4035B | 4-stage parallel-input/parallel- output shift register | 101 | SCL 4402B | Dual 4-input expandable NOR gate | 183 |
| SCL 4040B | 12-stage binary counter | 104 | SCL 4404B | 8-stage binary counter | 185 |
| SCL 4041UB | Quad true/complement buffer | 107 | SCL 4412B | Dual 4-input expandable NAND gate | 183 |
| SCL 4042B | Quad clocked latch | 111 | SCL 4416B | Quad analog switch | 187 |
| SCL 4043B | Quad NOR R/S latch w/3-state outputs | 113 | SCL 4426AB | Decade counter w/7-segment driver outputs | 191 |
| SCL 4044B | Quad NAND R/S latch w/3-state outputs | 113 | SCL 4428B | Binary-to-octal decoder | 196 |
| SCL 4046B | Phase-locked loop | 116 | SCL 4433AB | Decade counter w/7-segment driver outputs | 191 |
| | | | SCL 4441UB | Quad buffer/driver | 199 |

NUMERICAL DEVICE INDEX

| SSS Standard Part Number | Description | Page |
|-----------------------------|--|------|
| SCL 4445B | 21-stage frequency divider and oscillator | 201 |
| SCL 4446B | Phase-locked loop | 116 |
| SCL 4449UB | Hex inverter | 204 |
| SCL 4502B | Hex strobed inverting buffer w/3-stage outputs | 206 |
| SCL 4504B | Hex non-inverting level shifter | 208 |
| SCL 4508B | Dual 4-bit latch w/3-state outputs | 210 |
| SCL 4510B | BCD decade programmable up/down counter | 213 |
| SCL 4511B | BCD-to-7 segment latch/ decoder | 217 |
| SCL 4512B | 8-channel data selector | 220 |
| SCL 4514B | 4-to-16 line decoder w/ latch (active high outputs) | 224 |
| SCL 4515B | 4-to-16 line decoder w/ latch (active low outputs) | 224 |
| SCL 4516B | 4-stage binary programmable up/down counter | 227 |
| SCL 4517B | Dual 64-stage shift register | 231 |
| SCL 4518B | Dual BCD decade up counter | 234 |
| SCL 4520B | Dual 4-stage binary up counter | 234 |
| SCL 4522B | BCD decade programmable down counter | 237 |
| SCL 4526B | 4-stage binary programmable down counter | 237 |
| SCL 4527B | BCD rate multiplier | 241 |
| SCL 4528B | Dual monostable multivibrator | 245 |
| SCL 4531B | 12-bit parity tree | 249 |
| SCL 4532B | 8-bit priority encoder | 251 |
| SCL 4543B | BCD-to-7-segment latch | 255 |
| SCL 4555B | Dual 2-to-4 line decoder (active high outputs) | 258 |
| SCL 4556B | Dual 2-to-4 line decoder (active low outputs) | 258 |
| SCL 4581B | 4-bit arithmetic logic unit | 261 |
| SCL 4582B | Look-ahead carry block | 265 |
| SCL 4584B | Hex Schmitt trigger | 267 |
| SCL 4585B | 4-bit magnitude comparator | 269 |

Functional Index



FUNCTIONAL INDEX


| Function | Description | Standard Part Number | Replaces Industry Number | DIP Pkg. | Page |
|---------------------|-------------------|----------------------|--------------------------|----------|------|
| Gates and Inverters | NAND | SCL4011B | 4011 | 14 | 39 |
| | | SCL4011UB | 4011U | 14 | 41 |
| | | SCL4012B | 4012 | 14 | 39 |
| | | SCL4023B | 4023 | 14 | 39 |
| | | SCL4068B | 4068 | 14 | 39 |
| | AND | SCL4073B | 4073 | 14 | 156 |
| | | SCL4081B | 4081 | 14 | 156 |
| | | SCL4082B | 4082 | 14 | 156 |
| | NOR | SCL4001B | 4001 | 14 | 22 |
| | | SCL4001UB | 4001U | 14 | 24 |
| | | SCL4002B | 4002 | 14 | 22 |
| | | SCL4025B | 4025 | 14 | 22 |
| | | SCL4078B | 4078 | 14 | 22 |
| | OR | SCL4071B | 4071 | 14 | 149 |
| | | SCL4072B | 4072 | 14 | 149 |
| | | SCL4075B | 4075 | 14 | 149 |
| | COMPLEX | SCL4000B | 4000 | 14 | 20 |
| | | SCL4007UB | 4007U | 14 | 29 |
| | | SCL4030B | 4030 | 14 | 94 |
| | | SCL4070B | 4070 | 14 | 147 |
| | | SCL4077B | 4077 | 14 | 154 |
| | | SCL4085B | 4085 | 14 | 158 |
| | | SCL4086B | 4086 | 14 | 160 |
| | Inverters | SCL4019B | 4019 | 16 | 64 |
| | | SCL4069UB | 4069U | 14 | 145 |
| | Expandable Gates | SCL4449UB | 4449U * | 16 | 204 |
| | | SCL4402B | 4402 * | 16 | 183 |
| | | SCL4412B | 4412 * | 16 | 183 |
| | Level Shifting | SCL4009UB | 4009U | 16 | 36 |
| | | SCL4010B | 4010 | 16 | 36 |
| | | SCL4049UB | 4049U | 16 | 128 |
| | | SCL4050B | 4050 | 16 | 128 |
| | | SCL4504B | 4504 | 16 | 208 |
| Buffers | High Current | SCL4041UB | 4041U | 14 | 107 |
| | | SCL4441UB | 4441U * | 14 | 199 |
| | Tri-State | SCL4502B | 4502 | 16 | 206 |
| Encoder | 8 Bit Priority | SCL4532B | 4532 | 16 | 251 |
| Decoders | Logic Functions | SCL4028B | 4028 | 16 | 87 |
| | | SCL4428B | 4428 * | 14 | 196 |
| | | SCL4514B | 4514 | 24 | 224 |
| | | SCL4515B | 4515 | 24 | 224 |
| | | SCL4555B | 4555 | 16 | 258 |
| | | SCL4556B | 4556 | 16 | 258 |
| | Display Functions | SCL4026AB | 4026 | 16 | 80 |
| | | SCL4426AB | 4426 * | 16 | 191 |
| | | SCL4033AB | 4033 | 16 | 80 |
| | | SCL4433AB | 4433 * | 16 | 191 |
| | | SCL4511B | 4511 | 16 | 217 |
| | | SCL4543B | 4056 | 16 | 255 |

FUNCTIONAL INDEX

| Function | Description | Standard Part Number | Replaces Industry Number | DIP Pkg. | Page |
|---------------------------|--------------------------------------|----------------------|--------------------------|----------|------|
| Counters | Binary | SCL4024B | 4024 | 14 | 77 |
| | | SCL4404B | 4404 * | 14 | 185 |
| | | SCL4040B | 4040 | 16 | 104 |
| | | SCL4020B | 4020 | 16 | 66 |
| | | SCL4060B | 4060 | 16 | 136 |
| | | SCL4161B | 4161 | 16 | 170 |
| | | SCL4163B | 4163 | 16 | 170 |
| | | SCL4193B | 4193 | 16 | 178 |
| | | SCL4029B | 4029 | 16 | 90 |
| | | SCL4516B | 4516 | 16 | 227 |
| | | SCL4526B | 4526 | 16 | 237 |
| | | SCL4520B | 4520 | 16 | 234 |
| | Decade | SCL4192B | 4192 | 16 | 178 |
| | | SCL4510B | 4510 | 16 | 213 |
| | | SCL4160B | 4160 | 16 | 170 |
| | | SCL4162B | 4162 | 16 | 170 |
| | | SCL4522B | 4522 | 16 | 237 |
| | SCL4518B | 4518 | 16 | 234 | |
| | Decoded Outputs | SCL4017B | 4017 | 16 | 56 |
| | | SCL4022B | 4022 | 16 | 72 |
| | Johnson | SCL4018B | 4018 | 16 | 61 |
| Dividers/ Multipliers | 21-Stg Divider | SCL4445B | 4045 | 16 | 201 |
| | Rate Multiplier | SCL4527B | 4527 | 16 | 241 |
| | Phase-Locked Loop | SCL4046B | 4046 | 16 | 116 |
| | | SCL4446B | 4446 * | 16 | 116 |
| | Multivibrators | SCL4528B | 4528 | 16 | 245 |
| | | SCL4047B | 4047 | 16 | 124 |
| Arithmetic Logic | 4-Bit | SCL4582B | 4582 | 16 | 265 |
| | | SCL4585B | 4585 | 16 | 269 |
| | | SCL4008B | 4008 | 16 | 32 |
| | 12-Bit | SCL4531B | 4531 | 16 | 249 |
| Flip-Flops | 4-Bit A.L.U. | SCL4581B | 4581 | 24 | 261 |
| | Dual D Type | SCL4013B | 4013 | 14 | 44 |
| | Dual JK Type | SCL4027B | 4027 | 16 | 85 |
| | 4-Bit D Type | SCL4076B | 4076 | 16 | 151 |
| | Hex D Type | SCL4174B | 4174 | 16 | 175 |
| Latches | R-S Type | SCL4043B | 4043 | 16 | 113 |
| | | SCL4044B | 4044 | 16 | 113 |
| | Clocked | SCL4042B | 4042 | 16 | 111 |
| | | SCL4508B | 4508 | 24 | 210 |
| | Addressable | SCL4099B | 4099 | 16 | 168 |
| Schmitt Triggers | Quad | SCL4093B | 4093 | 14 | 162 |
| | Hex | SCL4584B | 4584 | 14 | 267 |
| Shift Registers | Ser In/Ser Out | SCL4006B | 4006 | 14 | 27 |
| | Ser In/Par Out | SCL4015B | 4015 | 16 | 48 |
| | Par In/Ser Out | SCL4014B | 4014 | 16 | 46 |
| | | SCL4021B | 4021 | 16 | 69 |
| | Par In/Par Out | SCL4035B | 4035 | 16 | 101 |
| | | SCL4034B | 4034 | 24 | 96 |
| | Bus Registers | SCL4094B | 4094 | 16 | 165 |
| | SCL4517B | 4517 | 16 | 231 | |
| Multiplexers and Switches | Digital Mux | SCL4512B | 4512 | 16 | 220 |
| | Analog Multiplexers & Demultiplexers | SCL4051B | 4051 | 16 | 131 |
| | | SCL4052B | 4052 | 16 | 131 |
| | | SCL4053B | 4053 | 16 | 131 |
| | Analog Switches | SCL4016B | 4016 | 14 | 50 |
| | | SCL4066B | 4066 | 14 | 140 |
| SCL4416B | | 4416 * | 14 | 187 | |

* Part Number is a sole source item of Solid State Scientific.

Family Specifications



THE 4000 SERIES FAMILY

INTRODUCTION

Solid State Scientific CMOS devices comprise a family of medium-speed integrated circuits with a superior combination of high noise immunity, wide operating voltage range, low power dissipation, and high fan-out. These characteristics greatly minimize power supply costs and simplify system design and layout.

The great majority of the devices in the 4000 Series exceed the JEDEC Standard Specifications for "B" Series CMOS Devices. For this reason, Solid State Scientific guarantees that all devices designated 4xxxB or 4xxxUB¹ will meet the electrical specifications given in the tables in this section. These standards are tighter than the JEDEC Specifications in several key areas, notably gate leakage currents (I_{DD}), output voltage (V_{OH} , V_{OL}) and, in several cases, output drive current (I_{OH} , I_{OL}). In addition, Solid State Scientific does not degrade any parameter for any commercial-temperature-range part type. The few device types which fail to meet the 4000B Series Family Specifications for any reason are designated by the suffix AB. These devices, however, are guaranteed to meet all Absolute Maximum Ratings and Recommended Operating Conditions of the 4000B Series, as well as most of the electrical characteristics. Therefore, these few part types are fully compatible with 4000B devices in virtually all applications.

All 4000 Series CMOS devices are available in commercial temperature range (-40°C to $+85^{\circ}\text{C}$) versions, and a variety of package configurations. Available packages include Frit-seal ceramic or Cerdip dual-in-line packages (C suffix — 14- and 16-lead types), welded-seal or side-brazed ceramic dual-in-line packages (D suffix — 14-, 16-, and 24-lead types), ceramic flat packs (K suffix — 14- and 16-lead types), leadless chip carriers (L suffix — 20 lead JEDEC), and bare chip form (H suffix) for those users manufacturing hybrid microcircuits. Commercial tem-

perature range devices are available in the Epoxy or plastic dual-in-line package (E suffix — 14-, 16- and 24-lead types). Since electrical parameters are never degraded for devices in this package, any mix of packages may be used in a system with confidence that they will be fully compatible throughout the entire range of valid operating conditions.

THE 4000B SERIES

Solid State Scientific anticipated the JEDEC Standard Specifications for "B" Series CMOS Devices by several years in several important areas. All part types have been consistently rated at 18 Vdc maximum operating voltage. This upgrading did not entail a process alteration; performance specifications for the higher voltages were simply added to the test programs for each device.

In addition, the decision of the JEDEC Committee to consider devices with buffered outputs as the standard part types in the "B" Series supports the position taken by Solid State Scientific in 1970. Since buffered-output gates exhibit higher noise immunity, standardized output drive independent of type and input pattern, and decreased ac sensitivity to output loading, they offer superior performance in digital logic applications. Gate functions in the 4000 Series have always been buffered, anticipating the decision of the JEDEC Committee by a full six years.

The following Family Specifications apply to all 4xxxB and 4xxxUB part types, unless otherwise specified on individual data sheets.

¹As defined in JEDEC Standard Specification

4000B SERIES FAMILY SPECIFICATIONS

ABSOLUTE MAXIMUM RATINGS¹

| | | | |
|-------------------------------------|----------|------------------------|------|
| DC Supply Voltage | V_{DD} | -0.5 to +18 | Vdc |
| Input Voltage | V_{IN} | -0.5 to $V_{DD} + 0.5$ | Vdc |
| DC Input Current (any one input) | I_{IN} | ± 10 | mAdc |
| Power Dissipation | P_T | 300 | mW |
| Storage Temperature Range | T_S | -65 to +150 | °C |

RECOMMENDED OPERATING CONDITIONS¹

| | | | |
|--------------------------------|----------|-------------|-----|
| DC Supply Voltage | V_{DD} | 3 to 15 | Vdc |
| Operating Temperature Range | T_A | | |
| C, D, F packages, chips | | -55 to +125 | °C |
| E package | | -40 to +85 | °C |

¹Voltage referenced to V_{SS}

Parametric limits are guaranteed for $V_{DD} = 5, 10,$ and 15 Vdc. Where low power is required, the lowest supply voltage, consistent with required speed, should be used. For larger noise immunity and higher speed, higher supply voltages should be specified. The lower limit of supply regulation is 3 Vdc or as determined by required system speed, noise immunity, or interface to other logic. The recommended upper limit is 15 Vdc or as determined by power dissipation restrictions or interface to other logic.

Unused inputs must be connected to V_{DD} , V_{SS} , or another input.

Care should be used in handling CMOS devices; static charges may damage the device.

ELECTRICAL SPECIFICATIONS

Parametric limits listed here are guaranteed for the entire 4000B Series Family unless otherwise specified on the individual data sheets.

STATIC CHARACTERISTICS ($V_{SS} = 0V$)

| PARAMETER | V_{DD} (Vdc) | CONDITIONS | T_{LOW}^1 | | +25°C | | | T_{HIGH}^1 | | Units |
|--------------------------------------|-------------------|--|-------------|------|-------|--------|------|--------------|------|-----------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT Gates | I_{DD} | $V_{IN} = V_{SS}$ or V_{DD} | — | 0.05 | — | 0.0005 | 0.05 | — | 1.5 | μ Adc |
| | | | — | 0.1 | — | 0.001 | 0.1 | — | 3.0 | |
| | | | — | 0.2 | — | 0.002 | 0.2 | — | 6.0 | |
| Buffers, Flip-Flops | | All valid input combinations | — | 1.0 | — | 0.005 | 1.0 | — | 30 | μ Adc |
| | | | — | 2.0 | — | 0.01 | 2.0 | — | 60 | |
| | | | — | 4.0 | — | 0.02 | 4.0 | — | 120 | |
| MSI | | | — | 5 | — | 0.05 | 5 | — | 150 | μ Adc |
| | | | — | 10 | — | 0.1 | 10 | — | 300 | |
| | | | — | 20 | — | 0.2 | 20 | — | 600 | |
| HIGH-LEVEL OUTPUT VOLTAGE | V_{OH} | $V_{IN} = V_{SS}$ or V_{DD} $ I_O \leq 1\mu A$ | 4.99 | — | 4.99 | 5 | — | 4.95 | — | Vdc |
| | | | 9.99 | — | 9.99 | 10 | — | 9.95 | — | |
| | | | 14.99 | — | 14.99 | 15 | — | 14.95 | — | |
| LOW-LEVEL OUTPUT VOLTAGE | V_{OL} | $V_{IN} = V_{SS}$ or V_{DD} $ I_O \leq 1\mu A$ | — | 0.01 | — | 0 | 0.01 | — | 0.05 | Vdc |
| | | | — | 0.01 | — | 0 | 0.01 | — | 0.05 | |
| | | | — | 0.01 | — | 0 | 0.01 | — | 0.05 | |
| MINIMUM INPUT HIGH VOLTAGE | V_{IH} | $V_O = 0.5V$ or $4.5V$ $V_O = 1.0V$ or $9.0V$ $V_O = 1.5V$ or $13.5V$ $ I_O \leq 1\mu A$ | — | 3.5 | — | 2.75 | 3.5 | — | 3.5 | Vdc |
| | | | — | 7.0 | — | 5.5 | 7.0 | — | 7.0 | |
| | | | — | 11.0 | — | 8.25 | 11.0 | — | 11.0 | |

¹ T_{LOW} = -55°C for C, D, F, and H devices

= -40°C for E device

T_{HIGH} = +125°C for C, D, F, and H devices

= +85°C for E device

STATIC CHARACTERISTICS ($V_{SS} = 0V$) Continued

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ¹ | | +25°C | | | T _{HIGH} ¹ | | Units | |
|--|--------------------------|------------|---|-------|-------|-------|-------------------|--------------------------------|-------|-------|------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | | |
| MAXIMUM INPUT LOW VOLTAGE | V _{IL} | 5 | V _O =0.5V or 4.5V | 1.5 | — | 1.5 | 2.25 | — | 1.5 | — | Vdc |
| | | 10 | V _O =1.0V or 9.0V | 3.0 | — | 3.0 | 4.5 | — | 3.0 | — | |
| | | 15 | V _O =1.5V or 13.5V | 4.0 | — | 4.0 | 6.75 | — | 4.0 | — | |
| | | | <i>i</i> _O ≤1μA | | | | | | | | |
| OUTPUT HIGH (SOURCE) CURRENT B Series | I _{OH} | 5 | V _{OH} =4.6V | -0.64 | — | -0.51 | -1.25 | — | -0.36 | — | mAdc |
| | | 10 | V _{OH} =9.5V | -1.6 | — | -1.3 | -3.25 | — | -0.9 | — | |
| | | 15 | V _{OH} =13.5V | -4.2 | — | -3.4 | -10 | — | -2.4 | — | |
| | | | V _{IN} =V _{SS} or V _{DD} | | | | | | | | |
| OUTPUT LOW (SINK) CURRENT B Series | I _{OL} | 5 | V _{OL} =0.4V | 0.64 | — | 0.51 | 1.25 | — | 0.36 | — | mAdc |
| | | 10 | V _{OL} =0.5V | 1.6 | — | 1.3 | 3.25 | — | 0.9 | — | |
| | | 15 | V _{OL} =1.5V | 4.2 | — | 3.4 | 10 | — | 2.4 | — | |
| | | | V _{IN} =V _{SS} or V _{DD} | | | | | | | | |
| INPUT CURRENT | I _{IN} | 15 | V _{IN} =0 or 15V | — | ±0.1 | — | ±10 ⁻⁵ | ±0.1 | — | ±1.0 | μAdc |

- ¹ T_{LOW} = -55°C for C, D, F, and H devices
= -40°C for E device
 T_{HIGH} = +125°C for C, D, F, and H devices
= +85°C for E device

DYNAMIC CHARACTERISTICS ($T_A = 25^\circ C$)

| PARAMETER | | V_{DD} (Vdc) | Min. | Typ. | Max. | Units |
|-------------------|----------|-------------------|------|------|------|-------|
| INPUT CAPACITANCE | C_{IN} | — | — | 5 | 7.5 | pF |

Part types designated "UB" meet the above parametric specifications with the following exception, unless otherwise specified on the individual data sheets.

| PARAMETER | V_{DD} (Vdc) | CONDITIONS | T_{LOW}^1 | | +25°C | | | T_{HIGH}^1 | | Unit |
|----------------------------|-------------------|------------|-----------------------|------|-------|------|------|--------------|------|------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| MINIMUM INPUT HIGH VOLTAGE | V_{IH} | 5 | $V_O=0.5V$ or $4.5V$ | — | 4.0 | — | 2.75 | 4.0 | — | Vdc |
| | | 10 | $V_O=1.0V$ or $9.0V$ | — | 8.0 | — | 5.5 | 8.0 | — | |
| | | 15 | $V_O=1.5V$ or $13.5V$ | — | 12.0 | — | 8.25 | 12.0 | — | |
| | | | $ I_O \leq 1\mu A$ | | | | | | | |
| MAXIMUM INPUT LOW VOLTAGE | V_{IL} | 5 | $V_O=0.5V$ or $4.5V$ | 1.0 | — | 1.0 | 2.25 | — | 1.0 | Vdc |
| | | 10 | $V_O=1.0V$ or $9.0V$ | 2.0 | — | 2.0 | 4.5 | — | 2.0 | |
| | | 15 | $V_O=1.5V$ or $13.5V$ | 3.0 | — | 3.0 | 6.75 | — | 3.0 | |
| | | | $ I_O \leq 1\mu A$ | | | | | | | |

- ¹ T_{LOW} = -55°C for C, D, F, and H devices
= -40°C for E device
 T_{HIGH} = +125°C for C, D, F, and H devices
= +85°C for E device

The user should consult the section of this book entitled "CMOS Design Considerations" in conjunction with the Family Specifications given here to assure proper system performance.

PARAMETER DEFINITIONS AND WAVEFORMS

DEFINITIONS

The following information provides detailed explanations of the electrical parameters specified on 4000 Series data sheets. These parameters are categorized into Absolute Maximum Ratings, Recommended Operating Conditions, Static Electrical Characteristics, and Dynamic Electrical Characteristics. Virtually all devices in the 4000 Series are fully described by a combination of the parameters identified in this section; in a few special cases, however, parameters unique to a device are defined on the individual data sheet.

While all parameters exhibit a statistical distribution about a mean value, only the mean value and one worst-case limit — either the minimum or the maximum value — appears on the data sheet. Following the EIA standard guidelines, the minimum limit value is always less than the mean or typical value, and the maximum

limit value is always greater than the typical value. Several parameters, therefore, require the prefix "minimum" or "maximum" in order to maintain the proper convention on the data sheet. These prefixes should not be confused with the minimum and maximum designations applied to limit values. Thus, "maximum clock frequency" has minimum limit values specified, while "minimum clock pulse width" has maximum limit values specified.

Each parameter is measured under a specified set of conditions: supply voltage, input voltages and currents, output voltages and currents, input signal switching characteristics, etc. To assist the designer in constructing his system, any given parameter is measured under the same test conditions for all devices in the 4000 Series, whether they fall into the B, UB, or AB designation.

ABSOLUTE MAXIMUM RATINGS

These ratings are absolute limits within which safe operation occurs. The presence of conditions outside these limits may cause severe device degradation, and possibly catastrophic failure. These ratings apply across the entire temperature range.

DC Supply Voltage Range

To prevent forward biasing and possibly damaging the structural and protective diode junctions present in CMOS construction, V_{DD} must never be more than 0.5Vdc negative with respect to V_{SS} .

The maximum limit of 18Vdc prevents primary breakdown of any internal device junction.

Input Voltage Range

The voltage at any device input must not exceed either the V_{SS} or V_{DD} supply voltages by more than 0.5Vdc. Unrestricted operation outside this range may damage the input protection diodes, or cause internal latch-up.

RECOMMENDED OPERATING CONDITIONS

These conditions specify ranges within which reliable operations may be maintained. Systems utilizing CMOS should be designed to operate within these ranges.

DC Supply Voltage Range

The lower limit of 3Vdc is based upon transistor threshold levels. The recommended maximum limit of 15V is substantially below the primary breakdown limit for the devices to allow for limited power-supply transient and regulation limits.

STATIC ELECTRICAL CHARACTERISTICS

These parameters apply to devices in the steady-state condition. They are specified at the low temperature limits (-55°C or -40°C), $+25^{\circ}\text{C}$, and the high temperature limits ($+125^{\circ}\text{C}$ or $+85^{\circ}\text{C}$), with typical values given at $+25^{\circ}\text{C}$.

Quiescent Device Current (I_{DD})

Quiescent current is defined as the current flowing

DC Input Current

To prevent excessive dissipation in the junctions of the protection diodes, input current must be limited to less than 10mAdc.

Maximum Package Power Dissipation

This requirement prevents excessive junction or package temperatures from developing. The maximum rating of 300mW includes both quiescent (dc) and dynamic (ac) dissipation, and should be calculated from the discussion of Power Dissipation in the section entitled "Design Considerations."

Storage Temperature Range

The temperature range within which devices may be stored without electrical connection is -65°C to $+150^{\circ}\text{C}$. Device reliability may be degraded when stored outside this range.

Operating Temperature Range

The maximum ambient temperature range within which the device may be reliably operated is -55°C to $+125^{\circ}\text{C}$ (the standard military temperature range) for the C, D, and F packages, and -40°C to $+85^{\circ}\text{C}$ (an extended commercial range) for the E package. Chips (H suffix) may be operated over the full military temperature range, -55°C to $+125^{\circ}\text{C}$.

into the V_{DD} terminal of the device with no load on the outputs. This current is measured under all valid input combinations (inputs tied in all valid combinations to V_{SS} or V_{DD}). The maximum limit reflects domination by surface leakage effects. Most devices exhibiting typical leakage currents are dominated by junction leakage which doubles with every 11°C increase in temperature.

These values have been standardized into three

categories: gates, buffers and flip-flops, and MSI devices. Solid State Scientific does not degrade this parameter for commercial temperature range devices (E package).

Output Voltage (V_{OH} , V_{OL})

V_{OH} is defined as the high-level output voltage under no-load conditions ($|I_O| < 1\mu A$), with inputs tied to V_{SS} or V_{DD} . Similarly, V_{OL} is the low-level output voltage measured under the same conditions. Both parameters are guaranteed to be no more than 0.01Vdc from the supply voltage at low temperature and +25°C, and no more than 0.05Vdc from the supply voltage at high temperature.

Input Voltage (V_{IH} , V_{IL})

V_{IH} and V_{IL} are defined as the minimum input high voltage and the maximum input low voltage, respectively, which produce no more than a 10% V_{DD} change in output voltage under no-load conditions ($|I_O| < 1\mu A$). This parameter differentiates device designations "B" and "UB".

In general, "B" devices have greater noise immunity, i.e., lower V_{IH} and higher V_{IL} , than "UB" devices because output buffering more effectively isolates outputs from input voltage variations.

Output Drive Currents (I_{OH} , I_{OL})

Output drive current is the source current (I_{OH}) with the output high, or the sink current (I_{OL}) with the output low, that flows out of or into the device from a load of specific voltage. Polarity is defined as positive when flowing into the output. Inputs are tied directly to V_{SS} or V_{DD} , output voltages are specified at equal voltage drops for both parameters at given supply voltage.

At $V_{DD} = 5Vdc$, I_{OH} and I_{OL} are specified at $V_{OH} = 4.6Vdc$ and $V_{OL} = 0.4Vdc$, respectively. Logic outputs of "B" and "UB" devices are capable of driving one low-power TTL load across temperature. Although the source current (I_{OH}) specification for these devices is lower than the sink current (I_{OL}) specification (I_{IL} (TTL) $>> I_{IH}$), many devices in the 4000 Series Family are designed for balanced drives at these output voltages.

All gates and flip-flops, and a number of MSI parts, fall into this category; this is noted on the individual data sheets.

At $V_{DD} = 10Vdc$, an output voltage drop of 0.5Vdc from either supply is used as the standard condition for specifying I_{OH} and I_{OL} .

At $V_{DD} = 15Vdc$, 1.5Vdc is used as the standard output voltage drop. Current values are designed to drive two standard HTL loads over temperature.

The limits at the temperature extremes reflect the 0.3%/°C current decrease with increasing temperature at 25°C characteristic of CMOS. Most device data sheets supply transistor characteristic curves for determination of output drive current under other operating conditions.

Solid State Scientific does not degrade these parameters for commercial temperature range devices (E package).

3-State Output Leakage Current (I_{ZL})

Leakage current at the output terminal of a 3-state device when disabled (high-impedance state) is measured under the two worst-case conditions: V_{DD} is applied at the output along with input combinations which would normally force the output low; V_{SS} is applied at the output along with input combinations which would normally force the output high.

Solid State Scientific does not degrade this parameter for commercial temperature range devices (E package).

Input Current

Input current is defined as the current that flows into or out of an input terminal when V_{SS} or V_{DD} is applied to that terminal. Input current consists of junction leakages in the diode protection circuit, and is typically $\pm 10pA$ dc. Worst-case input current is specified at $V_{DD} = 15Vdc$ across temperature, with a maximum of $\pm 1.0\mu A$ dc at +125°C (+85°C for commercial temperature range devices).

Solid State Scientific does not degrade this parameter for commercial temperature range devices.

DYNAMIC ELECTRICAL CHARACTERISTICS

Switching characteristics are specified at a total output load capacitance per output $C_L = 50pF$, ambient temperature $T_A = 25^\circ C$, and input rise and fall times t_r , $t_f = 20ns$ (except for maximum input rise and fall time specifications). Typical temperature coefficient for dynamic characteristics is $|0.3\%/^\circ C|$ (negative for maximum clock frequency (f_{CL}) and positive for other parameters). Solid State Scientific does not degrade dynamic parameters for commercial temperature range devices (E package).

Propagation Delay Time (t_{PLH} , t_{PHL})

These parameters are specified on all data sheets. For non-synchronous circuits and inputs, the delay time is measured from the 50% point of the input signal edge to the 50% point of the resulting output signal edge. For synchronous inputs (having a clock signal), the delay time is measured from the 50% of the clock signal edge associated with the input level to the 50% point of the resulting output signal edge. The designation "LH" refers to the low-to-high output transition; "HL" refers to the high-to-low output transition. Propagation delays increase linearly with load capacitance.

3-State Propagation Delay (t_{PHZ} , t_{PLZ} , t_{PZH} , t_{PZL})

The t_{PHZ} (high-level to 3-state) and t_{PLZ} (low-level to 3-state) propagation delays are measured from the 50% point of the disable input leading edge to the 90% point of the output signal falling edge (t_{PHZ}) or to the 10% point of the output signal rising edge (t_{PLZ}). The t_{PZH} (3-state to high-level) and t_{PZL} (3-state to low-level) propagation delays are measured from the 50% point of the disable input trailing edge to the 10% point of the output signal rising edge (t_{PZH}) or to the 90% point of the output signal falling edge (t_{PZL}). In addition to the 50pF load capacitance, a 1K Ω load resistor is tied to V_{SS} (t_{PHZ} and t_{PZH}) or V_{DD} (t_{PLZ} and t_{PZL}).

Output Transition Time (t_{TLH} , t_{THL})

These parameters refer to the rise (t_{TLH}) and fall (t_{THL}) times at device outputs. They are measured from the 10% to the 90% points of the output waveform. Both parameters are functions of output transistor sizes, and fall into standard categories in the same way as output drive current. Output transition times vary linearly with load capacitance C_L .

Minimum (Clock) Pulse Width (PW)

Minimum pulse width refers to that portion of the input signal between the active (leading) edge and the opposite (trailing) edge. It is defined as the interval between the 50% points of each edge. When applied to clock signals, this parameter also refers to the remaining portion of the signal, i.e., 50% duty cycle.

Maximum Clock Frequency (f_{CL})

The maximum clock frequency is the rate at which information can transfer through a synchronous circuit without developing system problems due to excessive propagation delays across internal stages.

Maximum Clock Rise and Fall Times (t_{rCL} , t_{fCL})

These limits refer to the maximum allowable input transition times which prevent interactions between internal stages from interfering with proper clocking. These parameters are measured from the 10% point to the 90% point of the input signal, and usually decrease with increasing operating voltage.

When synchronous stages are cascaded, however, maximum rise and fall times of the clock input should be equal to or less than the transition times of data outputs driving data inputs, plus the propagation delay of the output driving stage for the output capacitive load. This prevents improper operation resulting from logic state interaction between adjoining stages.

Minimum Setup Time (t_{setup})

Setup time refers to the minimum interval between the data or control input signal and the clock or strobe signal which guarantees proper entry of that information into the device. It is measured between the 50% points of the two appropriate edges.

Minimum Hold Time (t_{hold})

Hold time refers to the interval after the clock or strobe edge during which data or control information must remain valid. It is measured between the 50% points of the two appropriate edges.


Removal Time (t_{rem})

Removal time is defined as the interval after removing an asynchronous control input during which a clock or strobe signal edge may not be recognized. This parameter is similar to minimum setup time, and is measured from the 50% point of the control input trailing edge to the 50% point of the clock or strobe signal leading edge.


Input Capacitance (C_{IN})

The input capacitance is defined as the ac capacitance under zero bias conditions as applied to any input. This capacitance is typically 5pF for most devices; it is somewhat higher for inputs to high-current buffers.


DYNAMIC PARAMETER WAVEFORMS



Non-Synchronous Circuit Waveshapes and Timing Parameters



Synchronous Circuit Waveshapes and Timing Parameters



Three-State Propagation Delay Waveshape and Test Circuit

4000 Series Data



CMOS DUAL 3-INPUT NOR GATE PLUS INVERTER


FEATURES

- ◆ Buffered Gate Outputs
- ◆ Diode Protection on all Inputs
- ◆ Fully "B" Series Compatible


TRUTH TABLE (NOR GATE)

| INPUTS | OUTPUT |
|------------------------|--------|
| 0 0 0 | 1 |
| All other combinations | 0 |


LOGIC DIAGRAM



FUNCTION DIAGRAM



**CONNECTION DIAGRAM
(all packages)**



Add suffix for package:


- C 14-pin Cerdip
- D 14-pin Ceramic
- E 14-pin Epoxy
- F 14-pin Flat
- H Chip

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | -55 to +125 | °C |
| C, D, F, H Device | | -40 to +85 | °C |
| E Device | | | |

**SCHEMATIC DIAGRAM
(One of two NOR Gates)**



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS ¹.

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|------------|-------------------------------|------|-------|--------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | 5 | — | 0.05 | — | 0.0005 | 0.05 | — | 1.5 | μAdc |
| | | 10 | — | 0.10 | — | 0.001 | 0.10 | — | 3.0 | |
| | | 15 | — | 0.20 | — | 0.002 | 0.20 | — | 6.0 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.


= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.


= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETER | | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|------------------------|-------------------------------------|--------------------------|------|------|------|-------|
| PROPAGATION DELAY TIME | t _{PLH} , t _{PHL} | 5 | — | 125 | 250 | ns |
| | | 10 | — | 60 | 120 | |
| | | 15 | — | 45 | 90 | |
| | | | | | | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | — | 100 | 200 | ns |
| | | 10 | — | 50 | 100 | |
| | | 15 | — | 40 | 80 | |
| | | | | | | |



Typical P-Channel
Source Current Characteristics



Typical N-Channel
Sink Current Characteristics

CMOS NOR GATES





4001B – Quad 2-Input NOR
4002B – Dual 4-Input NOR
4025B – Triple 3-Input NOR
4078B – 8-Input NOR

FEATURES





- ◆ Buffered Outputs
- ◆ Diode Protection on all Inputs
- ◆ Fully "B" - Series Compatible

| Inputs | Output |
|------------------------|--------|
| 0 0 . . . 0 | 1 |
| All other combinations | 0 |

FUNCTION DIAGRAMS



CONNECTION DIAGRAMS (all packages)



RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | -55 to +125 | °C |
| C, D, F, H Device | | -40 to +85 | °C |
| E Device | | | |

ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|---|-------------------------------|------|-------|--------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | V _{IN} =V _{SS} or V _{DD} All valid input combinations | — | 0.05 | — | 0.0005 | 0.05 | — | 1.5 | μAdc |
| | | | — | 0.10 | — | 0.001 | 0.10 | — | 3.0 | |
| | | | — | 0.20 | — | 0.002 | 0.20 | — | 6.0 | |
| | | | — | — | — | — | — | — | — | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications."

² T_{LOW} = -55°C for C, D, F, H device.


= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.


= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETER | | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|------------------------|-------------------------------------|--------------------------|------|------|------|-------|
| PROPAGATION DELAY TIME | t _{PLH} , t _{PHL} | 5 | — | 125 | 250 | ns |
| | | 10 | — | 60 | 120 | |
| | | 15 | — | 45 | 90 | |
| | | — | — | — | — | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | — | 100 | 200 | ns |
| | | 10 | — | 50 | 100 | |
| | | 15 | — | 40 | 80 | |
| | | — | — | — | — | |




Typical P-Channel
Source Current Characteristics




Typical N-Channel
Sink Current Characteristics

LOGIC DIAGRAMS



SCHEMATIC DIAGRAM 4002B (1 of 2 gates)



CMOS NOR GATE (Unbuffered)

FEATURES


- ◆ Unbuffered Outputs for Quasi-Linear Applications
- ◆ Quad 2-Input NOR Configuration
- ◆ Diode Protection on all Inputs
- ◆ Output Drive Current Compatible with "B" Series
- ◆ Pin Compatible with Buffered 4001B

DESCRIPTION

The 4001UB consists of four positive-logic NOR gates. The outputs are unbuffered, making the device suitable for quasi-linear applications, such as gated oscillators, multivibrators, and pulse shaping circuits.

For digital applications, the buffered 4001B is recommended for its higher gain and input pattern insensitivity.

CONNECTION DIAGRAM (all packages)



Add suffix for package:

- C 14-pin Cerdip
- D 14-pin Ceramic
- E 14-pin Epoxy
- F 14-pin Flat
- H Chip

TRUTH TABLE


| Inputs | Output |
|------------------------|--------|
| 0 0 | 1 |
| All other combinations | 0 |

RECOMMENDED OPERATING CONDITIONS


For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | -55 to +125 | °C |
| C, D, F, H Device | | -40 to +85 | °C |
| E Device | | | |

SCHEMATIC DIAGRAM



LOGIC DIAGRAM



$$Y = \overline{A + B}$$

$V_{DD} = \text{Pin } 14$
 $V_{SS} = \text{Pin } 7$

ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS ¹.

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|--|-------------------------------|------|-------|--------|------|--------------------------------|------|------------------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | V _{IN} = V _{SS} or V _{DD} All valid input combinations | — | 0.05 | — | 0.0005 | 0.05 | — | 1.5 | μA _{dc} |
| | | | — | 0.10 | — | 0.001 | 0.10 | — | 3.0 | |
| | | | — | 0.20 | — | 0.002 | 0.20 | — | 6.0 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.



= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.


= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)


| PARAMETER | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|------------------------|-------------------------------------|------|------|------|-------|
| PROPAGATION DELAY TIME | t _{PLH} , t _{PHL} | — | 60 | 120 | ns |
| | 5 | — | 30 | 60 | |
| | 10 | — | 25 | 50 | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | — | 100 | 200 | ns |
| | 5 | — | 50 | 100 | |
| | 10 | — | 40 | 80 | |




APPLICATIONS INFORMATION



MONOSTABLE MULTIVIBRATOR



COMPENSATED MONOSTABLE MULTIVIBRATOR



SCHMITT TRIGGER

FEATURES

- ◆ Fully Static Operation
- ◆ Cascadable
- ◆ 5MHz Shift Rate @ 10Vdc




DESCRIPTION

The 4006B is comprised of 4 separate Shift Register sections: two sections of four stages and two sections of five stages with an output tap at the fourth stage. Each section has an independent single rail data path.

A common Clock signal is used for all stages. Data is shifted to the next stage on negative-going transitions of the Clock. Through appropriate connections of inputs and outputs, multiple register sections of 4, 5, 8 and 9 stages or single register sections of 10, 12, 13, 14, 16, 17 and 18 can be implemented using one 4006B package. Longer shift register sections can be assembled by using more than one 4006B.


This part is useful in serial shift register and time delay circuits.

TRUTH TABLE

| D_i | CL | $D_i + 1$ |
|-------|---|-----------|
| 0 |  | 0 |
| 1 |  | 1 |
| X |  | No Change |


X = Don't care

TYPICAL REGISTER STAGE



CMOS 18 STAGE SHIFT REGISTER

CONNECTION DIAGRAM
(all packages)



Add suffix for package:

- C 14-pin Cerdip
- D 14-pin Ceramic
- E 14-pin Epoxy
- F 14-pin Flat
- H Chip

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:


DC Supply Voltage $V_{DD} - V_{SS}$ 3 to 15 Vdc

Operating Temperature T_A

C, D, F, H Device -55 to +125 °C

E Device -40 to +85 °C

LOGIC DIAGRAM



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS ¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|---|-------------------------------|------|-------|------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | V _{IN} =V _{SS} or V _{DD} All valid input combinations | — | 5 | — | 0.05 | 5 | — | 150 | μAdc |
| | | | — | 10 | — | 0.1 | 10 | — | 300 | |
| | | | — | 20 | — | 0.2 | 20 | — | 600 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.

= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.

= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETER | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|---|-------------------------------------|------|------|------|-------|
| PROPAGATION DELAY TIME | t _{PLH} , t _{PHL} | 5 | — | 250 | ns |
| | | 10 | — | 125 | |
| | | 15 | — | 100 | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | — | 100 | ns |
| | | 10 | — | 50 | |
| | | 15 | — | 40 | |
| MINIMUM CLOCK PULSE WIDTH | PW _{CL} | 5 | — | 200 | ns |
| | | 10 | — | 100 | |
| | | 15 | — | 80 | |
| MAXIMUM CLOCK FREQUENCY | f _{CL} | 5 | 1.25 | 2.5 | MHz |
| | | 10 | 2.5 | 5.0 | |
| | | 15 | 3.0 | 6.0 | |
| MAXIMUM CLOCK RISE AND FALL TIME ¹ | t _{rCL} , t _{fCL} | 5 | 15 | — | μs |
| | | 10 | 5 | — | |
| | | 15 | 3 | — | |
| MINIMUM SETUP TIME | t _{setup} | 5 | — | 40 | ns |
| | | 10 | — | 25 | |
| | | 15 | — | 20 | |
| MINIMUM HOLD TIME | t _{hold} | 5 | — | 40 | ns |
| | | 10 | — | 25 | |
| | | 15 | — | 20 | |

¹ When units are cascaded, the maximum rise and fall times of the clock input should be equal to or less than the transition times of the data outputs driving data inputs, plus the propagation delay of the output driving stage for the output capacitive load.


CMOS DUAL COMPLEMENTARY PAIR PLUS INVERTER

FEATURES


- ◆ Low Output Impedance
- ◆ Extremely High Input Impedance
- ◆ Single Supply Operation - Positive or Negative
- ◆ All Inputs Diode-Protected

DESCRIPTION


4007UB contains three N-Channel and three P-Channel enhancement-type MOS transistors on a single monolithic silicon chip. The transistor elements are accessible through the package terminals to provide means for constructing various logic, transmission gating, and linear circuits.



Typ. P-Channel drain characteristics




Typ. N-Channel drain characteristics



Min. and max. voltage transfer characteristics for inverter

CONNECTION DIAGRAM (all packages)



Add suffix for package:



- C 14-pin Cerdip
- D 14-pin Ceramic
- E 14-pin Epoxy
- F 14-pin Flat
- H Chip

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | | |
| C, D, F, H Device | | -55 to +125 | °C |
| E Device | | -40 to +85 | °C |

SCHEMATIC DIAGRAM



Typ. current and voltage transfer characteristics for inverter

ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|-----------------|--------------------------|---|-------------------------------|------|-------|--------|------|--------------------------------|------|------------------|
| | | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | 5 | V _{IN} =V _{SS} or V _{DD} | — | 0.05 | — | 0.0005 | 0.05 | — | 1.5 | μA _{dc} |
| | | 10 | All valid input combinations | — | 0.10 | — | 0.001 | 0.10 | — | 3.0 | |
| | | 15 | | — | 0.20 | — | 0.002 | 0.20 | — | 6.0 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".² T_{LOW} = -55°C for C, D, F, H device.



= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.

= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50 pF, T_A = 25 °C)¹


| PARAMETER | | V _{DD} (V _{DC}) | Min. | Typ. | Max. | Units |
|------------------------|-------------------------------------|---------------------------------------|------|------|------|-------|
| PROPAGATION DELAY TIME | t _{PLH} , t _{PHL} | 5 | — | 55 | 110 | ns |
| | | 10 | — | 30 | 60 | |
| | | 15 | — | 25 | 50 | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | — | 100 | 200 | ns |
| | | 10 | — | 50 | 100 | |
| | | 15 | — | 40 | 80 | |

¹ Connected as inverterTyp. propagation delay time vs. C_L


Typ. dissipation characteristics

APPLICATIONS INFORMATION

Triple Inverters

(14, 2, 11); (8, 13);
(1, 5); (7, 4, 9)


3-Input NOR Gate

(13, 2); (1, 11);
(12, 5, 8); (7, 4, 9)


3-Input NAND Gate

(1, 12, 13); (2, 14, 11);
(4, 8); (5, 9)


Tree (Relay) Logic



High Sink-Current Driver

(6, 3, 10); (8, 5, 12);
(11, 14); (7, 4, 9)


High Source-Current Driver

(6, 3, 10); (13, 1, 12)
(14, 2, 11); (7, 9)



APPLICATIONS INFORMATION (Continued)

High Sink- and Source-Current Driver

(6,3,10); (14,2,11);
(7,4,9); (13,8,1,5,12)

**Dual Bi-Directional Transmission Gating**

(1,5,12), (2,9),
(11,4), (8,13,10), (6,3)

**3-State Buffer**

| INPUT | DISABLE | OUTPUT |
|-------|---------|--------|
| 1 | 0 | 0 |
| 0 | 0 | 1 |
| X | 1 | Open |

X = Don't Care

CMOS FOUR-BIT FULL ADDER

FEATURES

- ◆ Look-Ahead Carry Output
- ◆ High-Speed Operation


DESCRIPTION

The 4008B consists of four Full-Adder stages with fast Look-Ahead Carry provision from stage to stage. Circuitry is included to provide a fast Parallel-Carry-out bit to permit high-speed operation in arithmetic sections using several 4008B's. 4008B inputs include the four sets of bits to be added, A1 to A4 and B1 to B4, in addition to the Carry-in bit from a previous section. 4008B outputs include the four Sum bits, S1 and S4, in addition to the high-speed Parallel-Carry-out which may be utilized at a succeeding 4008B section.

TRUTH TABLE
(one stage)

| C _{in} | B | A | C _{out} | S |
|-----------------|---|---|------------------|---|
| 0 | 0 | 0 | 0 | 0 |
| 0 | 0 | 1 | 0 | 1 |
| 0 | 1 | 0 | 0 | 1 |
| 0 | 1 | 1 | 1 | 0 |
| 1 | 0 | 0 | 0 | 1 |
| 1 | 0 | 1 | 1 | 0 |
| 1 | 1 | 0 | 1 | 0 |
| 1 | 1 | 1 | 1 | 1 |

CONNECTION DIAGRAM
(all packages)



Add suffix for package:


- C 16-pin Cerdip
- D 16-pin Ceramic
- E 16-pin Epoxy
- F 16-pin Flat
- H Chip

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | -55 to +125 | °C |
| C, D, F, H Device | | -40 to +85 | °C |
| E Device | | | |

BLOCK DIAGRAM



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS ¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|--|-------------------------------|------|-------|------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | V _{IN} = V _{SS} or V _{DD} All valid input combinations | — | 5 | — | 0.05 | 5 | — | 150 | μAdc |
| | | | — | 10 | — | 0.1 | 10 | — | 300 | |
| | | | — | 20 | — | 0.2 | 20 | — | 600 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.



= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.


= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)


| PARAMETER | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|---|-------------------------------------|------|------|------|-------|
| PROPAGATION DELAY TIME Sum In to Sum Out | t _{PLH} , t _{PHL} | 5 | — | 400 | ns |
| | | 10 | — | 160 | |
| | | 15 | — | 115 | |
| | t _{PLH} , t _{PHL} | 5 | — | 310 | ns |
| | | 10 | — | 140 | |
| | | 15 | — | 110 | |
| | t _{PLH} , t _{PHL} | 5 | — | 380 | ns |
| | | 10 | — | 150 | |
| | | 15 | — | 115 | |
| | t _{PLH} , t _{PHL} | 5 | — | 180 | ns |
| | | 10 | — | 75 | |
| | | 15 | — | 55 | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | — | 100 | ns |
| | | 10 | — | 50 | |
| | | 15 | — | 40 | |



LOGIC DIAGRAM




APPLICATIONS INFORMATION




16-Bit Adder

APPLICATIONS INFORMATION (Continued)



2-Digit BCD-to-Binary Conversion



4-Bit Up/Down Counter

CMOS HEX BUFFERS/CONVERTERS


FEATURES

- ◆ Direct Drive of 2 TTL/DTL Loads
- ◆ Operation from Single or Dual Supplies
- ◆ All Inputs Diode-Protected

DESCRIPTION

The 4009UB and 4010B are single-chip monolithic silicon integrated circuits containing eighteen N-Channel and twelve P-Channel enhancement-mode MOS transistors connected to form six independent buffer/convert configurations. These devices are designed for use as hex CMOS-to-DTL or TTL logic level converters or hex CMOS current drivers. Conversion ranges are from CMOS logic operating at 3Vdc to 18Vdc supply levels to DTL or TTL logic operating at 3Vdc to 6Vdc supply levels. Conversion to logic output levels greater than 6Vdc is permitted providing $V_{CC} \leq V_{DD}$.


CONNECTION DIAGRAM (all packages)



Add Suffix for Package:

- C 16-pin Cerdip
- D 16-pin Ceramic
- E 16-pin Epoxy
- F 16-pin Flat
- H Chip

SCHEMATIC DIAGRAMS




RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-------------------|----------------------|---------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| | $V_{CC} - V_{SS}$ | 3 to 15 | Vdc |
| | $V_{CC} \leq V_{DD}$ | | |

| | | |
|-----------------------|-------|----------------|
| Operating Temperature | T_A | |
| C, D, F, H Device | | -55 to +125 °C |
| E Device | | -40 to +85 °C |

LOGIC DIAGRAMS



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹


| PARAMETER | | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------------------|-----------------|--------------------------|--|-------------------------------|------|-------|-------|------|--------------------------------|------|------------------|
| | | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT 4009UB | I _{DD} | 5 | V _{IN} = V _{SS} or V _{DD} | — | 0.25 | — | 0.005 | 0.25 | — | 7.5 | μA _{dc} |
| | | 10 | All valid input combinations | — | 0.50 | — | 0.01 | 0.50 | — | 15.0 | |
| | | 15 | | — | 1.00 | — | 0.02 | 1.00 | — | 30.0 | |
| QUIESCENT DEVICE CURRENT 4010B | I _{DD} | 5 | V _{IN} = V _{SS} or V _{DD} | — | 1.0 | — | 0.005 | 1.0 | — | 30 | μA _{dc} |
| | | 10 | All valid input combinations | — | 2.0 | — | 0.01 | 2.0 | — | 60 | |
| | | 15 | | — | 4.0 | — | 0.02 | 4.0 | — | 120 | |
| MINIMUM INPUT HIGH VOLTAGE 4009UB | V _{IH} | 5 | V _{OL} = 0.5V | — | 4.0 | — | 2.75 | 4.0 | — | 4.0 | Vdc |
| | | 10 | V _{OL} = 1.0V | — | 8.0 | — | 5.5 | 8.0 | — | 8.0 | |
| | | 15 | V _{OL} = 1.5V I _O ≤ 1μA | — | 12.0 | — | 8.25 | 12.0 | — | 12.0 | |
| MAXIMUM INPUT LOW VOLTAGE 4009UB | V _{IL} | 5 | V _{OH} = 3.6V | 1.0 | — | 1.0 | 2.25 | — | 1.0 | — | Vdc |
| | | 10 | V _{OH} = 7.2V | 2.0 | — | 2.0 | 4.5 | — | 2.0 | — | |
| | | 15 | V _{OH} = 10.8V I _O ≤ 1μA | 2.5 | — | 2.5 | 6.75 | — | 2.5 | — | |
| OUTPUT HIGH CURRENT (SOURCE) | I _{OH} | 5 | V _{OH} = 4.6 | −0.25 | — | −0.2 | — | — | −0.14 | — | mA _{dc} |
| | | 10 | V _{OH} = 9.5 | −0.62 | — | −0.5 | — | — | −0.35 | — | |
| | | 15 | V _{OH} = 13.5 | −1.9 | — | −1.5 | — | — | −1.1 | — | |
| OUTPUT LOW CURRENT (SINK) | I _{OL} | 5 | V _{OL} = 0.4V | 3.7 | — | 3.0 | 4.0 | — | 2.1 | — | mA _{dc} |
| | | 10 | V _{OL} = 0.5V | 9.9 | — | 8.0 | 10 | — | 5.6 | — | |
| | | 15 | V _{OL} = 1.5V V _{IN} = V _{SS} or V _{DD} | 29.8 | — | 24 | 36 | — | 16.8 | — | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".


² T_{LOW} = −55°C for C, D, F, H device T_{HIGH} = +125°C for C, D, F, H device
 = −40°C for E device. = + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)


| PARAMETER | | V _{DD} (Vdc) | V _{CC} (Vdc) | Min. | Typ. | Max. | Units | |
|--------------------------------------|------------------|--------------------------|--------------------------|------|------|------|-------|----|
| PROPAGATION DELAY TIME | Driving CMOS | t _{PLH} | 5 | 5 | — | 60 | 120 | ns |
| | | | 10 | 10 | — | 35 | 70 | |
| | | | 15 | 15 | — | 28 | 56 | |
| | | Driving TTL/DTL | 5 | 5 | — | 45 | 90 | ns |
| | | | 10 | 5 | — | 20 | 40 | |
| | | | 15 | 5 | — | 15 | 30 | |
| | Driving CMOS | t _{PHL} | 5 | 5 | — | 30 | 60 | ns |
| | | | 10 | 10 | — | 18 | 36 | |
| | | | 15 | 15 | — | 12 | 24 | |
| | | Driving TTL/DTL | 5 | 5 | — | 35 | 70 | ns |
| | | | 10 | 5 | — | 15 | 30 | |
| | | | 15 | 5 | — | 10 | 20 | |
| OUTPUT TRANSITION TIME | t _{TLH} | 5 | 5 | — | 150 | 300 | ns | |
| | | 10 | 10 | — | 75 | 150 | | |
| | | 15 | 15 | — | 60 | 120 | | |
| | t _{THL} | 5 | 5 | — | 30 | 60 | ns | |
| | | 10 | 10 | — | 20 | 40 | | |
| | | 15 | 15 | — | 12 | 24 | | |
| INPUT CAPACITANCE 4009UB 4010B | C _{IN} | — | — | — | 10 | 15 | pF | |
| | | — | — | — | 5 | 7.5 | | |




Typical P-Channel
Source Current Characteristics




Typical N-Channel
Sink Current Characteristics




Typ. voltage transfer characteristics as function of
temperature — 4009UB



Typ. voltage transfer characteristics as a function
of temperature — 4010B



Min. & max. voltage transfer charac-
teristics — 4009UB



Typ. dissipation characteristics —
4009UB, 4010B

CMOS NAND GATES

4011B – Quad 2-Input NAND
4012B – Dual 4-Input NAND
4023B – Triple 3-Input NAND
4068B – 8-Input NAND




FEATURES

- ◆ Buffered Outputs
- ◆ Diode Protection on all Inputs
- ◆ Fully "B"-Series Compatible





TRUTH TABLE

| Inputs | Output |
|------------------------|--------|
| 1 1 ... 1 | 0 |
| All other combinations | 1 |

FUNCTION DIAGRAMS



CONNECTION DIAGRAMS
(all packages)



RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-----------------------------------|-------------|-----------------|
| DC Supply Voltage | V _{DD} - V _{SS} | 3 to 15 | V _{dc} |
| Operating Temperature | T _A | | |
| C, D, F, H Device | | -55 to +125 | °C |
| E Device | | -40 to +85 | °C |

ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS ¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|--|-------------------------------|------|-------|--------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | V _{IN} = V _{SS} or V _{DD} All valid input combinations | - | 0.05 | - | 0.0005 | 0.05 | - | 1.5 | μAdc |
| | | | - | 0.10 | - | 0.001 | 0.10 | - | 3.0 | |
| | | | - | 0.20 | - | 0.002 | 0.20 | - | 6.0 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications."

² T_{LOW} = -55°C for C, D, F, H device.


= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.


= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETER | | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|------------------------|-------------------------------------|--------------------------|------|------|------|-------|
| PROPAGATION DELAY TIME | t _{PLH} , t _{PHL} | 5 | - | 125 | 250 | ns |
| | | 10 | - | 60 | 120 | |
| | | 15 | - | 45 | 90 | |
| | | 15 | - | 40 | 80 | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | - | 100 | 200 | ns |
| | | 10 | - | 50 | 100 | |
| | | 15 | - | 40 | 80 | |
| | | 15 | - | 40 | 80 | |




Typical P-Channel
Source Current Characteristics




Typical N-Channel
Sink Current Characteristics

LOGIC DIAGRAMS



SCHEMATIC DIAGRAM 4012B (1 of 2 gates)



CMOS NAND GATE (Unbuffered)

FEATURES

- ◆ Unbuffered Outputs for Quasi-Linear Applications
- ◆ Quad 2-Input NAND Configuration
- ◆ Diode Protection on all Inputs
- ◆ Output Drive Current Compatible with "B" Series
- ◆ Pin Compatible with Buffered 4011B

DESCRIPTION


The 4011UB consists of four positive-logic NAND gates. The outputs are unbuffered, making the device suitable for quasi-linear applications, such as gated oscillators, multivibrators, and pulse shaping circuits.

For digital applications, the buffered 4011B is recommended for its higher gain and input pattern insensitivity.

TRUTH TABLE

| Inputs | Output |
|------------------------|--------|
| 1 1 | 0 |
| All other combinations | 1 |

CONNECTION DIAGRAM
(all packages)



Add suffix for package:


- C 14-pin Cerdip
- D 14-pin Ceramic
- E 14-pin Epoxy
- F 14-pin Flat
- H Chip

RECOMMENDED OPERATING CONDITIONS


For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | -55 to +125 | °C |
| C, D, F, H Device | | -40 to +85 | °C |
| E Device | | | |

SCHEMATIC DIAGRAM



LOGIC DIAGRAM



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS ¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|------------|-------------------------------|------|-------|--------|------|--------------------------------|------|------------------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | 5 | — | 0.05 | — | 0.0005 | 0.05 | — | 1.5 | μA _{dc} |
| | | 10 | — | 0.10 | — | 0.001 | 0.10 | — | 3.0 | |
| | | 15 | — | 0.20 | — | 0.002 | 0.20 | — | 6.0 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.


= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.


= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETER | | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|------------------------|-------------------------------------|--------------------------|------|------|------|-------|
| PROPAGATION DELAY TIME | t _{PLH} , t _{PHL} | 5 | — | 60 | 120 | ns |
| | | 10 | — | 30 | 60 | |
| | | 15 | — | 25 | 50 | |
| | | — | — | — | — | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | — | 100 | 200 | ns |
| | | 10 | — | 50 | 100 | |
| | | 15 | — | 40 | 80 | |
| | | — | — | — | — | |




Typical P-Channel
Source Current Characteristics





Typical N-Channel
Sink Current Characteristics

APPLICATIONS INFORMATION



Gated Oscillator

Compensated Monostable Multivibrator
(Independent of Transfer Voltage)

Frequency Doubler

CMOS DUAL D-TYPE FLIP-FLOP

FEATURES

- ◆ Independent Set and Reset Controls
- ◆ Static Operation
- ◆ Logic Edge-Clocked Design
- ◆ 16MHz Toggle Rate @ 10Vdc

DESCRIPTION

The 4013B consists of two identical, independent D-type Flip-Flops. These devices can be used for shift register applications, and, by connecting the \bar{Q} output to the Data input, for counter and toggle applications. The logic level present at the D input is transferred to the Q output during the positive-going transition of the Clock pulse. Setting or resetting is independent of the Clock and is accomplished by a high level on the Set or Reset line, respectively.

TRUTH TABLE


| CL Δ | D | R | S | Q | \bar{Q} |
|-------------|---|---|---|---|-----------|
| | 0 | 0 | 0 | 0 | 1 |
| | 1 | 0 | 0 | 1 | 0 |
| | x | 0 | 0 | Q | \bar{Q} |
| x | x | 1 | 0 | 0 | 1 |
| x | x | 0 | 1 | 1 | 0 |
| x | x | 1 | 1 | 1 | 1 |

NO CHANGE


Δ = Level Change

x = Don't Care

LOGIC DIAGRAM



CONNECTION DIAGRAM (all packages)



RECOMMENDED OPERATING CONDITIONS

For maximum reliability:


DC Supply Voltage $V_{DD} - V_{SS}$ 3 to 15 Vdc

Operating Temperature T_A

C, D, F, H Device -55 to +125 °C

E Device -40 to +85 °C

BLOCK DIAGRAM



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|------------|---|------|-------|-------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | 5 | V _{IN} =V _{SS} or V _{DD} | 1.0 | — | 0.005 | 1.0 | — | 30 | μAdc |
| | | 10 | All valid input combinations | 2.0 | — | 0.01 | 2.0 | — | 60 | |
| | | 15 | | 4.0 | — | 0.02 | 4.0 | — | 120 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications."

² T_{LOW} = -55°C for C, D, F, H device.

= -40°C for E device.


T_{HIGH} = +125°C for C, D, F, H device.

= + 85°C for E device.


DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETER | | V _{DD} (V _{dc}) | Min. | Typ. | Max. | Units |
|---|-------------------------------------|---------------------------------------|--------------------|------------------|------------------|-------|
| CLOCKED OPERATION | | | | | | |
| PROPAGATION DELAY TIME | t _{PLH} , t _{PHL} | 5 10 15 | — — — | 125 65 45 | 250 130 90 | ns |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 10 15 | — — — | 100 50 40 | 200 100 80 | ns |
| MINIMUM CLOCK PULSE WIDTH | PW _{CL} | 5 10 15 | — — — | 70 30 20 | 140 60 40 | ns |
| MAXIMUM CLOCK FREQUENCY | f _{CL} | 5 10 15 | 4.0 8.0 12.5 | 7.0 16 25 | — — — | MHz |
| MAXIMUM CLOCK RISE AND FALL TIME ¹ | t _{rCL} , t _{fCL} | 5 10 15 | 15 10 5 | — — — | — — — | μs |
| MINIMUM SETUP TIME | t _{setup} | 5 10 15 | — — — | 25 10 7.5 | 50 20 15 | ns |
| MINIMUM HOLD TIME | t _{hold} | 5 10 15 | — — — | -25 -10 -5 | 0 0 0 | ns |
| SET AND RESET OPERATIONS | | | | | | |
| PROPAGATION DELAY TIME S to Q, R to Q | t _{PLH} | 5 10 15 | — — — | 125 65 45 | 250 130 90 | ns |
| MINIMUM SET AND RESET PULSE WIDTH | PW _S , PW _R | 5 10 15 | — — — | 65 30 25 | 130 60 50 | ns |
| SET AND RESET REMOVAL TIME | t _{rem} | 5 10 15 | — — — | 0 0 0 | 25 10 5 | ns |

¹When units are cascaded, the maximum rise and fall times of the clock input should be equal to or less than the transition times of the data outputs driving data inputs, plus the propagation delay of the output driving stage for the output capacitive load.



Typical P-Channel
Source Current Characteristics



Typical N-Channel
Sink Current Characteristics


CMOS 8-STAGE SHIFT REGISTER

FEATURES

- ◆ Synchronous Parallel Input/Serial Output
- ◆ Synchronous Serial Input/Serial Output
- ◆ Fully Static Operation — DC to 6 MHz @ 10Vdc
- ◆ Q Outputs from Stages 6, 7, and 8 Available

DESCRIPTION

The 4014B is an 8-stage Parallel-Input/Serial Output Register having common Clock and Parallel/Serial Control inputs, a single Serial Data input, and individual parallel Jam inputs to each register stage. Each register stage is a D-type, master-slave flip-flop. In addition to an output from stage 8, Q outputs are also available from stages 6 and 7. Parallel as well as serial entry is made into the register synchronous with the positive Clock line transition and under control of the Parallel/Serial Control input. When the Parallel/Serial Control input is low, data is serially shifted into the 8-stage register synchronously with the transition of the Clock line. When the Parallel/Serial Control input is high, data is jammed into the 8-stage register via the Parallel Input lines and synchronous with the positive transition of the Clock line. Changes on the Parallel/Serial Control should be made only while the Clock is low. Register expansion using multiple 4014B packages is permitted.



RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | | |
| C, D, F, H Device | | -55 to +125 | °C |
| E Device | | -40 to +85 | °C |

TRUTH TABLE

Serial Operation

| t | CLOCK | SER IN | P/S | Q6 t=n+6 | Q7 t=n+7 | Q8 t=n+8 |
|-----|-------|--------|-----|-------------|-------------|-------------|
| n | | 0 | 0 | 0 | ? | ? |
| n+1 | | 1 | 0 | 1 | 0 | ? |
| n+2 | | 0 | 0 | 0 | 1 | 0 |
| n+3 | | 1 | 0 | 1 | 0 | 1 |
| | | X | 0 | Q6 | Q7 | Q8 |


Parallel Operation

| CLOCK | SER IN | P/S | PI-m | *Qm |
|-------|--------|-----|------|-----|
| | X | 1 | 0 | 0 |
| | X | 1 | 1 | 1 |

*Q6, Q7, and Q8 are available externally

X = Don't Care

LOGIC DIAGRAM



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|---|-------------------------------|------|-------|------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | V _{IN} =V _{SS} or V _{DD} All valid input combinations | — | 5 | — | 0.05 | 5 | — | 150 | μAdc |
| | | | — | 10 | — | 0.1 | 10 | — | 300 | |
| | | | — | 20 | — | 0.2 | 20 | — | 600 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.

= -40°C for E device.


T_{HIGH} = +125°C for C, D, F, H device.

= + 85°C for E device.


DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETER | | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|---|-------------------------------------|--------------------------|------|------|------|-------|
| PROPAGATION DELAY TIME | t _{PLH} , t _{PHL} | 5 | — | 160 | 320 | ns |
| | | 10 | — | 80 | 160 | |
| | | 15 | — | 60 | 120 | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | — | 100 | 200 | ns |
| | | 10 | — | 50 | 100 | |
| | | 15 | — | 40 | 80 | |
| MINIMUM CLOCK PULSE WIDTH | PW _{CL} | 5 | — | 90 | 180 | ns |
| | | 10 | — | 40 | 80 | |
| | | 15 | — | 25 | 50 | |
| MAXIMUM CLOCK FREQUENCY | f _{CL} | 5 | 3.0 | 5 | — | MHz |
| | | 10 | 6.0 | 10 | — | |
| | | 15 | 8.5 | 14 | — | |
| MAXIMUM CLOCK RISE AND FALL TIME ¹ | t _{rCL} , t _{fCL} | 5 | 15 | — | — | μs |
| | | 10 | 15 | — | — | |
| | | 15 | 5 | — | — | |
| MINIMUM SETUP TIME Serial Input | t _{setup} | 5 | — | 60 | 120 | ns |
| | | 10 | — | 40 | 80 | |
| | | 15 | — | 30 | 60 | |
| P/S Input | t _{setup} | 5 | — | 90 | 180 | ns |
| | | 10 | — | 40 | 80 | |
| | | 15 | — | 30 | 60 | |
| Parallel Inputs | t _{setup} | 5 | — | 90 | 180 | ns |
| | | 10 | — | 40 | 80 | |
| | | 15 | — | 30 | 60 | |
| MINIMUM HOLD TIME All Inputs | t _{hold} | 5 | — | 40 | 80 | ns |
| | | 10 | — | 20 | 40 | |
| | | 15 | — | 10 | 20 | |

¹ When units are cascaded, the maximum rise and fall times of the clock input should be equal to or less than the transition times of the data outputs driving data inputs, plus the propagation delay of the output driving stage for the output capacitive load.



Typical P-Channel
Source Current Characteristics



Typical N-Channel
Sink Current Characteristics

CMOS DUAL 4-STAGE SHIFT REGISTER




FEATURES

- ◆ Serial Input/Parallel Output
- ◆ Direct Reset
- ◆ Two Independent Sections
- ◆ Fully Static Operation - DC to 5MHz @ 10Vdc

DESCRIPTION

The 4015B consists of two identical, independent, 4-stage Serial-Input/Parallel-Output Registers. Each register has independent Clock and Reset inputs as well as a single serial Data input. Q outputs are available from each of the four stages on both registers. All register stages are D-type, master-slave flip-flops. The logic level present at the Data input is transferred into the first register stage and shifted right one stage at each positive-going Clock transition. Resetting of all stages is accomplished by a high level on the Reset line. Register expansion to 8 stages using one 4015B package, or to more than 8 stages using additional 4015B's, is possible.

TRUTH TABLE


| CL* | D | R | Q ₁ | Q _n |
|--|---|---|----------------|------------------|
|  | 0 | 0 | 0 | Q _{n-1} |
|  | 1 | 0 | 1 | Q _{n-1} |
|  | X | 0 | Q ₁ | Q _n |
| X | X | 1 | 0 | 0 |

(NO CHANGE)


* = LEVEL CHANGE

X = DON'T CARE

LOGIC DIAGRAM



CONNECTION DIAGRAM
(all packages)



Add suffix for package:


- C 16-pin Cerdip
- D 16-pin Ceramic
- E 16-pin Epoxy
- F 16-pin Flat
- H Chip

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|----------------|-------------|-----|
| DC Supply Voltage | VDD - VSS | 3 to 15 | Vdc |
| Operating Temperature | T _A | | |
| C, D, F, H Device | | -55 to +125 | °C |
| E Device | | -40 to +85 | °C |

BLOCK DIAGRAM



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|------------|-------------------------------|------|-------|------|------|--------------------------------|------|------------------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | 5 | — | 5 | — | 0.05 | 5 | — | 150 | μA _{dc} |
| | | 10 | — | 10 | — | 0.1 | 10 | — | 300 | |
| | | 15 | — | 15 | — | 0.2 | 20 | — | 600 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.

= -40°C for E device.


T_{HIGH} = +125°C for C, D, F, H device.

= + 85°C for E device.


DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETER | | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|---|-------------------------------------|--------------------------|--------------------|-------------------|-------------------|-------|
| CLOCKED OPERATION | | | | | | |
| PROPAGATION DELAY TIME | t _{PLH} , t _{PHL} | 5 10 15 | — — — | 250 100 90 | 500 200 180 | ns |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 10 15 | — — — | 100 50 40 | 200 100 80 | ns |
| MINIMUM CLOCK PULSE WIDTH | PW _{CL} | 5 10 15 | — — — | 200 100 80 | 400 200 160 | ns |
| MAXIMUM CLOCK FREQUENCY | f _{CL} | 5 10 15 | 1.25 2.5 3.0 | 2.5 5.0 6.0 | — — — | MHz |
| MAXIMUM CLOCK RISE AND FALL TIME ¹ | t _{rCL} , t _{fCL} | 5 10 15 | 15 15 5 | — — — | — — — | μs |
| MINIMUM DATA INPUT DATA SETUP TIME | t _{setup} | 5 10 15 | — — — | 150 50 40 | 300 100 80 | ns |
| MINIMUM DATA INPUT HOLD TIME | t _{hold} | 5 10 15 | — — — | 0 0 0 | 50 25 15 | ns |
| RESET OPERATION | | | | | | |
| PROPAGATION DELAY TIME | t _{PHL} | 5 10 15 | — — — | 200 100 90 | 400 200 180 | ns |
| MINIMUM RESET PULSE WIDTH | PW _R | 5 10 15 | — — — | 200 80 60 | 400 160 120 | ns |
| RESET REMOVAL TIME | t _{rem} | 5 10 15 | — — — | 375 125 100 | 750 250 200 | ns |

¹ When units are cascaded, the maximum rise and fall times of the clock input should be equal to or less than the transition times of the data outputs driving data inputs, plus the propagation delay of the output driving stage for the output capacitive load.



Typical P-Channel
Source Current Characteristics



Typical N-Channel
Sink Current Characteristics

CMOS QUAD ANALOG SWITCH


FEATURES

- ◆ Wide Range of Digital and Analog Signal Levels- Digital or Analog Signals to 18 Volts peak
- ◆ Low ON Resistance — 200 Ω typ. over 15Vp-p Signal Input Range, @ 15Vdc
- ◆ Matched Switch Characteristics - 10 Ω typ. Difference between R_{ON} Values at a Fixed Bias Point over 15Vp-p Signal Input Range @ 15Vdc
- ◆ High On/Off Output Voltage Ratio - 65 dB typ. @ $f_{is} = 10\text{kHz}$, $R_L = 10\text{k}\Omega$
- ◆ High degree of Linearity - $\leq 0.4\%$ Distortion typ. @ $f_{is} = 1\text{kHz}$, $V_{is} = 5\text{V}_{p-p}$, $V_{DD}-V_{SS} \geq 10\text{V}$, $R_L = 10\text{k}\Omega$
- ◆ Extremely Low OFF Switch Leakage Resulting in Very Low Offset Current and High Effective OFF resistance - 10pA typ. @ $V_{DD}-V_{SS} = 10\text{V}$, $T_A = 25^\circ\text{C}$
- ◆ Extremely High Control Input Impedance (Control Circuit Isolated from Signal Circuit) 10¹² Ω typ.
- ◆ Low Crosstalk between Switches - -50dB typ. @ $f_{is} = 0.9\text{MHz}$, $R_L = 1\text{k}\Omega$
- ◆ Matched Control-Input to Signal-Output Capacitances - Reduces Output Signal Transients
- ◆ Transmits Frequencies up to 40MHz



DESCRIPTION

The 4016B is a single-chip monolithic silicon integrated circuit containing eight N-channel and eight P-channel enhancement-mode MOS transistors connected to form four independent bilateral signal switches. Each switch consists of both P- and N-channel devices with common source and drain connections. A single control signal is required per switch. Both P and N devices in a given switch are biased ON or OFF by the control signal. The CMOS switch permits peak input-signal voltage swings equal to the full supply voltage, a considerable advantage over single-channel types.

SCHEMATIC DIAGRAM



LOGIC DIAGRAM



RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|------------------|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | -55 to +125 | $^\circ\text{C}$ |
| C, D, F, H Device | | -40 to +85 | $^\circ\text{C}$ |
| E Device | | | |

ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | CONDITIONS | V _{SS} (Vdc) | V _{DD} (Vdc) | T _{LOW} ² | | 25°C | | | T _{HIGH} ² | | Units |
|---|---|--|--------------------------|-------------------------------|--------------------|-------------------|--------------------------|--------------------|--------------------------------|--------------------|-------|
| | | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} V _{IN} = V _{SS} or V _{DD} All valid input combinations | 0 0 0 | 5 10 15 | — — — | 0.05 0.1 0.2 | — — — | 0.0005 0.001 0.002 | 0.05 0.1 0.2 | — — — | 1.5 3.0 6.0 | μAdc |
| MINIMUM INPUT HIGH VOLTAGE (Control Input) | V _{IH} | 0 0 0 | 5 10 15 | — — — | 3.5 7.0 11.0 | — — — | 1.5 1.5 1.5 | 3.5 7.0 11.0 | — — — | 3.5 7.0 11.0 | Vdc |
| MAXIMUM INPUT LOW VOLTAGE (Control Input) | V _{IL} V _{IS} = V _{SS} V _{OS} = V _{DD} I _{OS} = 10μA | 0 0 0 | 5 10 15 | 0.9 0.9 0.9 | — — — | 0.7 0.7 0.7 | 1.5 1.5 1.5 | — — — | 0.4 0.4 0.4 | — — — | Vdc |
| SWITCH INPUT/OUTPUT LEAKAGE (Switch off) | I _{OFF} V _C = V _{SS} V _{IS} = V _{DD} | 0 | 15 | — — | ±0.1 — | — — | ±10 ⁻⁵ — | ±0.1 — | — — | ±1.0 — | μAdc |
| ON-RESISTANCE | R _{ON} V _{IS} = V _{DD} - V _{SS} V _C = V _{DD} 2 R _L = 10kΩ | 0 0 | 15 10 | — — | 360 600 | — — | 200 250 | 400 660 | — — | 520 840 | Ω |
| ON-RESISTANCE MATCH (Same package) | ΔR _{ON} V _C = V _{DD} R _L = 10kΩ | V _{IS} (Vdc) ±7.5 ±5 | | — — — | — — — | — — — | 10 15 | — — — | — — — | — — — | Ω |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications."² T_{LOW} = -55°C for C, D, F, H device.

= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.

= + 85°C for E device.

³ Conditions for measuring V_{IH}:

| V _{DD} | V _{OS} | V _{IS} | I _{OS} T _{LOW} | 25°C | T _{HIGH} | UNITS |
|-----------------|-----------------|-----------------|-------------------------------------|-------|-------------------|-------|
| 5 | 5 | 4.6 | -25 | -20 | -14 | mA |
| 10 | 10 | 9.5 | -62 | -50 | -35 | |
| 15 | 15 | 13.5 | -1.8 | -1.50 | -1.10 | |

DYNAMIC CHARACTERISTICS (C_L = 50 pF, T_A = 25°C)

| PARAMETER | CONDITIONS | V _{SS} (Vdc) | V _{DD} (Vdc) | Min. | Typ. | Max. | UNIT |
|---|--|---|--------------------------|------------------------|------------------------|----------------------|------|
| SIGNAL INPUTS (V _{IS}) AND OUTPUTS (V _{OS}) | | | | | | | |
| PROPAGATION DELAY TIME Signal input to signal output | t _{PLH} , t _{PHL} V _C = V _{DD} V _{IS} = square wave R _L = 10kΩ | 0 0 0 | 5 10 15 | — — — | 20 10 7.5 | 40 20 15 | ns |
| BANDWIDTH (-3dB) (Sine Wave) | BW V _C = V _{DD} V _{IS} = 5V _{pp} centered @0.0Vdc | R _L 1kΩ 10kΩ 100kΩ 1MΩ | | -5 — — — — | +5 — — — — | 54 40 38 37 | MHz |

ELECTRICAL CHARACTERISTICS (Continued)


DYNAMIC CHARACTERISTICS ($C_L = 50 \text{ pF}$, $T_A = 25^\circ\text{C}$) (Continued)

| PARAMETER | | | CONDITIONS | V _{SS} (Vdc) | V _{DD} (Vdc) | Min. | Typ. | Max. | Units | |
|---|--|--|--|---|--------------------------|---------------|------------------|---------------------------|------------------|----------------|
| SIGNAL INPUTS (V _{IS}) AND OUTPUTS (V _{OS}) (Continued) | | | | | | | | | | |
| INSERTION LOSS (= 20 log $10 \frac{V_{OS}}{V_{IS}}$) | | | V _C = V _{DD} V _{IS} = 5V _{pp} centered @0.0Vdc | R _L 1kΩ 10kΩ 100kΩ 1MΩ | -5 | +5 | - - - - | 2.3 0.2 0.1 0.05 | - - - - | dR |
| SIGNAL DISTORTION (Sine Wave) | | | V _C = V _{DD} V _{IS} = 5V _{pp} centered @0.0Vdc f _{IS} = 1.0kHz R _L = 10kΩ | | -5 | +5 | - | 0.4 | - | % |
| FEEDTHROUGH (-50dB) | | | V _C = V _{SS} V _{IS} = 5V _{pp} centered @0.0Vdc | R _L 1kΩ 10kΩ 100kΩ 1MΩ | 5 | +5 | - - - - | 1250 140 18 2 | - - - - | kHz |
| CROSSTALK (-50dB) (Between two switches) | | | V _C (A) = V _{DD} V _C (B) = V _{SS} V _{IS} (A) = 5V _{pp} centered @0.0Vdc R _L = 1.0k | | -5 | +5 | - | 0.9 | - | MHz |
| CAPACITANCE Input Output Feedthrough | C _{IS} C _{OS} C _{IOS} | | V _C = V _{SS} | | 5 | +5 | - - - | 4 4 0.2 | - - - | pF pF pF |
| CONTROL INPUT (V _C) | | | | | | | | | | |
| PROPAGATION DELAY TIME Turn on | t _{PLH} t _{PHL} | | V _{SS} ≤ V _{IS} ≤ V _{DD} R _L = 10kΩ | | 0 0 0 | 5 10 15 | - - - | 40 20 15 | 80 40 30 | ns |
| MAXIMUM INPUT FREQUENCY | f _C | | V _{SS} ≤ V _{IS} ≤ V _{DD} R _L = 1.0kΩ | | 0 0 0 | 5 10 15 | - - - | 5 10 12 | - - - | MHz |
| CROSSTALK (To signal port) | | | V _C = Square wave R _L = 10kΩ R _{IN} = 1.0kΩ | | 0 0 0 | 5 10 15 | - - - | 30 50 100 | - - - | mV |


TYPICAL ON-RESISTANCE CHARACTERISTICS

| CHARACTERISTIC* | SUPPLY CONDITIONS | | LOAD CONDITIONS | | | | | |
|-----------------|-------------------|-----------------|-------------------------|-----------------|--------------------------|-----------------|---------------------------|-----------------|
| | | | $R_L = 1\text{k}\Omega$ | | $R_L = 10\text{k}\Omega$ | | $R_L = 100\text{k}\Omega$ | |
| | V_{DD} (V) | V_{SS} (V) | VALUE (Ω) | V_{IS} (V) | VALUE (Ω) | V_{IS} (V) | VALUE (Ω) | V_{IS} (V) |
| R_{ON} | +15 | 0 | 200 | +15 | 200 | +15 | 180 | +15 |
| $R_{ON(max.)}$ | +15 | 0 | 200 | 0 | 200 | 0 | 200 | 0 |
| R_{ON} | +10 | 0 | 290 | +10 | 250 | +10 | 240 | +10 |
| $R_{ON(max.)}$ | +10 | 0 | 290 | 0 | 250 | 0 | 300 | 0 |
| R_{ON} | +5 | 0 | 880 | +5 | 470 | +5 | 450 | +5 |
| $R_{ON(max.)}$ | +5 | 0 | 600 | 0 | 580 | 0 | 800 | 0 |
| R_{ON} | +7.5 | -7.5 | 200 | +7.5 | 200 | +7.5 | 180 | +7.5 |
| $R_{ON(max.)}$ | +7.5 | -7.5 | 200 | -7.5 | 200 | -7.5 | 180 | -7.5 |
| R_{ON} | +5 | -5 | 260 | +5 | 250 | +5 | 240 | +5 |
| $R_{ON(max.)}$ | +5 | -5 | 310 | -5 | 250 | -5 | 240 | -5 |
| R_{ON} | +2.5 | -2.5 | 590 | +2.5 | 450 | +2.5 | 490 | +2.5 |
| $R_{ON(max.)}$ | +2.5 | -2.5 | 720 | -2.5 | 520 | -2.5 | 520 | -2.5 |
| R_{ON} | +2.5 | -2.5 | 232k | +2.5 | 300k | +2.5 | 870k | +2.5 |


* Variation from a perfect switch; $R_{ON} = 0\Omega$.




Typ. ON characteristics for 1 of 4 switches
 with $V_{DD} = +15V$, $V_{SS} = 0V$




Typ. ON characteristics for 1 of 4 switches
 with $V_{DD} = +10V$, $V_{SS} = 0V$




Typ. ON characteristics for 1 of 4 switches
 with $V_{DD} = +5V$, $V_{SS} = 0V$




Typ. ON characteristics for 1 of 4 switches
 with $V_{DD} = +7.5V$, $V_{SS} = -7.5V$




Typ. ON characteristics for 1 of 4 switches
 with $V_{DD} = +5V$, $V_{SS} = -5V$




Typ. ON characteristics for 1 of 4 switches
 with $V_{DD} = +2.5V$, $V_{SS} = -2.5V$




Typ. switch frequency response - switch ON



Typ. feedthru vs. freq. - switch OFF






Typ. crosstalk between switch circuits in the same package



Crosstalk-control input to signal output

APPLICATIONS INFORMATION



LOGIC FUNCTIONS USING THE 4016B




APPLICATIONS INFORMATION (Continued)

LATCHING DPDT SWITCH

The latch feature insures positive switching action in response to non-repetitive or erratic commands. A HIGH input to A₁ turns S₃ and S₄ ON, a HIGH to A₂ turns S₁ and S₂ ON. Desirable for use with limit detectors, peak detectors, or mechanical contact closures.



Digitally controlled resistor network



Digitally-controlled capacitor network.
(V_{C1} → V_{C7} are Select Inputs)

CMOS DECADE COUNTER/DIVIDER

FEATURES

- ◆ 10 Decoded Decimal Outputs
- ◆ Direct Reset
- ◆ Trigger from either Edge of Clock Input
- ◆ Carry Output for Cascading Stages
- ◆ Fully Static Operation—DC to 12MHz @ 10Vdc

DESCRIPTION

The 4017B consists of a 5-stage Johnson Decade Counter and an Output Decoder. Inputs include Clock, Reset, and Clock Enable signals.

The counter has interchangeable Clock and Clock Enable lines for incrementing on either a positive-going or negative-going transition, respectively. A high Reset signal clears the counter to its zero count.

Use of the Johnson decade counter configuration permits high-speed operation, 2-input decode gating, and spike-free decoded outputs. Anti-lock gating is provided, thus assuring proper counting sequence. The 10 decoded outputs are normally low and go high only at their respective decoded time slot. Each decoded output remains high for one full clock cycle. A Carry-out (C_{OUT}) signal completes one cycle every 10 clock input cycles and is used to directly clock the succeeding counter in multi-stage applications.

This part can be used in frequency division circuits as well as decade counter or decimal decode display applications.


FUNCTIONAL TRUTH TABLE
(Positive Logic)

| Clock | Clock Enable | Reset | Decode Output = n |
|-------|--------------|-------|-------------------|
| 0 | X | 0 | n |
| X | 1 | 0 | n |
| X | X | 1 | "0" |
| | 0 | 0 | n + 1 |
| | X | 0 | n |
| X | | 0 | n |
| 1 | | 0 | n + 1 |

x = Don't Care

If n < 5 Carry = "1", Otherwise = "0"

CONNECTION DIAGRAM
(all packages)



RECOMMENDED OPERATING CONDITIONS

For maximum reliability:


DC Supply Voltage $V_{DD} - V_{SS}$ 3 to 15 Vdc

Operating Temperature T_A

C, D, F, H Device -55 to +125 °C

E Device -40 to +85 °C

BLOCK DIAGRAM



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS ¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|-----------------------------|--------------------------|------------|-------------------------------|------|-------|------|------|--------------------------------|------|-----------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | 5 | — | 5 | — | 0.05 | 5 | — | 150 | μ Adc |
| | | 10 | — | 10 | — | 0.1 | 10 | — | 300 | |
| | | 15 | — | 20 | — | 0.2 | 20 | — | 600 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.

= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.

= + 85°C for E device.

ELECTRICAL CHARACTERISTICS

DYNAMIC CHARACTERISTICS ($C_L = 50\text{pF}$, $T_A = 25^\circ\text{C}$)

| PARAMETER | | V _{DD} (V _{dc}) | Min. | Typ. | Max. | Units | |
|--|-------------------------------------|---------------------------------------|----------|------|------|-------|----|
| CLOCKED OPERATION | | | | | | | |
| PROPAGATION DELAY TIME To Decoded Outputs | t _{PLH} , t _{PHL} | 5 | -- | 350 | 700 | ns | |
| | | 10 | -- | 200 | 400 | | |
| | | 15 | -- | 150 | 300 | | |
| | To Carry Output | t _{PLH} , t _{PHL} | 5 | -- | 325 | 650 | ns |
| | | | 10 | -- | 175 | 350 | |
| | | | 15 | -- | 125 | 250 | |
| OUTPUT TRANSITION TIME Decoded Outputs | t _{TLH} , t _{THL} | 5 | -- | 100 | 200 | ns | |
| | | 10 | -- | 50 | 100 | | |
| | | 15 | -- | 40 | 80 | | |
| | Carry Output | t _{TLH} , t _{THL} | 5 | -- | 100 | 200 | ns |
| | | | 10 | -- | 50 | 100 | |
| | | | 15 | -- | 40 | 80 | |
| MINIMUM CLOCK PULSE WIDTH | PW _{CL} | 5 | -- | 100 | 200 | ns | |
| | | 10 | -- | 40 | 70 | | |
| | | 15 | -- | 30 | 60 | | |
| MAXIMUM CLOCK FREQUENCY | f _{CL} | 5 | 2.5 | 5.0 | -- | MHz | |
| | | 10 | 7.0 | 12.0 | -- | | |
| | | 15 | 9.3 | 16.0 | -- | | |
| MAXIMUM CLOCK OR ENABLE RISE AND FALL TIME | t _{rCL} , t _{fCL} | 5 10 15 | NO LIMIT | | | | |
| MINIMUM ENABLE SETUP TIME | t _{setup} | 5 | -- | 100 | 300 | ns | |
| | | 10 | -- | 50 | 100 | | |
| | | 15 | -- | 35 | 70 | | |
| MINIMUM ENABLE REMOVAL TIME | t _{rem} | 5 | -- | 250 | 500 | ns | |
| | | 10 | -- | 100 | 200 | | |
| | | 15 | -- | 75 | 150 | | |
| RESET OPERATION | | | | | | | |
| PROPAGATION DELAY TIME To Decoded Outputs | t _{PLH} , t _{PHL} | 5 | -- | 325 | 650 | ns | |
| | | 10 | -- | 175 | 350 | | |
| | | 15 | -- | 125 | 250 | | |
| | To Carry Output | t _{PLH} , t _{PHL} | 5 | -- | 325 | 650 | ns |
| | | | 10 | -- | 175 | 350 | |
| | | | 15 | -- | 125 | 250 | |
| MINIMUM RESET PULSE WIDTH | PW _R | 5 | -- | 150 | 300 | ns | |
| | | 10 | -- | 75 | 150 | | |
| | | 15 | -- | 60 | 120 | | |
| RESET REMOVAL TIME | t _{rem} | 5 | -- | 250 | 500 | ns | |
| | | 10 | -- | 100 | 200 | | |
| | | 15 | -- | 80 | 160 | | |

STATIC CHARACTERISTICS¹

| PARAMETER | V_{DD} | CONDITIONS | T_{LOW}^2 | | 25°C | | | T_{HIGH}^2 | | Units |
|------------------|----------|-------------------------------|-------------|-----|------|-----|-----|--------------|-----|------------------|
| | | | Min | Max | Min | Typ | Max | Min | Max | |
| QUIESCENT DEVICE | 5 | $V_{IN} = V_{SS}$ or V_{DD} | -- | 5 | -- | -- | 5 | -- | 150 | µA _{dc} |
| CURRENT | 10 | All Valid Input | -- | 10 | -- | -- | 10 | -- | 300 | |
| | 15 | Combinations | -- | 20 | -- | -- | 20 | -- | 600 | |


NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications"² T_{LOW} = -55°C for C, D, F, H devices.

= -40°C for E devices.


 T_{HIGH} = +125°C for C, D, F, H devices.

= +85°C for E devices.

AC MEASUREMENT DEFINITION AND FUNCTIONAL WAVEFORMS




LOGIC DIAGRAM



APPLICATIONS INFORMATION

COUNTER EXPANSION


This figure shows a technique for extending the number of decoded output states for the 4017B. Decoded outputs are sequential within each stage and from stage to stage, with no dead time (except propagation delay).



DIVIDE-BY-N COUNTER

When the Nth decoded output is reached (Nth clock pulse), the S-R flip-flop (constructed from the 4001B) generates a reset pulse which clears the 4017B to its zero count. At this time, if the Nth decoded output is greater than or equal to 6, the C_{OUT} line goes high to clock the next counter section. The "0" decoded output also goes high at this time. Coincidence of the clock "low" and decoded "0" output "high" resets the S-R flip-flop to enable the 4017B.

If the Nth decoded output is less than 6, the C_{OUT} line will not go high, and, therefore, cannot be used. In this case, the "0" decoded output may be used to perform the clock function for the next counter.



CMOS PRESETTABLE TABLE DIVIDE-BY-N COUNTER

FEATURES


- ◆ Divide by any Number Between 2 and 10 with One External Gate
- ◆ Johnson Counter Configuration for Spike-Free Counting
- ◆ Fully Static operation - DC to 5MHz @ 10Vdc

DESCRIPTION


The 4018B consists of 5 Johnson-Counter stages, buffered Q outputs from each stage, and counter preset control gating. Clock, Reset, Data, Preset Enable, and 5 individual Jam inputs are provided. Divide-by 10, 8, 6, 4, or 2 counter configurations can be implemented by feeding the Q5, Q4, Q3, Q2, Q1 signals, respectively, back to the Data input. Divide-by-9, 7, 5, or 3 counter configurations can be implemented by use of a single SCL4081B gate to properly gate the feedback connections to the Data input. Divide-by functions greater than 10 can be achieved by use of multiple 4018B units. The counter is advanced one count at the positive clock-signal transition. A high Reset signal clears the counter to an all-zero condition. A high Preset-Enable signal allows information on the Jam inputs to preset the counter. Reset and Preset gating is provided to assure the proper counting sequence.

This device is particularly useful in frequency-division and control applications.

TIMING DIAGRAM



CONNECTION DIAGRAM (all packages)



Add suffix for package:

- C 16-pin Cerdip
- D 16-pin Ceramic
- E 16-pin Epoxy
- F 16-pin Flat
- H Chip

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:


DC Supply Voltage $V_{DD} - V_{SS}$ 3 to 15 Vdc

Operating Temperature T_A

C, D, F, H Device -55 to +125 °C

E Device -40 to +85 °C

BLOCK DIAGRAM



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|--|-------------------------------|------|-------|------|------|--------------------------------|------|------------------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | V _{IN} = V _{SS} or V _{DD} All valid input combinations | — | 5 | — | 0.05 | 5 | — | 150 | μA _{dc} |
| | | | — | 10 | — | 0.1 | 10 | — | 300 | |
| | | | — | 20 | — | 0.2 | 20 | — | 600 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.

= -40°C for E device.


T_{HIGH} = +125°C for C, D, F, H device.

= + 85°C for E device.


DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETER | | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|--|-------------------------------------|--------------------------|--------------------|-------------------|--------------------|-------|
| CLOCKED OPERATION | | | | | | |
| PROPAGATION DELAY TIME | t _{PLH} , t _{PHL} | 5 10 15 | — — — | 500 150 120 | 1000 300 240 | ns |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 10 15 | — — — | 130 65 50 | 260 130 100 | ns |
| MINIMUM CLOCK PULSE WIDTH | PW _{CL} | 5 10 15 | — — — | 200 100 80 | 400 200 160 | ns |
| MAXIMUM CLOCK FREQUENCY | f _{CL} | 5 10 15 | 1.25 2.5 3.0 | 2.5 5.0 6.0 | — — — | MHz |
| MAXIMUM CLOCK RISE AND FALL TIME ¹ | t _{rCL} , t _{fCL} | 5 10 15 | 15 15 5 | — — — | — — — | μs |
| MINIMUM DATA INPUT SETUP TIME | t _{setup} | 5 10 15 | — — — | 200 100 80 | 400 200 160 | ns |
| MINIMUM DATA INPUT HOLD TIME | t _{hold} | 5 10 15 | — — — | 0 0 0 | 100 50 40 | ns |
| PRESET OR RESET OPERATION | | | | | | |
| PROPAGATION DELAY TIME From PE or Reset Input | t _{PLH} , t _{PHL} | 5 10 15 | — — — | 500 250 200 | 1000 500 400 | ns |
| MINIMUM PRESET OR RESET PULSE WIDTH | PW _{PR} , PW _R | 5 10 15 | — — — | 200 100 80 | 400 200 160 | ns |
| MINIMUM JAM INPUT SETUP TIME | t _{setup} | 5 10 15 | — — — | 200 100 80 | 400 200 160 | ns |
| PRESET OR RESET REMOVAL TIME | t _{rem} | 5 10 15 | — — — | 375 125 90 | 750 250 180 | ns |

¹ When units are cascaded, the maximum rise and fall times of the clock input should be equal to or less than the transition times of the data outputs driving data inputs, plus the propagation delay of the output driving stage for the output capacitive load.




Typical P-Channel
Source Current Characteristics




Typical N-Channel
Sink Current Characteristics

LOGIC DIAGRAM



TYPICAL COUNTER STAGE



EXTERNAL CONTROL CONNECTIONS

EXTERNAL CONNECTIONS FOR DIVIDE
BY 10 9 8 7 6 5 4 3 OPERATION


DIVIDE BY 10
DIVIDE BY 8
DIVIDE BY 6
DIVIDE BY 4
DIVIDE BY 2

Q₅
Q₄
Q₃
Q₂
Q₁

CONNECTED
BACK TO
DATA

NO EXTERNAL
COMPONENTS
REQUIRED

÷3 ÷5 ÷7 ÷9
Q₁ Q₂ Q₃ Q₄
Q₂ Q₃ Q₄ Q₅



CONNECTED BACK TO DATA
INPUTS ALL TO DATA

CMOS QUAD AND-OR SELECT GATE

FEATURES

- ◆ Replaces Three Simple Gate Packages
- ◆ Medium Speed Operation
- ◆ All Inputs Diode-Protected
- ◆ All Outputs Buffered


DESCRIPTION

The 4019B is comprised of four "AND-OR Select" gate configurations, each consisting of two 2-input AND gates driving a single 2-input OR gate. Selection is accomplished by control bits K_a and K_b . In addition to selection of either channel A or channel B information, the control bits can be applied simultaneously to accomplish the logical $A + B$ function.


TRUTH TABLE
(one of four gates)

| K_a | K_b | D |
|-------|-------|-----|
| 0 | 0 | 0 |
| 1 | 0 | A |
| 0 | 1 | B |
| 1 | 1 | A+B |

SCHEMATIC DIAGRAM
(one of four gates)



CONNECTION DIAGRAM
(all packages)



Add suffix for package:

- C 16-pin Cerdip
- D 16-pin Ceramic
- E 16-pin Epoxy
- F 16-pin Flat
- H Chip

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:


DC Supply Voltage $V_{DD} - V_{SS}$ 3 to 15 Vdc

Operating Temperature T_A

C, D, F, H Device -55 to +125 °C

E Device -40 to +85 °C

LOGIC DIAGRAM



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹


| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|--|-------------------------------|------|-------|-------|------|--------------------------------|------|------------------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | 5 | — | 1.0 | — | 0.005 | 1.0 | — | 30 | μA _{dc} |
| | 10 | V _{IN} = V _{SS} or V _{DD} | — | 2.0 | — | 0.01 | 2.0 | — | 60 | |
| | 15 | All valid input combinations | — | 4.0 | — | 0.02 | 4.0 | — | 120 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".
² T_{LOW} = -55°C for C, D, F, H device.
= -40°C for E device.


T_{HIGH} = +125°C for C, D, F, H device.
= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)


| PARAMETER | | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|--|-------------------------------------|--------------------------|------|------|------|-------|
| PROPAGATION DELAY TIME From Any Input | t _{PLH} , t _{PHL} | 5 | — | 150 | 300 | ns |
| | | 10 | — | 60 | 120 | |
| | | 15 | — | 50 | 100 | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | — | 100 | 200 | ns |
| | | 10 | — | 50 | 100 | |
| | | 15 | — | 40 | 80 | |




Typical P-Channel
Source Current Characteristics



Typical N-Channel
Sink Current Characteristics



"Shift left/shift right" register.



"True/complement" selector.

CMOS 14-STAGE BINARY COUNTER

FEATURES


- ◆ 14 Fully Static Stages
- ◆ Buffered Outputs Available from 12 Stages
- ◆ Common Reset Line
- ◆ 8MHz Counting Rate @ 10Vdc
- ◆ All Inputs Buffered

DESCRIPTION

The 4020B consists of 14 ripple-carry binary counter stages with appropriate input buffers and reset circuitry. Buffered outputs are externally available from stages 1, and 4 through 14. The counter is reset to its "all zeroes" state by a high level on the Reset input. The counter is advanced one count on the negative-going transition of each input pulse. Isolation from external noise and the effects of loading is provided by output buffering.

Applications include time delay circuits, counter controls, and frequency-dividing circuits.

CONNECTION DIAGRAM (all packages)



Add suffix for package:

- C 16-pin Cerdip
- D 16-pin Ceramic
- E 16-pin Epoxy
- F 16-pin Flat
- H Chip

TRUTH TABLE

| CLOCK | RESET | OUTPUT STATE |
|-------|-------|-----------------------|
| | 0 | No Change |
| | 0 | Advance to next state |
| X | 1 | All Outputs are low |


X = Don't Care

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | | |
| C, D, F, H Device | | -55 to +125 | °C |
| E Device | | -40 to +85 | °C |

LOGIC DIAGRAM



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--|--------------------------|---|-------------------------------|------|-------|------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT I _{DD} | 5 | V _{IN} =V _{SS} or V _{DD} | — | 5 | — | 0.05 | 5 | — | 150 | μAdc |
| | 10 | All valid input combinations | — | 10 | — | 0.1 | 10 | — | 300 | |
| | 15 | | — | 20 | — | 0.2 | 20 | — | 600 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.


= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.


= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETER | | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|---------------------------------------|-------------------------------------|--------------------------|------|------|------|-------|
| CLOCKED OPERATION | | | | | | |
| PROPAGATION DELAY TIME Clock to Q1 | t _{PLH} , t _{PHL} | 5 | — | 180 | 360 | ns |
| | | 10 | — | 80 | 160 | |
| | | 15 | — | 65 | 130 | |
| Q _i to Q _i + 1 | t _{PLH} , t _{PHL} | 5 | — | 100 | 200 | ns |
| | | 10 | — | 40 | 80 | |
| | | 15 | — | 30 | 60 | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | — | 100 | 200 | ns |
| | | 10 | — | 40 | 80 | |
| | | 15 | — | 30 | 60 | |
| MINIMUM CLOCK PULSE WIDTH | PW _{CL} | 5 | — | 70 | 140 | ns |
| | | 10 | — | 30 | 60 | |
| | | 15 | — | 20 | 40 | |
| MAXIMUM CLOCK FREQUENCY | f _{CL} | 5 | 3.0 | 4.5 | — | MHz |
| | | 10 | 6.0 | 9.0 | — | |
| | | 15 | 7.5 | 11.0 | — | |
| MAXIMUM CLOCK RISE AND FALL TIME | t _{rCL} , t _{fCL} | 5 | — | 100 | 50 | μs |
| | | 10 | — | 100 | 50 | |
| | | 15 | — | 100 | 50 | |
| RESET OPERATION | | | | | | |
| PROPAGATION DELAY TIME | t _{PHL} | 5 | — | 200 | 400 | ns |
| | | 10 | — | 100 | 200 | |
| | | 15 | — | 75 | 150 | |
| MINIMUM RESET PULSE WIDTH | PW _R | 5 | — | 100 | 200 | ns |
| | | 10 | — | 40 | 80 | |
| | | 15 | — | 30 | 60 | |
| RESET REMOVAL TIME | t _{rem} | 5 | — | 150 | 300 | ns |
| | | 10 | — | 65 | 125 | |
| | | 15 | — | 40 | 75 | |




Typical P-Channel
Source Current Characteristics




Typical N-Channel
Sink Current Characteristics

TIMING DIAGRAM



TYPICAL COUNTER STAGE



CMOS 8-STAGE STATIC SHIFT REGISTER

FEATURES

- ◆ Asynchronous Parallel Input/Serial Output
- ◆ Synchronous Serial Input/Serial Output
- ◆ Fully Static Operation - DC to 8MHz @ 10Vdc
- ◆ Q Outputs from Stages 6, 7, and 8 Available


DESCRIPTION

The 4021B is an 8-Stage Parallel or Serial-Input/Serial-Output Shift Register having common Clock and Parallel/Serial Control inputs, a single Serial Data input, and individual parallel Jam inputs to each register stage. Each register stage is a D-type, master-slave flip-flop. "Q" outputs are available from the sixth, seventh, and eighth stages. When the Parallel/Serial Control input is low, data is serially shifted into the 8-stage register synchronously with the positive-going transition of the Clock pulse.

When the Parallel/Serial Control input is "high" data is jammed into the 8-stage register via the Parallel input line asynchronously with the Clock line.

Register expansion is possible using additional 4021B packages.

CONNECTION DIAGRAM (all packages)



Add suffix for package:

- C 16-pin Cerdip
- D 16-pin Ceramic
- E 16-pin Epoxy
- F 16-pin Flat
- H Chip

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | | |
| C, D, F, H Device | | -55 to +125 | °C |
| E Device | | -40 to +85 | °C |

TRUTH TABLE

SERIAL OPERATION:


| t | CLOCK | SER IN | P/S | Q6 t=n+6 | Q7 t=n+7 | Q8 t=n+8 |
|-----|-------|--------|-----|-------------|-------------|-------------|
| n | | 0 | 0 | 0 | ? | ? |
| n+1 | | 1 | 0 | 1 | 0 | ? |
| n+2 | | 0 | 0 | 0 | 1 | 0 |
| n+3 | | 1 | 0 | 1 | 0 | 1 |
| | | X | 0 | Q6 | Q7 | Q8 |

PARALLEL OPERATION:

| CLOCK | SER IN | P/S | PI-m | *Q _m |
|-------|--------|-----|------|-----------------|
| X | X | 1 | 0 | 0 |
| X | X | 1 | 1 | 1 |

*Q6, Q7, & Q8 are available externally
X = Don't Care

LOGIC DIAGRAM



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS ¹

| PARAMETER | | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|-----------------------------|-----------------|--------------------------|--|-------------------------------|------|-------|------|------|--------------------------------|------|-------|
| | | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | 5 | V _{IN} = V _{SS} or V _{DD} | — | 5 | — | 0.05 | 5 | — | 150 | μAdc |
| | | 10 | All valid input combinations | — | 10 | — | 0.01 | 10 | — | 300 | |
| | | 15 | | — | 20 | — | 0.2 | 20 | — | 600 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.

= -40°C for E device.


T_{HIGH} = +125°C for C, D, F, H device.

= + 85°C for E device.


DYNAMIC CHARACTERISTICS (C_L = 50 pF, T_A = 25°C)

| PARAMETER | | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|---|-------------------------------------|--------------------------|------|------|------|-------|
| PROPAGATION DELAY TIME | t _{PLH} , t _{PHL} | 5 | — | 180 | 360 | ns |
| From Clock or P/S Input | | 10 | — | 90 | 180 | |
| | | 15 | — | 75 | 150 | |
| | | | | | | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | — | 100 | 200 | ns |
| | | 10 | — | 50 | 100 | |
| | | 15 | — | 40 | 80 | |
| | | | | | | |
| MINIMUM CLOCK PULSE WIDTH | PW _{CL} | 5 | — | 90 | 180 | ns |
| | | 10 | — | 40 | 80 | |
| | | 15 | — | 25 | 50 | |
| | | | | | | |
| MAXIMUM CLOCK FREQUENCY | f _{CL} | 5 | 3 | 5 | — | MHz |
| | | 10 | 6 | 12 | — | |
| | | 15 | 8 | 16 | — | |
| | | | | | | |
| MAXIMUM CLOCK RISE & FALL TIME ¹ | t _{rCL} , t _{fCL} | 5 | 15 | — | — | μs |
| | | 10 | 15 | — | — | |
| | | 15 | 15 | — | — | |
| | | | | | | |
| MINIMUM P/S PULSE WIDTH | PW | 5 | — | 80 | 160 | ns |
| | | 10 | — | 40 | 80 | |
| | | 15 | — | 25 | 50 | |
| | | | | | | |
| MINIMUM SETUP TIME | t _{setup} | 5 | — | 60 | 120 | ns |
| Parallel or Serial Inputs | | 10 | — | 40 | 80 | |
| | | 15 | — | 30 | 60 | |
| | | | | | | |
| MINIMUM HOLD TIME | t _{hold} | 5 | — | 100 | 200 | ns |
| Parallel or Serial Inputs | | 10 | — | 30 | 60 | |
| | | 15 | — | 20 | 40 | |
| | | | | | | |
| P/S REMOVAL TIME | t _{rem} | 5 | — | 140 | 280 | ns |
| | | 10 | — | 70 | 140 | |
| | | 15 | — | 50 | 100 | |
| | | | | | | |

¹ When units are cascaded, the maximum rise and fall times of the clock input should be equal to or less than the transition times of the data outputs driving data inputs, plus the propagation delay of the output driving stage for the output capacitive load.




Typical P-Channel
Source Current Characteristics



Typical N-Channel
Sink Current Characteristics

TYPICAL REGISTER STAGE



FEATURES

- ◆ Eight Decoded Outputs
- ◆ Direct Reset
- ◆ Trigger from either Edge of Clock Input
- ◆ Carry Output for Cascading Stages
- ◆ Fully Static Operation - DC to 5MHz @ 10Vdc

DESCRIPTION





The 4022 B consists of a 4-stage Johnson Divide-by-8 Counter and an Output Decoder. Inputs include Clock, Reset, and Clock Enable signals.

The counter has interchangeable Clock and Clock Enable lines for incrementing on either a positive-going or negative-going transition, respectively. A high Reset signal clears the counter to its zero count.

Use of the Johnson divide-by-eight counter configuration permits high-speed operation, 2-input decode gating, and spike-free decoded outputs. Anti-lock gating is provided, thus assuring proper counting sequence. The 8 decoded outputs are normally low and go high only at their respective decoded time slot. Each decoded output remains high for one full clock cycle. A Carry-out (C_{OUT}) signal completes one cycle every 8 clock input cycles and is used to directly clock the succeeding counter in multi-stage applications.

This part can be used in frequency division circuits as well as octal counter or octal decode display applications.


FUNCTIONAL TRUTH TABLE
(Positive Logic)

| Clock | Clock Enable | Reset | Output = n |
|---|---|-------|------------|
| 0 | X | 0 | n |
| X | 1 | 0 | n |
|  | 0 | 0 | n + 1 |
|  | X | 0 | n |
| 1 |  | 0 | n + 1 |
| X |  | 0 | n |
| X | X | 1 | "0" |

X Don't Care If n < 4 Carry = 1, otherwise = 0

CMOS OCTAL COUNTER/DIVIDER

CONNECTION DIAGRAM
(all packages)



Add suffix for package:


- C 16-pin Cerdip
- D 16-pin Ceramic
- E 16-pin Epoxy
- F 16-pin Flat
- H Chip

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-----------------------------------|-------------|-----|
| DC Supply Voltage | V _{DD} - V _{SS} | 3 to 15 | Vdc |
| Operating Temperature | T _A | | |
| C, D, F, H Device | | -55 to +125 | °C |
| E Device | | -40 to +85 | °C |

BLOCK DIAGRAM



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS ¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|-----------------------------|--------------------------|------------|-------------------------------|------|-------|------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | 5 | — | 5 | — | 0.05 | 5 | — | 150 | μAdc |
| | | 10 | — | 10 | — | 0.1 | 10 | — | 300 | |
| | | 15 | — | 20 | — | 0.2 | 20 | — | 600 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.

= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.


= + 85°C for E device.

ELECTRICAL CHARACTERISTICS (Continued)


DYNAMIC CHARACTERISTICS ($C_L = 50\text{pF}$, $T_A = 25^\circ\text{C}$)

| PARAMETER | | V _{DD} (V _{dc}) | Min. | Typ. | Max. | Units | |
|---|-------------------------------------|---------------------------------------|------|------|------|-------|----|
| CLOCKED OPERATION | | | | | | | |
| PROPAGATION DELAY TIME | To Decoded Outputs | t _{PLH} , t _{PHL} | 5 | — | 600 | 1200 | ns |
| | | | 10 | — | 240 | 480 | |
| | | | 15 | — | 180 | 360 | |
| | To Carry Output | t _{PLH} , t _{PHL} | 5 | — | 500 | 1000 | ns |
| | | | 10 | — | 200 | 400 | |
| | | | 15 | — | 150 | 300 | |
| OUTPUT TRANSITION TIME | Decoded Outputs | t _{TLH} , t _{THL} | 5 | — | 250 | 500 | ns |
| | | | 10 | — | 125 | 250 | |
| | | | 15 | — | 90 | 180 | |
| | Carry Output | t _{TLH} , t _{THL} | 5 | — | 180 | 360 | ns |
| | | | 10 | — | 90 | 180 | |
| | | | 15 | — | 65 | 130 | |
| MINIMUM CLOCK PULSE WIDTH | PW _{CL} | 5 | — | 200 | 400 | ns | |
| | | 10 | — | 100 | 200 | | |
| | | 15 | — | 80 | 160 | | |
| MAXIMUM CLOCK FREQUENCY | f _{CL} | 5 | 1.25 | 2.5 | — | MHz | |
| | | 10 | 2.5 | 5.0 | — | | |
| | | 15 | 3.0 | 6.0 | — | | |
| MAXIMUM CLOCK OR ENABLE RISE AND FALL TIME | t _{rCL} , t _{fCL} | 5 | 15 | — | — | μs | |
| | | 10 | 15 | — | — | | |
| | | 15 | 5 | — | — | | |
| MINIMUM ENABLE SETUP TIME | t _{setup} | 5 | — | 175 | 350 | ns | |
| | | 10 | — | 75 | 150 | | |
| | | 15 | — | 55 | 110 | | |
| MINIMUM ENABLE REMOVAL TIME | t _{rem} | 5 | — | 250 | 500 | ns | |
| | | 10 | — | 100 | 200 | | |
| | | 15 | — | 75 | 150 | | |
| RESET OPERATION | | | | | | | |
| PROPAGATION DELAY TIME | To Decoded Outputs | t _{PLH} , t _{PHL} | 5 | — | 500 | 1000 | ns |
| | | | 10 | — | 200 | 400 | |
| | | | 15 | — | 140 | 280 | |
| | To Carry Output | t _{PLH} | 5 | — | 400 | 800 | ns |
| | | | 10 | — | 150 | 300 | |
| | | | 15 | — | 110 | 220 | |
| MINIMUM RESET PULSE WIDTH | PW _R | 5 | — | 150 | 300 | ns | |
| | | 10 | — | 75 | 150 | | |
| | | 15 | — | 60 | 120 | | |
| RESET REMOVAL TIME | t _{rem} | 5 | — | 250 | 500 | ns | |
| | | 10 | — | 100 | 200 | | |
| | | 15 | — | 80 | 160 | | |

AC MEASUREMENT DEFINITION AND FUNCTIONAL WAVEFORMS




LOGIC DIAGRAM



APPLICATIONS INFORMATION

COUNTER EXPANSION

This figure shows a technique for extending the number of decoded output states for the 4022 B. Decoded outputs are sequential within each stage and from stage to stage, with no dead time (except propagation delay).




DIVIDE-BY-N-COUNTER

When the Nth decoded output is reached (Nth clock pulse) the S-R flip-flop (constructed from the 4001B) generates a reset pulse which clears the 4022B to its zero count. At this time, if the Nth decoded output is greater than or equal to 4, the C_{OUT} line goes high to clock the next counter section. The "0" decoded output also goes high at this time. Coincidence of the clock "low" and de-

coded "0" output "high" resets the S-R flip-flop to enable the 4022B.

If the Nth decoded output is less than 4, the C_{OUT} line will not go high, and, therefore, cannot be used. In this case, the "0" decoded output may be used to perform the clock function for the next counter.



CMOS 7-STAGE BINARY COUNTER


FEATURES

- ◆ 7 Fully Static Stages
- ◆ Buffered Outputs Available from All Stages
- ◆ Common Reset Line
- ◆ 8 MHz Counting Rate @ 10Vdc
- ◆ All Inputs Buffered

DESCRIPTION

The 4024B is a single chip monolithic medium scale integrated circuit containing N-Channel and P-Channel enhancement-mode MOS transistors. Seven single-phase clocked counting stages are provided with the Q output of each stage accessible. The Counter is reset to "zero" by a high level on the Reset input. Each counter stage is a static master-slave flip-flop. The counter state is advanced one count on the negative-going transition of each input pulse.

CONNECTION DIAGRAM
(all packages)



TRUTH TABLE


| Clock | Reset | State |
|-------|-------|-------------------|
| 0 | 0 | No Change |
| 0 | 1 | All Outputs Low |
| 1 | 0 | No Change |
| 1 | 1 | All Outputs Low |
| | 0 | No Change |
| | 1 | All Outputs Low |
| | 0 | Advance One Count |
| | 1 | All Outputs Low |

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | | |
| C, D, F, H Device | | -55 to +125 | °C |
| E Device | | -40 to +85 | °C |

LOGIC DIAGRAM



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS ¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|------------|-------------------------------|------|-------|------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | 5 | — | 5 | — | 0.05 | 5 | — | 150 | μAdc |
| | | 10 | — | 10 | — | 0.1 | 10 | — | 300 | |
| | | 15 | — | 20 | — | 0.2 | 20 | — | 600 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.


= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.


= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50 pF, T_A = 25°C)

| PARAMETER | | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|---|-------------------------------------|--------------------------|------|------|------|-------|
| CLOCKED OPERATION | | | | | | |
| PROPAGATION DELAY TIME Clock to Q _i | t _{PLH} , t _{PHL} | 5 | — | 180 | 360 | ns |
| | | 10 | — | 80 | 160 | |
| | | 15 | — | 65 | 130 | |
| Q _i to Q _{i + 1} | t _{PLH} , t _{PHL} | 5 | — | 100 | 200 | ns |
| | | 10 | — | 40 | 80 | |
| | | 15 | — | 30 | 60 | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | — | 100 | 200 | ns |
| | | 10 | — | 50 | 100 | |
| | | 15 | — | 40 | 80 | |
| MINIMUM CLOCK PULSE WIDTH | PW _{CL} | 5 | — | 120 | 240 | ns |
| | | 10 | — | 60 | 120 | |
| | | 15 | — | 45 | 90 | |
| MAXIMUM CLOCK FREQUENCY | f _{CL} | 5 | 2 | 4 | — | MHz |
| | | 10 | 5 | 10 | — | |
| | | 15 | 6 | 12 | — | |
| MAXIMUM CLOCK RISE AND FALL TIME | t _{rCL} , t _{fCL} | 5 | 15 | — | — | μs |
| | | 10 | 10 | — | — | |
| | | 15 | 5 | — | — | |
| RESET OPERATION | | | | | | |
| PROPAGATION DELAY TIME | t _{PHL} | 5 | — | 200 | 400 | ns |
| | | 10 | — | 100 | 200 | |
| | | 15 | — | 80 | 160 | |
| MINIMUM RESET PULSE WIDTH | PW _R | 5 | — | 200 | 400 | ns |
| | | 10 | — | 100 | 200 | |
| | | 15 | — | 80 | 160 | |
| RESET REMOVAL TIME | t _{rem} | 5 | — | 200 | 400 | ns |
| | | 10 | — | 100 | 200 | |
| | | 15 | — | 80 | 160 | |




Typical P-Channel
Source Current Characteristics



Typical N-Channel
Sink Current Characteristics

TYPICAL COUNTER STAGE



CMOS DECADE 7-SEGMENT DECODERS

FEATURES

- ◆ Decade Counter and 7-Segment Decoder in One Package
- ◆ Easily Interfaced with 7-Segment Display Types
- ◆ Direct Reset
- ◆ Display Enable Function (4026AB)
- ◆ Ripple Blanking and Lamp Test Functions (4033AB)
- ◆ Trigger from either Edge of Clock Input
- ◆ Carry Output for Cascading Stages
- ◆ Fully Static Operation - DC to 5MHz @ 10Vdc

DESCRIPTION

These two devices each consist of a 5-stage Johnson Decade Counter and an Output Decoder which converts the Johnson code to a 7-segment decoded output for driving each stage in a numerical display. A high Reset signal clears the decade counter to its zero count. The counters have interchangeable Clock and Clock Enable lines for incrementing on either a positive-going or negative-going transition, respectively. Antilock gating is provided on the Johnson counter, thus assuring proper counting sequence. The Carry-Out (C_{OUT}) signal completes one cycle every ten clock input cycles and is used to directly clock the succeeding decade in a multi-decade counting chain.

4026AB


When the Display Enable is low, the seven decoded outputs are forced off regardless of the state of the counter. Activation of the display only when required results in significant power savings. This system also facilitates implementation of display-character multiplexing.

The Carry Out and ungated "C-segment" signals are not gated by the Display Enable and therefore are available continuously. This feature is a requirement in implementation of certain divider functions such as divide-by-60 and divide-by-12.

4033AB

The 4033AB has provisions for automatic blanking of the non-significant zeros in a multi-digit decimal number which results in an easily readable display consistent with normal writing practice. For example, the number 0050.0700 in an eight digit display would be displayed as 50.07. Zero suppression on the integer side is obtained by connecting the RBI terminal of the 4033AB associated with the most significant digit in the display to a "low-level" voltage and connecting the RBO terminal of that stage to the RBI terminal of the 4033AB in the next-lower-significant position in the display. This procedure is continued for each succeeding 4033AB on the integer side of the display. On the fraction side of the display the

CONNECTION DIAGRAM (all packages)



1 4026AB
2 4033AB

Add suffix for package:

| | |
|---|----------------|
| C | 16-pin Cerdip |
| D | 16-pin Ceramic |
| E | 16-pin Epoxy |
| F | 16-pin Flat |
| H | Chip |

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | -55 to +125 | °C |
| C, D, F, H Device | | -40 to +85 | °C |
| E Device | | | |


RBI of the 4033AB associated with the least significant digit is connected to a "low-level" voltage and the RBO of the 4033AB is connected to the RBI terminal of the 4033AB in the next-more-significant-digit position. Again, this procedure is continued for each 4033AB on the fraction side of the display.

In a purely fractional number the zero immediately preceding the decimal point can be displayed by connecting the RBI of that stage to a high voltage (instead of to the RBO of the next-more-significant stage). For Example: optional zero - 0.7346.


Likewise, the zero in a number such as 763.0 can be displayed by connecting the RBI of the 4033AB associated with it to a "high-level" voltage.

A "high" Lamp Test signal turns on all outputs.


LOGIC DIAGRAM



TIMING DIAGRAM




DISPLAY




4026AB Decode Counter/7-Segment Decoder with Display Enable


LOGIC DIAGRAM



TIMING DIAGRAM



DISPLAY



4033AB Decode Counter/7-Segment Decoder with Ripple Blanking

ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS ¹

| PARAMETER | | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units | |
|------------------------------|-----------------|--------------------------|---|---|-------|-------|-------|------|--------------------------------|-------|------------------|------------------|
| | | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | | |
| QUIESCENT DEVICE CURRENT | I _{DD} | 5 | V _{IN} =V _{SS} or V _{DD} | — | 5 | — | 0.05 | 5 | — | 150 | μAdc | |
| CURRENT | | 10 | All valid input combinations | — | 10 | — | 0.1 | 10 | — | 300 | | |
| | | 15 | | — | 20 | — | 0.2 | 20 | — | 600 | | |
| OUTPUT HIGH (SOURCE) CURRENT | I _{OH} | | | | | | | | | | | |
| Decoded outputs | | 5 | V _{OH} =4.6V | -0.175 | — | -0.14 | -0.28 | — | -0.10 | — | mA _{Dc} | |
| | | 10 | V _{OH} =9.5V | -0.375 | — | -0.3 | -0.6 | — | -0.21 | — | | |
| | | 15 | V _{OH} =13.5V | -1.25 | — | -1.0 | -2.5 | — | -0.7 | — | | |
| | | | V _{IN} =V _{SS} or V _{DD} | | | | | | | | | |
| Carry output | | 5 | V _{OH} =4.6V | -0.19 | — | -0.15 | -0.4 | — | -0.11 | — | mA _{Dc} | |
| | | 10 | V _{OH} =9.5V | -0.43 | — | -0.35 | -1.0 | — | -0.25 | — | | |
| | | 15 | V _{OH} =13.5V | -1.57 | — | -1.25 | -4.0 | — | -0.88 | — | | |
| | | | V _{IN} =V _{SS} or V _{DD} | | | | | | | | | |
| Remaining Outputs | | 5 | V _{OH} =4.6V | -0.10 | — | -0.08 | -0.2 | — | -0.056 | — | mA _{Dc} | |
| | | 10 | V _{OH} =9.5V | -0.25 | — | -0.20 | -0.5 | — | -0.14 | — | | |
| | | 15 | V _{OH} =13.5V | -0.75 | — | -0.60 | -1.5 | — | -0.42 | — | | |
| | | | V _{IN} =V _{SS} or V _{DD} | | | | | | | | | |
| OUTPUT LOW (SINK) CURRENT | | I _{OL} | | | | | | | | | | |
| All Outputs Except Carry | | | 5 | V _{OL} =0.4V | 0.125 | — | 0.1 | 0.3 | — | 0.07 | — | mA _{Dc} |
| | | | 10 | V _{OL} =0.5V | 0.31 | — | 0.25 | 0.6 | — | 0.175 | — | |
| | | | 15 | V _{OL} =1.5V | 1.44 | — | 1.15 | 2.5 | — | 0.81 | — | |
| | | | | V _{IN} =V _{SS} or V _{DD} | | | | | | | | |
| Carry output | 5 | | V _{OL} =0.4V | 0.19 | — | 0.15 | 0.4 | — | 0.11 | — | mA _{Dc} | |
| | 10 | | V _{OL} =0.5V | 0.45 | — | 0.35 | 1.0 | — | 0.25 | — | | |
| | 15 | | V _{OL} =1.5V | 1.57 | — | 1.25 | 4.0 | — | 0.88 | — | | |
| | | | V _{IN} =V _{SS} or V _{DD} | | | | | | | | | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.

= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.

= + 85°C for E device.




ELECTRICAL CHARACTERISTICS (Continued)

DYNAMIC CHARACTERISTICS ($C_L = 50\text{pF}$, $T_A = 25^\circ\text{C}$)

| PARAMETER | | V _{DD} (V _{DC}) | Min. | Typ. | Max. | Units |
|--|--|---------------------------------------|------|------|------|-------|
| CLOCKED OPERATION | | | | | | |
| PROPAGATION DELAY TIME Clock to Decoded Outputs | t _{PLH} , t _{PHL} | 5 | — | 500 | 1000 | ns |
| | | 10 | — | 225 | 450 | |
| | | 15 | — | 175 | 350 | |
| Clock to Carry Out | t _{PLH} , t _{PHL} | 5 | — | 450 | 900 | ns |
| | | 10 | — | 125 | 250 | |
| | | 15 | — | 100 | 200 | |
| OUTPUT TRANSITION TIME Decoded Outputs | t _{TLH} , t _{THL} | 5 | — | 250 | 500 | ns |
| | | 10 | — | 125 | 250 | |
| | | 15 | — | 100 | 200 | |
| Carry Output | t _{TLH} , t _{THL} | 5 | — | 200 | 400 | ns |
| | | 10 | — | 100 | 200 | |
| | | 15 | — | 80 | 160 | |
| MINIMUM CLOCK OR ENABLE PULSE WIDTH | PW _{CL} , PW _{CE} | 5 | — | 200 | 400 | ns |
| | | 10 | — | 100 | 200 | |
| | | 15 | — | 80 | 160 | |
| MAXIMUM CLOCK FREQUENCY | f _{CL} | 5 | 1.25 | 2.5 | — | MHz |
| | | 10 | 2.5 | 5.0 | — | |
| | | 15 | 3.0 | 6.0 | — | |
| MAXIMUM CLOCK OR ENABLE RISE AND FALL TIME | t _{rCL} , t _{fCL} | 5 | 15 | — | — | μs |
| | | 10 | 15 | — | — | |
| | | 15 | 3 | — | — | |
| MINIMUM CLOCK OR ENABLE SETUP TIME | t _{setup} | 5 | — | 250 | 500 | ns |
| | | 10 | — | 100 | 200 | |
| | | 15 | — | 80 | 160 | |
| RESET OPERATION | | | | | | |
| PROPAGATION DELAY TIME Reset to Decoded Outputs | t _{PLH} , t _{PHL} | 5 | — | 700 | 1400 | ns |
| | | 10 | — | 250 | 500 | |
| | | 15 | — | 200 | 400 | |
| Reset to Carry Output | t _{PLH} , t _{PHL} | 5 | — | 500 | 1000 | ns |
| | | 10 | — | 125 | 250 | |
| | | 15 | — | 100 | 200 | |
| MINIMUM RESET PULSE WIDTH | PW _R | 5 | — | 200 | 400 | ns |
| | | 10 | — | 100 | 200 | |
| | | 15 | — | 80 | 160 | |
| RESET REMOVAL TIME | t _{rem} | 5 | — | 375 | 750 | ns |
| | | 10 | — | 150 | 300 | |
| | | 15 | — | 125 | 250 | |

DISPLAY INTERFACE

LIGHT EMITTING DIODE DISPLAYS

LOW-POWER
INCANDESCENT READOUTSASSUMED
TRANSISTOR
CHARACTERISTICS

$\beta_{dc} (\text{min.}) \geq 30$
 $V_{CE}(\text{sat.}) \leq 0.50 \text{ V}$
 $@V_{DD} \geq 3.5 \text{ V (min.)}$
 $I_B \geq 0.25 \text{ mA (min.)}$
 $I_T \leq 7.5 \text{ mA (min.)}$

4049UB

$@V_{DD} = 10 \text{ V (min.)}$
 $V_O \text{ "0"} \leq 0.6 \text{ V}$
 $I_T = 8 \text{ mA (min.)}$
 $@V_{DD} = 6 \text{ V (min.)}$
 $V_O \text{ "0"} \leq 1.0 \text{ V}$
 $I_T = 5 \text{ mA (min.)}$
 $V_T \approx 1.5 \text{ V TO } 3.5 \text{ V}$


INCANDESCENT
READOUTSASSUMED
TRANSISTOR
CHARACTERISTICS

$\beta_{dc} (\text{min.}) \geq 25$
 $V_{CE}(\text{sat.}) \leq 0.50 \text{ V}$
 $@V_{DD} = 8 \text{ V (min.)}$
 $I_B = 1.0 \text{ mA (min.)}$
 $I_T = 24 \text{ mA (min.)}$

4049UB

$@V_{DD} = 10 \text{ V (min.)}$
 $V_O \text{ "0"} \leq 2 \text{ V}$
 $I_T = 20 \text{ mA (min.)}$
 $V_T \approx 3.5 \text{ V TO } 6 \text{ V}$


NEON READOUTS



TRANSISTOR CHARACTERISTICS

Leakage with transistor cutoff $\leq 0.05 \text{ mA}$
 $V_{BR} C_{ER} \dots > V_T$
 $\beta_{dc} (\text{min}) \geq 30$

LOW-VOLTAGE VACUUM FLUORESCENT READOUTS



TUBE REQUIREMENTS: 100 to 300 μA /segment at tube voltages of 12 V to 25 V depending on required brightness. Filament requirement 45 mA at 1.6 V, AC or DC.

CMOS DUAL J-K FLIP-FLOP


FEATURES

- ◆ Individual Set and Reset Controls
- ◆ Fully Static Operation
- ◆ Logic Edge-Clocked Design
- ◆ 8MHz Toggle Rate @ 10Vdc

DESCRIPTION

The 4027B consists of two identical independent CMOS J-K master-slave Flip-Flops. The 4027B is useful in performing control, register, and toggle functions. Logic levels present at the J and K inputs along with internal self-steering control the state of each flip-flop; changes in the flip-flop state are synchronous with the positive-going transition of the Clock pulse. Set and Reset functions are independent of the Clock and are initiated when a high level signal is present at either the Set or Reset input.

CONNECTION DIAGRAM (all packages)



Add suffix for package:

| | | | |
|---|----------------|---|-------------|
| C | 16-pin Cerdip | F | 16-pin Flat |
| D | 16-pin Ceramic | H | Chip |
| E | 16-pin Epoxy | | |

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | -55 to +125 | °C |
| C, D, F, H Device | | -40 to +85 | °C |
| E Device | | | |

TRUTH TABLE

| $\bullet t_{n-1}$ INPUTS | | | | | | $\dagger t_n$ OUTPUTS | |
|--------------------------|---|---|---|---|---|-----------------------|----|
| CL▲ | J | K | S | R | Q | Q | Q̄ |
| | 1 | X | 0 | 0 | 0 | 1 | 0 |
| | X | 0 | 0 | 0 | 1 | 1 | 0 |
| | 0 | X | 0 | 0 | 0 | 0 | 1 |
| | X | 1 | 0 | 0 | 1 | 0 | 1 |
| | X | X | 0 | 0 | X | (No Change) | |
| X | X | X | 1 | 0 | X | 1 | 0 |
| X | X | X | 0 | 1 | X | 0 | 1 |
| X | X | X | 1 | 1 | X | 1 | 1 |


WHERE 1 = HIGH LEVEL
0 = LOW LEVEL

▲ - LEVEL CHANGE
X - DON'T CARE


● t_{n-1} REFERS TO THE INTERVAL PRIOR TO THE POSITIVE CLOCK PULSE TRANSITION

† t_n REFERS TO THE TIME INTERVAL AFTER THE POSITIVE CLOCK PULSE TRANSITION

LOGIC DIAGRAM (one of two Flip-Flops)



BLOCK DIAGRAM



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|------------|-------------------------------|------|-------|-------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | 5 | — | 1.0 | — | 0.005 | 1.0 | — | 30 | μAdc |
| | | 10 | — | 2.0 | — | 0.01 | 2.0 | — | 60 | |
| | | 15 | — | 4.0 | — | 0.02 | 4.0 | — | 120 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.

= -40°C for E device.


T_{HIGH} = +125°C for C, D, F, H device.

= + 85°C for E device.


DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETER | | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|---|-------------------------------------|--------------------------|-------------------|------------------|-------------------|-------|
| CLOCKED OPERATION | | | | | | |
| PROPAGATION DELAY TIME | t _{PLH} , t _{PHL} | 5 10 15 | — — — | 150 65 50 | 300 130 100 | ns |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 10 15 | — — — | 100 50 40 | 200 100 80 | ns |
| MINIMUM CLOCK PULSE WIDTH | PW _{CL} | 5 10 15 | — — — | 165 60 50 | 330 120 100 | ns |
| MAXIMUM CLOCK FREQUENCY | f _{CL} | 5 10 15 | 1.5 4.0 5.0 | 3.0 8.0 10 | — — — | MHz |
| MAXIMUM CLOCK RISE AND FALL TIME ¹ | t _{rCL} , t _{fCL} | 5 10 15 | 15 5 3 | — — — | — — — | μs |
| MINIMUM SETUP TIME | t _{setup} | 5 10 15 | — — — | 100 50 40 | 200 100 80 | ns |
| MINIMUM HOLD TIME | t _{hold} | 5 10 15 | — — — | -25 -10 -5 | 0 0 0 | ns |
| SET AND RESET OPERATION | | | | | | |
| PROPAGATION DELAY TIME S to Q, R to Q | t _{PLH} | 5 10 15 | — — — | 150 65 50 | 300 130 100 | ns |
| MINIMUM SET AND RESET PULSE WIDTH | PW _S , PW _R | 5 10 15 | — — — | 100 50 40 | 200 100 80 | ns |
| SET AND RESET REMOVAL TIME | t _{rem} | 5 10 15 | — — — | 0 0 0 | 25 10 5 | ns |

¹ When units are cascaded, the maximum rise and fall times of the clock input should be equal to or less than the transition times of the data outputs driving data inputs, plus the propagation delay of the output driving stage for the output capacitive load.



Typical P-Channel
Source Current Characteristics



Typical N-Channel
Sink Current Characteristics

FEATURES

- ◆ BCD-to-Decimal or Binary-to-Octal Decoding
- ◆ Buffered Outputs go High on Selection
- ◆ Low Outputs for all Illegal Input Combinations

DESCRIPTION

The 4028B types are BCD-to-Decimal or Binary-to-Octal Decoders consisting of pulse shaping circuits on all 4 inputs, decoding/logic gates, and 10 output buffers. A BCD code applied to the four inputs, A to D, results in a high level at the selected one of 10 decimal decoded outputs. Similarly, a 3-bit binary code applied to inputs A through C is decoded in octal code at output 0 to 7. A high-level signal at the D input inhibits octal decoding and causes outputs 0 through 7 to go low. If unused, the D input must be connected to V_{SS} .


Expanded decoding such as binary-to-hexadecimal (1-of-16), etc., can be achieved by using other 4028B devices. This part is useful for code conversion, address decoding, memory selection control, demultiplexing, and readout decoding.

TRUTH TABLE

| Input | | | | Output | | | | | | | | | |
|-------|---|---|---|--------|---|---|---|---|---|---|---|---|---|
| D | C | B | A | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 |
| 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 |
| 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 |
| 0 | 0 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 |
| 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 |
| 0 | 1 | 0 | 1 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 |
| 0 | 1 | 1 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 |
| 0 | 1 | 1 | 1 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 1 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 1 | 0 | 0 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 1 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 1 | 0 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 1 | 1 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |

CMOS BCD-TO-DECIMAL DECODER

CONNECTION DIAGRAM
(all packages)



Add suffix for package:


- C 16-pin Cerdip
- D 16-pin Ceramic
- E 16-pin Epoxy
- F 16-pin Flat
- H Chip

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | -55 to +125 | °C |
| C, D, F, H Device | | -40 to +85 | °C |
| E Device | | | |

BLOCK DIAGRAM



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|--|-------------------------------|------|-------|------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | V _{IN} = V _{SS} or V _{DD} All valid input combinations | — | 5 | — | 0.05 | 5 | — | 150 | μAdc |
| | | | — | 10 | — | 0.1 | 10 | — | 300 | |
| | | | — | 20 | — | 0.2 | 20 | — | 600 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.


= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.


= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETER | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|------------------------|-------------------------------------|------|------|------|-------|
| PROPAGATION DELAY TIME | t _{PLH} , t _{PHL} | 5 | — | 150 | ns |
| | | 10 | — | 60 | |
| | | 15 | — | 50 | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | — | 90 | ns |
| | | 10 | — | 50 | |
| | | 15 | — | 40 | |




Typical P-Channel
Source Current Characteristics



Typical N-Channel
Sink Current Characteristics


LOGIC DIAGRAM



APPLICATIONS INFORMATION

CODE CONVERSION CIRCUIT


The circuit shown here converts any 4-bit code to a decimal or hexadecimal code. The table shows a number of codes and the decimal or hexadecimal number in these codes which must be applied to the input terminals of the 4028B to select a particular output. For example: in order to get a "high" on output No. 8 the input must be either an 8 expressed in 4-Bit Binary code, a 15 expressed in 4-Bit Gray code, or a 5 expressed in Excess-3 code.



| INPUTS | | | | INPUT CODES | | OUTPUT NUMBER | | | | | | | | | | | | | |
|--------|---|---|---|--------------|------------|---------------|------|-------|-------|---|---|---|---|---|---|---|---|---|---|
| | | | | 4-BIT BINARY | 4-BIT GRAY | | | | | | | | | | | | | | |
| D | C | B | A | Hexa Decimal | Decimal | EXCESS-3 | GRAY | ALNEN | 4-2-1 | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 |
| 0 | 0 | 0 | 0 | 0 | 0 | | | | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 0 | 0 | 0 | 1 | 1 | 1 | | | | | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 0 | 0 | 1 | 0 | 2 | 3 | | | | | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 0 | 0 | 1 | 1 | 3 | 2 | | | | | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 0 | 1 | 0 | 0 | 4 | 7 | 1 | 4 | 4 | | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 |
| 0 | 1 | 0 | 1 | 5 | 6 | 2 | | | | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 |
| 0 | 1 | 1 | 0 | 6 | 4 | 3 | 1 | 4 | | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 |
| 0 | 1 | 1 | 1 | 7 | 5 | 4 | 2 | | | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 |
| 1 | 0 | 0 | 0 | 8 | 15 | 5 | | | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 |
| 1 | 0 | 0 | 1 | 9 | 14 | 6 | | | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 |
| 1 | 0 | 1 | 0 | 10 | 12 | 7 | 9 | | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 |
| 1 | 0 | 1 | 1 | 11 | 13 | 8 | 5 | | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 |
| 1 | 1 | 0 | 0 | 12 | 8 | 9 | 5 | 8 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 |
| 1 | 1 | 0 | 1 | 13 | 9 | 6 | 7 | 7 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 |
| 1 | 1 | 1 | 0 | 14 | 11 | 8 | 8 | 8 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 |
| 1 | 1 | 1 | 1 | 15 | 10 | 7 | 9 | 9 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 |

Code Conversion Chart

6-BIT BINARY TO 1-OF-64 ADDRESS DECODER



CMOS PRESETTABLE UP/DOWN COUNTER

FEATURES

- ◆ Binary or Decade Up/Down Counting
- ◆ BCD Outputs in Decade Mode
- ◆ Asynchronous Preset Enable
- ◆ Internally Synchronous for High Speed
- ◆ Logic Edge-Clocked Design
- ◆ 6MHz Counting Rate @ 10Vdc
- ◆ Carry Output for Cascading Stages


DESCRIPTION

The 4029B consists of a four-stage Binary or BCD Decade Up/Down Counter with provisions for look-ahead carry in both counting modes. The inputs consist of a single Clock, Carry-in (Clock Enable), Binary/Decade, Up/Down, Preset Enable, and four individual Jam signals. Four separate buffered Q signals and a Carry-out signal are provided as outputs.

A high Preset Enable signal allows information on the Jam inputs to preset the counter to any state asynchronously with the Clock. A low on each Jam line, when the Preset/Enable signal is high, resets the counter to its zero count. The counter is advanced one count at the positive transition of the Clock when the Carry-in and Preset Enable signals are low. Advancement is inhibited when the Carry-in or Preset Enable signals are high. The Carry-out signal is normally high and goes low when the counter reaches its maximum count in the Up mode or the minimum count in the Down mode provided the Carry-in signal is low. The Carry-in signal in the low state can thus be considered a "Clock Enable". The Carry-in terminal must be connected to V_{SS} when not in use.

Binary counting is accomplished when the Binary/Decade input is high; the counter counts in the Decade mode when the Binary/Decade input is low. The counter counts up when the Up/Down input is high, and Down when the Up/Down input is low. Multiple packages can be connected in either a parallel-clocking or a ripple-clocking arrangement. Parallel-clocking provides synchronous control and hence faster response from all counting outputs. Ripple-clocking allows for longer clock input rise and fall times.

This counter finds primary use in up/down and difference counting and programmable frequency synthesizer applications. It is also useful in A/D and D/A conversion techniques and for magnitude and sign generation.



RECOMMENDED OPERATING CONDITIONS

For maximum reliability:


| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | | |
| C, D, F, H Device | | -55 to +125 | °C |
| E Device | | -40 to +85 | °C |


TRUTH TABLE

| \overline{CI} | U/D | PE | B/D | Action |
|-----------------|-----|----|-----|---------------------|
| 1 | X | 0 | X | No Count |
| 0 | 1 | 0 | 0 | Count Up (Decade) |
| 0 | 1 | 0 | 1 | Count Up (Binary) |
| 0 | 0 | 0 | 0 | Count Down (Decade) |
| 0 | 0 | 0 | 1 | Count Down (Binary) |
| X | X | 1 | X | Preset |

X = Don't Care


BLOCK DIAGRAM






TIMING DIAGRAMS

Binary Mode



Decade Mode



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (V _{dc}) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|---------------------------------------|------------|-------------------------------|------|-------|------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | 5 | — | 5 | — | 0.05 | 5 | — | 150 | μAdc |
| | | 10 | — | 10 | — | 0.1 | 10 | — | 300 | |
| | | 15 | — | 20 | — | 0.2 | 20 | — | 600 | |

NOTES: ¹ Remaining Static Characteristics are listed under "4000B Series Family Specifications"

² T_{LOW} = -55°C for C, D, F, H device.

= -40°C for E device.


T_{HIGH} = +125°C for C, D, F, H device.

= + 85°C for E device.


DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETER | | V _{DD} (V _{DC}) | Min. | Typ. | Max. | Units | | |
|---|----------------------------------|--|----------------------------------|------|------|---------------|-----|----|
| CLOCKED OPERATION | | | | | | | | |
| PROPAGATION DELAY TIME Clock to Q Clock to $\overline{\text{Carry Out}}$ $\overline{\text{Carry In}}$ to $\overline{\text{Carry Out}}$ | $t_{\text{PLH}}, t_{\text{PHL}}$ | 5 | — | 250 | 500 | ns | | |
| | | 10 | — | 120 | 240 | | | |
| | | 15 | — | 90 | 180 | | | |
| | | 5 | — | 280 | 560 | ns | | |
| | | 10 | — | 130 | 260 | | | |
| | | 15 | — | 95 | 190 | | | |
| | | 5 | — | 170 | 340 | ns | | |
| | | 10 | — | 70 | 140 | | | |
| | | 15 | — | 50 | 100 | | | |
| OUTPUT TRANSITION TIME | $t_{\text{TLH}}, t_{\text{THL}}$ | 5 | — | 100 | 200 | ns | | |
| 10 | — | 50 | 100 | | | | | |
| 15 | — | 40 | 80 | | | | | |
| MINIMUM CLOCK PULSE WIDTH | PW_{CL} | 5 | — | 170 | 340 | ns | | |
| 10 | — | 85 | 170 | | | | | |
| 15 | — | 70 | 140 | | | | | |
| MAXIMUM CLOCK FREQUENCY | f_{CL} | 5 | 2.0 | 4 | — | MHz | | |
| 10 | 4.0 | 8 | — | | | | | |
| 15 | 5.5 | 11 | — | | | | | |
| MAXIMUM CLOCK RISE AND FALL TIME ¹ | $t_{\text{rCL}}, t_{\text{fCL}}$ | 5 | 15 | — | — | μs | | |
| 10 | 15 | — | — | | | | | |
| 15 | 15 | — | — | | | | | |
| MINIMUM SETUP TIME Carry In Up/Down, B/D | t_{setup} | 5 | — | 150 | 300 | ns | | |
| | | 10 | — | 65 | 130 | | | |
| | | 15 | — | 50 | 100 | | | |
| | | 5 | — | 325 | 650 | ns | | |
| | | 10 | — | 115 | 230 | | | |
| | | 15 | — | 85 | 170 | | | |
| | | PRESET OPERATION | | | | | | |
| | | PROPAGATION DELAY TIME Preset Enable to Q | $t_{\text{PLH}}, t_{\text{PHL}}$ | 5 | — | 360 | 720 | ns |
| | | | | 10 | — | 140 | 280 | |
| 15 | — | | | 110 | 220 | | | |
| Preset Enable to $\overline{\text{Carry Out}}$ | | 5 | — | 410 | 820 | ns | | |
| | | 10 | — | 165 | 330 | | | |
| | | 15 | — | 130 | 260 | | | |
| MINIMUM PRESET ENABLE PULSE WIDTH | PW_{PE} | 5 | — | 170 | 340 | ns | | |
| | | 10 | — | 85 | 170 | | | |
| | | 15 | — | 70 | 140 | | | |
| PRESET ENABLE REMOVAL TIME | t_{rem} | 5 | — | 325 | 650 | ns | | |
| | | 10 | — | 110 | 220 | | | |
| | | 15 | — | 90 | 180 | | | |

¹ When units are cascaded, the maximum rise and fall times of the clock input should be equal to or less than the transition times of the data outputs driving data inputs, plus the propagation delay of the output driving stage for the output capacitive load.




Typical P-Channel
Source Current Characteristics




Typical N-Channel
Sink Current Characteristics

APPLICATIONS INFORMATION

CASCADING CONNECTIONS



PROGRAMMABLE CASCADED FREQUENCY DIVIDER



CMOS QUAD EXCLUSIVE-OR GATE

FEATURES

- ◆ Buffered Outputs
- ◆ Diode Protection on all Inputs
- ◆ Fully "B"-Series Compatible
- ◆ Pin Compatible with 4070 types, MC14507, 74C86

DESCRIPTION


The 4030B contains four independent exclusive-OR gates integrated on a single monolithic silicon chip. Each exclusive-OR gate consists of five N-Channel and five P-Channel enhancement-mode transistors, plus output buffering devices.

TRUTH TABLE
(one of four gates)


| A | B | Y |
|---|---|---|
| 0 | 0 | 0 |
| 1 | 0 | 1 |
| 0 | 1 | 1 |
| 1 | 1 | 0 |

Where 1 = High Level
0 = Low Level


LOGIC DIAGRAM



SCHEMATIC DIAGRAM
(one of four gates)



CONNECTION DIAGRAM
(all packages)



Add suffix for package:

- C 14-pin Cerdip
- D 14-pin Ceramic
- E 14-pin Epoxy
- F 14-pin Flat
- H Chip


RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | -55 to +125 | °C |
| C, D, F, H Device | | -40 to +85 | °C |
| E Device | | | |

Note: The 4030B is identical to the 4070B; the devices are fully interchangeable in all applications.

FUNCTION DIAGRAM



V_{DD} = Pin 14
 V_{SS} = Pin 7

ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS ¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|---|-------------------------------|------|-------|--------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | 5 V _{IN} =V _{SS} or V _{DD} | — | 0.05 | — | 0.0005 | 0.05 | — | 1.5 | μAdc |
| | | 10 All valid input combinations | — | 0.10 | — | 0.001 | 0.10 | — | 3.0 | |
| | | 15 | — | 0.20 | — | 0.002 | 0.20 | — | 6.0 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.


= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.


= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETER | | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|------------------------|-------------------------------------|--------------------------|------|------|------|-------|
| PROPAGATION DELAY TIME | t _{PLH} , t _{PHL} | 5 | — | 140 | 280 | ns |
| | | 10 | — | 65 | 130 | |
| | | 15 | — | 50 | 100 | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | — | 100 | 200 | ns |
| | | 10 | — | 50 | 100 | |
| | | 15 | — | 40 | 80 | |




Typical P-Channel
Source Current Characteristics



Typical N-Channel
Sink Current Characteristics

APPLICATIONS INFORMATION 8-BIT TWO'S COMPLEMENT ADDER/SUBTRACTOR



| x_8 | x_7 | x_6 | x_5 | x_4 | x_3 | x_2 | x_1 | | x_8 | x_7 | x_6 | x_5 | x_4 | x_3 | x_2 | x_1 | |
|-------|-------|-------|-------|-------|-------|-------|-------|-----|-------|-------|-------|-------|-------|-------|-------|-------|------|
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -0 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | -1 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | -1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | -2 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | -2 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -3 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -3 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | -4 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -4 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -5 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -5 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -6 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -6 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -7 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -7 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -8 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -8 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -9 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -9 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -10 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -10 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -11 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -11 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -12 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -12 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -13 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -13 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -14 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -14 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -15 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -15 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -16 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -16 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -17 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -17 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -18 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -18 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -19 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -19 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -20 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -20 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -21 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -21 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -22 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -22 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -23 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -23 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -24 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -24 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -25 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -25 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -26 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -26 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -27 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -27 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -28 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -28 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -29 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -29 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -30 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -30 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -31 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -31 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -32 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -32 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -33 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -33 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -34 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -34 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -35 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -35 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -36 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -36 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -37 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -37 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -38 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -38 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -39 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -39 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -40 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -40 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -41 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -41 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -42 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -42 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -43 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -43 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -44 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -44 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -45 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -45 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -46 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -46 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -47 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -47 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -48 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -48 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -49 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -49 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -50 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -50 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -51 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -51 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -52 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -52 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -53 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -53 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -54 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -54 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -55 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -55 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -56 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -56 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -57 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -57 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -58 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -58 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -59 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -59 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -60 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -60 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -61 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -61 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -62 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -62 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -63 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -63 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -64 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -64 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -65 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -65 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -66 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -66 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -67 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -67 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -68 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -68 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -69 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -69 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -70 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -70 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -71 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -71 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -72 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -72 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -73 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -73 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -74 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -74 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -75 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -75 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -76 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -76 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -77 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -77 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -78 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -78 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -79 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -79 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -80 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -80 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -81 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -81 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -82 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -82 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -83 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -83 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -84 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -84 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -85 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -85 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -86 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -86 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -87 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -87 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -88 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -88 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -89 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -89 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -90 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -90 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -91 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -91 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -92 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -92 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -93 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -93 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -94 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -94 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -95 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -95 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -96 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -96 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -97 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -97 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -98 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -98 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -99 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | -99 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -100 |

CMOS 8-BIT UNIVERSAL BUS REGISTER

FEATURES

- ◆ Bidirectional Parallel Data Inputs
- ◆ Parallel or Serial Inputs/Parallel Outputs
- ◆ Asynchronous or Synchronous Parallel Data Loading
- ◆ Data Recirculation for Register Storage
- ◆ Parallel Enable on Data Lines for Bus Connection
- ◆ Static Operation - DC to 5MHz @ 10Vdc

DESCRIPTION

The 4034 B is a Static Eight-Stage Parallel- or Serial-Input/Parallel-Output Register. It can be used to:


1. bidirectionally transfer parallel information between two buses,
2. convert serial data to parallel form and direct the parallel data to either of two buses,
3. store (recirculate) parallel data, or
4. accept parallel data from either of two buses and convert that data to serial form.

Inputs that control the operations include a single phase Clock (CL), "A" Data Enable (AE), Asynchronous/Synchronous (A/S), "A" bus to "B" bus/"B" bus to "A" bus (A/B), and Parallel/Serial (P/S). Data inputs include 16 bidirectional Parallel Data lines of which the eight "A" Data lines are inputs (outputs) and the "B" Data lines are outputs (inputs) depending on the signal level on the A/B input. In addition, an input for Serial data is also provided.

All register stages are D-type master/slave flip-flops with separate master and slave clock inputs generated internally to allow synchronous or asynchronous data transfer from master to slave. Isolation from external noise and the effects of loading is provided by output buffering.

Useful applications for this device include pseudo-random code generation, sample-and-hold register, frequency and phase comparators, address or buffer register, and serial/parallel input/output conversion.

CONNECTION DIAGRAM (all packages)



Add suffix for package:


- D 24-pin Ceramic
- E 24-pin Epoxy
- H Chip

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | | |
| D, H Device | | -55 to +125 | °C |
| E Device | | -40 to +85 | °C |

BLOCK DIAGRAM



OPERATING INFORMATION

The 4034 B is composed of eight register cells connected in cascade with additional control logic. Each register cell is composed of one "D" master-slave flip-flop with separate internal clocks, and two data transfer gates allowing the data to be transferred bidirectionally from bus A to bus B and from bus B to bus A, and to be memorized. Besides the single phase clock and the serial data inputs, the control logic provides four other features:

A Enable Input — When high, this input enables the bus A data lines.

A/B Input (Data A or B) — This input controls the direction of data flow: when high, the data

flows from bus A to bus B; when low, the data flows from bus B to bus A.

P/S Input (Parallel/Serail) — This input controls the data input mode (Parallel or Serial). When high, the data is transferred to the register in a parallel asynchronous mode or a parallel synchronous mode (positive clock transition). When low, the data is entered into the register in a serial synchronous mode (positive clock transition).


A/S Input (Asynchronous/Synchronous to the Clock) — When this input is high, the data is transferred independently from the clock rate; when low, the clock is enabled and the data is transferred synchronously.

Truth Table for Register Input Levels and the Resulting Operation
(L = Low Level, H = High, X = Don't Care)


| "A" Enable | P/S | A/B | A/S | Operation* |
|------------|-----|-----|-----|--|
| L | L | L | X | Serial Mode; Synch. Serial Data Input, "A" Parallel Data Outputs Disabled |
| L | L | H | X | Serial Mode; Synch. Serial Data Input, "B" Parallel Data Output |
| L | H | L | L | Parallel Mode; "B" Synch. Parallel Data Inputs, "A" Parallel Data Outputs Disabled |
| L | H | L | H | Parallel Mode; "B" Asynch. Parallel Data Inputs, "A" Parallel Data Outputs Disabled |
| L | H | H | L | Parallel Mode; "A" Parallel Data Inputs Disabled, "B" Parallel Data Outputs, Synch Data Recirculation |
| L | H | H | H | Parallel Mode; "A" Parallel Data Inputs Disabled, "B" Parallel Data Outputs, Asynch Data Recirculation |
| H | L | L | X | Serial Mode; Synch. Serial Data Input, "A" Parallel Data Output |
| H | L | H | X | Serial Mode; Synch. Serial Data Input, "B" Parallel Data Output |
| H | H | L | L | Parallel Mode; "B" Synch. Parallel Data Input, "A" Parallel Data Output |
| H | H | L | H | Parallel Mode; "B" Asynch. Parallel Data Input, "A" Parallel Data Output |
| H | H | H | L | Parallel Mode; "A" Synch. Parallel Data Input, "B" Parallel Data Output |
| H | H | H | H | Parallel Mode; "A" Asynch. Parallel Data Input, "B" Parallel Data Output |

* Outputs change at positive transition of clock in the serial mode and when the A/S control input is "low" in the parallel mode.

TIMING DIAGRAM



LOGIC DIAGRAM



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------------|--------------------------|------------|-------------------------------|------|-------|-------------------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | 5 | — | 5 | — | 0.05 | 5 | — | 150 | μAdc |
| | | 10 | — | 10 | — | 0.1 | 10 | — | 300 | |
| | | 15 | — | 20 | — | 0.2 | 20 | — | 600 | |
| 3-STATE OUTPUT LEAKAGE CURRENT | I _{ZL} | 15 | — | ±0.1 | — | ±10 ⁻⁴ | ±0.1 | — | ±1.0 | μAdc |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for D, H device.

= -40°C for E device.

T_{HIGH} = +125°C for D, H device.


= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)


| PARAMETER | | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|---|--|--------------------------|------|------|------|-------|
| PROPAGATION DELAY TIME | t _{PLH} , t _{PHL} | 5 | — | 350 | 700 | ns |
| | | 10 | — | 120 | 240 | |
| | | 15 | — | 100 | 200 | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | — | 180 | 360 | ns |
| | | 10 | — | 90 | 180 | |
| | | 15 | — | 70 | 140 | |
| MINIMUM CLOCK PULSE WIDTH | PW _{CL} | 5 | — | 125 | 250 | ns |
| | | 10 | — | 50 | 100 | |
| | | 15 | — | 40 | 80 | |
| MAXIMUM CLOCK FREQUENCY | f _{CL} | 5 | 2 | 4 | — | MHz |
| | | 10 | 4 | 8 | — | |
| | | 15 | 6 | 12 | — | |
| MAXIMUM CLOCK RISE AND FALL TIME ¹ | t _{rCL} , t _{fCL} | 5 | 15 | — | — | μs |
| | | 10 | 15 | — | — | |
| | | 15 | 15 | — | — | |
| MINIMUM HIGH-LEVEL PULSE WIDTH AE, P/S, A/S Inputs | PW _{AE} , PW _{P/S} , PW _{A/S} | 5 | — | 180 | 360 | ns |
| | | 10 | — | 90 | 180 | |
| | | 15 | — | 70 | 140 | |
| MINIMUM SETUP TIME A, B; Serial Inputs | t _{setup} | 5 | — | 140 | 280 | ns |
| | | 10 | — | 70 | 140 | |
| | | 15 | — | 50 | 100 | |

¹ When units are cascaded, the maximum rise and fall times of the clock input should be equal to or less than the transition times of the data outputs driving data inputs, plus the propagation delay of the output driving stage for the output capacitive load.


APPLICATIONS INFORMATION




16-Bit parallel in/parallel out, parallel in/serial out, serial in/parallel out, serial in/serial out register.




16-Bit Serial in/gated parallel out register



N-stage shift register with fixed serial output line.




Sample and hold register - serial/parallel in parallel out.




Frequency and phase comparator

APPLICATIONS INFORMATION (Continued)



Shift right/shift left with parallel inputs



Single and double-bus systems

CMOS 4-BIT PARALLEL-IN/PARALLEL-OUT SHIFT REGISTER

FEATURES

- ◆ 4-Stage Clocked Serial-Shift Operation
- ◆ Synchronous Parallel Loading of All Stages
- ◆ J-K Serial Inputs to First Stage
- ◆ Asynchronous True/Complement Control of all Outputs
- ◆ Asynchronous Reset
- ◆ Static Operation — DC to 6MHz @ 10Vdc

DESCRIPTION

The 4035B is a Four-Stage Clocked Serial Register having provisions for synchronous parallel inputs to each stage and serial inputs to the first stage via J \bar{K} logic. Register stages 2, 3, and 4 are coupled in a serial "D" flip-flop configuration when the register is in the serial mode (Parallel/Serial control low).

Parallel entry via the "D" line of each register stage is permitted only when the Parallel/Serial control is high. In the parallel or serial mode information is transferred on positive Clock transitions.

When the True/Complement control is high, the true contents of the register are available at the output terminals. When the True/Complement control is low, the outputs are the complements of the data in the register. The True/Complement control functions asynchronously with respect to the Clock signal.

J \bar{K} input logic is provided on the first stage serial input to minimize logic requirements, particularly in counting and sequence-generation applications. With J \bar{K} inputs connected together, the first stage becomes a "D" flip-flop. An asynchronous common Reset is also provided.


This device may be used for shift-right/shift-left registers, parallel-to-serial/serial-to-parallel conversion, sequence generation, up/down Johnson or ring counters, pseudo-random code generation, frequency and phase comparators, and sample-and-hold registers.

TRUTH TABLE

| CL | t_{n-1} (Inputs) | | | | t_n (Outputs) |
|----|--------------------|-----------|---|-----------|-----------------------------|
| | J | \bar{K} | R | Q_{n-1} | Q_n |
| | 0 | X | 0 | 0 | 0 |
| | 1 | X | 0 | 0 | 1 |
| | X | 0 | 0 | 1 | 0 |
| | 1 | 0 | 0 | Q_{n-1} | \bar{Q}_{n-1} Toggle Mode |
| | X | 1 | 0 | 1 | 1 |
| | X | X | 0 | Q_{n-1} | Q_{n-1} |
| | X | X | 1 | X | 0 |

X = Don't Care

CONNECTION DIAGRAM
(all packages)



Add suffix for package:


- C 16-pin Cerdip
- D 16-pin Ceramic
- E 16-pin Epoxy
- F 16-pin Flat
- H Chip

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | -55 to +125 | °C |
| C, D, F, H Device | | -40 to +85 | °C |
| E Device | | | |

BLOCK DIAGRAM



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | | V _{DD} (V _{dc}) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|-----------------------------|-----------------|---------------------------------------|---|-------------------------------|------|-------|------|------|--------------------------------|------|------------------|
| | | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | 5 | V _{IN} =V _{SS} or V _{DD} | — | 5 | — | 0.05 | 5 | — | 150 | μA _{dc} |
| | | 10 | All valid input combinations | — | 10 | — | 0.1 | 10 | — | 300 | |
| | | 15 | | — | 20 | — | 0.2 | 20 | — | 600 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.

= -40°C for E device.


T_{HIGH} = +125°C for C, D, F, H device.

= + 85°C for E device.


DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETER | | V _{DD} (V _{dc}) | Min. | Typ. | Max. | Units |
|---|-------------------------------------|---------------------------------------|------|------|------|-------|
| CLOCKED OPERATION | | | | | | |
| PROPAGATION DELAY TIME From Clock Input | t _{PLH} , t _{PHL} | 5 | — | 250 | 500 | ns |
| | | 10 | — | 100 | 200 | |
| | | 15 | — | 75 | 150 | |
| From T/C Input | t _{PLH} , t _{PHL} | 5 | — | 150 | 300 | ns |
| | | 10 | — | 60 | 120 | |
| | | 15 | — | 45 | 90 | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | — | 80 | 160 | ns |
| | | 10 | — | 40 | 80 | |
| | | 15 | — | 30 | 60 | |
| MINIMUM CLOCK PULSE WIDTH | PW _{CL} | 5 | — | 100 | 200 | ns |
| | | 10 | — | 45 | 90 | |
| | | 15 | — | 30 | 60 | |
| MAXIMUM CLOCK FREQUENCY | f _{CL} | 5 | 2.0 | 4.0 | — | MHz |
| | | 10 | 5.0 | 10.0 | — | |
| | | 15 | 6.0 | 12.0 | — | |
| MAXIMUM CLOCK RISE & FALL TIME ¹ | t _{rCL} , t _{fCL} | 5 | 15 | — | — | μs |
| | | 10 | 15 | — | — | |
| | | 15 | 15 | — | — | |
| MINIMUM SETUP TIME J, K Inputs | t _{setup} | 5 | — | 110 | 220 | ns |
| | | 10 | — | 40 | 80 | |
| | | 15 | — | 30 | 60 | |
| P/S, Parallel Inputs | t _{setup} | 5 | — | 70 | 140 | ns |
| | | 10 | — | 25 | 50 | |
| | | 15 | — | 20 | 40 | |
| MINIMUM HOLD TIME J, K inputs | t _{hold} | 5 | — | -25 | 25 | ns |
| | | 10 | — | -10 | 10 | |
| | | 15 | — | - 5 | 5 | |
| P/S, Parallel Inputs | t _{hold} | 5 | — | -25 | 25 | ns |
| | | 10 | — | -10 | 10 | |
| | | 15 | — | - 5 | 5 | |
| RESET OPERATION | | | | | | |
| PROPAGATION DELAY TIME | t _{PHL} | 5 | — | 230 | 460 | ns |
| | | 10 | — | 120 | 240 | |
| | | 15 | — | 90 | 180 | |
| MINIMUM RESET PULSE WIDTH | PW _R | 5 | — | 125 | 250 | ns |
| | | 10 | — | 55 | 110 | |
| | | 15 | — | 40 | 80 | |

¹ When units are cascaded, the maximum rise and fall times of the clock input should be equal to or less than the transition times of the data outputs driving data inputs, plus the propagation delay of the output driving stage for the output capacitive load.




Typical P-Channel
Source Current Characteristics




Typical N-Channel
Sink Current Characteristics

LOGIC DIAGRAM



APPLICATIONS INFORMATION



Shift Left/Shift Right Register

CMOS 12-STAGE BINARY COUNTER

FEATURES


- ◆ 12 Fully Static Stages
- ◆ All 12 Buffered Outputs Available
- ◆ Common Reset Line
- ◆ 8MHz Counting Rate @ 10Vdc
- ◆ All Inputs Buffered

DESCRIPTION

The 4040 B consists of 12-ripple-carry binary counter stages with appropriate input buffers and reset circuitry. The counter is reset to its "all 0's" state by a high level on the Reset input. The counter is advanced one count on the negative-going transition of each input pulse. Isolation from external noise and the effects of loads is provided by output buffering.

Applications include time delay circuits, counter controls, and frequency dividers.

CONNECTION DIAGRAM (all packages)



Add suffix for package:

- C 16-pin Cerdip
- D 16-pin Ceramic
- E 16-pin Epoxy
- F 16-pin Flat
- H Chip

TRUTH TABLE

| Clock | Reset | Output State |
|-------|-------|-----------------------|
| | 0 | No Change |
| | 0 | Advance to next state |
| x | 1 | All Outputs are low |

X = Don't Care

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

DC Supply Voltage $V_{DD} - V_{SS}$ 3 to 15 Vdc

Operating Temperature T_A


C, D, F, H Device

E Device

-55 to +125 °C

-40 to +85 °C

LOGIC DIAGRAM



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|------------|-------------------------------|------|-------|------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | 5 | — | 5 | — | 0.05 | 5 | — | 150 | μAdc |
| | | 10 | — | 10 | — | 0.1 | 10 | — | 300 | |
| | | 15 | — | 20 | — | 0.2 | 20 | — | 600 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.


= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.


= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETER | | V _{DD} (V _{DC}) | Min. | Typ. | Max. | Units |
|---------------------------------------|-------------------------------------|---------------------------------------|------|------|------|-------|
| CLOCKED OPERATION | | | | | | |
| PROPAGATION DELAY TIME Clock to Q1 | t _{PLH} , t _{PHL} | 5 | — | 180 | 320 | ns |
| | | 10 | — | 80 | 160 | |
| | | 15 | — | 65 | 130 | |
| Q _i to Q _{i + 1} | t _{PLH} , t _{PHL} | 5 | — | 100 | 200 | ns |
| | | 10 | — | 40 | 60 | |
| | | 15 | — | 30 | 30 | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | — | 100 | 200 | ns |
| | | 10 | — | 40 | 80 | |
| | | 15 | — | 30 | 60 | |
| MINIMUM CLOCK PULSE WIDTH | PW _{CL} | 5 | — | 70 | 140 | ns |
| | | 10 | — | 30 | 60 | |
| | | 15 | — | 20 | 40 | |
| MAXIMUM CLOCK FREQUENCY | f _{CL} | 5 | 3.0 | 4.5 | — | MHz |
| | | 10 | 6.0 | 9.0 | — | |
| | | 15 | 7.5 | 11.0 | — | |
| MAXIMUM CLOCK RISE AND FALL TIME | t _{rCL} , t _{fCL} | 5 | 50 | 100 | — | μs |
| | | 10 | 50 | 100 | — | |
| | | 15 | 50 | 100 | — | |
| RESET OPERATION | | | | | | |
| PROPAGATION DELAY TIME | t _{PHL} | 5 | — | 200 | 400 | ns |
| | | 10 | — | 100 | 200 | |
| | | 15 | — | 75 | 150 | |
| MINIMUM RESET PULSE WIDTH | PW _R | 5 | — | 100 | 200 | ns |
| | | 10 | — | 40 | 80 | |
| | | 15 | — | 30 | 60 | |
| RESET REMOVAL TIME | t _{rem} | 5 | — | 150 | 300 | ns |
| | | 10 | — | 65 | 125 | |
| | | 15 | — | 40 | 75 | |




Typical P-Channel
Source Current Characteristics




Typical N-Channel
Sink Current Characteristics

TIMING DIAGRAM



TYPICAL COUNTER STAGE



CMOS QUAD TRUE/COMPLEMENT BUFFER

FEATURES


- ◆ Both True and Complement Outputs Available Simultaneously
- ◆ High Source and Sink Current
- ◆ Diode Protection on All Inputs

DESCRIPTION

The 4041UB Quad True/Complement Buffer is a monolithic integrated circuit constructed with P-Channel and N-Channel enhancement-mode devices. The outputs have low resistance and are capable of sinking or sourcing high currents for use in driver applications where high noise immunity and low power dissipation are required.

This device is useful as a line-driver, CMOS-to-TTL driver, low-power resistor-network driver for A/D and D/A conversion, display and clock drivers.

CONNECTION DIAGRAM (all packages)



Add suffix for package:


- C 14-pin Cerdip
- D 14-pin Ceramic
- E 14-pin Epoxy
- F 14-pin Flat
- H Chip

RECOMMENDED OPERATING CONDITIONS


For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | -55 to +125 | °C |
| C, D, F, H Device | | -55 to +125 | °C |
| E Device | | -40 to +85 | °C |

SCHEMATIC DIAGRAM (one of four buffers)



LOGIC DIAGRAM



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (V _{de}) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|---|---------------------------------------|---|-------------------------------|------|-------|-------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | 5 V _{IN} =V _{SS} or V _{DD} | — | 1.0 | — | 0.005 | 1.0 | — | 30 | μAdc |
| | | 10 All valid input combinations | — | 2.0 | — | 0.01 | 2.0 | — | 60 | |
| | | 15 | — | 4.0 | — | 0.02 | 4.0 | — | 120 | |
| MINIMUM INPUT HIGH VOLTAGE Non-Inverting Outputs | V _{IH} | 5 V _{OH} =4.5V | — | 3.5 | — | 2.75 | 3.5 | — | 3.5 | Vdc |
| | | 10 V _{OH} =9.0V | — | 7.0 | — | 5.5 | 7.0 | — | 7.0 | |
| | | 15 V _{OH} =13.5V | — | 11.0 | — | 8.25 | 11.0 | — | 11.0 | |
| | | I _O ≤ 1μA | | | | | | | | |
| | | 5 V _{OL} =0.5V | — | 4.0 | — | 2.75 | 4.0 | — | 4.0 | |
| | | 10 V _{OL} =1.0V | — | 8.0 | — | 5.5 | 8.0 | — | 8.0 | |
| Inverting Outputs | V _{IH} | 15 V _{OL} =1.5V | — | 12.0 | — | 8.25 | 12.0 | — | 12.0 | Vdc |
| | | I _O ≤ 1μA | | | | | | | | |
| | | 5 V _{OL} =0.5V | 1.5 | — | 1.5 | 2.25 | — | 1.5 | — | |
| | | 10 V _{OL} =1.0V | 3.0 | — | 3.0 | 4.5 | — | 3.0 | — | |
| | | 15 V _{OL} =1.5V | 4.0 | — | 4.0 | 6.75 | — | 4.0 | — | |
| | | I _O ≤ 1μA | | | | | | | | |
| MAXIMUM INPUT LOW VOLTAGE Non-Inverting Outputs | V _{IL} | 5 V _{OH} =4.5V | 1.0 | — | 1.0 | 2.25 | — | 1.0 | — | Vdc |
| | | 10 V _{OH} =9.0V | 2.0 | — | 2.0 | 4.5 | — | 2.0 | — | |
| | | 15 V _{OH} =13.5V | 3.0 | — | 3.0 | 6.75 | — | 3.0 | — | |
| | | I _O ≤ 1μA | | | | | | | | |
| | | 5 V _{OH} =4.5V | 1.0 | — | 1.0 | 2.25 | — | 1.0 | — | |
| | | 10 V _{OH} =9.0V | 2.0 | — | 2.0 | 4.5 | — | 2.0 | — | |
| Inverting Outputs | V _{IL} | 15 V _{OH} =13.5V | 3.0 | — | 3.0 | 6.75 | — | 3.0 | — | Vdc |
| | | I _O ≤ 1μA | | | | | | | | |
| | | 5 V _{OH} =4.6V | -1.7 | — | -1.4 | -2.8 | — | -1.0 | — | |
| | | 10 V _{OH} =9.5V | -5.0 | — | -4.0 | -8.0 | — | -2.8 | — | |
| | | 15 V _{OH} =13.5V | -16 | — | -13 | -26 | — | -9 | — | |
| | | V _{IN} =V _{DD} | | | | | | | | |
| OUTPUT HIGH (SOURCE) CURRENT | I _{OH} | 5 V _{OH} =4.6V | -0.75 | — | -0.6 | -1.0 | — | -0.42 | — | mAdc |
| | | 10 V _{OH} =9.5V | -2.2 | — | -1.8 | -3.6 | — | -1.3 | — | |
| | | 15 V _{OH} =13.5V | -8.0 | — | -6.5 | -13 | — | -4.5 | — | |
| | | V _{IN} =V _{SS} | | | | | | | | |
| | | 5 V _{OL} =0.4V | 2.0 | — | 1.6 | 3.2 | — | 1.1 | — | mAdc |
| | | 10 V _{OL} =0.5V | 6.2 | — | 5.0 | 10 | — | 3.5 | — | |
| Non-Inverting Outputs | I _{OL} | 15 V _{OL} =1.5V | 23 | — | 18.5 | 38 | — | 13 | — | |
| | | V _{IN} =V _{SS} | | | | | | | | |
| | | 5 V _{OL} =0.4V | 1.0 | — | 0.8 | 1.3 | — | 0.56 | — | mAdc |
| | | 10 V _{OL} =0.5V | 2.5 | — | 2.0 | 4.0 | — | 1.4 | — | |
| | | 15 V _{OL} =1.5V | 11 | — | 8.5 | 17 | — | 5.8 | — | |
| | | V _{IN} =V _{DD} | | | | | | | | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.

= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.


= + 85°C for E device.

ELECTRICAL CHARACTERISTICS (Continued)


DYNAMIC CHARACTERISTICS ($C_L = 50\text{pF}$, $T_A = 25^\circ\text{C}$)

| PARAMETER | | V_{DD} (Vdc) | Min. | Typ. | Max. | Units |
|---|-----------------------|-------------------|------|------|------|-------|
| PROPAGATION DELAY TIME Non-Inverting Outputs | t_{PLH} , t_{PHL} | 5 | — | 60 | 120 | ns |
| | | 10 | — | 35 | 70 | |
| | | 15 | — | 25 | 50 | |
| Inverting Outputs | t_{PLH} , t_{PHL} | 5 | — | 60 | 120 | ns |
| | | 10 | — | 35 | 70 | |
| | | 15 | — | 25 | 50 | |
| OUTPUT TRANSITION TIME Non-Inverting Outputs | t_{TLH} , t_{THL} | 5 | — | 40 | 80 | ns |
| | | 10 | — | 20 | 40 | |
| | | 15 | — | 15 | 30 | |
| Inverting Outputs | t_{TLH} , t_{THL} | 5 | — | 35 | 70 | ns |
| | | 10 | — | 20 | 40 | |
| | | 15 | — | 15 | 30 | |
| INPUT CAPACITANCE | C_{IN} | — | — | 10 | 15 | pF |

NON-INVERTING (TRUE) OUTPUT




Typical P-Channel
Source Current Characteristics




Typical N-Channel
Sink Current Characteristics





INVERTING (COMPLEMENT) OUTPUT




Typical P-Channel
Source Current Characteristics



Typical N-Channel
Sink Current Characteristics

Typical transition time vs. C_L -true output.Typical transition time vs. C_L -complement output.Typical propagation delay time vs. C_L -true output.Typical propagation delay time vs. C_L -complement output.

APPLICATIONS INFORMATION



*4041UB

For resolution and accuracy of $\pm \frac{1}{2}$ least significant bit (LSB), choose the values for R (shown in Table I) where R equals the value of the external ladder resistor plus the switch source impedance.

TABLE I. RESISTANCE VALUES AT $V_{DD}-V_{SS} = 5V$, $T_A = 25^\circ C$

| RESOLUTION | ACCURACY OF 1/2 LSB | R_{min} (Ω) |
|------------|------------------------------|------------------------|
| 4 bit | $\pm 3.25\%$ of full scale | 3.5 k |
| 6 bit | $\pm 0.8\%$ of full scale | 14 k |
| 8 bit | $\pm 0.2\%$ of full scale | 56 k |
| 10 bit | $\pm 0.05\%$ of full scale | 224 k |
| 12 bit | $\pm 0.0125\%$ of full scale | 896 k |

The values have been tabulated for $V_{DD} = 5V$ and $V_{SS} = 0V$. For different supply (reference) voltages, the switch source impedance must be computed and added to the value of R shown in Table I).

TABLE II. ON RESISTANCE VALUES AT $V_{DS} = 0.1V$, $T_A = 25^\circ C$

| $V_{DD}-V_{SS}$ (Volts) | R_N (Ω) | R_P (Ω) |
|-------------------------|--------------------|--------------------|
| 5 | 175 ± 50 | 200 ± 75 |
| 10 | 75 ± 25 | 90 ± 30 |

CMOS QUAD LATCH

FEATURES



- ◆ Common Clock
- ◆ Positive- or Negative-Edge Clocking
- ◆ Q and \bar{Q} Outputs Available from Each Latch

DESCRIPTION

4042B devices contain four Latch circuits, each strobed by a common Clock. Complementary buffered outputs are available from each circuit.


Information present at the Data input is transferred to outputs Q and \bar{Q} during the Clock level which is programmed by the Polarity input. For Polarity = 0 the transfer occurs during the 0 Clock level and for Polarity = 1 the transfer occurs during the 1 Clock level. The outputs follow the Data inputs providing the Clock and Polarity levels defined above are present. When a Clock transition occurs (positive for Polarity = 0 and negative for Polarity = 1) the information present at the input during the Clock transition is retained at the outputs until an opposite Clock transition occurs.

TRUTH TABLE


| CLOCK | POLARITY | Q |
|---|----------|-------|
| 0 | 0 | D |
|  | 0 | LATCH |
| 1 | 1 | D |
|  | 1 | LATCH |

LOGIC DIAGRAMS


One of four latches



Clock Input Control



CONNECTION DIAGRAM (all packages)




RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | -55 to +125 | °C |
| C, D, F, H Device | | -55 to +125 | °C |
| E Device | | -40 to +85 | °C |

BLOCK DIAGRAM



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|---|-------------------------------|------|-------|------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | V _{IN} =V _{SS} or V _{DD} All valid input combinations | — | 5 | — | 1.0 | 5 | — | 150 | μAdc |
| | | | — | 10 | — | 2.0 | 10 | — | 300 | |
| | | | — | 20 | — | 4.0 | 20 | — | 600 | |



NOTES: ¹ Remaining Static Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.
= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.
= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETER | | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|--|-------------------------------------|--------------------------|------|------|------|-------|
| PROPAGATION DELAY TIME From Data Inputs | t _{PLH} , t _{PHL} | 5 | — | 110 | 220 | ns |
| | | 10 | — | 55 | 110 | |
| | | 15 | — | 40 | 80 | |
| From Clock Polarity Inputs | t _{PLH} , t _{PHL} | 5 | — | 150 | 300 | ns |
| | | 10 | — | 75 | 150 | |
| | | 15 | — | 50 | 100 | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | — | 100 | 200 | ns |
| | | 10 | — | 50 | 100 | |
| | | 15 | — | 40 | 80 | |
| MINIMUM CLOCK PULSE WIDTH | PW _{CL} | 5 | — | 100 | 200 | ns |
| | | 10 | — | 50 | 100 | |
| | | 15 | — | 30 | 60 | |
| MAXIMUM CLOCK RISE AND FALL TIME | t _{rCL} , t _{fCL} | 5 | 15 | — | — | μs |
| | | 10 | 5 | — | — | |
| | | 15 | 3 | — | — | |
| MINIMUM DATA INPUT SETUP TIME | t _{setup} | 5 | — | -20 | 50 | ns |
| | | 10 | — | -10 | 30 | |
| | | 15 | — | -5 | 25 | |
| MINIMUM DATA INPUT HOLD TIME | t _{hold} | 5 | — | 0 | 100 | ns |
| | | 10 | — | 0 | 50 | |
| | | 15 | — | 0 | 40 | |



CMOS QUAD 3-STATE R-S LATCHES

FEATURES

- ◆ Separate Set and Reset Inputs for each Latch
- ◆ Active-High (4043 B) or Active-Low (4044 B) Inputs
- ◆ 3-State Outputs with Common Enable

DESCRIPTION

4043 B types are Quad cross-coupled 3-state CMOS NOR Latches, and the 4044 B types are Quad cross-coupled 3-state CMOS NAND Latches. Each latch has a separate Q output and individual Set and Reset inputs. The Q outputs are gated through transmission gates controlled by a common Enable input. A logic "1" or "high" on the Enable input connects the latch states to the Q outputs. A logic "0" or "low" on the Enable input disconnects the latch states from the Q outputs, resulting in an open circuit condition on the Q outputs. The open circuit feature allows common bussing of the outputs. The logic operation of the latches is summarized in the truth table below.

TRUTH TABLES

4043 B

| S | R | E | Q |
|---|---|---|-----|
| X | X | 0 | OC* |
| 0 | 0 | 1 | NC+ |
| 1 | 0 | 1 | 1 |
| 0 | 1 | 1 | 0 |
| 1 | 1 | 1 | Δ |

* OPEN CIRCUIT

+ NO CHANGE

Δ DOMINATED BY S = 1 INPUT

4044 B


| S | R | E | Q |
|---|---|---|-----|
| X | X | 0 | OC* |
| 1 | 1 | 1 | NC+ |
| 0 | 0 | 1 | 1 |
| 1 | 1 | 1 | 0 |
| 0 | 0 | 1 | ΔΔ |

* OPEN CIRCUIT

+ NO CHANGE

ΔΔ DOMINATED BY R = 0 INPUT

CONNECTION DIAGRAMS (all packages)



Add suffix for package:

| | | | |
|---|----------------|---|-------------|
| C | 16-pin Cerdip | F | 16-pin Flat |
| D | 16-pin Ceramic | H | Chip |
| E | 16-pin Epoxy | | |

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:


DC Supply Voltage $V_{DD} - V_{SS}$ 3 to 15 Vdc

Operating Temperature T_A

C, D, F, H Device -55 to +125 °C

E Device -40 to +85 °C

BLOCK DIAGRAMS



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------------|--------------------------|--------------------------|-------------------------------|------|-------|-------------------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | 5 | — | 1.0 | — | 0.005 | 1.0 | — | 30 | μAdc |
| | | 10 | — | 2.0 | — | 0.01 | 2.0 | — | 60 | |
| | | 15 | — | 4.0 | — | 0.02 | 4.0 | — | 120 | |
| 3-STATE OUTPUT LEAKAGE CURRENT | I _{ZL} | Enable = V _{SS} | — | ±0.1 | — | ±10 ⁻⁴ | ±0.1 | — | ±1.0 | μAdc |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.


= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.


= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETER | | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|--|---|--------------------------|------|------|------|-------|
| PROPAGATION DELAY TIME From S or R Inputs | t _{PLH} , t _{PHL} | 5 | — | 150 | 300 | ns |
| | | 10 | — | 70 | 140 | |
| | | 15 | — | 50 | 100 | |
| | From Enable Input t _{PHZ} , t _{PLZ} t _{PZH} , t _{PZL} | 5 | — | 75 | 150 | ns |
| | | 10 | — | 35 | 70 | |
| | | 15 | — | 30 | 60 | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | — | 100 | 200 | ns |
| | | 10 | — | 50 | 100 | |
| | | 15 | — | 40 | 80 | |
| MINIMUM SET OR RESET PULSE WIDTH | PW _S , PW _R | 5 | — | 80 | 160 | ns |
| | | 10 | — | 40 | 80 | |
| | | 15 | — | 30 | 60 | |
| SET OR RESET REMOVAL TIME | t _{ram} | 5 | — | 25 | 50 | ns |
| | | 10 | — | 15 | 30 | |
| | | 15 | — | 10 | 20 | |




Typical P-Channel
Source Current Characteristics





Typical N-Channel
Sink Current Characteristics

LOGIC DIAGRAMS




APPLICATIONS INFORMATION

Switch bounce eliminator



Multiple bus storage



CMOS PHASE-LOCKED LOOPS

FEATURES

- ◆ Very low power consumption — 70 μ W (typ) @ $f_o = 10$ kHz, 5Vdc
- ◆ Operating frequency range (no offset) — Up to 3MHz (typ) @ 10Vdc (4046B) Up to 4MHz (typ) @ 10Vdc (4446B)
- ◆ Low frequency drift — 0.04%/°C (typ) @ 10Vdc
- ◆ Choice of two phase comparators:
 1. Exclusive-OR network
 2. Edge-controlled memory network with phase-pulse output for lock indication
- ◆ VCO Inhibit control for ON-OFF keying and ultra-low standby power consumption
- ◆ High VCO linearity 1% (typ)
- ◆ Source-follower output of VCO control input (Demodulator Output)
- ◆ Zener Diode to assist Supply Regulation


APPLICATIONS

- ◆ FM demodulator and modulator
- ◆ Frequency synthesis and multiplication
- ◆ Frequency discriminator
- ◆ Data synchronization
- ◆ Voltage-to-frequency conversion
- ◆ Tone decoding
- ◆ FSK-Modems
- ◆ Signal conditioning

DESCRIPTION

The 4046B and 4446B phase-locked loops contain two phase comparators, a voltage-controlled oscillator (VCO), source follower, and zener diode. The comparators have two common inputs. The Signal input can be used directly coupled to large voltage signals, or indirectly coupled (with a series capacitor) to small voltage signals. The self-bias circuit adjusts small voltage signals in the linear region of the amplifier. Phase comparator I (an exclusive-OR gate) provides a digital error signal PCI_{OUT} , and maintains 90° phase shift at the center frequency between Signal and Comparator inputs (both at 50% duty cycle). Phase comparator II (with leading edge sensing logic) provides digital error signals $PCII_{OUT}$ and Phase Pulses, and maintains a 0° phase shift between input signals (duty cycle is immaterial). The linear VCO produces an output signal VCO_{OUT} whose frequency is determined by the voltage of input VCO_{IN} and the capacitor and resistors connected to pins C1A, C1B, R1, and R2. The source follower output, Demod Out, with an external resistor is used where the VCO_{IN} signal is needed but no loading can be tolerated. The inhibit input Inh , when high, disables the VCO and source follower to minimize standby power consumption. The zener diode can be used to assist in power supply regulation.

CONNECTION DIAGRAM (all packages)



Add suffix for package:

| | |
|---|----------------|
| C | 16-pin Cerdip |
| D | 16-pin Ceramic |
| E | 16-pin Epoxy |
| F | 16-pin Flat |
| H | Chip |

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | | |
| C, D, F, H Device | | -55 to +125 | °C |
| E Device | | -40 to +85 | °C |

BLOCK DIAGRAM




Fig. 1

VCO SECTION

The VCO requires one external capacitor (C1) and one to two external resistors (R1 or R1 and R2). Resistor R1 and capacitor C1 determine the frequency range of the VCO and resistor R2 enables the VCO to have a frequency offset if required. The high input impedance ($10^{12}\Omega$) of the VCO simplifies the design of low-pass filters by permitting the designer a wide choice of resistor-to-capacitor ratios. In order not to load the low-pass filter, a source-follower output of the VCO input voltage is provided at terminal 10 (DEMODULA-

TOR OUTPUT). If this terminal is used, a load resistor (R_L) of $50k\Omega$ or more should be connected from this terminal to V_{SS} . If unused, this terminal should be left open. The VCO can be connected directly or through frequency dividers to the comparator input of the phase comparators. A full CMOS logic swing is available at the output of the VCO. A logic 0 on the INHIBIT input "enables" the VCO and the source follower, while a logic 1 "turns off" both to minimize stand-by power consumption.

PHASE COMPARATORS

The phase-comparator signal input (terminal 14) can be direct-coupled provided the signal swing is within CMOS logic levels [logic "0" $\leq 30\%$ ($V_{DD} - V_{SS}$), logic "1" $\geq 70\%$ ($V_{DD} - V_{SS}$)]. For smaller swings the signal must be capacitively coupled to the self-biasing amplifier at the signal input.

Phase comparator I is an exclusive-OR network; it operates analogously to an over-driven balanced mixer. To maximize the lock range, the signal and comparator-input frequencies must have a 50% duty cycle. With no signal or noise on the signal input, this phase comparator has an average output voltage equal to $V_{DD}/2$. The low-pass filter connected to the output of phase comparator I supplies the averaged voltage to the VCO input, and causes the VCO to oscillate at the center frequency (f_0).

The frequency range of input signals on which the PLL will lock, if it was initially out of lock, is defined as the frequency capture range ($2f_c$).

The frequency range of input signals on which the loop will stay locked if it was initially in lock is defined as the frequency lock range ($2f_L$). The capture range can not exceed the lock range.

With phase comparator I, the range of frequencies over which the PLL can acquire lock (capture range) is dependent on the low-pass-filter characteristics, and can be made as large as the lock range. Phase-comparator I enables a PLL system to remain in lock in spite of high amounts of noise in the input signal.

One characteristic of this type of phase comparator is that it may lock onto input frequencies that are close to harmonics of the VCO center-frequency. A second characteristic is that the phase angle between the signal and the comparator input varies between 0° and 180° , and is 90° at the center frequency. Figure 2 shows the (typical) triangular phase-to-output response characteristic of phase-comparator I. Typical waveforms for a CMOS phase-locked-loop employing phase comparator I in locked condition is shown in Figure 3.




Fig. 2 — Phase-comparator I characteristics at low-pass filter output.




Fig. 3 — Typical waveforms employing phase comparator I in locked condition





Fig. 4 — Typical waveforms employing phase comparator II in locked condition.

Phase-comparator II is an edge-controlled digital memory network. It consists of several flip-flop stages, control gating, and a three state output circuit comprising p- and n-type drivers having a common output node. When the p-MOS or n-MOS drivers are ON, they pull the output up to V_{DD} or down to V_{SS} , respectively. This type of phase comparator acts only on the positive edges of the signal and comparator inputs. The duty cycles of the signal and comparator inputs are not important since positive transitions control the PLL system utilizing this type of comparator. If the signal lags the comparator input in phase, the n-type output driver is maintained ON for a time corresponding to the phase difference. If the comparator input lags the signal in phase, the p-type output driver is maintained ON for a time corresponding to the phase difference. Subsequently, the capacitor voltage of the low-pass filter connected to this phase comparator is adjusted until the signal and comparator inputs are equal in both phase and frequency. At this stable point, both p- and n-type output

drivers remain OFF. Thus, the phase comparator output becomes an open circuit and holds the voltage on the capacitor of the low-pass filter constant. Moreover, the signal at the "phase pulses" output is a high level which can be used for indicating a locked condition. Thus, for phase comparator II, no phase difference exists between signal and comparator input over the full VCO frequency range. Moreover, the power dissipation due to the low-pass filter is reduced when this type of phase comparator is used because both the p- and n-type output drivers are OFF for most of the signal input cycle.

It should be noted that the PLL lock range for this type of phase comparator is equal to the capture range, independent of the low-pass filter. With no signal present at the signal input, the VCO is adjusted to its lowest frequency for phase comparator II. Figure 4 shows typical waveforms for a CMOS PLL employing phase comparator II in a locked condition.







DESIGN INFORMATION

This information is a guide for approximating the values of external components for the 4046B and 4446B in a Phase-Locked Loop system. The selected external components must be within the following ranges:

$$R_1, R_2 \geq 2k\Omega, R_S \geq 10k\Omega$$

$$C_1 \geq 15pF$$

In addition to the given design information refer to Figure 5 for R_1 , R_2 , and C_1 component selections.

| CHARACTERISTICS | USING PHASE COMPARATOR I | | USING PHASE COMPARATOR II | |
|---|---|--|---|--|
| | VCO WITHOUT OFFSET $R_2 = \infty$ | VCO WITH OFFSET | VCO WITHOUT OFFSET $R_2 = \infty$ | VCO WITH OFFSET |
| VCO Frequency |  |  |  |  |
| For No Signal Input | VCO in PLL system will adjust to center frequency, f_0 | | VCO in PLL system will adjust to lowest operating frequency, f_{min} | |
| Frequency Lock Range, $2f_L$ | $2f_L = \text{full VCO frequency range}$ $2f_L = f_{max} - f_{min}$ | | | |
| Frequency Capture Range, $2f_C$ |  $2f_C \approx \frac{1}{\pi} \sqrt{\frac{2\pi f_L}{\tau}}$ | | $f_C = f_L$ | |
| Loop Filter Component Selection |  <p>For $2f_C$, see Ref.</p> | | | |
| Phase Angle between Signal and Comparator | 90° at center frequency (f_0), approximating 0° and 180° at ends of lock range ($2f_L$) | | Always 0° in lock | |
| Locks on Harmonics of Center Frequency | Yes | | No. | |
| Signal Input Noise Rejection | High | | Low | |
| VCO Component Selection | <ul style="list-style-type: none">Given: f_0Use f_0 with Fig.5a to determine R1 and C1 | <ul style="list-style-type: none">Given: f_0 and f_LCalculate f_{min} from the equation $f_{min} = f_0 - f_L$Use f_{min} with Fig. 5b to determine R2 and C1Calculate $\frac{f_{max}}{f_{min}}$ from the equation $\frac{f_{max}}{f_{min}} = \frac{f_0 + f_L}{f_0 - f_L}$Use $\frac{f_{max}}{f_{min}}$ with Fig.5c to determine ratio R2/R1 to obtain R1 | <ul style="list-style-type: none">Given: f_{max}Calculate f_0 from the equation $f_0 = \frac{f_{max}}{2}$Use f_0 with Fig.5a to determine R1 and C1 | <ul style="list-style-type: none">Given: f_{min} & f_{max}Use f_{min} with Fig.5b to determine R2 and C1Calculate $\frac{f_{max}}{f_{min}}$Use $\frac{f_{max}}{f_{min}}$ with Fig.5c to determine ratio R2/R1 to obtain R1 |

REF. G. S. Moschytz, "Miniaturized RC Filters Using Phase-Locked Loop", BSTJ, May, 1965.

ELECTRICAL CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|------------|--|------|-------|------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | 5 | Inhibit = V _{DD} | — | 5 | — | 0.05 | — | 150 | μAdc |
| | | 10 | Signal Input = V _{DD} | — | 10 | — | 0.01 | — | 300 | |
| | | 15 | | — | 20 | — | 0.2 | — | 600 | |
| TOTAL POWER DISSIPATION | P _T | | Inh = V _{SS} , VCO _{IN} = $\frac{V_{DD}}{2}$ f _o = 10kHz, C _L = 15pF, R ₁ = 1MΩ, R ₂ = R _S = ∞ | | | | | | | mW |
| | | 5 | | — | — | — | 0.07 | — | — | |
| | | 10 | | — | — | — | 0.6 | — | — | |
| | | 15 | | — | — | — | 2.4 | — | — | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.

= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.

= + 85°C for E device.

| PARAMETER | | CONDITIONS | V _{DD} | 25°C | | | UNIT | | |
|---|------------------|---|-----------------|---------------|--|-------------------|-------------|-----|----|
| | | | | Min. | Typ. | Max. | | | |
| VCO SECTION | | | | | | | | | |
| MAXIMUM OPERATING FREQUENCY 4046B 4446B | f _{max} | R2 = ∞ VCO _{IN} = V _{DD} | R1 C1 | | | | | | |
| | | | 10k 50pF | 5 10 15 | 0.5 1.0 1.3 | 0.8 1.5 1.9 | — — — | MHz | |
| | | | 5k 50pF | 5 10 15 | 0.6 1.4 1.8 | 1.0 2.1 2.7 | — — — | MHz | |
| | | | 2k 50pF | 5 10 15 | — — — | 1.3 2.9 3.8 | — — — | MHz | |
| | | | R1 C1 | | | | | | |
| | | | 10k 50pF | 5 10 15 | 0.7 1.3 1.9 | 1.0 2.0 2.8 | — — — | MHz | |
| | | | 5k 50pF | 5 10 15 | 0.9 1.9 2.6 | 1.3 2.9 3.9 | — — — | MHz | |
| | | | 2k 50pF | 5 10 15 | — — — | 1.8 3.9 5.4 | — — — | MHz | |
| | | | LINEARITY | | R2 = ∞ VCO _{IN} = 2.5±0.3V, R1 ≥ 10kΩ VCO _{IN} = 5.0±2.5V, R1 ≥ 400kΩ VCO _{IN} = 7.5±5.0V, R1 ≥ 1MΩ | 5 | — | 1 | — |
| | | 10 | | | | — | 1 | — | |
| | | 15 | | | | — | 1 | — | |
| | | INPUT CAPACITANCE | C _{IN} | Pin 14 Only | — | — | — | 10 | pF |
| All Other Inputs | — | | | — | — | 7.5 | | | |

ELECTRICAL CHARACTERISTICS (Continued)

| PARAMETER | CONDITIONS | V _{DD} | +25°C | | | UNIT | | | |
|--|-------------------------------------|---|--------------------------------------|-------------------------------------|-------------------|--------------------|-------------------|-------------------|-----------------|
| | | | Min. | Typ. | Max. | | | | |
| VCO SECTION (Continued) | | | | | | | | | |
| TEMPERATURE-FREQUENCY STABILITY No Offset | | R2 = ∞ | 5 | — | 0.12-0.24 | % / °C | | | |
| | | | 10 | — | 0.04-0.08 | | | | |
| | | | 15 | — | 0.015-0.03 | | | | |
| | With Offset | R2 ≤ 10X R1 | 5 | — | 0.06-0.12 | % / °C | | | |
| | | | 10 | — | 0.05-0.1 | | | | |
| | | | 15 | — | 0.03-0.06 | | | | |
| INPUT RESISTANCE (VCO _{IN}) | R _{IN} | 5, 10, 15 | — | 10 ⁶ | — | MΩ | | | |
| OUTPUT DUTY CYCLE | | All valid input combinations and voltages | — | 50 | — | % | | | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | C _L = 50pF | 5 10 15 | — — — | 100 50 40 | 200 100 80 | ns | | |
| PHASE COMPARATORS | | | | | | | | | |
| INPUT RESISTANCE Signal Input | R _{IN} | | 5 10 15 | 1 0.2 0.1 | 3 0.7 0.3 | — — — | MΩ | | |
| | | | Comparator Input | R _{IN} | 5, 10, 15 | — | 10 ⁶ | — | MΩ |
| | | | | | | | | | |
| AC-COUPLED INPUT SENSITIVITY Signal Input | V _{IN} | | 5 10 15 | — — — | 200 400 700 | 400 800 1400 | mV | | |
| OUTPUT TRANSITION TIME PCI, PCII Outputs | t _{TLH} , t _{THL} | C _L = 50pF | 5 10 15 | — — — | 100 50 40 | 200 100 80 | ns | | |
| | | | Phase Pulses Output | t _{TLH} , t _{THL} | 5 10 15 | — — — | 130 65 50 | 260 130 100 | ns |
| | | | | | | | | | |
| | | | | | | | | | |
| | DEMODULATOR OUTPUT | | | | | | | | |
| | OFFSET VOLTAGE | | VCO _{IN} - V _{DEM} | R _S > 50kΩ | 5 10 15 | — — — | 1.4 1.6 1.8 | 2.2 2.2 2.2 | V _{dc} |
| LINEARITY | | R _S > 50kΩ VCO _{IN} = 2.5±0.3V VCO _{IN} = 5.0±2.5V VCO _{IN} = 7.5±5.0V | 5 10 15 | — — — | 0.1 0.6 0.8 | — — — | % | | |
| ZENER DIODE | | | | | | | | | |
| ZENER VOLTAGE | V _Z | I _Z = 50μA | — | 6.3 | 7.0 | 7.7 | V | | |
| DYNAMIC RESISTANCE | R _Z | I _Z = 1mA | — | — | 100 | — | Ω | | |




Fig. 5 (a) Typical center frequency (f_0) vs C1 ($R_2 = \infty$, $V_{COIN} = \frac{V_{DD}}{2}$, $T_A = 25^\circ\text{C}$)




Fig. 5 (b) Typical frequency offset vs C1 ($V_{COIN} = V_{SS}$, $T_A = 25^\circ\text{C}$)




Fig. 5 (c) Typical f_{max}/f_{min} vs R_2/R_1




Fig. 6 (a) - Typical VCO power dissipation at center frequency vs R1.




Fig. 6 (b) - Typical VCO power dissipation at f_{min} vs R2.




Fig. 6 (c) - Typical source follower power dissipation vs R_S .

NOTE: To obtain approximate total power dissipation of PLL system for no-signal input

$$P_D (\text{Total}) = P_D (f_0) + P_D (f_{MIN}) + P_D (R_S) \\ \text{— Phase Comparator I}$$

$$P_D (\text{Total}) = P_D (f_{MIN}) \\ \text{— Phase Comparator II}$$




Fig. 7 - Typical lock range vs signal input amplitude





Fig. 8(a, b) - Typical VCO linearity vs R1 and C1

CMOS MONOSTABLE/ASTABLE MULTIVIBRATOR

FEATURES


- Low Power Consumption
- Monostable (one-shot) or (Astable) Operation
- True and Complementary Buffered Outputs
- Only One External R and C Required
- Enabled with either a Low or a High Level in Astable Mode
- Triggered on either a Low to High or High to Low Transition in Monostable Mode
- Asynchronous Master Reset
- Output Pulse Width Independent of Trigger Pulse, in Monostable Mode
- May Be Utilized as Free Running or Gated Oscillator, in Astable Mode

DESCRIPTION


4047B is capable of operating in either the monostable or astable mode. It requires an external capacitor (between pins 1 and 3) and an external resistor (between pins 2 and 3) to determine the output pulse width in the monostable mode, and the output frequency in the astable mode.

Astable operation is enabled by a high level on the astable input or low level on the $\overline{\text{astable}}$ input. The output frequency (at 50% duty cycle) at Q and \overline{Q} outputs is determined by the timing components. A frequency twice that of Q is available at the Oscillator Output; a 50% duty cycle is not guaranteed.

BLOCK DIAGRAM



CONNECTION DIAGRAM



Monostable operation is obtained when the device is triggered by low-to-high transition at + trigger input or high-to-low transition at -trigger input. The device can be retriggered by applying a simultaneous low-to-high transition to both the + trigger and retrigger inputs.

A high level on Reset input resets the outputs Q to low, \overline{Q} to high.

Absolute Maximum Ratings

| | |
|--|--|
| V_{DD} DC Supply Voltage | – 0.5 to + 18V _{DC} |
| V_{IN} Input Voltage | – 0.5 to V_{DD} + 0.5V _{DC} |
| T_S Storage Temperature Range | – 65°C to + 150°C |
| P_D Package Dissipation | 500mW |
| T_L Lead Temperature (Soldering, 10 seconds) | 300°C |

Recommended Operating Conditions

| | |
|-----------------------------------|-------------------------------|
| V_{DD} DC Supply Voltage | 3 to 15V _{DC} |
| V_{IN} Input Voltage | 0 to V_{DD} V _{DC} |
| T_A Operating Temperature Range | – 55°C to + 125°C |
| SCL4047BC, D, F, H | |
| SCL4047BE | – 40°C to + 85°C |

ELECTRICAL CHARACTERISTICS**STATIC CHARACTERISTICS** ¹

| PARAMETER | V_{DD} (Vdc) | CONDITIONS | T_{LOW} ² | | +25°C | | | T_{HIGH} ² | | Units |
|--------------------------|-------------------|---|------------------------|------|-------|--------|------|-------------------------|------|-----------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I_{DD} | $V_{IN}=V_{SS}$ or V_{DD} All valid input combinations | – | 1.0 | – | 0.0005 | 1.0 | – | 30 | μ Adc |
| | 5 | | – | 2.0 | – | 0.001 | 2.0 | – | 60 | |
| | 10 | | – | 4.0 | – | 0.002 | 4.0 | – | 120 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = –55°C for C, D, F, H device.

= –40°C for E device.


T_{HIGH} = +125°C for C, D, F, H device.

= + 85°C for E device.

AC ELECTRICAL CHARACTERISTICS

$T_A = 25^\circ\text{C}$, $C_L = 50\text{ pF}$

| PARAMETER | | CONDITIONS | MIN | TYP | MAX | UNITS |
|--------------------|--|--|-----|-------------------|--------------------|---------|
| t_{PHL}, t_{PLH} | Propagation Delay Time Astable, Astable to OSC Out | $V_{DD} = 5V$ $V_{DD} = 10V$ $V_{DD} = 15V$ | | 200 100 80 | 400 200 160 | ns |
| t_{PHL}, t_{PLH} | Astable, Astable to Q Q | $V_{DD} = 5V$ $V_{DD} = 10V$ $V_{DD} = 15V$ | | 550 250 200 | 900 500 400 | ns |
| t_{PHL}, t_{PLH} | + Trigger, – Trigger to Q Q | $V_{DD} = 5V$ $V_{DD} = 10V$ $V_{DD} = 15V$ | | 700 300 240 | 1200 600 480 | ns |
| t_{PHL}, t_{PLH} | + Trigger, Retrigger to Q Q | $V_{DD} = 5V$ $V_{DD} = 10V$ $V_{DD} = 15V$ | | 300 175 150 | 600 300 250 | ns |
| t_{PHL}, t_{PLH} | Reset to Q Q | $V_{DD} = 5V$ $V_{DD} = 10V$ $V_{DD} = 15V$ | | 300 125 100 | 500 250 200 | ns |
| t_{THL}, t_{TLH} | Transition Time Q, Q, OSC Out | $V_{DD} = 5V$ $V_{DD} = 10V$ $V_{DD} = 15V$ | | 100 50 40 | 200 100 80 | ns |
| t_{WL}, t_{WH} | Minimum Input Pulse Duration | Any Input $V_{DD} = 5V$ $V_{DD} = 10V$ $V_{DD} = 15V$ | | 500 200 160 | 1000 400 320 | ns |
| t_{RCL}, t_{FCL} | + Trigger, Retrigger, Rise and Fall Time | $V_{DD} = 5V$ $V_{DD} = 10V$ $V_{DD} = 15V$ | | | 15 5 5 | μ s |
| C_{IN} | Average Input Capacitance | Any Input | | 5 | 7.5 | pF |




TRUTH TABLE

| FUNCTION | TERMINAL CONNECTIONS | | | OUTPUT PULSE FROM | TYPICAL OUTPUT PERIOD OR PULSE WIDTH |
|--------------------------|----------------------|--------------------|----------------|-------------------|--------------------------------------|
| | TO V _{DD} | TO V _{SS} | INPUT PULSE TO | | |
| Astable Multivibrator | 4, 5, 6, 14 | 7, 8, 9, 12 | | 10, 11, 13 | $t_A(10, 11) = 4.40 RC$ |
| Free-Running | 4, 6, 14 | 7, 8, 9, 12 | 5 | 10, 11, 13 | |
| True Gating | 6, 14 | 5, 7, 8, 9, 12 | 4 | 10, 11, 13 | $t_A(13) = 2.20 RC$ |
| Complement Gating | | | | | |
| Monostable Multivibrator | 4, 14 | 5, 6, 7, 9, 12 | 8 | 10, 11 | |
| Positive-Edge Trigger | 4, 8, 14 | 5, 7, 9, 12 | 6 | 10, 11 | $t_M(10, 11) = 2.48 RC$ |
| Negative-Edge Trigger | 4, 14 | 5, 6, 7, 9 | 8, 12 | 10, 11 | |
| Retriggerable | | | | | |
| External Countdown* | 14 | 5, 6, 7, 8, 9, 12 | (See Figure) | (See Figure) | (See Figure) |


Note: External resistor between terminals 2 and 3. External capacitor between terminals 1 and 3.

*Typical Implementation of External Countdown Option



TYPICAL PERFORMANCE CHARACTERISTICS


Typical Q, \bar{Q} , Osc Out Period Accuracy vs Supply Voltage (Astable Mode Operation)



V_{DD} — SUPPLY VOLTAGE (V)

| | $f_{Q, \bar{Q}}$ | R | C |
|---|------------------|------|---------|
| A | 1000 kHz | 22k | 10 pF |
| B | 100 kHz | 22k | 100 pF |
| C | 10 kHz | 220k | 100 pF |
| D | 1 kHz | 220k | 1000 pF |
| E | 100 Hz | 2.2M | 1000 pF |


Typical Q, \bar{Q} and Osc Out Period Accuracy vs Temperature Astable Mode Operation



T_A — AMBIENT TEMPERATURE (°C)

| | $f_{Q, \bar{Q}}$ | R | C |
|---|------------------|------|---------|
| A | 1000 kHz | 22k | 10 pF |
| B | 100 kHz | 22k | 100 pF |
| C | 10 kHz | 220k | 100 pF |
| D | 1 kHz | 220k | 1000 pF |


Typical Q, \bar{Q} , Pulse Width Accuracy vs Supply Voltage Monostable Mode Operation



V_{DD} — SUPPLY VOLTAGE (V)

| | t_M | R | C |
|---|-------------|------|---------|
| A | 2 μ s | 22K | 10 pF |
| B | 7 μ s | 22k | 100 pF |
| C | 60 μ s | 220k | 100 pF |
| D | 550 μ s | 220k | 1000 pF |
| E | 5.5ms | 2.2M | 1000 pF |




Typical Q and \bar{Q} Pulse Width Accuracy vs Temperature Monostable Mode Operation



T_A — TEMPERATURE (°C)

| | t_M | R | C |
|---|-------------|------|---------|
| A | 2 μ s | 22K | 10 pF |
| B | 7 μ s | 22k | 100 pF |
| C | 60 μ s | 220k | 100 pF |
| D | 550 μ s | 220k | 1000 pF |

TIMING DIAGRAMS



CMOS HEX BUFFERS/CONVERTERS

FEATURES


- ◆ Direct Drive of 2 TTL/DTL Loads
- ◆ Operation from Single Supply
- ◆ Pin-for Pin Replacements for 4009UB 4010B

DESCRIPTION

The 4049UB and 4050B are Inverting and Non-Inverting Hex Buffers, respectively, and feature logic-level conversions using only one supply voltage (V_{CC}). The Input-signal high level (V_{IH}) can exceed the V_{CC} supply voltage when these devices are used for logic-level conversions. These devices are intended for use as CMOS-to-DTL/TTL converters and can drive directly two DTL/TTL Loads.


The 4049UB and 4050B are interchangeable with 4009 UB and 4010B devices, respectively. In these applications the 4049UB and 4050B are pin-compatible with the 4009UB and 4010B, respectively, and can be substituted for these devices in existing as well as in new designs. Terminal No. 16 is not connected internally on the 4049UB or 4050B; therefore, connection to this terminal is of no consequence to circuit operation.

SCHEMATIC DIAGRAMS



CONNECTION DIAGRAM

(all packages)



RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

DC Supply Voltage $V_{CC} - V_{SS}$ 3 to 15 Vdc


Operating Temperature T_A

C, D, F, H Device -55 to +125 °C

E Device -40 to +85 °C

Note: These devices contain input protection networks to V_{SS} only. Therefore, V_{IH} (max) may exceed V_{CC} without damage (subject to absolute maximum ratings).

LOGIC DIAGRAMS



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{CC} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|---------------------------|--------------------------|--|-------------------------------|------|-------|-------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{CC} | V _{IN} =V _{SS} or V _{DD} All valid input combinations | – | 1.0 | – | 0.005 | 1.0 | – | 30 | μAdc |
| | | | – | 2.0 | – | 0.01 | 2.0 | – | 60 | |
| | | | – | 4.0 | – | 0.02 | 4.0 | – | 120 | |
| OUTPUT LOW (SINK) CURRENT | I _{OL} | V _{OL} =0.4V V _{OL} =0.5V V _{OL} =1.5V V _{IN} =V _{SS} or V _{DD} | 3.7 | – | 3.0 | 6.4 | – | 2.1 | – | mAdc |
| | | | 10 | – | 8.0 | 16 | – | 5.6 | – | |
| | | | 30 | – | 24.0 | 40 | – | 16.8 | – | |
| | | | | | | | | | | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.


= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.


= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)


| PARAMETER | | V _{IN} (Vdc) | V _{CC} (Vdc) | Min. | Typ. | Max. | Units | | | |
|----------------------------------|------------------|--------------------------|--------------------------|------------------|------|------|-------|----|-----|----|
| PROPAGATION DELAY TIME 4049UB | t _{PLH} | 5 | 5 | — | 60 | 120 | ns | | | |
| | | 10 | 10 | — | 32 | 65 | | | | |
| | | 15 | 15 | — | 25 | 50 | | | | |
| | | 10 | 5 | — | 45 | 90 | ns | | | |
| | | 15 | 5 | — | 45 | 90 | | | | |
| | | 5 | 5 | — | 70 | 140 | ns | | | |
| | 10 | 10 | — | 40 | 80 | | | | | |
| | 15 | 15 | — | 30 | 60 | | | | | |
| | 4050B | t _{PLH} | 10 | 5 | — | 45 | 90 | ns | | |
| | | | 15 | 5 | — | 40 | 80 | | | |
| | | | 5 | 5 | — | 32 | 65 | | ns | |
| | | | 10 | 10 | — | 20 | 40 | | | |
| 15 | | | 15 | — | 15 | 30 | | | | |
| 10 | | | 5 | — | 15 | 30 | ns | | | |
| 15 | 5 | — | 10 | 20 | | | | | | |
| 5 | 5 | — | 55 | 110 | ns | | | | | |
| 10 | 10 | — | 27 | 55 | | | | | | |
| 15 | 15 | — | 15 | 30 | | | | | | |
| 4049UB | t _{PHL} | 10 | 5 | — | 50 | 100 | ns | | | |
| | | 15 | 5 | — | 50 | 100 | | | | |
| | | 5 | 5 | — | 80 | 160 | | ns | | |
| | | 10 | 10 | — | 40 | 80 | | | | |
| | | 15 | 15 | — | 30 | 60 | | | | |
| | | 4050B | t _{PHL} | 5 | 5 | — | 30 | 60 | ns | |
| 10 | 10 | | | — | 20 | 40 | | | | |
| 15 | 15 | | | — | 15 | 30 | | | | |
| OUTPUT TRANSITION TIME | | | | t _{TLH} | 5 | 5 | — | 80 | 160 | ns |
| | | | | | 10 | 10 | — | 40 | 80 | |
| | | | | | 15 | 15 | — | 30 | 60 | |
| | | t _{THL} | 5 | 5 | — | 30 | 60 | ns | | |
| | | | 10 | 10 | — | 20 | 40 | | | |
| | | | 15 | 15 | — | 15 | 30 | | | |
| INPUT CAPACITANCE 4049UB | | C _{IN} | — | — | — | 15 | 22.5 | pF | | |




Typical P-Channel
Source Current Characteristics



Typical N-Channel
Sink Current Characteristics



Typical voltage transfer characteristics as a function
of temperature for 4049UB.



Typical voltage transfer characteristics as a function
of temperature for 4050B.

CMOS ANALOG MULTIPLEXERS/DEMULTIPLEXERS

FEATURES

- ◆ Wide Range of Digital and Analog Signal Levels: Digital-3 to 15V, Analog-to 15V_{p-p}
- ◆ Low ON-Resistance: 80Ω (typ.) over entire 15V_{p-p} Signal-Input Range for V_{DD}-V_{EE} = 15V
- ◆ High OFF-Resistance: Input Leakage ± 10pA (typ.) @ V_{DD}-V_{EE} = 10V
- ◆ Logic-Level Conversion for Digital Addressing Signals of 3 to 15V (V_{DD}-V_{SS} = 3V to 15V) to Switch Analog Signals to 15V_{p-p} (V_{DD}-V_{EE} = 15V)
- ◆ Matched Switch Characteristics: ΔR_{ON} = 5Ω (typ.) for V_{DD}-V_{EE} = 18V
- ◆ Very Low Quiescent Power Dissipation under all Digital Control Input and Supply Conditions: 1μW typ. @ V_{DD}-V_{SS} = V_{DD}-V_{EE} = 10V
- ◆ Binary Address Decoding on Chip

DESCRIPTION

The 4051B, 4052B, and 4053B are Digitally-Controlled Analog Switches having low ON-impedance and very low OFF leakage current. Control of analog signals up to 15V_{p-p} can be achieved by digital signal amplitudes of 3 to 15V. For example, if V_{DD} = +5V, V_{SS} = 0V, and V_{EE} = -5V, analog signals from -5V to +5V can be controlled by digital inputs of 0 to 5V. The multiplexer circuits dissipate extremely low quiescent power over the full V_{DD} - V_{SS} and V_{DD} - V_{EE} supply-voltage ranges, independent of the logic state of the control signals. When a logic "1" is present at the Inhibit input terminal all channels are OFF.




4051B is a Single 8-Channel Multiplexer having three binary Control inputs, A, B, and C, and an Inhibit input. The three binary signals select 1 of 8 channels to be turned ON and connect the input to the output.

4052B is a Differential 4-Channel Multiplexer having two binary Control inputs, A and B, and an Inhibit input. The two binary input signals select 1 of 4 pairs of channels to be turned on and connect the differential analog inputs to the differential outputs.

4053B is a Triple 4-Channel Multiplexer having three separate digital Control inputs, A, B, and C and an Inhibit input. Each control input selects one of a pair of channels which are connected in a single-pole double-throw configuration.

When the devices are used as demultiplexers, the "CHANNEL IN/OUT" terminals are the outputs and the "COMMON OUT/IN" terminal(s) is (are) the input(s).

CONNECTION DIAGRAMS (all packages)




RECOMMENDED OPERATING CONDITIONS

For maximum reliability:


| | | | |
|-----------------------|-----------------------------------|-------------|-----------------|
| DC Supply Voltage | V _{DD} - V _{SS} | 3 to 15 | V _{dc} |
| | V _{DD} - V _{EE} | 3 to 15 | V _{dc} |
| Operating Temperature | T _A | | |
| C, D, F, H Device | | -55 to +125 | °C |
| E Device | | -40 to +85 | °C |

NOTE: There are no restrictions on the relative magnitudes of V_{SS} and V_{EE}, providing Absolute Maximum Ratings are observed.


LOGIC DIAGRAMS



4051B
Single 8-Channel Multiplexer



4052B
Differential 4-Channel Multiplexer



4053B
Triple 2-Channel Multiplexer

TRUTH TABLE

| INPUT STATES | | | | "ON" CHANNELS | | |
|--------------|---|---|---|---------------|--------|------------|
| INHIBIT | C | B | A | 4051 | 4052 | 4053 |
| 0 | 0 | 0 | 0 | 0 | 0x, 0y | cx, bx, ax |
| 0 | 0 | 0 | 1 | 1 | 1x, 1y | cx, bx, ay |
| 0 | 0 | 1 | 0 | 2 | 2x, 2y | cx, by, ax |
| 0 | 0 | 1 | 1 | 3 | 3x, 3y | cx, by, ay |
| 0 | 1 | 0 | 0 | 4 | | cy, bx, ax |
| 0 | 1 | 0 | 1 | 5 | | cy, bx, ay |
| 0 | 1 | 1 | 0 | 6 | | cy, by, ax |
| 0 | 1 | 1 | 1 | 7 | | cy, by, ay |
| 1 | * | * | * | NONE | NONE | NONE |

* = Don't care

ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | CONDITIONS | V _{SS} (Vdc) | V _{DD} (Vdc) | V _{EE} (Vdc) | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--|---|--------------------------|--------------------------|--------------------------|-------------------------------|------|-------|-------|------|--------------------------------|-------|-------|
| | | | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} V _{IN} =V _{SS} or V _{DD} All valid input combinations | 0 | +5 | 0 | — | 5 | — | 0.05 | 5 | — | 150 | μAdc |
| | | 0 | +10 | 0 | — | 10 | — | 0.1 | 10 | — | 300 | |
| | | | +5 | -5 | | | | | | | | |
| | | 0 | +15 | 0 | — | 20 | — | 0.2 | 20 | — | 600 | |
| | | | +7.5 | -7.5 | | | | | | | | |
| MINIMUM INPUT HIGH VOLTAGE (Control and Inhibit Inputs) | V _{IH} V _S =V _{EE} V _{OS} =V _{DD} I _{OS} =10μA | 0 | 5 | 0 | — | 3.5 | — | 2.75 | 3.5 | — | 3.5 | Vdc |
| | | 0 | 10 | 0 | — | 7.0 | — | 5.5 | 7.0 | — | 7.0 | |
| | | 0 | 15 | 0 | — | 11.0 | — | 8.25 | 11.0 | — | 11.0 | |
| MAXIMUM INPUT LOW VOLTAGE (Control and Inhibit Inputs) | V _{IL} V _S =V _{EE} V _{OS} =V _{DD} I _{OS} =10μA | 0 | 5 | 0 | 1.5 | — | 1.5 | 2.25 | — | 1.5 | — | Vdc |
| | | 0 | 10 | 0 | 3.0 | — | 3.0 | 4.5 | — | 3.0 | — | |
| | | 0 | 15 | 0 | 4.0 | — | 4.0 | 6.75 | — | 4.0 | — | |
| SWITCH INPUT/ OUTPUT LEAKAGE Any channel OFF | I _{OFF} V _{IN} =V _{SS} or V _{DD} V _S =±7.5Vdc | 0 | +7.5 | -7.5 | — | ±100 | — | ±0.01 | ±100 | — | ±1000 | nAdc |
| | | | | | | | | | | | | |
| | All channels OFF I _{OFF} I _{nh} =7.5Vdc V _S =±7.5Vdc | 0 | +7.5 | -7.5 | | | | | | | | nAdc |
| | | | | | — | ±400 | — | ±0.08 | ±400 | — | ±1000 | |
| | | | | | — | ±200 | — | ±0.04 | ±200 | — | ±1000 | |
| ON-RESISTANCE | R _{ON} V _{IN} =V _{SS} or V _{DD} V _{EE} ≤V _S ≤V _{DD} R _L =10kΩ | -7.5 | +7.5 | -7.5 | | | | | | | | Ω |
| | | 0 | +15 | 0 | — | 220 | — | 125 | 280 | — | 400 | |
| | | -5 | +5 | -5 | — | 310 | — | 180 | 400 | — | 590 | |
| | | 0 | +10 | 0 | | | | | | | | |
| | | -2.5 | +2.5 | -2.5 | — | 2000 | — | 470 | 2500 | — | 3500 | |
| ON-RESISTANCE MATCH (Same Package) | ΔR _{ON} V _{IN} =V _{SS} or V _{DD} V _{EE} ≤V _S ≤V _{DD} R _L =10kΩ | -7.5 | +7.5 | -7.5 | — | — | — | 5 | — | — | — | Ω |
| | | 0 | +15 | 0 | | | | 10 | — | — | — | |
| | | -5 | +10 | -5 | — | — | — | 10 | — | — | — | |
| | | 0 | +10 | 0 | | | | | | | | |
| | | -2.5 | +2.5 | -2.5 | — | — | — | 50 | — | — | — | |
| | | 0 | +5 | 0 | | | | | | | | |

NOTES: ¹ Remaining Static Characteristics are listed under "4000B Series Family Specifications".

² In certain applications, the external load-resistor current may include both V_{DD} and signal-line components. To avoid drawing V_{DD} current when switch current flows into terminals 1, 4, 8, or 11, the voltage drop across the bidirectional switch must not exceed 0.8 volt (calculated from R_{ON} values shown).


No V_{DD} current will flow through R_L if the switch current flows into terminals 2, 3, 9, or 10. Failure to observe this condition may result in distortion of the signal.

ELECTRICAL CHARACTERISTICS (Continued)


DYNAMIC CHARACTERISTICS ($C_L = 50\text{pF}$, $T_A = 25^\circ\text{C}$)

| PARAMETER | CONDITIONS | | V _{SS} (Vdc) | V _{DD} (Vdc) | V _{EE} (Vdc) | Min. | Typ. | Max. | Units |
|---|--------------------------------------|--|-------------------------------|--|-----------------------------------|----------------------------|--|--|-------|
| SIGNAL INPUTS (V _{in}) AND OUTPUTS (V _{out}) | | | | | | | | | |
| PROPAGATION DELAY TIME Signal Input to Signal Output | t _{PLH} t _{PHL} | Inh = V _{SS} V _{IN} =V _{SS} or V _{DD} V _{in} = Square Wave R _L = 10kΩ | 0 0 0 | 5 10 15 | 0 0 0 | — — — | 30 15 12.5 | 60 30 25 | ns |
| BANDWIDTH (-3dB) (Sine Wave) | BW | Inh = V _{SS} R _L V _{IN} =V _{SS} 1kΩ or V _{DD} 10kΩ V _{in} =5V _{p-p} 100kΩ centered 1MΩ @ 0.0Vdc | 0 | +5 | -5 | — — — — | 54 40 38 37 | — — — — | MHz |
| INSERTION LOSS (= 20 log ₁₀ $\frac{V_{os}}{V_{in}}$) | | Inh = V _{SS} R _L V _{IN} =V _{SS} 1kΩ or V _{DD} 10kΩ V _{in} =5V _{p-p} 100kΩ centered 1MΩ @ 0.0Vdc | 0 | +5 | -5 | — — — — | 2.3 0.2 0.1 0.05 | — — — — | dB |
| SIGNAL DISTORTION (Sine Wave) | | Inh = V _{SS} V _{IN} =V _{SS} or V _{DD} V _{in} = 5V _{p-p} centered @ 0.0Vdc f _{in} = 1.0kHz R _L = 10kΩ | -7.5 -5 -2.5 | +7.5 +5 +2.5 | -7.5 -5 -2.5 | — — — | 0.1 0.2 1.0 | — — — | % |
| FEEDTHROUGH (-40dB) | | Inh = V _{SS} R _L V _{IN} =V _{SS} 1kΩ or V _{DD} 10kΩ V _{in} =5V _{p-p} 100kΩ centered 1MΩ @0.0Vdc | 0 | +5 | -5 | — — — — | 1250 140 18 2 | — — — — | kHz |
| CROSSTALK (-40dB) Between two switches | | Inh = V _{SS} V _{IN} =V _{SS} or V _{DD} V _{in} =5V _{p-p} centered @ 0.0Vdc R _L = 1.0kΩ | 0 | +5 | -5 | — | 1.0 | — | MHz |
| CAPACITANCE Input | C _{in} | Inh = V _{DD} | 0 | +5 | -5 | — | 5 | — | pF |
| Common | C _{os} | 4051B | 0 | +5 | -5 | — | 30 | — | pF |
| | | 4052B | | | | — | 18 | — | |
| Feedthrough | C _{ios} | 4053B | 0 | +5 | -5 | — | 10 | — | pF |
| CONTROL INPUTS | | | | | | | | | |
| PROPAGATION DELAY TIME ¹ | t _{PLH} t _{PHL} | Inh = V _{SS} V _{EE} ≤ V _{in} ≤ V _{DD} R _L = 10kΩ | 0 0 0 0 -2.5 0 | +7.5 +15 +5 +10 +2.5 +5 | -7.5 0 -5 0 -2.5 0 | — — — — — — | 160 120 225 160 400 360 | 320 240 450 320 800 720 | ns |
| INHIBIT INPUT | | | | | | | | | |
| PROPAGATION DELAY TIME | t _{PLH} t _{PHL} | V _{IN} =V _{SS} or V _{DD} V _{in} = V _{DD} R _L = 10kΩ | 0 0 0 0 -2.5 0 | +7.5 +15 +5 +10 +2.5 +5 | -7.5 0 -5 0 -2.5 0 | — — — — — — | 160 120 200 160 400 360 | 320 240 400 320 800 720 | ns |
| INHIBIT RECOVERY TIME ² | t _{rel} | V _{IN} =V _{SS} or V _{DD} V _{EE} ≤ V _{in} ≤ V _{DD} R _L = 10kΩ | 0 0 0 0 -2.5 0 | +7.5 +15 +5 +10 +2.5 +5 | -7.5 0 -5 0 -2.5 0 | — — — — — — | 150 80 200 105 300 225 | 300 160 400 210 600 450 | ns |


Notes: ¹ Channel Overlap time — interval following change of control input during which two channels may be ON simultaneously.
² Interval following removal of Inhibit during which channel information is invalid.




Typical Channel "ON" resistance vs. signal voltage




Typical "ON" characteristics



Typ. switch frequency response-switch "ON"




Typ. feedthru vs. freq. - switch "OFF"



Typ. crosstalk between switch circuits in the same package

SCHEMATIC DIAGRAM OF ONE SWITCH



CMOS 14-STAGE COUNTER AND OSCILLATOR

FEATURES



- ◆ 14 Fully Static Stages
- ◆ 10 Buffered Outputs Available
- ◆ Common Reset Line
- ◆ 8MHz Counting Rate @ 10Vdc
- ◆ All Active Oscillator Components on Chip for R-C or Crystal Control

DESCRIPTION

The 4060 B consists of an oscillator section and 14 ripple-carry binary counter stages. The oscillator configuration allows design of either R-C or crystal oscillator circuits. A Reset input is provided which resets the counter to the all-0's state. A high level on the Reset line accomplishes the reset function. The state of the counter is advanced one step in binary order on the negative transition of the Clock input ϕ . All inputs and outputs are fully buffered. Outputs are available from stages 4 through 10 and 12 through 14.


Applications include timers, frequency dividers, delay circuits and counter controls.

TRUTH TABLE

| CLOCK | RESET | OUTPUT STATE |
|---|-------|-----------------------|
|  | 0 | No Change |
|  | 0 | Advance to next state |
| X | 1 | All Outputs are low |

X = Don't Care

CONNECTION DIAGRAM (all packages)



Add suffix for package:

- C 16-pin Cerdip
- D 16-pin Ceramic
- E 16-pin Epoxy
- F 16-pin Flat
- H Chip

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

DC Supply Voltage $V_{DD} - V_{SS}$ 3 to 15 V_O

Operating Temperature T_A


C, D, F, H Device

E Device

-55 to +125 °C

-40 to +85 °C

LOGIC DIAGRAM



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|-----------------------------|--------------------------|--|-------------------------------|------|-------|------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | V _{IN} =V _{SS} or V _{DD} All valid input combinations | — | 5 | — | 0.05 | 5 | — | 150 | μAdc |
| | | | — | 10 | — | 0.1 | 10 | — | 300 | |
| | | | — | 20 | — | 0.2 | 20 | — | 600 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.


= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.


= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETER | | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|---------------------------------------|-------------------------------------|--------------------------|------|------|------|-------|
| CLOCKED OPERATION | | | | | | |
| PROPAGATION DELAY TIME Clock to Q4 | t _{PLH} , t _{PHL} | 5 | — | 400 | 800 | ns |
| | | 10 | — | 200 | 400 | |
| | | 15 | — | 150 | 300 | |
| Q _i to Q _i + 1 | t _{PLH} , t _{PHL} | 5 | — | 100 | 200 | ns |
| | | 10 | — | 40 | 80 | |
| | | 15 | — | 30 | 60 | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | — | 100 | 200 | ns |
| 10 | — | 40 | 80 | | | |
| 15 | — | 30 | 60 | | | |
| MINIMUM CLOCK PULSE WIDTH | PW _{CL} | 5 | — | 70 | 140 | ns |
| 10 | — | 30 | 60 | | | |
| 15 | — | 20 | 40 | | | |
| MAXIMUM CLOCK FREQUENCY | f _{CL} | 5 | 3.0 | 4.5 | — | MHz |
| | | 10 | 6.0 | 9.0 | — | |
| | | 15 | 7.5 | 11.0 | — | |
| MAXIMUM CLOCK RISE AND FALL TIME | t _{rCL} , t _{fCL} | 5 | 50 | 100 | — | μs |
| | | 10 | 50 | 100 | — | |
| | | 15 | 50 | 100 | — | |
| RESET OPERATION | | | | | | |
| PROPAGATION DELAY TIME | t _{PHL} | 5 | — | 200 | 400 | ns |
| | | 10 | — | 100 | 200 | |
| | | 15 | — | 75 | 150 | |
| MINIMUM RESET PULSE WIDTH | PW _R | 5 | — | 100 | 200 | ns |
| | | 10 | — | 40 | 80 | |
| | | 15 | — | 30 | 60 | |
| RESET REMOVAL TIME | t _{rem} | 5 | — | 150 | 300 | ns |
| | | 10 | — | 65 | 125 | |
| | | 15 | — | 40 | 75 | |




Typical P-Channel
Source Current Characteristics




Typical N-Channel
Sink Current Characteristics


TIMING DIAGRAM




TYPICAL COUNTER STAGE




APPLICATIONS INFORMATION




Typical RC oscillator circuit



Typical crystal oscillator circuit



Input pulse-shaping circuit (Schmitt trigger)



Input circuit characteristics for pulse-shaping circuit.

CMOS QUAD ANALOG SWITCH


FEATURES

- ◆ Transmission or Multiplexing of Analog or Digital Signals
- ◆ 80Ω Typical ON-Resistance for 15-Volt operation
- ◆ Switch ON-Resistance Matched to within 5Ω over 15-Volt Signal-Input Range
- ◆ ON-Resistance Flat over Full Peak-to-Peak Signal Range
- ◆ High Degree of Linearity:
 $\leq 0.5\%$ Distortion (typ) @ $f_{is} = 1\text{kHz}$,
 $V_{is} = 5\text{V}_{p-p}$, $V_{DD}-V_{SS} \geq 10\text{V}$, $R_L = 10\text{k}\Omega$
- ◆ Extremely Low OFF switch Leakage Resulting in very Low Offset Current and High Effective OFF Resistance:
 10pA (typ) @ $V_{DD}-V_{SS} = 10\text{V}$, $T_A = 25^\circ\text{C}$
- ◆ Extremely High Control Input Impedance (Control Circuit Isolated from Signal Circuit):
 $10^{12}\Omega$ (typ)
- ◆ Low Crosstalk between Switches:
 -50dB (typ) @ $f_{is} = 0.9\text{MHz}$, $R_L = 1\text{k}\Omega$
- ◆ Matched Control-Input to Signal-Output Capacitance Reduces Output Signal Transients
- ◆ Frequency Response, Switch ON = 40MHz (typ)


DESCRIPTION

The 4066B is a Quad Bilateral Switch intended for the transmission or multiplexing of analog or digital signals. It is pin-for-pin compatible with the 4016B, but exhibits a much lower ON-resistance. In addition, the ON-resistance is relatively constant over the full input signal range. The 4066 consists of four independent bilateral switches. A single control signal is required per switch. Both the P and the N device in a given switch are biased ON or OFF simultaneously by the control signal. As shown below, the well of the N-channel device on each switch is either tied to the input when the switch is ON or to V_{SS} when the switch is OFF. This configuration minimizes the variation of the switch-transistor threshold voltage with input-signal, and thus keeps the ON-resistance low over the full operating range.

SCHEMATIC DIAGRAM (one of four switches)



CONNECTION DIAGRAM (all packages)




RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | | |
| C, D, F, H Device | | -55 to +125 | °C |
| E Device | | -40 to +85 | °C |

The advantages over single-channel switches include peak input-signal voltage swings equal to the full supply voltage, and more constant ON-impedance over the input-signal range. For sample-and-hold applications, the 4016 is recommended. When the control input is high the switch will be ON. When the control input is low the switch will be OFF.

LOGIC DIAGRAM



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS

| PARAMETER | | CONDITIONS | V _{SS} (Vdc) | V _{DD} (Vdc) | T _{LOW} ² | | 25°C | | | T _{HIGH} ² | | Units |
|---|------------------|--|--------------------------|--------------------------|-------------------------------|------|------|--------|------|--------------------------------|-------|-------|
| | | | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | V _{IN} = V _{SS} or V _{DD} All valid input combinations | 0 | 5 | — | 0.05 | — | 0.0005 | 0.05 | — | 1.5 | μAdc |
| | | | 0 | 10 | — | 0.1 | — | 0.001 | 0.1 | — | 3.0 | |
| | | | 0 | 15 | — | 0.2 | — | 0.002 | 0.2 | — | 6.0 | |
| MINIMUM INPUT HIGH VOLTAGE (Control Input) | V _{IH} | V _{IS} = V _{SS} V _{OS} = V _{DD} I _{OS} = 10μA | 0 | 5 | — | 3.5 | — | 2.75 | 3.5 | — | 3.5 | Vdc |
| | | | 0 | 10 | — | 7.0 | — | 5.5 | 7.0 | — | 7.0 | |
| | | | 0 | 15 | — | 11.0 | — | 8.25 | 11.0 | — | 11.0 | |
| MAXIMUM INPUT LOW VOLTAGE (Control Input) | V _{IL} | V _{IS} = V _{SS} V _{OS} = V _{DD} I _{OS} = 10μA | 0 | 5 | 1.0 | — | 1.0 | 2.25 | — | 1.0 | — | Vdc |
| | | | 0 | 10 | 2.0 | — | 2.0 | 4.5 | — | 2.0 | — | |
| | | | 0 | 15 | 3.0 | — | 3.0 | 6.75 | — | 3.0 | — | |
| SWITCH INPUT/OUTPUT LEAKAGE | I _{OFF} | V _C = V _{SS} V _{IS} = ±7.5Vdc | -7.5 | +7.5 | — | ±100 | — | ±0.01 | ±100 | — | ±1000 | nAdc |
| ON-RESISTANCE | R _{ON} | V _C = V _{DD} V _{IS} = V _{SS} /V _{DD} V _{OS} = $\frac{V_{DD}-V_{SS}}{2}$ R _L = 10kΩ | -7.5 | +7.5 | — | 220 | — | 80 | 280 | — | 320 | Ω |
| | | | 0 | +15 | — | — | — | — | — | — | — | Ω |
| | | | -5 | +5 | — | 400 | — | 120 | 500 | — | 550 | Ω |
| ON-RESISTANCE MATCH (Same package) | ΔR _{ON} | V _C = V _{DD} V _{IS} = V _{SS} /V _{DD} V _{OS} = $\frac{V_{DD}-V_{SS}}{2}$ R _L = 10kΩ | -2.5 | +2.5 | — | 2000 | — | 270 | 2500 | — | 3500 | Ω |
| | | | 0 | +5 | — | — | — | — | — | — | — | Ω |
| | | | -7.5 | +7.5 | — | — | — | 5 | — | — | — | Ω |
| | | | 0 | +15 | — | — | — | — | — | — | — | Ω |
| | | | -5 | +5 | — | — | — | 10 | — | — | — | Ω |
| | | | 0 | +10 | — | — | — | — | — | — | — | Ω |
| | | | -2.5 | +2.5 | — | — | — | 10 | — | — | — | Ω |
| | | | 0 | +5 | — | — | — | — | — | — | — | Ω |
| | | | -7.5 | +7.5 | — | — | — | — | — | — | — | Ω |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under 4000B Series Family Specifications .

² T_{LOW} = -55°C for C, D, F, H device.

= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.

= + 85°C for E device.


³ Conditions for measuring V_{IH}:

| V _{DD} | V _{OS} | V _{IS} | I _{OS} | | T _{HIGH} | UNITS |
|-----------------|-----------------|-----------------|------------------|-------|-------------------|-------|
| | | | T _{LOW} | 25°C | | |
| 5 | 5 | 4.6 | -.25 | -.20 | -.14 | mA |
| 10 | 10 | 9.5 | -.62 | -.50 | -.35 | |
| 15 | 15 | 13.5 | -1.8 | -1.50 | -1.10 | |


ELECTRICAL CHARACTERISTICS (Continued)

DYNAMIC CHARACTERISTICS ($C_L = 50\text{pF}$, $T_A = 25^\circ\text{C}$)


| PARAMETER | CONDITIONS | V_{SS} (Vdc) | V_{DD} (Vdc) | Min. | Typ. | Max. | Units |
|--|---|------------------------|------------------------|-----------------------|---------------------------|------------------|-------|
| SIGNAL INPUTS (V_{is}) AND OUTPUTS (V_{os}) | | | | | | | |
| PROPAGATION DELAY TIME Signal Input to Signal Output | t_{PLH} , t_{PHL} $V_c = V_{DD}$ $V_{is} = \text{Square Wave}$ $R_L = 10\text{k}\Omega$ | 0 0 0 | 5 10 15 | — — — | 20 10 7.5 | 40 20 15 | ns |
| BANDWIDTH (-3dB) (Sine Wave) | BW $V_c = V_{DD}$ $V_{is} = 5V_{p-p}$ centered @ 0.0Vdc R_L 1k Ω 10k Ω 100k Ω 1M Ω | -5 — — — — | +5 — — — — | — — — — — | 54 40 38 37 | — — — — | MHz |
| INSERTION LOSS ($= 20 \log_{10} \frac{V_{os}}{V_{is}}$) | $V_c = V_{DD}$ $V_{is} = 5V_{p-p}$ centered @ 0.0Vdc R_L 1k Ω 10k Ω 100k Ω 1M Ω | -5 — — — — | +5 — — — — | — — — — — | 2.3 0.2 0.1 0.05 | — — — — | dB |
| SIGNAL DISTORTION (Sine Wave) | $V_c = V_{DD}$ $V_{is} = 5V_{p-p}$ centered @ 0.0Vdc $f_{is} = 1.0\text{kHz}$ $R_L = 10\text{k}\Omega$ | -5 | +5 | — | 0.16 | — | % |
| FEEDTHROUGH (-50dB) | $V_c = V_{SS}$ $V_{is} = 5V_{p-p}$ centered @ 0.0Vdc R_L 1k Ω 10k Ω 100k Ω 1M Ω | -5 | +5 | — — — — | 1250 140 18 2 | — — — — | kHz |
| CROSSTALK (-50dB) Between two switches | $V_c(A) = V_{DD}$ $V_c(B) = V_{SS}$ $V_{is}(A) = 5V_{p-p}$ centered @ 0.0Vdc $R_L = 10\text{k}\Omega$ | -5 | +5 | — | 0.9 | — | MHz |
| CAPACITANCE Input | C_{is} | | | — | 8 | — | pF |
| Output | C_{os} | $V_C = V_{SS}$ | -5 | +5 | — | 8 | pF |
| Feedthrough | C_{ios} | | | — | 0.5 | — | pF |
| CONTROL INPUT (V_C) | | | | | | | |
| PROPAGATION DELAY TIME Turn on | t_{PC} $V_{SS} \leq V_{is} \leq V_{DD}$ $R_L = 10\text{k}\Omega$ | 0 0 0 | 5 10 15 | — — — | 50 25 20 | 100 50 40 | ns |
| MAXIMUM INPUT FREQUENCY | f_c $V_{SS} \leq V_{is} \leq V_{DD}$ $R_L = 1.0\text{k}\Omega$ | 0 0 0 | 5 10 15 | — — — | 5 10 12 | — — — | MHz |
| CROSSTALK (To signal port) | $V_c = \text{Square Wave}$ $R_L = 10\text{k}\Omega$ $R_{in} = 1.0\text{k}\Omega$ | 0 0 0 | 5 10 15 | — — — | 30 50 100 | — — — | mV |




Typical channel ON resistance vs. signal voltage for three values of supply voltage ($V_{DD} - V_{SS}$)




Typical ON characteristics for 1 of 4 channels.




Typ. switch frequency response - switch "ON"



Typ. feedthru vs. freq. - switch "OFF"



Typ. crosstalk between switch circuits in the same package




Test circuit, crosstalk-control input to signal output


SPECIAL CONSIDERATIONS – 4066B

1. In applications where separate power sources are used to drive V_{DD} and the signal inputs, the V_{DD} current capability should exceed V_{DD}/R_L (R_L = effective external load of the 4 4066B bilateral switches). This provision avoids any permanent current flow or clamp action on the V_{DD} supply when power is applied or removed from 4066B.
2. In certain applications, the external load-resistor current may include both V_{DD} and signal-line components. To avoid drawing V_{DD} current when switch current flows into terminals 1, 4, 8, or 11, the voltage drop across the bidirectional switch must not exceed 0.8 volt (calculated from R_{ON} values shown). No V_{DD} current will flow through R_L if the switch current flows into terminals 2, 3, 9, or 10. Failure to observe this condition may result in distortion of the signal.

APPLICATIONS INFORMATION



Basic Switch Functions using the 4066B



Active Low Pass Filter with Digitally Selected Break Frequency

CMOS HEX INVERTER

FEATURES



- ◆ Fully "B"-Series Compatible
- ◆ Diode Protection on all Inputs
- ◆ Pin Compatible with 74C04

DESCRIPTION

The 4069UB consists of six CMOS inverter circuits. The device is intended for general-purpose inverter applications where the higher output drive and level-shifting feature of the 4009UB and 4049UB are not required.* The 4069UB is particularly useful for quasi-linear circuits such as oscillators (See Applications Information).


*For pin-to-pin compatibility with the 4009UB and 4049UB, the 4449UB is available.

SCHEMATIC DIAGRAM (one of six inverters)



Typical current and voltage transfer characteristics

CONNECTION DIAGRAM (all packages)




RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | -55 to +125 | °C |
| C, D, F, H Device | | -40 to +85 | °C |
| E Device | | | |

LOGIC DIAGRAM



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|---|-------------------------------|------|-------|--------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | V _{IN} =V _{SS} or V _{DD} All valid input combinations | — | 0.05 | — | 0.0005 | 0.05 | — | 1.5 | μAdc |
| | | | — | 0.10 | — | 0.001 | 0.10 | — | 3.0 | |
| | | | — | 0.20 | — | 0.002 | 0.20 | — | 6.0 | |


NOTES: ¹ Remaining Static Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.
= -40°C for E device.


T_{HIGH} = +125°C for C, D, F, H device.
= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETER | | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|------------------------|-------------------------------------|--------------------------|------|------|------|-------|
| PROPAGATION DELAY TIME | t _{PLH} , t _{PHL} | 5 | — | 50 | 100 | ns |
| | | 10 | — | 25 | 50 | |
| | | 15 | — | 20 | 40 | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | — | 75 | 150 | ns |
| | | 10 | — | 35 | 70 | |
| | | 15 | — | 30 | 60 | |




Typical P-Channel
Source Current Characteristics




Typical N-Channel
Sink Current Characteristics


APPLICATIONS INFORMATION



Typical crystal oscillator circuit



Typical RC oscillator circuit



Input pulse shaping circuit (Schmitt
Trigger)

FEATURES

- ◆ Buffered Outputs
- ◆ Diode Protection on all Inputs
- ◆ Fully "B"-Series Compatible
- ◆ Pin Compatible with 4030 types, MC14507, 74C86

DESCRIPTION


The 4070B contains four independent exclusive-OR gates integrated on a single monolithic silicon chip. Each exclusive-OR gate consists of five N-channel and five P-channel enhancement-mode transistors, plus output buffering devices.

TRUTH TABLE
(one of four gates)


| A | B | Y |
|---|---|---|
| 0 | 0 | 0 |
| 1 | 0 | 1 |
| 0 | 1 | 1 |
| 1 | 1 | 0 |

Where 1 = High Level
0 = Low Level

LOGIC DIAGRAM




SCHEMATIC DIAGRAM
(one of four gates)



CMOS QUAD EXCLUSIVE-OR GATE

CONNECTION DIAGRAM
(all packages)



Add suffix for package:

- C 14-pin Cerdip
- D 14-pin Ceramic
- E 14-pin Epoxy
- F 14-pin Flat
- H Chip


RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | -55 to +125 | °C |
| C, D, F, H Device | | -40 to +85 | °C |
| E Device | | | |

Note: The 4070B is identical to the 4030B; the devices are fully interchangeable in all applications.

FUNCTION DIAGRAM



$$Y = A \oplus B$$

V_{DD} = Pin 14
 V_{SS} = Pin 7

ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|---|-------------------------------|------|-------|--------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | V _{IN} =V _{SS} or V _{DD} All valid input combinations | — | 0.05 | — | 0.0005 | 0.05 | — | 1.5 | μAdc |
| | | | — | 0.10 | — | 0.001 | 0.10 | — | 3.0 | |
| | | | — | 0.20 | — | 0.002 | 0.20 | — | 6.0 | |
| | | | — | — | — | — | — | — | — | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.


= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.


= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)


| PARAMETER | | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|------------------------|-------------------------------------|--------------------------|------|------|------|-------|
| PROPAGATION DELAY TIME | t _{PLH} , t _{PHL} | 5 | — | 140 | 280 | ns |
| | | 10 | — | 65 | 130 | |
| | | 15 | — | 50 | 100 | |
| | | — | — | — | — | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | — | 100 | 200 | ns |
| | | 10 | — | 50 | 100 | |
| | | 15 | — | 40 | 80 | |
| | | — | — | — | — | |



Typical P-Channel
Source Current Characteristics



Typical N-Channel
Sink Current Characteristics

APPLICATIONS INFORMATION
8-BIT TWO'S COMPLEMENT ADDER/SUBTRACTOR

| X ₈ | X ₇ | X ₆ | X ₅ | X ₄ | X ₃ | X ₂ | X ₁ | X ₈ | X ₇ | X ₆ | X ₅ | X ₄ | X ₃ | X ₂ | X ₁ | |
|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|-----|
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | -1 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -2 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -3 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | -4 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | -5 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | -6 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -7 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -8 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -9 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -10 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -11 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -12 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -13 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -14 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -15 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -16 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -17 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -18 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -19 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -20 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -21 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -22 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -23 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -24 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -25 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -26 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -27 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -28 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -29 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -30 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -31 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -32 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -33 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -34 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -35 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -36 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -37 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -38 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -39 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -40 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -41 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -42 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -43 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -44 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -45 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -46 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -47 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -48 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -49 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | -50 |

Two's complement numbers and
their equivalent decimal values

CMOS OR GATES

4071B - Quad 2-Input OR
4072B - Dual 4-Input OR
4075B - Triple 3-Input OR


FEATURES

- ◆ Buffered Outputs
- ◆ Diode Protection on all Inputs
- ◆ Fully "B"-Series Compatible




TRUTH TABLE

| Inputs | Output |
|------------------------|--------|
| 00 . . . 0 | 0 |
| All other combinations | 1 |

FUNCTION DIAGRAMS



CONNECTION DIAGRAMS (all packages)



RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | -55 to +125 | °C |
| C, D, F, H Device | | -40 to +85 | °C |
| E Device | | | |

ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|---|-------------------------------|------|-------|--------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | V _{IN} =V _{SS} or V _{DD} All valid input combinations | — | 0.05 | — | 0.0005 | 0.05 | — | 1.5 | μAdc |
| | | | — | 0.10 | — | 0.001 | 0.10 | — | 3.0 | |
| | | | — | 0.20 | — | 0.002 | 0.20 | — | 6.0 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.


= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.


= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)



| PARAMETER | | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|------------------------|-------------------------------------|--------------------------|------|------|------|-------|
| PROPAGATION DELAY TIME | t _{PLH} , t _{PHL} | 5 | — | 100 | 200 | ns |
| | | 10 | — | 50 | 100 | |
| | | 15 | — | 40 | 80 | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | — | 90 | 180 | ns |
| | | 10 | — | 45 | 90 | |
| | | 15 | — | 40 | 80 | |



Typical P-Channel
Source Current Characteristics
LOGIC DIAGRAMS



Typical N-Channel
Sink Current Characteristics
SCHEMATIC DIAGRAM 4072B (1 of 2 gates)



CMOS 4-BIT D-TYPE REGISTER






FEATURES

- ◆ 3-State Outputs with Gated Control Lines
- ◆ Fully Independent Clock
- ◆ Asynchronous Reset
- ◆ Fully Static Operation - DC to 12MHz @ 10Vdc

DESCRIPTION

The 4076B 4-bit Register consists of four D-Type flip-flops operating synchronously from a common Clock. OR-gated Output Disable inputs force the outputs into a high-impedance state for use in bus-organized systems. OR-gated Data Disable inputs cause the Q outputs to be fed back to the D inputs of the flip-flops. Thus, they are inhibited from changing state while the clocking process remains undisturbed. An asynchronous Master Reset is provided to clear all four flip-flops simultaneously independent of the Clock or Disable inputs.

TRUTH TABLE


| Reset | Clock | Data Input Disable | | Data D | Next State Output Q | |
|-------|---|--------------------|----|--------|---------------------|----|
| | | G1 | G2 | | | |
| 1 | X | X | X | X | 0 | |
| 0 | 0 | X | X | X | Q | NC |
| 0 |  | 1 | X | X | Q | NC |
| 0 |  | X | 1 | X | Q | NC |
| 0 |  | 0 | 0 | 1 | 1 | |
| 0 |  | 0 | 0 | 0 | 0 | |
| 0 | 1 | X | X | X | Q | NC |
| 0 |  | X | X | X | Q | NC |

When either Output Disable M or N is high, the outputs are disabled (high impedance state); however sequential operation of the flip-flops is not affected.

1 ≡ High Level
0 ≡ Low Level

X = Don't Care
NC = No Change

CONNECTION DIAGRAM (all packages)



Add suffix for package:


- C 16-pin Cerdip
- D 16-pin Ceramic
- E 16-pin Epoxy
- F 16-pin Flat
- H Chip

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | | |
| C, D, F, H Device | | -55 to +125 | °C |
| E Device | | -40 to +85 | °C |

BLOCK DIAGRAM



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------------|--------------------------|------------|-------------------------------|------|-------|-------------------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | 5 | — | 5 | — | 0.05 | 5 | — | 150 | μAdc |
| | | 10 | — | 10 | — | 0.1 | 10 | — | 300 | |
| | | 15 | — | 20 | — | 0.2 | 20 | — | 600 | |
| 3-STATE OUTPUT LEAKAGE CURRENT | I _{ZL} | 15 | — | ±0.1 | — | ±10 ⁻⁴ | ±0.1 | — | ±1.0 | μAdc |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.

= -40°C for E device.


T_{HIGH} = +125°C for C, D, F, H device.

= + 85°C for E device.


DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETER | | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|---|-------------------------------------|--------------------------|------|------|------|-------|
| CLOCKED OPERATION | | | | | | |
| PROPAGATION DELAY TIME Clock to Q Output Disable to Q | t _{PLH} , t _{PHL} | 5 | — | 150 | 300 | ns |
| | | 10 | — | 70 | 140 | |
| | | 15 | — | 45 | 90 | |
| | t _{PHZ} , t _{PLZ} | 5 | — | 75 | 150 | ns |
| | | 10 | — | 40 | 80 | |
| | | 15 | — | 30 | 60 | |
| | t _{PZH} , t _{PZL} | 5 | — | 80 | 160 | ns |
| | | 10 | — | 35 | 70 | |
| | | 15 | — | 25 | 50 | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | — | 100 | 200 | ns |
| 10 | — | 50 | 100 | | | |
| 15 | — | 40 | 80 | | | |
| MINIMUM CLOCK PULSE WIDTH | PW _{CL} | 5 | — | 80 | 160 | ns |
| 10 | — | 40 | 80 | | | |
| 15 | — | 30 | 60 | | | |
| MAXIMUM CLOCK FREQUENCY | f _{CL} | 5 | 3.0 | 6.0 | — | MHz |
| 10 | 6.0 | 12 | — | | | |
| 15 | 8.0 | 16 | — | | | |
| MAXIMUM CLOCK RISE & FALL TIME ¹ | t _{rCL} , t _{fCL} | 5 | 15 | — | — | μs |
| 10 | 15 | — | — | | | |
| 15 | 15 | — | — | | | |
| MINIMUM SETUP TIME Data Inputs Data Disable Inputs | t _{setup} | 5 | — | 75 | 150 | ns |
| | | 10 | — | 40 | 80 | |
| | | 15 | — | 30 | 60 | |
| | t _{setup} | 5 | — | 100 | 200 | ns |
| | | 10 | — | 60 | 120 | |
| | | 15 | — | 45 | 90 | |
| MINIMUM HOLD TIME All Inputs | t _{hold} | 5 | — | 75 | 150 | ns |
| 10 | — | 35 | 70 | | | |
| 15 | — | 30 | 60 | | | |
| RESET OPERATION | | | | | | |
| PROPAGATION DELAY TIME | t _{PHL} | 5 | — | 200 | 400 | ns |
| 10 | — | 100 | 200 | | | |
| 15 | — | 75 | 150 | | | |
| MINIMUM RESET PULSE WIDTH | PW _R | 5 | — | 75 | 150 | ns |
| 10 | — | 40 | 80 | | | |
| 15 | — | 30 | 60 | | | |
| RESET REMOVAL TIME | t _{rem} | 5 | — | 100 | 200 | ns |
| 10 | — | 60 | 120 | | | |
| 15 | — | 45 | 90 | | | |

¹ When units are cascaded, the maximum rise and fall times of the clock input should be equal to or less than the transition times of the data outputs driving data inputs, plus the propagation delay of the output driving stage for the output capacitive load.




Typical P-Channel
Source Current Characteristics




Typical N-Channel
Sink Current Characteristics


TIMING DIAGRAM



THREE-STATE PROPAGATION DELAY WAVESHAVE AND CIRCUIT



LOGIC DIAGRAM



CMOS QUAD EXCLUSIVE-NOR GATE

FEATURES

- ◆ Buffered Outputs
- ◆ Diode Protection on all Inputs
- ◆ Fully "B"-Series Compatible

DESCRIPTION


The 4077B contains four independent exclusive-NOR gates integrated on a single monolithic silicon chip. Each exclusive-NOR gate consists of five N-channel and five P-channel enhancement-mode transistors, plus output buffering devices.

TRUTH TABLE
(one of four gates)


| A | B | Y |
|---|---|---|
| 0 | 0 | 1 |
| 1 | 0 | 0 |
| 0 | 1 | 0 |
| 1 | 1 | 1 |

Where 1 = High Level
0 = Low Level


LOGIC DIAGRAM
(one of four gates)



SCHEMATIC DIAGRAM
(one of four gates)



CONNECTION DIAGRAM
(all packages)



Add suffix for package:


- C 14-pin Cerdip
- D 14-pin Ceramic
- E 14-pin Epoxy
- F 14-pin Flat
- H Chip

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | -55 to +125 | °C |
| C, D, F, H Device | | -40 to +85 | °C |
| E Device | | | |

FUNCTION DIAGRAM



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|--|-------------------------------|------|-------|--------|------|--------------------------------|------|------------------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | V _{IN} = V _{SS} or V _{DD} All valid input combinations | — | 0.05 | — | 0.0005 | 0.05 | — | 1.5 | μA _{dc} |
| | | | — | 0.10 | — | 0.001 | 0.10 | — | 3.0 | |
| | | | — | 0.20 | — | 0.002 | 0.20 | — | 6.0 | |
| | | | — | — | — | — | — | — | — | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.


= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.


= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETER | | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|------------------------|-------------------------------------|--------------------------|------|------|------|-------|
| PROPAGATION DELAY TIME | t _{PLH} , t _{PHL} | 5 | — | 150 | 300 | ns |
| | | 10 | — | 65 | 130 | |
| | | 15 | — | 50 | 100 | |
| | | — | — | — | — | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | — | 100 | 200 | ns |
| | | 10 | — | 50 | 100 | |
| | | 15 | — | 40 | 80 | |
| | | — | — | — | — | |



Typical P-Channel
Source Current Characteristics



Typical N-Channel
Sink Current Characteristics

CMOS AND GATES

4081B - Quad 2-Input AND
4082B - Dual 4-Input AND
4073B - Triple 3-Input AND




FEATURES

- ◆ Buffered Outputs
- ◆ Diode Protection on all Inputs
- ◆ Fully "B"-Series Compatible

TRUTH TABLE




| Inputs | Output |
|------------------------|--------|
| 1 1 ... 1 | 1 |
| All other combinations | 0 |

FUNCTION DIAGRAMS



V_{DD} = Pin 14
 V_{SS} = Pin 7
 for all Devices

CONNECTION DIAGRAMS
(all packages)



RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | -55 to +125 | °C |
| C, D, F, H Device | | -40 to +85 | °C |
| E Device | | | |

ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|--|-------------------------------|------|-------|--------|------|--------------------------------|------|------------------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | V _{IN} = V _{CC} or V _{DD} All valid input combinations | - | 0.05 | - | 0.0005 | 0.05 | - | 1.5 | μA _{dc} |
| | 5 | | - | 0.10 | - | 0.001 | 0.10 | - | 3.0 | |
| | 10 | | - | 0.20 | - | 0.002 | 0.20 | - | 6.0 | |
| | 15 | | - | - | - | - | - | - | - | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.


= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.



= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)


| PARAMETER | | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|------------------------|-------------------------------------|--------------------------|------|------|------|-------|
| PROPAGATION DELAY TIME | t _{PLH} , t _{PHL} | 5 | - | 120 | 240 | ns |
| | | 10 | - | 60 | 120 | |
| | | 15 | - | 45 | 90 | |
| | | - | - | - | - | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | - | 100 | 200 | ns |
| | | 10 | - | 50 | 100 | |
| | | 15 | - | 40 | 80 | |
| | | - | - | - | - | |



Typical P-Channel
Source Current Characteristics
LOGIC DIAGRAMS



Typical N-Channel
Sink Current Characteristics
SCHEMATIC DIAGRAM - 4082B (1 of 2 gates)



CMOS DUAL 2-WIDE, 2-INPUT AND-OR-INVERTER GATE

FEATURES

- Medium-speed operation — $t_{PHL} = 90$ ns;
 $t_{PLH} = 125$ ns (typ.) at 10 V
- Individual inhibit controls
- Standardized symmetrical output characteristics
- 100% tested for quiescent current at 18 V
- Maximum input current of $1 \mu A$ at 15 V over full temperature range; 100 nA at 15 V and $25^\circ C$
- Noise margin (over full package-temperature range):
1 V at $V_{DD} = 5$ V
2 V at $V_{DD} = 10$ V
2.5 V at $V_{DD} = 15$ V
- 5-V, 10-V, and 15-V parametric ratings
- Meets all requirements of JEDEC Tentative Standard No. 13A, "Standard Specifications for Description of 'B' Series CMOS Devices"

DESCRIPTION

The 4085 contains a pair of AND-OR-INVERT gates, each consisting of two 2-input AND gates driving a 3-input NOR gate. Individual inhibit controls are provided for both A-O-I gates.


The 4085B types are supplied in 14-lead dual-in-line ceramic packages (D and C suffixes), 14-lead dual-in-line plastic packages (E suffix), 14-lead ceramic flat packs (F suffix), and in chip form (H suffix).

RECOMMENDED OPERATING CONDITIONS


For maximum reliability, nominal operating conditions should be selected so that operation is always within the following ranges:

| CHARACTERISTIC | LIMITS | | UNITS |
|---|--------|------|-------|
| | Min. | Max. | |
| Supply Voltage Range (For $T_A = \text{Full}$ Package Temperature Range) | 3 | 18 | V |


CONNECTION DIAGRAM



TOP VIEW



FUNCTIONAL DIAGRAM



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|--|-------------------------------|------|-------|--------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | V _{IN} = V _{SS} or V _{DD} All valid input combinations | — | 0.05 | — | 0.0005 | 0.05 | — | 1.5 | μAdc |
| | | | — | 0.10 | — | 0.001 | 0.10 | — | 3.0 | |
| | | | — | 0.20 | — | 0.002 | 0.20 | — | 6.0 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.

= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.

= + 85°C for E device.

ABSOLUTE MAXIMUM RATINGS

DC SUPPLY-VOLTAGE RANGE, (V_{DD})

(Voltages referenced to V_{SS} Terminal) -0.5 to +20V

INPUT VOLTAGE RANGE,

ALL INPUTS -0.5 to V_{DD} +0.5V

DC INPUT CURRENT,

ANY ONE INPUT ±10 mA

POWER DISSIPATION PER PACKAGE (P_D):

For T_A = -40 to +60°C
(PACKAGE TYPE E) 500 mW

For T_A = +60 to +85°C

For T_A = +60 to +85°C
(PACKAGE TYPE E) Derate Linearly
at 12 mW/°C to 200 mW

For T_A = -55 to +100°C
(PACKAGE TYPES D, F, C) 500 mW

For T_A = +100 to +125°C
(PACKAGE TYPES D, F, C) . Derate Linearly
at 12 mW/°C to 200 mW

DEVICE DISSIPATION

PER OUTPUT TRANSISTOR

For T_A = FULL PACKAGE-TEMPERATURE
RANGE (All Package Types) 100 mW

OPERATING TEMPERATURE RANGE (T_A):

PACKAGE TYPES D, F, C, H . -55 to +125°C

PACKAGE TYPE E -40 to +85°C

STORAGE TEMPERATURE

RANGE (T_{stg}) -65 to +150°C


LEAD TEMPERATURE (DURING SOLDERING):

At distance 1/16 ± 1/32 inch (1.59 ± 0.79mm)
from case for 10 s max. +265°C

DYNAMIC ELECTRICAL CHARACTERISTICS

(T_A = 25°C, Input t_r, t_f = 20 ns, C_L = 50pF, R_L = 200 KΩ)

| CHARACTERISTICS | | CONDITIONS | | LIMITS | | UNITS |
|---|-----------------------------|-----------------|------|--------|----|-------|
| | | V _{DD} | Typ. | Max. | | |
| Propagation Delay Time (Data) High-to-Low Level | ^t _{PHL} | 5 | 225 | 450 | ns | |
| | | 10 | 90 | 180 | | |
| | | 15 | 65 | 130 | | |
| Low-to-High Level | ^t _{PLH} | 5 | 310 | 620 | ns | |
| | | 10 | 125 | 250 | | |
| | | 15 | 90 | 180 | | |
| Propagation Delay Time (Inhibit) High-to-Low Level | ^t _{PHL} | 5 | 150 | 300 | ns | |
| | | 10 | 60 | 120 | | |
| | | 15 | 40 | 80 | | |
| Low-to-High Level | ^t _{PLH} | 5 | 250 | 500 | ns | |
| | | 10 | 100 | 200 | | |
| | | 15 | 70 | 140 | | |
| Transition Time ^t _{THL} , ^t _{TLH} | | 5 | 100 | 200 | ns | |
| | | 10 | 50 | 100 | | |
| | | 15 | 40 | 80 | | |
| Input Capacitance | ^C _{IN} | Any Input | 5 | 7.5 | pF | |



CMOS EXPANDABLE 4-WIDE, 2-INPUT AND-OR INVERT GATE

FEATURES

- Medium-speed operation — $t_{PHL} = 90$ ns;
 $t_{PLH} = 140$ ns (typ.) at 10 V
- INHIBIT and ENABLE inputs
- Buffered outputs
- 100% tested for quiescent current at 15 V
- Maximum input leakage current of $1\mu A$ over full package-temperature range; 100 nA at 15 V and 25° C
- Noise margin (over full package temperature range):
1 V at $V_{DD} = 5$ V
2 V at $V_{DD} = 10$ V
2.5 V at $V_{DD} = 15$ V
- Standardized, symmetrical output characteristics
- 5-V, 10-V, and 15-V parametric ratings
- Meets all requirements of JEDEC Tentative Standard No. 13A, "Standard Specifications for Description of 'B' Series CMOS Devices"

DESCRIPTION

The 4086B contains one 4-wide 2-input AND-OR-INVERT gate with an INHIBIT/EXP input and an ENABLE/EXP input. For a 4-wide A-O-I-function INHIBIT/EXP is tied to V_{SS} and ENABLE/EXP to V_{DD} . See Fig. 2 and its associated explanation for applications where a capability greater than 4-wide is required.


The 4086B is supplied in 14-lead dual-in-line ceramic packages (D and C suffixes), 14-lead dual-in-line plastic packages (E suffix), 14-lead ceramic flat packs (F suffix), and in chip form (H suffix).

RECOMMENDED OPERATING CONDITIONS


For maximum reliability, nominal operating conditions should be selected so that operation is always within the following ranges:

| CHARACTERISTIC | LIMITS | | UNITS |
|---|--------|------|-------|
| | Min. | Max. | |
| Supply Voltage Range (For $T_A = \text{Full}$ Package Temperature Range) | 3 | 18 | V |

CONNECTION DIAGRAM



TOPVIEW



FUNCTIONAL DIAGRAM




FIGURE 1
TYPICAL VOLTAGE AND CURRENT
TRANSFER CHARACTERISTICS

ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|---|--------------------------|---|-------------------------------|------|-------|--------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT I _{DD} | 5 | V _{IN} =V _{SS} or V _{DD} | — | 0.05 | — | 0.0005 | 0.05 | — | 1.5 | μAdc |
| | 10 | All valid input combinations | — | 0.10 | — | 0.001 | 0.10 | — | 3.0 | |
| | 15 | | — | 0.20 | — | 0.002 | 0.20 | — | 6.0 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.

= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.

= + 85°C for E device.

ABSOLUTE MAXIMUM RATINGS

DC SUPPLY-VOLTAGE RANGE, (V_{DD})

(Voltages referenced to

V_{SS} Terminal) -0.5 to +18 V

INPUT VOLTAGE RANGE,

ALL INPUTS -0.5 to V_{DD} +0.5 V

DC INPUT CURRENT,

ANY ONE INPUT ±10 mA

POWER DISSIPATION PER PACKAGE (P_D):

For T_A = -40 to +60°C

(PACKAGE TYPE E) 500 mW

For T_A = +60 to +85°C

(PACKAGE TYPE E) Derate Linearly

at 12 mW/°C to 200 mW

For T_A = -55 to +100°C

(PACKAGE TYPES D, C, F) 500 mW

For T_A = +100 to +125°C

(PACKAGE TYPES D, C, F) Derate

Linearly at 12 mW/°C to 200 mW

DEVICE DISSIPATION

PER OUTPUT TRANSISTOR

For T_A = FULL PACKAGE-TEMPERATURE

RANGE (All Package Types) 100 mW

OPERATING TEMPERATURE RANGE (T_A):

PACKAGE TYPES D, F, C, H -55 to +125°C

PACKAGE TYPE E -40 to +85°C

STORAGE TEMPERATURE


RANGE (T_{stg}) -65 to +150°C

LEAD TEMPERATURE (DURING SOLDERING):

At distance 1/16 ± 1/32 inch (1.59 ± 0.79 mm)

from case for 10 s max. +265°C

Fig. 3 shows two 4086's utilized to obtain an 8-wide 2-input A-O-I function. The output (J1) of one 4086 is fed directly to the ENABLE/EXP2 line of the second 4086. In a similar fashion, any NAND gate output can be fed directly into the ENABLE/EXP input to obtain a 5-wide A-O-I function. In addition, any AND gate output can be fed directly into the INHIBIT/EXP input with the same result.




J1: A1 B1 C1 D1 E1 F1 G1 H1
J2: A2 B2 C2 D2 E2 F2 G2 H2
TWO 4086B'S CONNECTED
AS AN 8 WIDE 2 INPUT A-O-I GATE

DYNAMIC ELECTRICAL CHARACTERISTICS

(T_A = 25°C; Input t_r, t_f = 20ns, C_L = 50pF, R_L = 200KΩ)

| CHARACTERISTIC | CONDITIONS | LIMITS | | UNITS |
|---|---|------------------------|-----------|-------|
| | | V _{DD} (V) | TYP. MAX. | |
| Propagation Delay Time (Data) | | 5 | 225 450 | ns |
| | High to Low Level, t _{PHL} | 15 | 90 180 | |
| | Low to High Level, t _{PLH} | 5 | 350 700 | |
| Propagation Delay Time (Inhibit) High to Low Level, t _{PHL} (INH) | | 10 | 140 280 | ns |
| | Low to High Level, t _{PLH} (INH) | 15 | 100 200 | |
| | | 5 | 150 300 | |
| Transition Time, t _{THL} t _{TLH} | | 10 | 60 120 | ns |
| | | 15 | 40 80 | |
| | | 5 | 250 500 | |
| Input Capacitance C _{IN} | | 10 | 100 200 | pF |
| | | 15 | 70 140 | |
| | | 5 | 100 200 | |



*ALL INPUTS PROTECTED BY
STANDARD CMOS PROTECT-1™
NETWORK

CMOS QUAD SCHMITT TRIGGER


FEATURES

- ◆ Schmitt Trigger Action on each Input with no External Components
- ◆ Quad 2-Input NAND Configuration
- ◆ Noise Immunity Greater than 50%
- ◆ No Limit on Input Rise and Fall Times


DESCRIPTION

The 4093B consists of four Schmitt trigger circuits. Each circuit functions as a 2-input NAND gate with Schmitt trigger action on both inputs. The gate switches at different points for positive- and negative-going signals. The difference between the positive voltage (V_P) and the negative voltage (V_N) is defined as the hysteresis voltage (V_H). This device is useful in high-noise environments and in wave and pulse shapers and multivibrators.

LOGIC DIAGRAM



CONNECTION DIAGRAM (all packages)




RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | | |
| C, D, F, H Device | | -55 to +125 | °C |
| E Device | | -40 to +85 | °C |

BLOCK DIAGRAM



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|------------------------------------|-------------------------------------|--|-------------------------------|------|-------|--------|------|--------------------------------|------|-----------------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | V _{IN} = V _{SS} or V _{DD} All valid input combinations | — | 1.0 | — | 0.0005 | 1.0 | — | 30 | μAdc |
| | | | — | 2.0 | — | 0.001 | 2.0 | — | 60 | |
| | | | — | 4.0 | — | 0.002 | 4.0 | — | 120 | |
| POSITIVE TRIGGER THRESHOLD VOLTAGE | V _P (V _L) | | 3 typ | | 2.3 | 2.9 | 3.5 | 2.9 typ | | Vdc |
| | | | 5.9 typ | | 4.5 | 5.9 | 7.0 | 5.9 typ | | |
| | | | 8.9 typ | | 6.8 | 8.9 | 11 | 8.9 typ | | |
| NEGATIVE TRIGGER THRESHOLD VOLTAGE | V _N (V _H) | | 2.6 typ | | 1.5 | 2.3 | 2.7 | 2.1 typ | | Vdc |
| | | | 4 typ | | 3.0 | 3.9 | 5.5 | 3.8 typ | | |
| | | | 5.5 typ | | 4.0 | 5.4 | 8.2 | 5.3 typ | | |
| HYSTERESIS VOLTAGE | V _H | | .4 | 2.0 | .4 | .75 | 2.0 | .4 | 2.0 | V _{dc} |
| | | | .7 | 3.0 | .7 | .95 | 3.0 | .7 | 3.0 | |
| | | | .85 | 4.0 | .85 | 1.20 | 4.0 | .85 | 4.0 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.


= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.


= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25 °C)


| PARAMETER | | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|------------------------|-------------------------------------|--------------------------|------|------|------|-------|
| PROPAGATION DELAY TIME | t _{PLH} , t _{PHL} | 5 | — | 190 | 380 | ns |
| | | 10 | — | 90 | 180 | |
| | | 15 | — | 65 | 130 | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | — | 100 | 200 | ns |
| | | 10 | — | 50 | 100 | |
| | | 15 | — | 40 | 80 | |




Typical P-Channel
Source Current Characteristics




Typical N-Channel
Sink Current Characteristics




Definition of V_p , V_n and V_H .




Transfer characteristic of 1 of 4 gates.




Input and output characteristics.




Typical current and voltage transfer characteristics.



Typical voltage transfer characteristics as a function of temperature.




Typical trigger threshold voltage vs. V_{DD} .




Typical per cent hysteresis vs. supply voltage.


APPLICATIONS INFORMATION



Wave shaper.



Monostable multivibrator.



Astable multivibrator.

CMOS 8-STAGE SHIFT-AND-STORE BUS REGISTER

FEATURES:

- 3-state parallel outputs for connection to common bus
- Separate serial outputs synchronous to both positive and negative clock edges for cascading
- Medium speed operation—5 MHz at 10 V
- Quiescent current specified to 15 V
- Maximum input leakage of 1 μ A at 15 V (full package-temperature range)
- 1-V noise margin (full package-temperature range)
- 5-V, 10-V, and 15-V parametric ratings

DESCRIPTION:

The 4094B is an 8-stage serial shift register having a storage latch associated with each stage for strobing data from the serial input to parallel buffered 3-state outputs. The parallel outputs may be connected directly to common bus lines. Data is shifted on positive clock transitions. The data in each shift register stage is transferred to the storage register when the STROBE input is high. Data in the storage register appears at the outputs whenever the OUTPUT-ENABLE signal is high.


Two serial outputs are available for cascading a number of 4094B devices.

Data is available at the Q_s serial output terminal on positive clock edges to allow for high-speed operation in cascaded systems in which the clock rise time is fast. The same serial information, available at the Q'_s terminal on the next negative clock edge, provides a means for cascading 4094B devices when the clock rise time is slow.


APPLICATIONS

- Serial-to-parallel data conversion
- Remote control holding register
- Dual-rank shift, hold, and bus applications

CONNECTION DIAGRAM




FUNCTIONAL DIAGRAM



RECOMMENDED OPERATING CONDITIONS at $T_A = 25^\circ\text{C}$, Except as Noted.
 For maximum reliability, nominal operating conditions should be selected so that operation is always within the following ranges:

| CHARACTERISTIC | V_{DD} (V) | LIMITS | | UNITS |
|---|-----------------|--------|------|---------------|
| | | MIN. | MAX. | |
| Supply-Voltage Range (For T_A = Full Package-Temperature Range) | | 3 | 18 | V |
| Data Setup Time, t_s | 5 | 125 | — | ns |
| | 10 | 55 | — | |
| | 15 | 35 | — | |
| Clock Pulse Width, t_w | 5 | 200 | — | ns |
| | 10 | 100 | — | |
| | 15 | 83 | — | |
| Clock Input Frequency, f_{CL} | 5 | dc | 1.25 | MHz |
| | 10 | | 2.5 | |
| | 15 | | 3 | |
| Clock Rise & Fall Time, t_{CL} , t_{CL}^* | 5, 10, 15 | — | 15 | μs |
| Strobe Pulse Width, t_w | 5 | 200 | — | ns |
| | 10 | 80 | — | |
| | 15 | 70 | — | |

*If more than one unit is cascaded t_{CL} (for Q_N only) should be made less than or equal to the sum of the fixed propagation delay at 50 pF and the transition time of the output driving stage for the estimated capacitive load.




TRUTH TABLE

| CL▲ | Output Enable | Strobe | Data | Parallel Outputs | | Serial Outputs | |
|-----|---------------|--------|------|------------------|-----------|----------------|-----|
| | | | | Q1 | QN | QS* | Q'S |
| | 0 | X | X | OC | OC | Q7 | NC |
| | 0 | X | X | OC | OC | NC | Q7 |
| | 1 | 0 | X | NC | NC | Q7 | NC |
| | 1 | 1 | 0 | 0 | Q_{N-1} | Q7 | NC |
| | 1 | 1 | 1 | 1 | Q_{N-1} | Q7 | NC |
| | 1 | 1 | 1 | NC | NC | NC | Q7 |

▲ = Level Change Logic 1 \equiv High NC = No Change
 X = Don't Care Logic 0 \equiv Low OC = Open Circuit

*At the positive clock edge information in the 7th shift register stage is transferred to the 8th register stage and the Q_N output.



STATIC ELECTRICAL CHARACTERISTICS¹

| PARAMETER | V _{DD} | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--|-----------------|-------------------------------|------|-------|-------------------|------|--------------------------------|------|-------|
| | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT (I _{DD}) | 5 | — | 5 | — | 0.02 | 5 | — | — | μA |
| | 10 | — | 10 | — | 0.02 | 10 | — | — | |
| | 15 | — | 20 | — | 0.02 | 20 | — | — | |
| 3-STATE OUTPUT LEAKAGE CURRENT (I _L) | 15 | — | ±0.1 | — | ±10 ⁻⁴ | ±0.1 | — | ±1 | μA |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications"

² T_{LOW} = -55°C for C, D, F, H devices.

= -40°C for E Devices.

T_{HIGH} = +125°C for E, D, F, H devices.

= +85°C for E devices.

DYNAMIC ELECTRICAL CHARACTERISTICS

At T_A = 25°C; Input t_r, t_f = 20 ns, C_L = 50 pF

| CHARACTERISTIC | V _{DD} (V) | LIMITS ALL PACKAGES | | | UNITS |
|--|------------------------|------------------------|------|------|-------|
| | | MIN. | TYP. | MAX. | |
| Propagation Delay Time. t _{PHL} , t _{PLH} Clock to Serial Output (Q's) | 5 | — | 300 | 600 | ns |
| | 10 | — | 125 | 250 | |
| | 15 | — | 95 | 190 | |
| Clock to Serial Output (Q's) | 5 | — | 230 | 460 | ns |
| | 10 | — | 110 | 220 | |
| | 15 | — | 75 | 150 | |
| Clock to Parallel Output | 5 | — | 420 | 840 | ns |
| | 10 | — | 195 | 390 | |
| | 15 | — | 135 | 270 | |
| Strobe to Parallel Output | 5 | — | 290 | 580 | ns |
| | 10 | — | 145 | 290 | |
| | 15 | — | 100 | 200 | |
| Output Enable to Parallel Output: t _{PHL} | 5 | — | 140 | 280 | ns |
| | 10 | — | 75 | 150 | |
| | 15 | — | 55 | 110 | |
| t _{PLH} | 5 | — | 225 | 450 | ns |
| | 10 | — | 95 | 190 | |
| | 15 | — | 70 | 140 | |
| Minimum Strobe Pulse Width, t _w | 5 | — | 100 | 200 | ns |
| | 10 | — | 40 | 80 | |
| | 15 | — | 35 | 70 | |
| Minimum Clock Pulse Width, t _w | 5 | — | 100 | 200 | ns |
| | 10 | — | 50 | 100 | |
| | 15 | — | 40 | 83 | |
| Minimum Data Setup Time, t _s | 5 | — | 60 | 125 | ns |
| | 10 | — | 30 | 55 | |
| | 15 | — | 20 | 35 | |
| Transition Time: t _{THL} , t _{TLH} | 5 | — | 100 | 200 | ns |
| | 10 | — | 50 | 100 | |
| | 15 | — | 40 | 80 | |
| Clock Rise and Fall Time: t _r , t _f | 5, 10, 15 | — | — | 15 | μs |
| Max. Clock Input Frequency, f _{CL} | 5 | 1.25 | 2.5 | — | MHz |
| | 10 | 2.5 | 5 | — | |
| | 15 | 3 | 6 | — | |
| Average Input Capacitance, C _i (Any Input) | — | — | 5 | — | pF |

8-BIT ADDRESSABLE LATCH

FEATURES

- Serial data input
- Active parallel output
- Storage register capability
- Master clear
- Can function as demultiplexer

APPLICATIONS

- Multi-line decoders
- A/D converters


DESCRIPTION

The 4099B 8-bit addressable latch is a serial-input, parallel-output storage register that can perform a variety of functions.

Data are inputted to a particular bit in the latch when that bit is addressed (by means of inputs A0, A1, A2) and when WRITE DISABLE is at a low level. When WRITE DISABLE is high, data entry is inhibited; however, all 8 outputs can be continuously read independent of WRITE DISABLE and address inputs.


A master RESET input is available, which resets all bits to a logic "0" level when RESET and WRITE DISABLE are at a high level. When RESET is at a high level, and WRITE DISABLE is at a low level, the latch acts as a 1-of-8 demultiplexer; the bit that is addressed has an active output which follows the data input, while all unaddressed bits are held to a logic "0" level.

LOGIC DIAGRAM



*ALL INPUTS ARE PROTECTED BY COSMOS PROTECTION NETWORK

CONNECTION DIAGRAM



TRUTH TABLE

| WD | R | Addressed Latch | Unaddressed Latch |
|----|---|---------------------|---------------------|
| 0 | 0 | D | Holds previous data |
| 0 | 1 | D | 0 |
| 1 | 0 | Holds previous data | |
| 1 | 1 | 0 | 0 |

TIMING DIAGRAMS




Fig. 1 — Definition of WRITE DISABLE ON time.




Fig. 2 — Master timing diagram.

ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS^{1, 2}

| PARAMETER | V _{DD} | I _{LOW2} | | + 25°C | | | T _{HIGH} | | Units |
|--|-----------------|-------------------|------|--------|------|------|-------------------|------|---------|
| | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT I _{DD} CURRENT | 5 | — | 5 | — | 0.02 | 5 | — | 150 | μ A |
| | 10 | — | 10 | — | 0.02 | 10 | — | 300 | |
| | 15 | — | 20 | — | 0.02 | 20 | — | 600 | |

DYNAMIC CHARACTERISTICS

T_A = 25° C, C_L = 50 pF, Input t_r, t_f = 20 ns, R_L = 200 K

| CHARACTERISTIC | SEE FIG 2* | V _{DD} (V) | ALL PACKAGE TYPES TYP. | LIMITS MAX. | UNITS |
|--|---------------|------------------------|---------------------------|-------------------|-------|
| Propagation Delay: t _{PLH} , t _{PHL} | (1) | 5 10 15 | 200 75 50 | 400 150 100 | |
| Data to Output WRITE DISABLE to Output. | (2) | 5 10 15 | 200 80 60 | 400 160 120 | ns |
| Reset to Output, t _{PHL} | (3) | 5 10 15 | 175 80 65 | 350 160 130 | |
| Address to Output, t _{PLH} , t _{PHL} | (9) | 5 10 15 | 225 100 75 | 450 200 150 | |
| Transition Time, T _{THL} , (Any Output) t _{TLH} | | 5 10 15 | 100 50 40 | 200 100 80 | ns |
| Minimum Pulse Width, t _w Data | (4) | 5 10 15 | 100 50 40 | 200 100 80 | ns |
| Address | (8) | 5 10 15 | 200 100 65 | 400 200 125 | ns |
| Reset | (5) | 5 10 15 | 75 40 25 | 150 75 50 | ns |
| Minimum Setup Time, t _s Data to WRITE DISABLE | (6) | 5 10 15 | 50 25 20 | 100 50 35 | ns |
| Minimum Hold Time, t _H Data to WRITE DISABLE | (7) | 5 10 15 | 75 40 25 | 150 75 50 | ns |
| Average Input Capacitance C _i | Any Input | | 5 | — | pF |

*Circled numbers refer to times indicated on master timing diagram.

Note: In addition to the above characteristics, a WRITE DISABLE ON time (the time that WRITE DISABLE is at a high level) must be observed during an address change for the total time that the external address lines A0, A1, and A2 are settling to a stable level, to prevent a wrong cell from being addressed (see Fig. 1).

CMOS SYNCHRONOUS 4-BIT COUNTERS

FEATURES

- ◆ BCD Decade (4160B, 4162B) or 4-Bit Binary (4161B, 4163B) Counting
- ◆ Internal Look-Ahead for Fast Counting
- ◆ Carry Output for Cascading
- ◆ Synchronously Programmable
- ◆ Synchronous Counting
- ◆ Load Control Input
- ◆ Clear Input - Asynchronous (4160B, 4161B) or Synchronous (4162B, 4163B)
- ◆ Static Operation - DC to 5MHz @ 10Vdc

DESCRIPTION

The 4160B - 4163B are Synchronous Programmable Counters constructed with complementary MOS P-Channel and N-Channel enhancement-mode devices in a single monolithic structure. These counters are functionally equivalent to the 74160 - 74163 TTL counters.

Two are synchronous programmable decade counters with asynchronous and synchronous Clear inputs respectively (4160, 4162). The other two are 4-bit binary counters with asynchronous and synchronous Clear respectively (4161, 4163).

SYNCHRONOUS MODE SELECTION 4160B/4161B

| L | PE | TE | Mode |
|---|----|----|-----------|
| L | X | X | Preset |
| H | L | X | No Change |
| H | X | L | No Change |
| H | H | H | Count |


H = High level L = Low level X = Don't care

SYNCHRONOUS MODE SELECTION 4162B/4163B

| CLR | L | PE | TE | Mode |
|-----|---|----|----|-----------|
| H | L | X | X | Preset |
| H | H | L | X | No Change |
| H | H | X | L | No Change |
| H | H | H | H | Count |
| L | X | X | X | Reset |

H = High level L = Low level X = Don't care

CONNECTION DIAGRAM (all packages)



Add suffix for package:


- C 16-pin Cerdip
- D 16-pin Ceramic
- E 16-pin Epoxy
- F 16-pin Flat
- H Chip

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | | |
| C, D, F, H Device | | -55 to +125 | °C |
| E Device | | -40 to +85 | °C |

BLOCK DIAGRAM



SELECTOR GUIDE

| CLEAR | MODULUS | |
|--------------|---------|--------|
| | DECADE | BINARY |
| Asynchronous | 4160B | 4161B |
| Synchronous | 4162B | 4163B |

ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|--|-------------------------------|------|-------|------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | V _{IN} = V _{SS} or V _{DD} All valid input combinations | — | 5 | — | 0.05 | 5 | — | 150 | μAdc |
| | | | — | 10 | — | 0.1 | 10 | — | 300 | |
| | | | — | 20 | — | 0.2 | 20 | — | 600 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.

= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.

= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)


| PARAMETER | | V _{DD} (Vdc) | Min. | Typ. | Max. | Units | | |
|--|-------------------------------------|--|-------------------------------------|------|------|-------|-----|----|
| CLOCKED OPERATION | | | | | | | | |
| PROPAGATION DELAY TIME Clock to Q | t _{PLH} , t _{PHL} | 5 | — | 200 | 400 | ns | | |
| | | 10 | — | 80 | 160 | | | |
| | | 15 | — | 60 | 120 | | | |
| | | Clock to Carry Out | 5 | — | 240 | 480 | ns | |
| | | | 10 | — | 95 | 190 | | |
| | | | 15 | — | 75 | 150 | | |
| | | TE to Carry Out | 5 | — | 180 | 360 | ns | |
| | | | 10 | — | 70 | 140 | | |
| | | | 15 | — | 50 | 100 | | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | — | 100 | 200 | ns | | |
| 10 | — | 50 | 100 | | | | | |
| 15 | — | 40 | 80 | | | | | |
| MINIMUM CLOCK PULSE WIDTH | PW _{CL} | 5 | — | 85 | 170 | ns | | |
| 10 | — | 35 | 70 | | | | | |
| 15 | — | 25 | 50 | | | | | |
| MAXIMUM CLOCK FREQUENCY | f _{CL} | 5 | 2.0 | 3.0 | — | MHz | | |
| 10 | 5.5 | 8.5 | — | | | | | |
| 15 | 8.0 | 12.0 | — | | | | | |
| MAXIMUM CLOCK RISE AND FALL TIME ¹ | t _{rCL} , t _{fCL} | 5 | 50 | ∞ | — | ms | | |
| 10 | 50 | ∞ | — | | | | | |
| 15 | 50 | ∞ | — | | | | | |
| MINIMUM SETUP TIME Data to Clock | t _{setup} | 5 | — | 120 | 240 | ns | | |
| | | 10 | — | 45 | 90 | | | |
| | | 15 | — | 30 | 65 | | | |
| | | Load to Clock | 5 | — | 120 | 240 | ns | |
| | | | 10 | — | 45 | 90 | | |
| | | | 15 | — | 30 | 65 | | |
| | | PE or TE to Clock | 5 | — | 170 | 340 | ns | |
| | | | 10 | — | 70 | 140 | | |
| | | | 15 | — | 50 | 100 | | |
| | | CLEAR OPERATION | | | | | | |
| | | PROPAGATION DELAY TIME Clear to Q (4160, 4161 only) | t _{PLH} , t _{PHL} | 5 | — | 150 | 300 | ns |
| | | | | 10 | — | 50 | 100 | |
| 15 | — | | | 30 | 60 | | | |
| | | | | | | | | |
| MINIMUM SETUP TIME Clear to Clock (4162, 4163 only) | t _{setup} | 5 | — | 120 | 240 | ns | | |
| | | 10 | — | 50 | 100 | | | |
| | | 15 | — | 30 | 60 | | | |
| | | | | | | | | |

¹ When units are cascaded, the maximum rise and fall times of the clock input should be equal to or less than the transition times of the data outputs driving data inputs, plus the propagation delay of the output driving stage for the output capacitive load.


4160B, 4162B LOGIC DIAGRAM (Clear is synchronous for 4162B)

Sequence illustrated in waveforms:

1. Clear outputs to zero.
2. Preset to BCD seven.
3. Count to eight, nine, zero, one, two and three.
4. Inhibit




4160B, 4162B TIMING DIAGRAM




4161B, 4163B LOGIC DIAGRAM (Clear is Synchronous for 4163B)

Sequence illustrated in waveforms:

1. Clear outputs to zero.
2. Preset to binary twelve.
3. Count to thirteen, fourteen, fifteen, zero, one and two.
4. Inhibit.



4161B, 4163B TIMING DIAGRAM



CMOS HEX TYPE D FLIP-FLOP


FEATURES:

- Static Operation
- All Inputs and Outputs Buffered
- Diode Protection on All Inputs
- Supply Voltage Range = 3.0 Vdc to 18 Vdc
- Output Compatible with Two HTL Loads, Two Low-Power TTL Loads or One Low-Power Schottky TTL Load
- Functional Equivalent to TTL 74174

DESCRIPTION:

The 4174B hex type D flip-flop is constructed with MOS P-channel and N-channel enhancement mode devices in a single monolithic structure. Data on the D inputs which meets the setup time requirements is transferred to the Q outputs on the positive edge of the clock pulse. All six flip-flops share common clock and reset inputs. The reset is active low, and independent of the clock.

CONNECTION DIAGRAM



V_{DD} = Pin 16
 V_{SS} = Pin 8

MAXIMUM RATINGS (Voltages referenced to V_{SS})

| Rating | Symbol | Value | Unit |
|---|-----------|---------------------------|------|
| DC Supply Voltage | V_{DD} | -0.5 to +18 | Vdc |
| Input Voltage, All Inputs | V_{in} | -0.5 to $V_{DD} + 0.5$ | Vdc |
| DC Current Drain per Pin | I | 10 | mAdc |
| Operating Temperature Range—C, D, F, H E | T_A | -55 to +125 -40 to +85 | °C |
| Storage Temperature Range | T_{stg} | -65 to +150 | °C |

This device contains circuitry to protect the inputs against damage due to high static voltages or electric fields; however, it is advised that normal precautions be taken to avoid application of any voltage higher than maximum rated voltages to this high impedance circuit. For proper operation it is recommended that V_{in} and V_{out} be constrained to the range $V_{SS} < (V_{in} \text{ or } V_{out}) < V_{DD}$.

Unused inputs must always be tied to an appropriate logic voltage level (e.g., either V_{SS} or V_{DD}).

TRUTH TABLE (Positive Logic)

| INPUTS | | | OUTPUT |
|--------|------|-------|--------|
| Clock | Data | Reset | Q |
| | 0 | 1 | 0 |
| | 1 | 1 | 1 |
| | X | 1 | Q |
| X | X | 0 | 0 |

No
Change

X = Don't Care

SWITCHING CHARACTERISTICS* ($C_L = 50 \text{ pF}$, $T_A = 25^\circ\text{C}$)

| Characteristic | Symbol | V_{DD} Vdc | All Types | | | Unit |
|--|--------------------|-----------------|-------------------|---------------------|-------------------|---------------|
| | | | Min | Typ | Max | |
| Output Rise and Fall Time | t_r, t_f | 5.0 10 15 | — — — | 100 50 40 | 200 100 80 | ns |
| Propagation Delay Time—Clock to Q | t_{PLH}, t_{PHL} | 5.0 10 15 | — — — | 150 70 50 | 300 140 100 | ns |
| Propagation Delay Time—Reset to Q | t_{PHL} | 5.0 10 15 | — — — | 250 100 75 | 500 200 150 | ns |
| Minimum Clock Pulse Width | PW_C | 5.0 10 15 | — — — | 75 45 35 | 150 90 70 | ns |
| Minimum Reset Pulse Width | PW_R | 5.0 10 15 | — — — | 100 50 40 | 200 100 80 | ns |
| Maximum Clock Pulse Frequency | PRF | 5.0 10 15 | 2.0 5.0 6.5 | 7.0 12.0 15.5 | — — — | MHz |
| Maximum Clock Pulse Rise and Fall Time | t_r, t_f | 5.0 10 15 | 15 15 15 | — — — | — — — | μs |
| Data Setup Time | t_{setup} | 5.0 10 15 | — — — | 20 10 0 | 40 20 15 | ns |
| Data Hold Time | t_{hold} | 5.0 10 15 | — — — | 40 20 15 | 80 40 30 | ns |
| Reset Removal Time** | t_{rem} | 5.0 10 15 | — — — | 125 50 40 | 250 100 80 | ns |

*The formulas given are for the typical characteristics only.


**The reset signal must be high prior to a positive-going transition of the clock.

STATIC CHARACTERISTICS¹


| PARAMETER | V_{DD} (Vdc) | CONDITIONS | T_{LOW}^2 | | +25°C | | | T_{HIGH}^2 | | Units |
|--------------------------|-------------------|--|-------------|---------------|-------------|-------------------------|---------------|--------------|-------------------|-----------------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I_{DD} | 5 10 15 $V_{IN} = V_{SS}$ or V_{DD} All valid input combinations | — — — | 5 10 20 | — — — | 0.005 0.010 0.015 | 5 10 20 | — — — | 150 300 600 | μAdc |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".² $T_{LOW} = -55^\circ\text{C}$ for C, D, H device.= -40°C for E device. $T_{HIGH} = +125^\circ\text{C}$ for C, D, F, H device.= $+85^\circ\text{C}$ for E device.

TIMING DIAGRAM



FUNCTIONAL BLOCK DIAGRAM



CMOS PRESETTABLE UP-DOWN COUNTERS (Dual Clock with Reset)

FEATURES:

- Individual clock lines for counting up or counting down
- Synchronous high-speed carry and borrow propagation delays for cascading
- Asynchronous reset and preset capability
- Medium-speed operation— $f_{CL} = 8 \text{ MHz (typ.) @ } 10 \text{ V}$

DESCRIPTION:

The SSS- 4192B Presettable BCD Up/Down Counter and the 4193B Presettable Binary Up/Down Counter each consist of 4 synchronously clocked, gated "D" type flip-flops connected as a counter. The inputs consist of 4 individual jam lines, a $\overline{\text{PRESET ENABLE}}$ control, individual CLOCK UP and CLOCK DOWN signals and a master RESET . Four buffered Q signal outputs as well as $\overline{\text{CARRY}}$ and $\overline{\text{BORROW}}$ outputs for multiple-stage counting schemes are provided.



The counter is cleared so that all outputs are in a low state by a high on the RESET line. A RESET is accomplished asynchronously with the clock. Each output is individually programmable asynchronously with the clock to the level on the corresponding jam input when the $\overline{\text{PRESET ENABLE}}$ control is low.

The counter counts up one count on the positive clock edge of the CLOCK UP signal provided the CLOCK DOWN line is high. The counter counts down one count on the positive clock edge of the CLOCK DOWN signal provided the CLOCK UP line is high.

The $\overline{\text{CARRY}}$ and $\overline{\text{BORROW}}$ signals are high when the counter is counting up or down. The $\overline{\text{CARRY}}$ signal goes low one-half clock


APPLICATIONS:

- Up/down difference counting
- Multistage ripple counting
- Synchronous frequency dividers
- A/D and D/A conversion
- Programmable binary or BCD counting



cycle after the counter reaches its maximum count in the count-up mode. The $\overline{\text{BORROW}}$ signal goes low one-half clock cycle after the counter reaches its minimum count in the count-down mode. Cascading of multiple packages is easily accomplished without the need for additional external circuitry by tying the $\overline{\text{BORROW}}$ and $\overline{\text{CARRY}}$ outputs to the CLOCK DOWN and CLOCK UP inputs, respectively, of the succeeding counter package.



The 4192B and 4193B types are supplied in 16-lead hermetic dual-in-line ceramic packages (C and D suffixes), 16-lead dual-in-line plastic packages (E suffix), 16-lead ceramic flat packages (F suffix), and in chip form (H suffix).




STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|------------|-------------------------------|------|-------|------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | 5 | — | 5 | — | 0.04 | 5 | — | 150 | μAdc |
| | | 10 | — | 10 | — | 0.04 | 10 | — | 300 | |
| | | 15 | — | 20 | — | 0.04 | 20 | — | 600 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under “4000B Series Family Specifications”.
² T_{LOW} = -55°C for C, D, H device.
= -40°C for E device.
T_{HIGH} = +125°C for C, D, F, H device.
= + 85°C for E device.



Typical P-Channel
Source Current Characteristics




Typical N-Channel
Sink Current Characteristics

RECOMMENDED OPERATING CONDITIONS**For maximum reliability:**DC Supply Voltage $V_{DD} - V_{SS}$ 3 to 15 VdcOperating Temperature T_A -55 to +125 °C



C, D, F, H Device -40 to +85 °C

E Device -40 to +85 °C


**DYNAMIC ELECTRICAL CHARACTERISTICS at $T_A = 25^\circ\text{C}$** Input $t_r, t_f = 20\text{ ns}$, $C_L = 50\text{ pF}$, $R_L = 200\text{ k}\Omega$

| CHARACTERISTIC | V_{DD} (V) | LIMITS | | | UNITS |
|--|-----------------|---------------|-------------------|-------------------|---------------|
| | | Min. | Typ. | Max. | |
| Propagation Delay Time t_{PHL}, t_{PLH} : CLOCK UP or CLOCK DOWN to Q, RESET to Q | 5 10 15 | — — — | 250 120 90 | 500 240 180 | ns |
| \overline{PE} to Q | 5 10 15 | — — — | 200 100 70 | 400 200 140 | ns |
| CLOCK UP to \overline{CARRY} , CLOCK DOWN to BORROW | 5 10 15 | — — — | 160 80 60 | 320 160 120 | ns |
| RESET or \overline{PE} to BORROW or \overline{CARRY} | 5 10 15 | — — — | 300 150 110 | 600 300 220 | ns |
| Transition Time, t_{THL}, t_{TLH} | 5 10 15 | — — — | 100 50 40 | 200 100 80 | ns |
| Min. Removal Time, t_{rem}^* RESET or PE | 5 10 15 | — — — | 40 20 15 | 80 40 30 | ns |
| Min. Pulse Width, t_w RESET | 5 10 15 | — — — | 240 150 130 | 480 300 260 | ns |
| \overline{PE} | 5 10 15 | — — — | 120 85 70 | 240 170 140 | ns |
| CLOCK | 5 10 15 | — — — | 90 45 30 | 180 90 60 | ns |
| Max. Clock Input Frequency, f_{CL} | 5 10 15 | 2 4 5.5 | 4 8 11 | — — — | MHz |
| Clock Rise & Fall time, t_r, t_f | 5 10 15 | — — — | — — — | 15 15 5 | μs |
| Input Capacitance, C_{IN} : RESET | — | — | 10 | 15 | pF |
| All Other Inputs | — | — | 5 | 7.5 | pF |


*The time required for RESET or PRESET ENABLE control to be removed before clocking (see timing diagram).



4192B timing diagram.



4193B timing diagram.



Internal logic of Flip-flop.

TRUTH TABLE

| CLOCK UP | CLOCK DOWN | PRESET ENABLE | RESET | ACTION |
|----------|------------|---------------|-------|------------|
| | 1 | 1 | 0 | COUNT UP |
| | 1 | 1 | 0 | NO COUNT |
| 1 | | 1 | 0 | COUNT DOWN |
| 1 | | 1 | 0 | NO COUNT |
| X | X | 0 | 0 | PRESET |
| X | X | X | 1 | RESET |

1 = HIGH LEVEL 0 = LOW LEVEL X = DON'T CARE

CMOS EXPANDABLE GATES



FEATURES

- ◆ Dual 4-Input Gates with Uncommitted Output Transistors
- ◆ Simplifies Construction of Combinational Logic Functions
- ◆ CMOS-to-TTL Interface Capability
- ◆ All Inputs Diode-Protected


DESCRIPTION

These devices are buffered Dual 4-input NOR Gates (4402B) and NAND Gates (4412B), with uncommitted output transistors. Gate expansion, complex combinational gating, and interface circuits can be constructed from these devices.

LOGIC DIAGRAMS




Typical P-Channel
Source Current Characteristics



RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | -55 to +125 | °C |
| C, D, F, H Device | | -55 to +125 | °C |
| E Device | | -40 to +85 | °C |



Typical N-Channel
Sink Current Characteristics

ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|--|-------------------------------|------|-------|--------|------|--------------------------------|------|------------------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | V _{IN} = V _{SS} or V _{DD} All valid input combinations | — | 0.05 | — | 0.0005 | 0.05 | — | 1.5 | μA _{dc} |
| | | | — | 0.10 | — | 0.001 | 0.10 | — | 3.0 | |
| | | | — | 0.20 | — | 0.002 | 0.20 | — | 6.0 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.

= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.


= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)


| PARAMETER | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|---|-------------------------------------|------|------|------|-------|
| PROPAGATION DELAY TIME Connected as Dual 4-Input Gates | t _{PLH} , t _{PHL} | — | — | — | — |
| | 5 | — | 125 | 250 | ns |
| | 10 | — | 60 | 120 | |
| | 15 | — | 45 | 90 | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | — | — | — | — |
| | 5 | — | 100 | 200 | ns |
| | 10 | — | 50 | 100 | |
| | 15 | — | 40 | 80 | |

APPLICATIONS INFORMATION

4402B



4412B



For additional information, see Application Note AN-102.

CMOS 8-STAGE BINARY COUNTER



FEATURES

- ◆ 8-Stage Synchronous Counter
- ◆ Buffered Outputs from all 8 Stages
- ◆ Direct Reset
- ◆ Fully Static Operation – DC to 8MHz @ 10Vdc

DESCRIPTION


The 4404B consists of eight synchronous, single-phase clocked counting stages, with the Q output of each stage accessible. The counter is reset to all "zeroes" by a high level on the Reset line. Each stage of the counter utilizes a master-slave flip-flop configuration. The state of the counter is advanced one step in binary order on the negative-going transition of the input clock pulse.

TRUTH TABLE

| CLOCK | RESET | OUTPUT STATE |
|---|-------|-----------------------|
|  | 0 | No Change |
|  | 0 | Advance to next state |
| X | 1 | All Outputs are low |

X = Don't Care

CONNECTION DIAGRAM (all packages)



Add suffix for package:

- C 14-pin Cerdip
- D 14-pin Ceramic
- E 14-pin Epoxy
- F 14-pin Flat
- H Chip

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:


DC Supply Voltage $V_{DD} - V_{SS}$ 3 to 15 Vdc

Operating Temperature T_A

C, D, F, H Device -55 to +125 °C

E Device -40 to +85 °C

LOGIC DIAGRAM



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|--|-------------------------------|------|-------|------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | V _{IN} = V _{SS} or V _{DD} All valid input combinations | — | 5 | — | 0.05 | 5 | — | 150 | μAdc |
| | | | — | 10 | — | 0.1 | 10 | — | 300 | |
| | | | — | 20 | — | 0.2 | 20 | — | 600 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.



= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.

= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETER | | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|----------------------------------|-------------------------------------|--------------------------|------|------|------|-------|
| CLOCKED OPERATION | | | | | | |
| PROPAGATION DELAY TIME | t _{PLH} , t _{PHL} | 5 | — | 250 | 500 | ns |
| | | 10 | — | 125 | 250 | |
| | | 15 | — | 100 | 200 | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | — | 100 | 200 | ns |
| | | 10 | — | 50 | 100 | |
| | | 15 | — | 40 | 80 | |
| MINIMUM CLOCK PULSE WIDTH | PW _{CL} | 5 | — | 125 | 250 | ns |
| | | 10 | — | 65 | 130 | |
| | | 15 | — | 50 | 100 | |
| MAXIMUM CLOCK FREQUENCY | f _{CL} | 5 | 2.0 | 4.0 | — | MHz |
| | | 10 | 4.0 | 8.0 | — | |
| | | 15 | 5 | 10 | — | |
| MAXIMUM CLOCK RISE AND FALL TIME | t _{rCL} , t _{fCL} | 5 | 15 | — | — | μs |
| | | 10 | 5 | — | — | |
| | | 15 | 3 | — | — | |
| RESET OPERATION | | | | | | |
| PROPAGATION DELAY TIME | t _{PHL} | 5 | — | 175 | 350 | ns |
| | | 10 | — | 75 | 150 | |
| | | 15 | — | 60 | 120 | |
| MINIMUM RESET PULSE WIDTH | PW _R | 5 | — | 100 | 200 | ns |
| | | 10 | — | 50 | 100 | |
| | | 15 | — | 40 | 80 | |
| RESET REMOVAL TIME | t _{rem} | 5 | — | 200 | 400 | ns |
| | | 10 | — | 90 | 180 | |
| | | 15 | — | 65 | 130 | |



CMOS QUAD ANALOG SWITCH


FEATURES

- ◆ DPDT Switch Operation Without External Logic
- ◆ Wide Range of Digital and Analog Signal Levels — Digital or Analog Signal to 18 Volts peak
- ◆ Low ON Resistance — 200 Ω typ. over 15V_{p-p} Signal Input Range, V_{DD} - V_{SS} = 15V
- ◆ Matched Switch Characteristics - 10 Ω typ. Difference Between R_{ON} Values at a Fixed Bias Point over 15 V_{p-p} Signal Input Range, V_{DD} - V_{SS} = 15V
- ◆ High "ON/OFF" Output Voltage Ratio — 65 dB typ. @ f_{is} = 10 kHz, R_L = 10 k Ω
- ◆ High Degree of Linearity — 0.4% Distortion typ. @ f_{is} = 1 kHz, V_{is} = 5 V_{p-p}, V_{DD} - V_{SS} = 10V, R_L = 10 k Ω
- ◆ Extremely low OFF Switch Leakage Resulting in Very Low Offset Current and High Effective OFF Switch Resistance — 10 pA typ. @ V_{DD} - V_{SS} = 10V, T_A = 25° C
- ◆ Extremely High Control Input Impedance (Control Circuit Isolated from Signal Circuit) — 10¹² Ω typ.
- ◆ Low Crosstalk Between Switches — -50dB typ. @ f_{is} = 0.9 MHz, R_L = 1k Ω
- ◆ Matched Control-Input to Signal-Output Capacitances - Reduces Output Signal Transients
- ◆ Transmits Frequencies up to 40MHz


DESCRIPTION

The 4416B is a single-chip monolithic silicon integrated circuit containing eight N-channel and eight P-channel enhancement-mode MOS transistors connected to form four independent bilateral signal switches. Each switch consists of both P- and N-channel devices with common source and drain connections. A single control signal is required per switch. Both P and N devices in a given switch are biased ON or OFF by the control signal.

SCHEMATIC DIAGRAM



CONNECTION DIAGRAM (all packages)



Add suffix for package:

| | | | |
|---|----------------|---|-------------|
| C | 14-pin Cerdip | F | 14-pin Flat |
| D | 14-pin Ceramic | H | Chip |
| E | 14-pin Epoxy | | |


RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-----------------------------------|-------------|-----|
| DC Supply Voltage | V _{DD} - V _{SS} | 3 to 15 | Vdc |
| Operating Temperature | T _A | -55 to +125 | °C |
| C, D, F, H Device | | -55 to +125 | °C |
| E Device | | -40 to +85 | °C |

The CMOS switch permits peak input-signal voltage swings equal to the full supply voltage, a considerable advantage over single-channel types. When the control input is high the switch will be ON. When the control input is low the switch will be OFF.

LOGIC DIAGRAM



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | CONDITIONS | V _{SS} (Vdc) | V _{DD} (Vdc) | T _{LOW} ² | | 25°C | | | T _{HIGH} ² | | Units |
|---|---|--|--------------------------|-------------------------------|-------------------|-------------|-------------------|-------------------|--------------------------------|-------------------|-------|
| | | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} V _{IN} = V _{SS} or V _{DD} All valid input combinations | 0 | 5 | — | 0.05 | — | 0.0005 | 0.05 | — | 1.5 | μAdc |
| | | 0 | 10 | — | 0.1 | — | 0.001 | 0.1 | — | 3.0 | |
| | | 0 | 15 | — | 0.2 | — | 0.002 | 0.2 | — | 6.0 | |
| MINIMUM INPUT HIGH VOLTAGE (Control Input) | V _{IH} V _{IS} = V _{SS} V _{OS} = V _{DD} I _{OS} = 10μA | 0 | 5 | — | 2.9 | — | 1.5 | 2.7 | — | 2.4 | Vdc |
| | | 0 | 10 | — | 2.9 | — | 1.5 | 2.7 | — | 2.4 | |
| | | 0 | 15 | — | 2.9 | — | 1.5 | 2.7 | — | 2.4 | |
| MAXIMUM INPUT LOW VOLTAGE (Control Input) | V _{IL} V _{IS} = V _{SS} V _{OS} = V _{DD} I _{OS} = 10μA | 0 | 5 | 0.9 | — | 0.7 | 1.5 | — | 0.4 | — | Vdc |
| | | 0 | 10 | 0.9 | — | 0.7 | 1.5 | — | 0.4 | — | |
| | | 0 | 15 | 0.9 | — | 0.7 | 1.5 | — | 0.4 | — | |
| SWITCH INPUT/OUTPUT LEAKAGE (Switch off) | I _{OFF} V _C = V _{SS} ⁴ V _{IS} | ±7.5 ±5 | +7.5 +5 | — | ±250 ±125 | — | ±0.1 ±0.01 | ±250 ±125 | — | ±2500 ±1250 | nAdc |
| | | | | | | | | | | | |
| ON-RESISTANCE | R _{ON} V _C = V _{DD} ⁴ R _L = 10kΩ | V _{IS} (Vdc) | | | | | | | | | |
| | | +7.5 -7.5 ±0.25 | -7.5 +7.5 | — — — | 200 200 180 | — — — | 100 100 80 | 220 220 200 | — — — | 450 450 420 | Ω |
| | | +5 -5 ±0.25 | +5 +5 | — — — | 260 260 260 | — — — | 160 160 150 | 300 300 290 | — — — | 500 500 500 | Ω |
| | | +15 +0.25 +9.3 | 0 +15 | — — — | 230 100 250 | — — — | 130 40 150 | 250 120 270 | — — — | 500 260 580 | Ω |
| | | +10 +0.25 +5.6 | 0 +10 | — — — | 220 100 400 | — — — | 120 60 220 | 240 130 420 | — — — | 500 280 900 | Ω |
| | | | | | | | | | | | |
| ON-RESISTANCE MATCH (Same package) | ΔR _{ON} V _C = V _{DD} ⁴ R _L = 10kΩ | V _{IS} (Vdc) ±7.5 ±5 | -7.5 +7.5 +5 | — — — | — — — | — — — | 10 15 | — — — | — — — | — — — | Ω |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".² T_{LOW} = -55°C for C, D, F, H device.

= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.

= + 85°C for E device.

⁴ Reverse polarity of V_C (control input) for switches B and C.DYNAMIC CHARACTERISTICS (C_L = 50 pF, T_A = 25°C)

| PARAMETER | CONDITIONS | V _{SS} (Vdc) | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|---|---|---|--------------------------|------|------|------|-------|
| SIGNAL INPUTS (V _{IS}) AND OUTPUTS (V _{OS}) | | | | | | | |
| PROPAGATION DELAY TIME Signal input to signal output | t _{PLH} , t _{PHL} V _C = V _{DD} ¹ V _{IS} = square wave R _L = 10kΩ | 0 | 5 | — | 20 | 40 | ns |
| | | 0 | 10 | — | 10 | 20 | |
| | | 0 | 15 | — | 7.5 | 15 | |
| BANDWIDTH (-3dB) (Sine Wave) | BW V _C = V _{DD} ¹ V _{IS} = 5V _{r-p} centered @0.0Vdc | R _L 1kΩ 10kΩ 100kΩ 1MΩ | -5 | +5 | — | 54 | MHz |
| | | | | | — | 40 | |
| | | | | | — | 38 | |
| | | | | | — | 37 | |
| | | | | | — | — | |

ELECTRICAL CHARACTERISTICS (Continued)

DYNAMIC CHARACTERISTICS ($C_L = 50 \text{ pF}$, $T_A = 25^\circ\text{C}$) (Continued)


| PARAMETER | CONDITIONS | V_{SS} (Vdc) | V_{DD} (Vdc) | Min. | Typ. | Max. | Units |
|---|---|-------------------|-------------------|-------------|---------------------------|----------------|-------|
| SIGNAL INPUTS (V_{IS}) AND OUTPUTS (V_{OS}) (Continued) | | | | | | | |
| INSERTION LOSS ($= 20 \log_{10} \frac{V_{OS}}{V_{IS}}$) | $V_C = V_{DD}^1$ $V_{IS} = 5V_{pp}$ centered @0.0Vdc R_L 1k Ω 10k Ω 100k Ω 1M Ω | -5 | +5 | — | 2.3 0.2 0.1 0.05 | — | dB |
| SIGNAL DISTORTION (Sine Wave) | $V_C = V_{DD}^1$ $V_{IS} = 5V_{pp}$ centered @0.0Vdc $f_{IS} = 1.0\text{kHz}$ $R_L = 10k\Omega$ | -5 | +5 | — | 0.4 | — | % |
| FEEDTHROUGH (-50dB) | $V_C = V_{SS}^1$ $V_{IS} = 5V_{pp}$ centered @0.0Vdc R_L 1k Ω 10k Ω 100k Ω 1M Ω | -5 | +5 | — | 1250 140 18 2 | — | kHz |
| CROSSTALK (-50dB) (Between two switches) | $V_C(A) = V_{DD}^1$ $V_C(B) = V_{SS}^1$ $V_{IS}(A) = 5V_{pp}$ centered @0.0Vdc $R_L = 1.0k$ | -5 | +5 | — | 0.9 | — | MHz |
| CAPACITANCE Input Output Feedthrough | C_{IS} C_{OS} C_{IOS} $V_C = V_{SS}^1$ | -5 | +5 | — | 4 4 0.2 | — | pF |
| CONTROL INPUT (V_C) | | | | | | | |
| PROPAGATION DELAY TIME Turn on | t_{PLH} t_{PHL} $V_{SS} < V_{IS} < V_{DD}$ $R_L = 10k\Omega$ | 0 0 0 | 5 10 15 | — — — | 40 20 15 | 80 40 30 | ns |
| MAXIMUM INPUT FREQUENCY | f_c $V_{SS} < V_{IS} < V_{DD}$ $R_L = 1.0k\Omega$ | 0 0 0 | 5 10 15 | — — — | 5 10 12 | — | MHz |
| CROSSTALK (To signal port) | $V_C = \text{Square wave}$ $R_L = 10k\Omega$ $R_{IN} = 1.0k\Omega$ | 0 0 0 | 5 10 15 | — — — | 30 50 100 | — | mV |

NOTE: ¹ Reverse polarity of V_C (control input) for switches B and C.


TYPICAL ON-RESISTANCE CHARACTERISTICS

| CHARACTERISTIC* | SUPPLY CONDITIONS | | LOAD CONDITIONS | | | | | |
|-----------------|-------------------|-----------------|-----------------------|-----------------|-----------------------|-----------------|-----------------------|-----------------|
| | V_{DD} (V) | V_{SS} (V) | $R_L = 1k\Omega$ | | $R_L = 10k\Omega$ | | $R_L = 100k\Omega$ | |
| | | | VALUE (Ω) | V_{IS} (V) | VALUE (Ω) | V_{IS} (V) | VALUE (Ω) | V_{IS} (V) |
| R_{ON} | +15 | 0 | 200 | +15 | 200 | +15 | 180 | +15 |
| | | | 200 | 0 | 200 | 0 | 200 | 0 |
| $R_{ON(max)}$ | +15 | 0 | 300 | +11 | 300 | +9.3 | 320 | +9.2 |
| | | | 290 | +10 | 250 | +10 | 240 | +10 |
| R_{ON} | +10 | 0 | 290 | 0 | 250 | 0 | 300 | 0 |
| $R_{ON(max)}$ | +10 | 0 | 500 | +7.4 | 560 | +5.6 | 610 | +5.5 |
| | | | 860 | +5 | 470 | +5 | 450 | +5 |
| R_{ON} | +5 | 0 | 600 | 0 | 580 | 0 | 800 | 0 |
| $R_{ON(max)}$ | +5 | 0 | 1.7k | +4.2 | 7k | +2.9 | 33k | +2.7 |
| | | | 200 | +7.5 | 200 | +7.5 | 180 | +7.5 |
| R_{ON} | +7.5 | -7.5 | 200 | -7.5 | 200 | -7.5 | 180 | -7.5 |
| $R_{ON(max)}$ | +7.5 | -7.5 | 290 | ± 0.25 | 280 | ± 0.25 | 400 | ± 0.25 |
| | | | 260 | +5 | 250 | +5 | 240 | +5 |
| R_{ON} | +5 | -5 | 310 | -5 | 250 | -5 | 240 | -5 |
| $R_{ON(max)}$ | +5 | -5 | 600 | ± 0.25 | 580 | ± 0.25 | 760 | ± 0.25 |
| | | | 590 | +2.5 | 450 | +2.5 | 490 | +2.5 |
| R_{ON} | +2.5 | -2.5 | 720 | -2.5 | 520 | -2.5 | 520 | -2.5 |
| $R_{ON(max)}$ | +2.5 | -2.5 | 232k | ± 0.25 | 300k | ± 0.25 | 870k | ± 0.25 |


* Variation from a perfect switch: $R_{ON} = 0\Omega$.




Typ. switch frequency response - switch "ON"



Typ. feedthru vs. freq. - switch "OFF"




Typ. crosstalk between switch circuits in the same package



Test circuit, Crosstalk-control input to signal output.

APPLICATIONS INFORMATION

4416B connected as a DPDT Switch



CMOS DECADE COUNTER/7-SEGMENT DECODER/DRIVERS

FEATURES

- ◆ Monolithic Construction of Bipolar Transistors on Outputs Allow Direct Display Drive
- ◆ Decade Counter and 7-Segment Decoder in One Package
- ◆ Direct Reset
- ◆ Display Enable Function (4426AB)
- ◆ Ripple Blanking and Lamp Test Functions (4433AB)
- ◆ Trigger from either Edge of Clock Input
- ◆ Carry Output for Cascading Stages
- ◆ Fully Static Operation - DC to 5MHz @ 10Vdc

DESCRIPTION

These two devices each consist of a 5-stage Johnson decade counter and an output decoder which converts the Johnson code to a 7-segment decoded output for driving each stage in a numerical display. A "high" Reset signal clears the decade counter to its zero count. The counters have interchangeable Clock and Clock Enable lines for incrementing on either a positive-going or negative-going transition, respectively. Antilock gating is provided on the Johnson counter, thus assuring proper counting sequence. The Carry-Out (COUT) signal completes one cycle every ten clock input cycles and is used to directly clock the succeeding decade in a multi-decade counting chain.


4426AB

When the Display Enable is "low" the seven decoded outputs are forced off regardless of the state of the counter. Activation of the display only when required results in significant power savings. This system also facilitates implementation of display-character multiplexing.

The Carry Out and ungated "C-segment" signals are not gated by the Display Enable and therefore are available continuously. This feature is a requirement in implementation of certain divider functions such as divide-by-60 and divide-by-12.

4433AB

The 4433AB has provisions for automatic blanking of the nonsignificant zeros in a multi-digit decimal number which results in an easily readable display consistent with normal writing practice. For example, the number 0050.0700 in an eight-digit display would be displayed as 50.07. Zero suppression on the integer side is obtained by connecting the RBI terminal of the 4433AB associated with the most significant digit in the display to a "low-level" voltage and connecting the RBO terminal of that stage to the RBI terminal of the 4433AB in the next-lower significant position in the display. This procedure is continued for each succeeding 4433AB on the integer side of the display. On the fraction side of the display



RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | | |
| C, D, F, H Device | | -55 to +125 | °C |
| E Device | | -40 to +85 | °C |

play the RBI of the 4433AB associated with the least significant digit is connected to a "low level" voltage and the RBO of the 4433AB is connected to the RBI terminal of the 4433AB in the next more-significant-digit position. Again, this procedure is continued for all 4433AB on the fraction side of the display.

In a purely fractional number the zero immediately preceding the decimal point can be displayed by connecting the RBI of that stage to a "high-level" voltage (instead of to the RBO of the next more-significant stage). For Example: optional zero - 0.7346.


Likewise, the zero in a number such as 736.0 can be displayed by connecting the RBI of the 4433AB associated with it to a "high-level" voltage.

A "high" Lamp Test signal turns on all outputs.


BIPOLAR OUTPUTS

These devices are functionally and pin-for-pin interchangeable with all CMOS device types 4026AB and 4433AB. All counting and decoding in 4426AB and 4433AB devices is implemented with CMOS transistor circuitry. In order to furnish higher output drive for applications such as driving LED's, bipolar Darlington transistors have been furnished at each display drive output.


LOGIC DIAGRAM



TIMING DIAGRAM




DISPLAY




Collector of each output transistor internally tied to V_{DD}.

4426AB Decade Counter/7-Segment Decoder/Driver with Display Enable.


LOGIC DIAGRAM



TIMING DIAGRAM



DISPLAY



Collector of each output transistor internally tied to V_{DD}.

4433B Decade Counter/7-Segment Decoder/Driver with Ripple Blanking.

ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS^{1, 3}

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--|--------------------------|---|-------------------------------|-------|-------|------|-------|--------------------------------|-------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | V _{IN} = V _{SS} or V _{DD} All valid input combinations | — | 5 | — | 0.05 | 5 | — | 150 | μAdc |
| | | | — | 10 | — | 0.1 | 10 | — | 300 | |
| | | | — | 15 | — | 0.2 | 20 | — | 600 | |
| | | | — | 15 | — | 0.2 | 20 | — | 600 | |
| HIGH LEVEL OUTPUT VOLTAGE Decoded Outputs | V _{OH} | V _{IN} = V _{SS} or V _{DD} I _O < 1μA | 4.25 | — | 4.25 | — | — | 4.25 | — | Vdc |
| | | | 9.25 | — | 9.25 | — | — | 9.25 | — | |
| | | | 14.25 | — | 14.25 | — | — | 14.25 | — | |
| | | | 14.25 | — | 14.25 | — | — | 14.25 | — | |
| MINIMUM INPUT HIGH VOLTAGE | V _{IH} | V _O = 0.5V or 4.25V V _O = 1.0V or 9.0V V _O = 1.5V or 13.5V I _O < 1μA | — | 3.75 | — | 2.75 | 3.75 | — | 3.75 | Vdc |
| | | | — | 7.5 | — | 5.5 | 7.5 | — | 7.5 | |
| | | | — | 11.25 | — | 8.25 | 11.25 | — | 11.25 | |
| | | | — | 11.25 | — | 8.25 | 11.25 | — | 11.25 | |
| MAXIMUM INPUT LOW VOLTAGE | V _{IL} | V _O = 0.5V or 4.25V V _O = 1.0V or 9.0V V _O = 1.5V or 13.5V I _O < 1μA | 1.25 | — | 1.25 | 2.25 | — | 1.25 | — | Vdc |
| | | | 2.5 | — | 2.5 | 4.5 | — | 7.5 | — | |
| | | | 3.75 | — | 3.75 | 6.75 | — | 3.75 | — | |
| | | | 3.75 | — | 3.75 | 6.75 | — | 3.75 | — | |
| OUTPUT HIGH (SOURCE) CURRENT Decoded Outputs ³ | I _E | V _{OH} = 3.5V V _{OH} = 8.5V V _{OH} = 13.5V V _{IN} = V _{SS} or V _{DD} | — | — | -15 | -25 | — | — | — | mAdc |
| | | | — | — | — | -60 | — | — | — | |
| | | | — | — | — | -100 | — | — | — | |
| | | | — | — | — | -100 | — | — | — | |
| | I _{OH} | V _{OH} = 4.6V V _{OH} = 9.5V V _{OH} = 13.5V V _{IN} = V _{SS} or V _{DD} | -0.10 | — | -0.10 | -0.4 | — | -0.07 | — | mAdc |
| | | | -0.30 | — | -0.30 | -1.0 | — | -0.20 | — | |
| | | | -0.90 | — | -0.90 | -4.0 | — | -0.65 | — | |
| | | | -0.90 | — | -0.90 | -4.0 | — | -0.65 | — | |
| | I _{OH} | V _{OH} = 4.6V V _{OH} = 9.5V V _{OH} = 13.5V V _{IN} = V _{SS} or V _{DD} | -0.08 | — | -0.08 | -0.2 | — | -0.06 | — | mAdc |
| | | | -0.20 | — | -0.20 | -0.5 | — | -0.14 | — | |
| | | | -0.60 | — | -0.60 | -1.5 | — | -0.42 | — | |
| | | | -0.60 | — | -0.60 | -1.5 | — | -0.42 | — | |
| OUTPUT LOW (SINK) CURRENT | I _{OL} | V _{OL} = 0.4V V _{OL} = 0.5V V _{OL} = 1.5V V _{IN} = V _{SS} or V _{DD} | -0.10 | — | -0.10 | 0.4 | — | -0.07 | — | mAdc |
| | | | -0.30 | — | -0.30 | 1.0 | — | -0.20 | — | |
| | | | -0.90 | — | -0.90 | 4.0 | — | -0.65 | — | |
| | | | -0.90 | — | -0.90 | 4.0 | — | -0.65 | — | |
| | I _{OL} | V _{OL} = 0.4V V _{OL} = 0.5V V _{OL} = 1.5V V _{IN} = V _{SS} or V _{DD} | 0.13 | — | -0.08 | 0.25 | — | -0.06 | — | mAdc |
| | | | 0.31 | — | -0.20 | 0.6 | — | -0.14 | — | |
| | | | 1.43 | — | -0.60 | 2.5 | — | -0.42 | — | |
| | | | 1.43 | — | -0.60 | 2.5 | — | -0.42 | — | |
| | I _{OL} | V _{OL} = 0.4V V _{OL} = 0.5V V _{OL} = 1.5V V _{IN} = V _{SS} or V _{DD} | 0.13 | — | -0.08 | 0.25 | — | -0.06 | — | mAdc |
| | | | 0.31 | — | -0.20 | 0.6 | — | -0.14 | — | |
| | | | 1.43 | — | -0.60 | 2.5 | — | -0.42 | — | |
| | | | 1.43 | — | -0.60 | 2.5 | — | -0.42 | — | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".² T_{LOW} = -55°C for C, D, F, H device.

= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.



= + 85°C for E device.

³ Observe Package Power Dissipation rating.



ELECTRICAL CHARACTERISTICS (Continued)**DYNAMIC CHARACTERISTICS** ($C_L = 50\text{pF}$, $T_A = 25^\circ\text{C}$)

| PARAMETER | | V _{DD} (V _{dc}) | Min. | Typ. | Max. | Units | |
|--|--|---------------------------------------|------|------|------|-------|----|
| CLOCKED OPERATION | | | | | | | |
| PROPAGATION DELAY TIME Clock to Decoded Outputs | t _{PLH} , t _{PHL} | 5 | — | 850 | 1700 | ns | |
| | | 10 | — | 250 | 500 | | |
| | | 15 | — | 200 | 400 | | |
| | Clock to Carry Out | t _{PLH} , t _{PHL} | 5 | — | 500 | 1000 | ns |
| | | | 10 | — | 125 | 250 | |
| | | | 15 | — | 100 | 200 | |
| OUTPUT TRANSITION TIME Decoded Outputs | t _{TLH} , t _{THL} | 5 | — | 450 | 900 | ns | |
| | | 10 | — | 200 | 400 | | |
| | | 15 | — | 150 | 300 | | |
| | Carry Output | t _{TLH} , t _{THL} | 5 | — | 250 | 500 | ns |
| | | | 10 | — | 125 | 250 | |
| | | | 15 | — | 100 | 200 | |
| MINIMUM CLOCK OR ENABLE PULSE WIDTH | PW _{CL} , PW _{CE} | 5 | — | 200 | 400 | ns | |
| | | 10 | — | 100 | 200 | | |
| | | 15 | — | 80 | 160 | | |
| | | | | | | | |
| MAXIMUM CLOCK FREQUENCY | f _{CL} | 5 | 1.25 | 2.5 | — | MHz | |
| | | 10 | 2.5 | 5.0 | — | | |
| | | 15 | 3.0 | 6.0 | — | | |
| | | | | | | | |
| MAXIMUM CLOCK OR ENABLE RISE AND FALL TIME | t _{rCL} , t _{fCL} | 5 | 15 | — | — | μs | |
| | | 10 | 15 | — | — | | |
| | | 15 | 3 | — | — | | |
| | | | | | | | |
| MINIMUM CLOCK OR ENABLE SETUP TIME | t _{setup} | 5 | — | 250 | 500 | ns | |
| | | 10 | — | 100 | 200 | | |
| | | 15 | — | 80 | 160 | | |
| | | | | | | | |
| RESET OPERATION | | | | | | | |
| PROPAGATION DELAY TIME Reset to Decoded Outputs | t _{PLH} , t _{PHL} | 5 | — | 700 | 1400 | ns | |
| | | 10 | — | 250 | 500 | | |
| | | 15 | — | 200 | 400 | | |
| | Reset to Carry Output | t _{PLH} , t _{PHL} | 5 | — | 500 | 1000 | ns |
| | | | 10 | — | 125 | 250 | |
| | | | 15 | — | 100 | 200 | |
| MINIMUM RESET PULSE WIDTH | PW _R | 5 | — | 200 | 400 | ns | |
| | | 10 | — | 100 | 200 | | |
| | | 15 | — | 80 | 160 | | |
| | | | | | | | |
| RESET REMOVAL TIME | t _{rem} | 5 | — | 375 | 750 | ns | |
| | | 10 | — | 150 | 300 | | |
| | | 15 | — | 125 | 250 | | |
| | | | | | | | |

OUTPUT NETWORK



DISPLAY INTERFACE



CMOS BINARY-TO-OCTAL DECODER

FEATURES

- ◆ Binary-to-Octal Decoding
- ◆ Buffered Outputs Go High on Selection
- ◆ Strobe Input for Simple Expansion


DESCRIPTION

The 4428B is a one-of-eight CMOS Strobed Decoder. The three inputs labeled X_0 , X_1 , and X_2 , constitute a three-bit word which defines a number from 0 to 7, and activates one of eight outputs of the decoder. The Strobe line inhibits the outputs from responding to the inputs. If the Strobe line is a logic "1", one of eight outputs is a logic "1". This is an important feature of the Strobe since many 4428B's may be cascading to produce a 1 or N X 8 strobed decoder. This array is particularly useful in expanding memory systems.

TRUTH TABLE – Strobe at Logical 1

| Address Input | | | | Output | | | | | | | |
|---------------|-------|-------|-------|--------|-----|-----|-----|-----|-----|-----|-----|
| | X_2 | X_1 | X_0 | "0" | "1" | "2" | "3" | "4" | "5" | "6" | "7" |
| PIN | 10 | 11 | 8 | 3 | 12 | 2 | 13 | 1 | 5 | 6 | 4 |
| | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | 0 | 0 | 1 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 |
| | 0 | 1 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 |
| | 0 | 1 | 1 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 |
| | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 |
| | 1 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 |
| | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 |
| | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 |

CONNECTION DIAGRAM (all packages)



Add suffix for package:


- C 14-pin Cerdip
- D 14-pin Ceramic
- E 14-pin Epoxy
- F 14-pin Flat
- H Chip

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | -55 to +125 | °C |
| C, D, F, H Device | | -40 to +85 | °C |
| E Device | | | |

BLOCK DIAGRAM



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS ¹:

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|--|-------------------------------|------|-------|------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | 5 V _{IN} = V _{SS} or V _{DD} | — | 5 | — | 0.05 | 5 | — | 150 | μAdc |
| | | 10 All valid input combinations | — | 10 | — | 0.1 | 10 | — | 300 | |
| | | 15 | — | 20 | — | 0.2 | 20 | — | 600 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.


= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.


= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETERS | | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|------------------------|-------------------------------------|--------------------------|------|------|------|-------|
| PROPAGATION DELAY TIME | t _{PLH} , t _{PHL} | 5 | — | 225 | 450 | ns |
| | | 10 | — | 100 | 200 | |
| | | 15 | — | 70 | 140 | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | — | 100 | 200 | ns |
| | | 10 | — | 50 | 100 | |
| | | 15 | — | 40 | 80 | |




Typical P-Channel
Source Current Characteristics




Typical N-Channel
Sink Current Characteristics

LOGIC DIAGRAM



APPLICATIONS INFORMATION
SIX-BIT BINARY 1-OF-64 DECODER



CMOS QUAD BUFFER-DRIVER



FEATURES

- ◆ Symmetrical High-Current Outputs
- ◆ High-Speed Operation with Large Capacitive Loads
- ◆ Low Output Impedance
- ◆ Diode Protection on all Inputs

DESCRIPTION


The 4441UB is a monolithic N-channel and P-channel enhancement-mode integrated circuit consisting of four large buffers for very high current capability. This device is useful as a line driver, low-power resistor-network driver for A/D and D/A conversion, display and clock drivers.

SCHEMATIC DIAGRAM
(one of four buffers)



Minimum and maximum transfer characteristics.

CONNECTION DIAGRAM
(all packages)



Add suffix for package:

| | | | |
|---|----------------|---|-------------|
| C | 14-pin Cerdip | F | 14-pin Flat |
| D | 14-pin Ceramic | H | Chip |
| E | 14-pin Epoxy | | |

RECOMMENDED OPERATING CONDITIONS



For maximum reliability:

DC Supply Voltage $V_{DD} - V_{SS}$ 3 to 15 Vdc

Operating Temperature T_A -55 to +125 °C

C, D, F, H Device -55 to +125 °C
E Device -40 to +85 °C

LOGIC DIAGRAM



Typical propagation delay time vs. C_L

ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|------------------------------|--------------------------|--|-------------------------------|------|-------|-------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | V _{IN} = V _{SS} or V _{DD} All valid input combinations | — | 1.0 | — | 0.005 | 1.0 | — | 30 | μAdc |
| | | | — | 2.0 | — | 0.01 | 2.0 | — | 60 | |
| | | | — | 4.0 | — | 0.02 | 4.0 | — | 120 | |
| OUTPUT HIGH (SOURCE) CURRENT | I _{OH} | V _{OH} = 4.6V V _{OH} = 9.5V V _{OH} = 13.5V V _{IN} = V _{SS} | -2.5 | — | -2.0 | -4.5 | — | -1.4 | — | mAdc |
| | | | -7.3 | — | -5.8 | -14.0 | — | -4.0 | — | |
| | | | -23.1 | — | -18.5 | -45 | — | -13.0 | — | |
| OUTPUT LOW (SINK) CURRENT | I _{OL} | V _{OL} = 0.4V V _{OL} = 0.5V V _{OL} = 1.5V V _{IN} = V _{DD} | 2.4 | — | 2.4 | 4.5 | — | 1.7 | — | mAdc |
| | | | 7.0 | — | 7.0 | 14.0 | — | 4.9 | — | |
| | | | 22.2 | — | 27 | 45 | — | 19 | — | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.


= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.


= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETER | | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|------------------------|-------------------------------------|--------------------------|------|------|------|-------|
| PROPAGATION DELAY TIME | t _{PLH} , t _{PHL} | 5 | — | 90 | 180 | ns |
| | | 10 | — | 45 | 90 | |
| | | 15 | — | 35 | 70 | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | — | 90 | 180 | ns |
| | | 10 | — | 45 | 90 | |
| | | 15 | — | 35 | 70 | |



Typical P-Channel
Source Current Characteristics



Typical N-Channel
Sink Current Characteristics

CMOS 21-STAGE DIVIDER

FEATURES

- ◆ Low Duty Cycle Push-Pull Outputs
- ◆ Inverter on Chip for Crystal Oscillator Circuit
- ◆ Buffered Output Available for Trimming Oscillator
- ◆ 21 Fully Static Stages
- ◆ 10MHz Counting Rate @ 10Vdc


DESCRIPTION

The 4445B monolithic aluminum gate CMOS integrated circuit consists of an oscillator inverter, 21 toggle flip-flops, and two flip-flops used to produce a 3.125% duty cycle output wave-form. Push-pull operation is provided by the inverter output buffers. A divide-by-4 frequency output is provided as an oscillator monitor or subsidiary high frequency output.

The 4445B is especially suited for low-power timekeeping applications such as desk or wall clocks, automobile clocks, and digital timing references. Its output is suitable for driving miniature synchronous motors, stepping motors, or external bipolar transistors in push-push fashion.

The 4445B is pin compatible with device type CD4045A. The extra function $f_o/4$ is provided on pin 11.

CONNECTION DIAGRAM (all packages)



Add suffix for package:

- C 16-pin Cerdip
- D 16-pin Ceramic
- E 16-pin Epoxy
- F 16-pin Flat
- H Chip

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:


DC Supply Voltage $V_{DD} - V_{SS}$ 3 to 15 Vdc

Operating Temperature T_A



C, D, F, H Device -55 to +125 °C

E Device -40 to +85 °C


TIMING DIAGRAM



LOGIC DIAGRAM



Typical propagation delay (f_o to y or y + d out) vs. V_{DD} . ($C_L = 50pF$).



Typical f_o vs. V_{DD} ($C_L = 50pF$).

ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS ¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|--|-------------------------------|------|-------|------|------|--------------------------------|------|------------------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | V _{IN} = V _{SS} or V _{DD} All valid input combinations | — | 5 | — | 0.05 | 5 | — | 150 | μA _{dc} |
| | | | — | 10 | — | 0.1 | 10 | — | 300 | |
| | | | — | 20 | — | 0.2 | 20 | — | 600 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.



= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.


= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETER | | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|----------------------------------|-------------------------------------|--------------------------|------|------|------|-------|
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | — | 100 | 200 | ns |
| | | 10 | — | 50 | 100 | |
| | | 15 | — | 40 | 80 | |
| MAXIMUM CLOCK FREQUENCY | f _{CL} | 5 | 3 | 6 | — | MHz |
| | | 10 | 5 | 10 | — | |
| | | 15 | 6 | 12 | — | |
| MAXIMUM CLOCK RISE AND FALL TIME | t _{rCL} , t _{fCL} | 5 | 15 | — | — | μs |
| | | 10 | 15 | — | — | |
| | | 15 | 5 | — | — | |




LOGIC DIAGRAM



APPLICATIONS INFORMATION

RECOMMENDED CIRCUIT FOR 2.097152 MHz OSCILLATOR



Typical clock motor driver

CMOS HEX INVERTER



FEATURES

- ◆ All Inputs Fully Diode-Protected
- ◆ Pin Compatible with 4009B, 4049B
- ◆ Fully "B"-Series Compatible

DESCRIPTION


The 4449UB consists of six CMOS inverter circuits. It is pin-compatible with the 4009UB, 4049UB, and equivalent device types. In systems which do not require the high output current and level-shifting capabilities of the buffers, the less expensive 4449 can be substituted directly with no change in board layout. The device is particularly useful for quasi-linear circuits, such as oscillators and multivibrators.

SCHEMATIC DIAGRAM (one of six inverters)



Typical current and voltage transfer characteristics.

CONNECTION DIAGRAM (all packages)



Add suffix for package:


- C 16-pin Cerdip
- D 16-pin Ceramic
- E 16-pin Epoxy
- F 16-pin Flat
- H Chip

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | | |
| C, D, F, H Device | | -55 to +125 | °C |
| E Device | | -40 to +85 | °C |

LOGIC DIAGRAM



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|--|-------------------------------|------|-------|--------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | V _{IN} = V _{SS} or V _{DD} All valid input combinations | — | 0.05 | — | 0.0005 | 0.05 | — | 1.5 | μAdc |
| | | | — | 0.10 | — | 0.001 | 0.10 | — | 3.0 | |
| | | | — | 0.20 | — | 0.002 | 0.20 | — | 6.0 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.


= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.


= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETER | | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|------------------------|-------------------------------------|--------------------------|------|------|------|-------|
| PROPAGATION DELAY TIME | t _{PLH} , t _{PHL} | 5 | — | 60 | 120 | ns |
| | | 10 | — | 30 | 60 | |
| | | 15 | — | 25 | 50 | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | — | 100 | 200 | ns |
| | | 10 | — | 50 | 100 | |
| | | 15 | — | 40 | 80 | |




Typical P-Channel
Source Current Characteristics




Typical N-Channel
Sink Current Characteristics


APPLICATIONS INFORMATION



Typical crystal oscillator circuit



Typical RC oscillator circuit



Input pulse shaping circuit (Schmitt
trigger)

CMOS STROBED HEX INVERTER/BUFFER

FEATURES

- ◆ 3-State Outputs with Separate Disable Control
- ◆ Common Input Inhibit Line
- ◆ TTL Output Drive Guaranteed Over Temperature Range
- ◆ Output Impedance $< 200 \Omega$ @ 5Vdc Guaranteed Over Temperature Range

DESCRIPTION


The 4502B is a Strobed Hex Inverter/Buffer with a common Data Input Inhibit Control and a common Output Disable Control. The 3-state output allows common bus configurations.

TRUTH TABLE


| D_n | Inhibit | Disable | Q_n |
|-------|---------|---------|----------------|
| 0 | 0 | 0 | 1 |
| 1 | 0 | 0 | 0 |
| X | 1 | 0 | 0 |
| X | X | 1 | High Impedance |

X = Don't Care

SCHEMATIC DIAGRAM (1 of 6 buffers)



CONNECTION DIAGRAM (all packages)



Add suffix for package:

| | | | |
|---|----------------|---|-------------|
| C | 16-pin Cerdip | F | 16-pin Flat |
| D | 16-pin Ceramic | H | Chip |
| E | 16-pin Epoxy | | |

RECOMMENDED OPERATING CONDITIONS



For maximum reliability:

DC Supply Voltage $V_{DD} - V_{SS}$ 3 to 15 Vdc


Operating Temperature T_A

C, D, F, H Device -55 to +125 °C
E Device -40 to +85 °C

LOGIC DIAGRAM



Typical P-Channel
Source Current Characteristics



Typical N-Channel
Sink Current Characteristics

ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------------|--------------------------|--|-------------------------------|------|-------|-------------------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | V _{IN} = V _{SS} or V _{DD} All valid input combinations | — | 1.0 | — | 0.005 | 1.0 | — | 30 | μAdc |
| | | | — | 2.0 | — | 0.01 | 2.0 | — | 60 | |
| | | | — | 4.0 | — | 0.02 | 4.0 | — | 120 | |
| OUTPUT LOW (SINK) CURRENT | I _{OL} | V _{OL} = 0.4V V _{OL} = 0.5V V _{OL} = 1.5V V _{IN} = V _{SS} or V _{DD} | 3.5 | — | 2.8 | 5.7 | — | 2.0 | — | mAdc |
| | | | 7.8 | — | 6.3 | 12.5 | — | 4.4 | — | |
| | | | 29 | — | 24.0 | 49 | — | 16 | — | |
| 3-STATE OUTPUT LEAKAGE CURRENT | I _{ZL} | | — | ±0.1 | — | ±10 ⁻⁴ | ±0.1 | — | ±1.0 | μAdc |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.


= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.

= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETER | | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|--|--|--------------------------|------|------|------|-------|
| PROPAGATION DELAY TIME From Data Inputs | t _{PLH} | 5 | — | 125 | 250 | ns |
| | | 10 | — | 60 | 120 | |
| | | 15 | — | 45 | 90 | |
| | t _{PHL} | 5 | — | 100 | 200 | ns |
| | | 10 | — | 50 | 100 | |
| | | 15 | — | 40 | 80 | |
| From Disable | t _{PHZ} , t _{PLZ} t _{PZH} , t _{PZL} | 5 | — | 65 | 130 | ns |
| | | 10 | — | 30 | 60 | |
| | | 15 | — | 25 | 50 | |
| OUTPUT TRANSITION TIME | t _{TLH} | 5 | — | 100 | 200 | ns |
| | | 10 | — | 50 | 100 | |
| | | 15 | — | 40 | 80 | |
| | t _{THL} | 5 | — | 60 | 120 | ns |
| | | 10 | — | 30 | 60 | |
| | | 15 | — | 20 | 40 | |

3-State AC Test Circuit and Waveforms (t_{PHZ}, t_{PZH}, t_{PLZ}, t_{PZL})

PRELIMINARY

FEATURES

- Up and down level-shifting capability
- Input Threshold Can Be Shifted for TTL Compatibility
- 3 to 18 Vdc Operation for V_{DD} and V_{CC}
- Diode Protected Inputs to V_{SS}


DESCRIPTION

The 4504B is a non-inverting hex level shifter that is designed to shift a TTL signal to CMOS logic levels for any CMOS supply voltage between 5 and 15 volts. The control input allows interface from CMOS to CMOS at one logic level to another logic level.

The V_{DD} level selects the output voltage levels and the V_{CC} level sets the input signal levels.

HEX NON-INVERTING LEVEL SHIFTER

CONNECTION DIAGRAM (all packages)



Add suffix for package:


- | | |
|------------------|---------------|
| C 16-pin Cerdip | F 16-pin Flat |
| D 16-pin Ceramic | H Chip |
| E 16-pin Epoxy | |

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | |
|-----------------------|-------------------|------------------|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 V_{dc} |
| Operating Temperature | T_A | -55 to +125 °C |
| C, D, F, H Device | | -55 to +125 °C |
| E Device | | -40 to +85 °C |

LOGIC DIAGRAM



STATIC CHARACTERISTICS

| PARAMETER | CONDITIONS | V _{SS} (Vdc) | V _{DD} (Vdc) | T _{Low} ² | | 25°C | | | T _{High} ² | | Units |
|--------------------------|-----------------|--|--------------------------|-------------------------------|------|------|------|--------|--------------------------------|------|-------|
| | | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | V _{IN} = V _{SS} or V _{DD} All valid input combinations | 0 | 5 | — | 0.05 | — | 0.0005 | 0.05 | — | 1.5 |
| | | | 0 | 10 | — | 0.1 | — | 0.001 | 0.1 | — | 3.0 |
| | | | 0 | 15 | — | 0.2 | — | 0.002 | 0.2 | — | 6.0 |
| | | | 0 | 15 | — | 0.2 | — | 0.002 | 0.2 | — | 6.0 |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under “4000B Series Family Specifications”

² T_{Low} = -55°C for C, D, F, H device.

= -40°C for E device.

T_{High} = +125°C for C, D, F, H device

= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| CHARACTERISTIC | SYMBOL | SHIFTING MODE | V _{CC} Vdc | V _{DD} Vdc | Limits | | | Units |
|-----------------------------------|-------------------------------------|--|------------------------|------------------------|--------|------|------|-------|
| | | | | | Min. | Typ. | Max. | |
| PROPAGATION DELAY, HIGH TO LOW | t _{PHL} | TTL – CMOS V _{DD} > V _{CC} | 5.0 | 10 | — | 120 | — | ns |
| | | | 5.0 | 15 | — | 120 | — | |
| | | CMOS – CMOS V _{DD} > V _{CC} | 5.0 | 10 | — | 100 | — | |
| | | | 5.0 | 15 | — | 120 | — | |
| | | | 10 | 15 | — | 50 | — | |
| | | CMOS – CMOS V _{CC} > V _{DD} | 10 | 5.0 | — | 160 | — | |
| PROPAGATION DELAY, LOW TO HIGH | t _{PHL} | TTL – CMOS V _{DD} > V _{CC} | 15 | 5.0 | — | 160 | — | ns |
| | | | 15 | 10 | — | 160 | — | |
| | | CMOS – CMOS V _{DD} > V _{CC} | 15 | 10 | — | 160 | — | |
| | | | 5.0 | 10 | — | 100 | — | |
| | | | 5.0 | 15 | — | 120 | — | |
| | | | 10 | 15 | — | 50 | — | |
| OUTPUT RISE AND FALL TIME | t _{TLH} , t _{THL} | ALL | 10 | 5.0 | — | 160 | — | ns |
| | | | 15 | 5.0 | — | 160 | — | |
| | | | 15 | 10 | — | 65 | — | |
| OUTPUT RISE AND FALL TIME | t _{TLH} , t _{THL} | ALL | — | 5.0 | — | 100 | — | ns |
| | | | — | 10 | — | 50 | — | |
| | | | — | 15 | — | 40 | — | |

CMOS DUAL 4-BIT LATCH

FEATURES


- ◆ Two Independent Four-Bit Latches
- ◆ 3-State Outputs
- ◆ Direct Reset
- ◆ All Inputs Buffered

DESCRIPTION

The 4508B consists of two identical independent 4-Bit Latches with separate Strobe (ST) and Master Reset (MR) controls. Separate Disable inputs force the outputs to a high-impedance state for bus line applications.

These devices find primary use in buffer storage, holding register, and display circuits, and other general digital logic applications.

CONNECTION DIAGRAM (all packages)



Add suffix for package:

- D 24-pin Ceramic
- E 24-pin Plastic
- H Chip

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:


| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | -55 to +125 | °C |
| D, H Device | | -40 to +85 | °C |
| E Device | | | |

TRUTH TABLE

| MR | ST | Disable | D3 | D2 | D1 | D0 | Q3 | Q2 | Q1 | Q0 |
|----|----|---------|----|----|----|----|----------------|----|----|----|
| 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 0 | 1 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 1 |
| 0 | 1 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 1 | 0 |
| 0 | 1 | 0 | 0 | 1 | 0 | 0 | 0 | 1 | 0 | 0 |
| 0 | 1 | 0 | 1 | 0 | 0 | 0 | 1 | 0 | 0 | 0 |
| 0 | 0 | 0 | X | X | X | X | Latched | | | |
| 1 | X | 0 | X | X | X | X | 0 | 0 | 0 | 0 |
| X | X | 1 | X | X | X | X | High Impedance | | | |

X = Don't Care

BLOCK DIAGRAM



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------------|--------------------------|--|-------------------------------|------|-------|-------------------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | V _{IN} = V _{SS} or V _{DD} All valid input combinations | — | 5 | — | 0.05 | 5 | — | 150 | μAdc |
| | | | — | 10 | — | 0.1 | 10 | — | 300 | |
| | | | — | 20 | — | 0.2 | 20 | — | 600 | |
| 3-STATE OUTPUT LEAKAGE CURRENT | I _{ZL} | | — | ±0.1 | — | ±10 ⁻⁴ | ±0.1 | — | ±1.0 | μAdc |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for D, H device.



= -40°C for E device.

T_{HIGH} = +125°C for D, H device.


= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETER | | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|--|--|--------------------------|------|------|------|-------|
| PROPAGATION DELAY TIME From Data Inputs | t _{PLH} , t _{PHL} | 5 | — | 220 | 440 | ns |
| | | 10 | — | 90 | 180 | |
| | | 15 | — | 60 | 120 | |
| | From Disable Input t _{PHZ} , t _{PLZ} t _{PZH} , t _{PZL} | 5 | — | 85 | 170 | ns |
| | | 10 | — | 45 | 90 | |
| | | 15 | — | 30 | 60 | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | — | 100 | 200 | ns |
| | | 10 | — | 50 | 100 | |
| | | 15 | — | 40 | 80 | |
| MINIMUM MASTER RESET PULSE WIDTH | PW _{MR} | 5 | — | 100 | 200 | ns |
| | | 10 | — | 50 | 100 | |
| | | 15 | — | 35 | 70 | |
| MINIMUM STROBE PULSE WIDTH | PW _{ST} | 5 | — | 70 | 140 | ns |
| | | 10 | — | 35 | 70 | |
| | | 15 | — | 20 | 40 | |
| MINIMUM SETUP TIME Data Inputs | t _{setup} | 5 | — | 25 | 50 | ns |
| | | 10 | — | 10 | 20 | |
| | | 15 | — | 5 | 10 | |
| MINIMUM HOLD TIME Data Inputs | t _{hold} | 5 | — | 0 | 0 | ns |
| | | 10 | — | 0 | 0 | |
| | | 15 | — | 0 | 0 | |




3-STATE AC TEST CIRCUIT AND WAVEFORMS




APPLICATIONS INFORMATION

BUS REGISTER



DUAL MULTIPLEXED BUS REGISTER WITH FUNCTION SELECT



FUNCTION SELECT

| A | B | Function |
|---|---|---------------------------------|
| 0 | 0 | Inhibit (all 0) |
| 1 | 0 | Select A Bus |
| 0 | 1 | Select B Bus |
| 1 | 1 | A _i + B _i |

FEATURES

- ◆ Internally Synchronous for High Speed
- ◆ Asynchronous Preset Enable
- ◆ Asynchronous Reset
- ◆ Logic Edge-Clocked Design
- ◆ 6MHz Counting Rate @ 10Vdc
- ◆ Carry Output for Cascading Stages

DESCRIPTION

The 4510B consists of a four-stage Up/Down Counter with provisions for "look-ahead" carry in both counting modes. The inputs consist of a single Clock, Carry-in (Clock Enable), Reset, Up/Down, Preset Enable, and four individual Jam signals. Four separate buffered Q signals and a Carry out signal are provided as outputs.

A high Preset Enable signal allows information on the Jam inputs to preset the counter to any state asynchronously with the Clock. A high on the Reset line resets all stages to the "zero" state. The counter is advanced one count at the positive transition of the Clock when the Carry-in and Preset Enable signals are low. Advancement is inhibited when the Carry-in or Preset Enable signals are high. The Carry-out signal is normally high and goes low when the counter reaches its maximum count in the Up mode or the minimum count in the Down mode, provided the Carry-in signal is low. The Carry-in signal in the low state can thus be considered a "Clock Enable." The Carry-in terminal must be connected to V_{SS} when not in use.

The counter counts Up when the Up/Down input is high, and Down when the Up/Down input is low. Multiple packages can be connected in either a parallel-clocking or a ripple-clocking arrangement. Parallel clocking provides synchronous control and hence faster response from all counting outputs. Ripple-clocking allows for longer clock input rise and fall times.

This counter finds primary use in up/down and differential counting and frequency synthesizer applications. It is also useful in A/D and D/A conversion and for magnitude and sign generation.


TRUTH TABLE

| CARRY IN | UP/DOWN | PRESET ENABLE | RESET | ACTION |
|----------|---------|---------------|-------|------------|
| 1 | X | 0 | 0 | No Count |
| 0 | 1 | 0 | 0 | Count Up |
| 0 | 0 | 0 | 0 | Count Down |
| X | X | 1 | 0 | Preset |
| X | X | X | 1 | Reset |

X = Don't Care

CMOS BCD UP/DOWN COUNTER

CONNECTION DIAGRAM
(all packages)



Add suffix for package:


- C 16-pin Cerdip
- D 16-pin Ceramic
- E 16-pin Epoxy
- F 16-pin Flat
- H Chip

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:


| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | | |
| C, D, F, H Device | | -55 to +125 | °C |
| E Device | | -40 to +85 | °C |

BLOCK DIAGRAM




V_{DD} = Pin 16
 V_{SS} = Pin 8

LOGIC DIAGRAM



TIMING DIAGRAM



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|--|-------------------------------|------|-------|------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | 5 10 15 V _{IN} = V _{SS} or V _{DD} All valid input combinations | — | 5 | — | 0.05 | 5 | — | 150 | μAdc |
| | | | — | 10 | — | 0.1 | 10 | — | 300 | |
| | | | — | 20 | — | 0.2 | 20 | — | 600 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.

= -40°C for E device.


T_{HIGH} = +125°C for C, D, F, H device.

= + 85°C for E device.


DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETER | | V _{DD} (V _{dc}) | Min. | Typ. | Max. | Units |
|--|-------------------------------------|---------------------------------------|-------------------|--------------------|-------------------|-------|
| CLOCKED OPERATION | | | | | | |
| PROPAGATION DELAY TIME Clock to Q Clock to <u>Carry Out</u> <u>Carry In</u> to <u>Carry Out</u> | t _{PLH} , t _{PHL} | 5 10 15 | — — — | 200 100 75 | 400 200 150 | ns |
| | | 5 10 15 | — — — | 210 120 90 | 420 240 180 | ns |
| | | 5 10 15 | — — — | 125 60 50 | 250 120 100 | ns |
| | | 5 10 15 | — — — | 100 50 40 | 200 100 80 | ns |
| | | 5 10 15 | — — — | 170 85 70 | 340 170 140 | ns |
| | | 5 10 15 | 2.0 4.0 5.5 | 4.0 8.0 11.0 | — — — | MHz |
| | | 5 10 15 | 15 15 15 | — — — | — — — | μs |
| | | 5 10 15 | — — — | 130 65 50 | 260 130 100 | ns |
| | | 5 10 15 | — — — | 250 100 75 | 500 200 150 | ns |
| PRESET OR RESET OPERATION | | | | | | |
| PROPAGATION DELAY TIME Preset Enable or Reset to Q Preset Enable or Reset to <u>Carry Out</u> | t _{PLH} , t _{PHL} | 5 10 15 | — — — | 210 105 90 | 420 210 180 | ns |
| | | 5 10 15 | — — — | 320 160 25 | 640 320 250 | ns |
| | | 5 10 15 | — — — | 100 50 40 | 200 100 80 | ns |
| | | 5 10 15 | — — — | 325 110 90 | 650 220 180 | ns |
| | | 5 10 15 | — — — | — — — | — — — | — |
| | | 5 10 15 | — — — | — — — | — — — | — |
| MINIMUM PRESET ENABLE OR RESET PULSE WIDTH | PW _{PE} , PW _R | 5 10 15 | — — — | 100 50 40 | 200 100 80 | ns |
| PRESET ENABLE OR RESET REMOVAL TIME | t _{rem} | 5 10 15 | — — — | 325 110 90 | 650 220 180 | ns |

¹ When units are cascaded, the maximum rise and fall times of the clock input should be equal to or less than the transition times of the data outputs driving data inputs, plus the propagation delay of the output driving stage for the output capacitive load.




Typical P-Channel
Source Current Characteristics




Typical N-Channel
Sink Current Characteristics

APPLICATIONS INFORMATION

CASCADING COUNTERS



Cascading Counter Packages.



Programmable Cascaded Frequency Divider

CMOS BCD-TO-SEVEN SEGMENT LATCH/DECODER/DRIVER

FEATURES

- ◆ High-Current Sourcing Bipolar Outputs (Up to 25 mA)
- ◆ Latched Storage of Input Code
- ◆ Blanking Input for Display Intensity Modulation
- ◆ Lamp Test Provision
- ◆ Readout Blanking for Illegal Input Combinations

DESCRIPTION

The 4511B provides the functions of a 4-bit storage latch, an 8421 BCD-to-seven segment decoder, and an output drive capability to source up to 25 mA of current. Lamp Test, Blanking, and Latch Enable inputs are used to test the display, turn off the display, and store a BCD code, respectively. It can be used with LED, incandescent, fluorescent, gas discharge, or liquid crystal readouts either directly or indirectly.

Applications include counter display drivers, seven-segment decimal display, and various clock, watch, and timer uses.


TRUTH TABLE

| LE | BI | LT | D | C | B | A | a | b | c | d | e | f | g | DISPLAY |
|----|----|----|---|---|---|---|---|---|---|---|---|---|---|---------|
| X | X | 0 | X | X | X | X | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 8 |
| X | 0 | 1 | X | X | X | X | 0 | 0 | 0 | 0 | 0 | 0 | 0 | Blank |
| 0 | 1 | 1 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 |
| 0 | 1 | 1 | 0 | 0 | 0 | 1 | 0 | 1 | 1 | 0 | 0 | 0 | 0 | 1 |
| 0 | 1 | 1 | 0 | 0 | 1 | 0 | 1 | 1 | 0 | 1 | 1 | 0 | 1 | 2 |
| 0 | 1 | 1 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 1 | 1 | 3 |
| 0 | 1 | 1 | 0 | 1 | 0 | 0 | 1 | 0 | 1 | 1 | 0 | 1 | 1 | 4 |
| 0 | 1 | 1 | 0 | 1 | 0 | 1 | 1 | 0 | 1 | 1 | 0 | 1 | 1 | 5 |
| 0 | 1 | 1 | 0 | 1 | 1 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | 6 |
| 0 | 1 | 1 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 7 |
| 0 | 1 | 1 | 1 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 8 |
| 0 | 1 | 1 | 1 | 0 | 0 | 1 | 1 | 1 | 1 | 0 | 0 | 1 | 1 | 9 |
| 0 | 1 | 1 | 1 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | Blank |
| 0 | 1 | 1 | 1 | 0 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | Blank |
| 0 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | Blank |
| 0 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | Blank |
| 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | Blank |
| 1 | 1 | 1 | X | X | X | X | * | * | * | * | * | * | * | * |


X = Don't care

* Depends upon the BCD code applied during the 0 to 1 transition of LE.

BLOCK DIAGRAM



CONNECTION DIAGRAM (all packages)



Add suffix for package:

- C 16-pin Cerdip
- D 16-pin Ceramic
- E 16-pin Epoxy
- F 16-pin Flat
- H Chip

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

DC Supply Voltage $V_{DD} - V_{SS}$ 3 to 15 Vdc


Operating Temperature T_A

C, D, F, H Device

-55 to +125 °C

E Device

-40 to +85 °C



The maximum continuous (worst case) derated output drive current applies to a single output with all other outputs sourcing an equal amount of current. Operation above the derating curve at a given temperature is not recommended.

ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | + 25°C | | | T _{HIGH} ² | | Units |
|------------------------------|--------------------------|---|-------------------------------|------|--------|-------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | V _{IN} = V _{SS} or V _{DD} All valid input combinations | — | 5 | — | 0.05 | 5 | — | 150 | μAdc |
| | | | — | 10 | — | 0.1 | 10 | — | 300 | |
| | | | — | 20 | — | 0.2 | 20 | — | 600 | |
| OUTPUT DRIVE VOLTAGE | V _{OUT} | I _{OH} = 0 mAdc — 5 — 10 — 15 — 20 — 25 | 4.99 | — | 4.99 | 5.0 | — | 4.95 | — | Vdc |
| | | | — | — | — | 4.25 | — | — | — | |
| | | | — | — | 3.9 | 4.13 | — | — | — | |
| | | | — | — | — | 3.95 | — | — | — | |
| | | | — | — | 3.4 | 3.75 | — | — | — | |
| | | | — | — | — | 3.5 | — | — | — | |
| | 10 | I _{OH} = 0 mAdc — 5 — 10 — 15 — 20 — 25 | 9.99 | — | 9.99 | 10 | — | 9.95 | — | Vdc |
| | | | — | — | — | 9.25 | — | — | — | |
| | | | — | — | 9.0 | 9.15 | — | — | — | |
| | | | — | — | — | 9.03 | — | — | — | |
| | | | — | — | 8.6 | 8.90 | — | — | — | |
| | | | — | — | — | 8.75 | — | — | — | |
| | 15 | I _{OH} = 0 mAdc — 5 — 10 — 15 — 20 — 25 | 14.99 | — | 14.99 | 15 | — | 14.96 | — | Vdc |
| | | | — | — | — | 14.25 | — | — | — | |
| | | | — | — | 14.0 | 14.18 | — | — | — | |
| | | | — | — | — | 14.08 | — | — | — | |
| | | | — | — | 13.6 | 13.95 | — | — | — | |
| | | | — | — | — | 13.80 | — | — | — | |
| OUTPUT LOW (SINK) CURRENT | I _{OL} | V _{OL} = 0.4V | 1.9 | — | 1.5 | 3.4 | — | 1.1 | — | mAdc |
| | | V _{OL} = 0.5V | 5.0 | — | 4.0 | 6.5 | — | 2.8 | — | |
| | | V _{OL} = 1.5V | 13.8 | — | 11.0 | 24 | — | 7.7 | — | |
| | | V _{IN} = V _{SS} or V _{DD} | — | — | — | — | — | — | — | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".² T_{LOW} = -55°C for C, D, F, H device.

= -40°C for E device.


T_{HIGH} = +125°C for C, D, F, H device.

= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)






| PARAMETER | | V _{DD} (Vdc) | Min. | Typ. | Max. | Units | |
|--|----------------------|--------------------------|------|------|------|-------|----|
| PROPAGATION DELAY TIME From Data Inputs | t _{PLH} | 5 | — | 520 | 1040 | ns | |
| | | 10 | — | 210 | 420 | | |
| | | 15 | — | 150 | 300 | | |
| | t _{PHL} | 5 | — | 660 | 1320 | ns | |
| | | 10 | — | 260 | 520 | | |
| | | 15 | — | 180 | 360 | | |
| | From Blanking Input | t _{PLH} | 5 | — | 300 | 600 | ns |
| | | | 10 | — | 125 | 250 | |
| | | | 15 | — | 100 | 200 | |
| | From Lamp Test Input | t _{PHL} | 5 | — | 500 | 1000 | ns |
| | | | 10 | — | 200 | 400 | |
| | | | 15 | — | 160 | 320 | |
| t _{PLH} | | 5 | — | 300 | 600 | ns | |
| | | 10 | — | 120 | 240 | | |
| | | 15 | — | 90 | 180 | | |
| t _{PHL} | 5 | — | 325 | 650 | ns | | |
| | 10 | — | 130 | 260 | | | |
| | 15 | — | 95 | 190 | | | |
| OUTPUT TRANSITION TIME | t _{PLH} | 5 | — | 170 | 250 | ns | |
| | | 10 | — | 120 | 200 | | |
| | | 15 | — | 100 | 180 | | |
| | t _{PHL} | 5 | — | 400 | 900 | ns | |
| | | 10 | — | 225 | 450 | | |
| | | 15 | — | 200 | 400 | | |
| MINIMUM DATA INPUT SETUP TIME | t _{setup} | 5 | — | 90 | 180 | ns | |
| | | 10 | — | 40 | 80 | | |
| | | 15 | — | 20 | 40 | | |
| MINIMUM DATA INPUT HOLD TIME | t _{hold} | 5 | — | -90 | 0 | ns | |
| | | 10 | — | -40 | 0 | | |
| | | 15 | — | -20 | 0 | | |
| MINIMUM LATCH ENABLE PULSE WIDTH | PW _{LE} | 5 | — | 260 | 520 | ns | |
| | | 10 | — | 110 | 220 | | |
| | | 15 | — | 85 | 130 | | |

LOGIC DIAGRAM



APPLICATIONS INFORMATION

DISPLAY CONNECTIONS



**A filament pre-warm resistor is recommended to reduce filament thermal shock and increase the effective cold resistance of the filament.

CMOS 8-CHANNEL DATA SELECTOR

FEATURES

- ◆ 3-State Output with Disable Control
- ◆ Separate Inhibit Input
- ◆ Selects One of Eight Data Sources
- ◆ Performs Parallel-To-Serial Conversion

DESCRIPTION


The 4512B is an 8-Channel Data Selector with Function Inhibit and Output Disable controls. One of eight binary inputs is selected by Select inputs A, B, and C, and is routed to the output Z. A high on the Disable input causes the Z output to assume a high-impedance state, regardless of other input conditions. This allows the output to interface directly with bus-oriented systems. When the Inhibit input is high, it forces the output low, providing the Disable input is low. By manipulation of the inputs, the 4512B can provide any logic functions of four variables (see Applications Information).

TRUTH TABLE

| C | B | A | INHIBIT | DISABLE | Z |
|---|---|---|---------|---------|----------------|
| 0 | 0 | 0 | 0 | 0 | X0 |
| 0 | 0 | 1 | 0 | 0 | X1 |
| 0 | 1 | 0 | 0 | 0 | X2 |
| 0 | 1 | 1 | 0 | 0 | X3 |
| 1 | 0 | 0 | 0 | 0 | X4 |
| 1 | 0 | 1 | 0 | 0 | X5 |
| 1 | 1 | 0 | 0 | 0 | X6 |
| 1 | 1 | 1 | 0 | 0 | X7 |
| φ | φ | φ | 1 | 0 | 0 |
| φ | φ | φ | φ | 1 | High Impedance |

φ = Don't Care

CONNECTION DIAGRAM
(all packages)



Add suffix for package:


- C 16-pin Cerdip
- D 16-pin Ceramic
- E 16-pin Epoxy
- F 16-pin Flat
- H Chip

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | -55 to +125 | °C |
| C, D, F, H Device | | -40 to +85 | °C |
| E Device | | | |

BLOCK DIAGRAM



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------------|--------------------------|--|-------------------------------|------|-------|-------------------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | V _{IN} = V _{SS} or V _{DD} All valid input combinations | — | 5 | — | 0.05 | 5 | — | 150 | μAdc |
| | | | — | 10 | — | 0.1 | 10 | — | 300 | |
| | | | — | 20 | — | 0.2 | 20 | — | 600 | |
| | | | — | — | — | — | — | — | — | |
| 3-STATE OUTPUT LEAKAGE CURRENT | I _{OL} | | — | ±0.1 | — | ±10 ⁻⁴ | ±0.1 | — | ±1.0 | μAdc |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.



= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.



= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETER | | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|--|-------------------------------------|-------------------------------------|------|------|------|-------|
| PROPAGATION DELAY TIME From Inhibit | t _{PLH} , t _{PHL} | 5 | — | 120 | 240 | ns |
| | | 10 | — | 55 | 110 | |
| | | 15 | — | 40 | 80 | |
| | | — | — | — | — | |
| | From Select Input | 5 | — | 225 | 450 | ns |
| | | 10 | — | 100 | 200 | |
| | | 15 | — | 75 | 150 | |
| | | — | — | — | — | |
| | From Data Input | 5 | — | 200 | 400 | ns |
| | | 10 | — | 80 | 160 | |
| | | 15 | — | 60 | 120 | |
| | | — | — | — | — | |
| | From Disable | t _{PHZ} , t _{PZH} | — | — | — | ns |
| | | t _{PLZ} , t _{PZL} | — | — | — | |
| | | 5 | — | 60 | 120 | |
| | | 10 | — | 30 | 60 | |
| | | 15 | — | 25 | 50 | |
| | | — | — | — | — | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | — | 100 | 200 | ns |
| | | 10 | — | 50 | 100 | |
| | | 15 | — | 40 | 80 | |
| | | — | — | — | — | |



LOGIC DIAGRAM




APPLICATIONS INFORMATION

32-INPUT MULTIPLEXER

Output terminals of several 4512B devices can be connected to a single data bus. One 4512B is selected by the 3-state Disable control, and the remaining devices are disabled into

a high-impedance state. A 32-input multiplexer utilizing four 4512B data selectors and a single 4011B is shown.



LOGIC FUNCTION GENERATORS

In addition to the standard application of multiplexers in data conversion techniques, these circuits can also be used in generating logic functions, which in many cases can reduce system package count.

A multiplexer is a multiple-position single-pole switch. One set of inputs selects the position of the switch. The second set of inputs collects the input data, which is transferred through the circuit to one output. By using the binary select inputs and the data inputs, the 4512B can generate any of the 65,536 different functions of four variables.


Assume the four binary inputs are A, B, C, and D, and that Z is the desired function. Using the

select inputs as the first three variables, any combination of A, B, and C will select a data input (assuming the output is enabled). For each combination of A, B, and C, the required output, as a function of the fourth variable D, can be HIGH or LOW or the same as D or the inverse of D. Therefore, the truth table may be examined and each data input of the 4512B is connected to V_{DD} , V_{SS} , D, or \bar{D} as required. In such fashion, the function is generated.

In the example shown, the first two outputs are the inverse of D, so X0 is connected to \bar{D} . The next two are HIGH, so X1 is connected to V_{DD} , etc.

| INPUT VARIABLES | | | | REQUIRED FUNCTION |
|-----------------|---|---|---|-------------------|
| A | B | C | D | Z |
| L | L | L | L | H |
| L | L | L | H | L |
| L | L | H | L | H |
| L | L | H | H | H |
| L | H | L | L | L |
| L | H | L | H | H |
| L | H | H | L | L |
| L | H | H | H | L |
| H | L | L | L | L |
| . | . | . | . | . |
| . | . | . | . | . |

H = HIGH Level
L = LOW Level



CMOS 4-TO-16 LINE DECODERS WITH LATCH

FEATURES

- ◆ Strobed Input Latch
- ◆ Inhibit Control
- ◆ Selected Output Active High (4514B) or Active Low (4515B)

DESCRIPTION

The 4514B and 4515B are two output options of a 4-to-16 Line Decoder with Latched Inputs. The 4514B presents a logic "1" at the selected output, and the 4515B presents a logic "0" at the selected output. The latches hold the last input data presented prior to the Strobe transition from "1" to "0". Inhibit allows all outputs to be placed at "0" (4514B), or "1" (4515B), regardless of the state of the Data or Strobe inputs.


Applications include code conversion, address decoding, memory selection control, demultiplexing, and readout decoding.

TRUTH TABLE (Strobe = 1)

| Inhibit | Data Inputs | | | | Selected Output 4514B = Logic "1" 4515B = Logic "0" |
|---------|-------------|---|---|---|--|
| | D | C | B | A | |
| 0 | 0 | 0 | 0 | 0 | S0 |
| 0 | 0 | 0 | 0 | 1 | S1 |
| 0 | 0 | 0 | 1 | 0 | S2 |
| 0 | 0 | 0 | 1 | 1 | S3 |
| 0 | 0 | 1 | 0 | 0 | S4 |
| 0 | 0 | 1 | 0 | 1 | S5 |
| 0 | 0 | 1 | 1 | 0 | S6 |
| 0 | 0 | 1 | 1 | 1 | S7 |
| 0 | 1 | 0 | 0 | 0 | S8 |
| 0 | 1 | 0 | 0 | 1 | S9 |
| 0 | 1 | 0 | 1 | 0 | S10 |
| 0 | 1 | 0 | 1 | 1 | S11 |
| 0 | 1 | 1 | 0 | 0 | S12 |
| 0 | 1 | 1 | 0 | 1 | S13 |
| 0 | 1 | 1 | 1 | 0 | S14 |
| 0 | 1 | 1 | 1 | 1 | S15 |
| 1 | X | X | X | X | All Outputs = "0", 4514B All Outputs = "1", 4515B |

X = Don't Care

**CONNECTION DIAGRAM
(all packages)**



Add suffix for package:


- D 24-pin Ceramic
- E 24-pin Epoxy
- H Chip

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | -55 to +125 | °C |
| D, H Device | | -40 to +85 | °C |
| E Device | | | |

BLOCK DIAGRAM



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------------------|--------------------------|---|-------------------------------|------|-------|------|------|--------------------------------|------|--------------------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT I_{DD} | 5 | $V_{IN} = V_{SS}$ or V_{DD} All valid input combinations | — | 5 | — | 0.05 | 5 | — | 150 | μA_{dc} |
| | 10 | | — | 10 | — | 0.1 | 10 | — | 300 | |
| | 15 | | — | 20 | — | 0.2 | 20 | — | 600 | |
| | | | | | | | | | | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.



= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.


= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETER | | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|--|--------------------|--------------------------|------|------|------|-------|
| PROPAGATION DELAY TIME From Data Inputs | t_{PLH}, t_{PHL} | 5 | — | 485 | 970 | ns |
| | | 10 | — | 185 | 370 | |
| | | 15 | — | 135 | 270 | |
| | | 5 | — | 250 | 500 | ns |
| | | 10 | — | 110 | 220 | |
| | | 15 | — | 85 | 170 | |
| From Inhibit Input | | 5 | — | 250 | 500 | ns |
| | | 10 | — | 110 | 220 | |
| | | 15 | — | 85 | 170 | |
| | | | | | | |
| OUTPUT TRANSITION TIME | t_{TLH}, t_{THL} | 5 | — | 100 | 200 | ns |
| | | 10 | — | 50 | 100 | |
| | | 15 | — | 40 | 80 | |
| | | | | | | |
| MINIMUM DATA INPUT SETUP TIME | t_{setup} | 5 | — | 75 | 150 | ns |
| | | 10 | — | 35 | 70 | |
| | | 15 | — | 20 | 40 | |
| | | | | | | |
| MINIMUM STROBE PULSE WIDTH | PW _{ST} | 5 | — | 125 | 250 | ns |
| | | 10 | — | 50 | 100 | |
| | | 15 | — | 40 | 75 | |
| | | | | | | |



LOGIC DIAGRAM



CMOS BINARY UP/DOWN COUNTER

FEATURES

- ◆ Internally Synchronous for High Speed
- ◆ Asynchronous Preset Enable
- ◆ Asynchronous Reset
- ◆ Logic Edge-Clocked Design
- ◆ 6MHz Counting Rate @ 10Vdc
- ◆ Carry Output for Cascading Stages

DESCRIPTION

The 4516B consists of a four-stage Up/Down Counter with provisions for "look-ahead" carry in both counting modes. The inputs consist of a single Clock, Carry-in (Clock Enable), Reset, Up/Down, Preset Enable, and four individual Jam signals. Four separate buffered Q signals and a Carry-out signal are provided as outputs.

A high Preset Enable signal allows information on the Jam inputs to preset the counter to any state asynchronously with the Clock. A high on the Reset line resets all stages to the "zero" state. The counter is advanced one count at the positive transition of the Clock when the Carry-in and Preset Enable signals are low. Advancement is inhibited when the Carry-in or Preset Enable signals are high. The Carry-out signal is normally high and goes low when the counter reaches its maximum count in the Up mode or the minimum count in the Down mode, provided the Carry-in signal is low. The Carry-in signal in the low state can thus be considered a "Clock Enable." The Carry-in terminal must be connected to V_{SS} when not in use.

The counter counts Up when the Up/Down input is high, and Down when the Up/Down input is low. Multiple packages can be connected in either a parallel-clocking or a ripple-clocking arrangement. Parallel clocking provides synchronous control and hence faster response from all counting outputs. Ripple-clocking allows for longer clock input rise and fall times.


This counter finds primary use in up/down and differential counting and frequency synthesizer applications. It is also useful in A/D and D/A conversion and for magnitude and sign generation.

TRUTH TABLE

| CARRY IN | UP/DOWN | PRESET ENABLE | RESET | ACTION |
|----------|---------|---------------|-------|------------|
| 1 | X | 0 | 0 | No Count |
| 0 | 1 | 0 | 0 | Count Up |
| 0 | 0 | 0 | 0 | Count Down |
| X | X | 1 | 0 | Preset |
| X | X | X | 1 | Reset |

X = Don't Care

CONNECTION DIAGRAM (all packages)



Add suffix for package:


- C 16-pin Cerdip
- D 16-pin Ceramic
- E 16-pin Epoxy
- F 16-pin Flat
- H Chip

RECOMMENDED OPERATING CONDITIONS


For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | | |
| C, D, F, H Device | | -55 to +125 | °C |
| E Device | | -40 to +85 | °C |


BLOCK DIAGRAM



LOGIC DIAGRAM



TIMING DIAGRAM



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--|--------------------------|--|-------------------------------|------|-------|------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT I _{DD} | 5 | V _{IN} = V _{SS} or V _{DD} | — | 5 | — | 0.05 | 5 | — | 150 | μAdc |
| | 10 | All valid input combinations | — | 10 | — | 0.1 | 10 | — | 300 | |
| | 15 | | — | 20 | — | 0.2 | 20 | — | 600 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.

= -40°C for E device.


T_{HIGH} = +125°C for C, D, F, H device.

= + 85°C for E device.


DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETER | | V _{DD} (V _{dc}) | Min. | Typ. | Max. | Units | | |
|---|------------------------------------|--|--------------------|------|------|-------|-----|----|
| CLOCKED OPERATION | | | | | | | | |
| PROPAGATION DELAY TIME Clock to Q Clock to $\overline{\text{Carry Out}}$ $\overline{\text{Carry In}}$ to $\overline{\text{Carry Out}}$ | t_{PLH}, t_{PHL} | 5 | — | 200 | 400 | ns | | |
| | | 10 | — | 100 | 200 | | | |
| | | 15 | — | 75 | 150 | | | |
| | | 5 | — | 210 | 420 | ns | | |
| | | 10 | — | 120 | 240 | | | |
| | | 15 | — | 90 | 180 | | | |
| | | 5 | — | 125 | 250 | ns | | |
| | | 10 | — | 60 | 120 | | | |
| | | 15 | — | 50 | 100 | | | |
| OUTPUT TRANSITION TIME | t_{TLH}, t_{THL} | 5 | — | 100 | 200 | ns | | |
| 10 | — | 50 | 100 | | | | | |
| 15 | — | 40 | 80 | | | | | |
| MINIMUM CLOCK PULSE WIDTH | PW _{CL} | 5 | — | 170 | 340 | ns | | |
| 10 | — | 85 | 170 | | | | | |
| 15 | — | 70 | 140 | | | | | |
| MAXIMUM CLOCK FREQUENCY | f _{CL} | 5 | 2.0 | 4.0 | — | MHz | | |
| 10 | 4.0 | 8.0 | — | | | | | |
| 15 | 5.5 | 11.0 | — | | | | | |
| MAXIMUM CLOCK RISE AND FALL TIME ¹ | t_{rCL}, t_{fCL} | 5 | 15 | — | — | μs | | |
| 10 | 15 | — | — | | | | | |
| 15 | 15 | — | — | | | | | |
| MINIMUM SETUP TIME Carry In Up/Down | t _{setup} | 5 | — | 130 | 260 | ns | | |
| | | 10 | — | 65 | 130 | | | |
| | | 15 | — | 50 | 100 | | | |
| | | 5 | — | 250 | 500 | ns | | |
| | | 10 | — | 100 | 200 | | | |
| | | 15 | — | 75 | 150 | | | |
| | | PRESET OR RESET OPERATION | | | | | | |
| | | PROPAGATION DELAY TIME Preset Enable or Reset to Q Preset Enable or Reset to $\overline{\text{Carry Out}}$ | t_{PLH}, t_{PHL} | 5 | — | 210 | 420 | ns |
| | | | | 10 | — | 105 | 210 | |
| 15 | — | | | 90 | 180 | | | |
| 5 | — | | | 320 | 640 | ns | | |
| 10 | — | | | 160 | 320 | | | |
| 15 | — | | | 125 | 250 | | | |
| MINIMUM PRESET ENABLE OR RESET PULSE WIDTH | PW _{PE} , PW _R | | | 5 | — | 100 | 200 | ns |
| 10 | — | | | 50 | 100 | | | |
| 15 | — | | | 40 | 80 | | | |
| PRESET ENABLE OR RESET REMOVAL TIME | t _{rem} | 5 | — | 325 | 650 | ns | | |
| 10 | — | 110 | 220 | | | | | |
| 15 | — | 90 | 180 | | | | | |

¹ When units are cascaded, the maximum rise and fall times of the clock input should be equal to or less than the transition times of the data outputs driving data inputs, plus the propagation delay of the output driving stage for the output capacitive load.




Typical P-Channel
Source Current Characteristics




Typical N-Channel
Sink Current Characteristics

APPLICATIONS INFORMATION

CASCADING COUNTERS



Cascading counter packages.



Programmable Cascaded Frequency Divider


CMOS 64-BIT DUAL SHIFT REGISTER

FEATURES

- Independent Clock, Write Enable Inputs
- Static Operation
- Positive Edge-Clocked Design
- 6.7MHz Toggle Rate @ 10 VDC
- Tri-State Output at 64th Bit
- Balanced Output Drive Current Specifications

DESCRIPTION

The SCL4517B dual 64-bit static shift register consists of two identical, independent, 64-bit registers. Each register has separate clock and write enable inputs, as well as outputs at bits 16, 32, 48, and 64. Data at the data input is entered by clocking, regardless of the state of the write enable input. An output is disabled (open circuited) when the write enable input is high. During this time, data appearing at the data input as well as the 16-bit, 32-bit, and 48-bit taps may be entered into the device by application of a clock pulse. This feature permits the register to be loaded with 64 bits in 16 clock periods, and also permits bus logic to be used. This device is useful in time delay circuits, temporary memory storage circuits, and other serial shift register applications.



FUNCTIONAL TRUTH TABLE

| WRITE CLOCK | ENABLE | DATA | 16-BIT TAP | 32-BIT TAP | 48-BIT TAP | 64-BIT TAP |
|----------------|--------|---------------------------|---------------------------------|---------------------------------|---------------------------------|-----------------------------|
| 0 | 0 | X | Content of 16-Bit Displayed | Content of 32-Bit Displayed | Content of 48-Bit Displayed | Content of 64-Bit Displayed |
| 0 | 1 | X | High Impedance | High Impedance | High Impedance | High Impedance |
| 1 | 0 | X | Content of 16-Bit Displayed | Content of 32-Bit Displayed | Content of 48-Bit Displayed | Content of 64-Bit Displayed |
| 1 | 1 | X | High Impedance | High Impedance | High Impedance | High Impedance |
| | 0 | Data entered into 1st Bit | Content of 16-Bit Displayed | Content of 32-Bit Displayed | Content of 48-Bit Displayed | Content of 64-Bit Displayed |
| | 1 | Data entered into 1st Bit | Data at tap entered into 17-Bit | Data at tap entered into 32-Bit | Data at tap entered into 48-Bit | High Impedance |
| | 0 | X | Content of 16-Bit Displayed | Content of 32-Bit Displayed | Content of 48-Bit Displayed | Content of 64-Bit Displayed |
| | 1 | X | High Impedance | High Impedance | High Impedance | High Impedance |

X = Don't Care

ELECTRICAL CHARACTERISTICS

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------------|-----------|-------------------|----------|
| DC Supply Voltage | V_{DD} | + 15 to - 0.5 | V_{dc} |
| Input Voltage, all inputs | V_{IN} | V_{DD} to - 0.5 | V_{dc} |
| DC Current Drain per Pin | 1 | 10 | mAdc |
| Operating Temperature Range | T_A | | |
| C, D, F, H Device | | - 55 to + 125 | °C |
| E Device | | - 40 to + 85 | °C |
| Storage Temperature Range | T_{STG} | - 65 to + 150 | °C |

STATIC CHARACTERISTICS¹

| PARAMETER | | V_{DD} (Vdc) | CONDITIONS | T_{LOW}^2 | | + 25°C | | | T_{HIGH}^2 | | Units |
|--------------------------|----------|-------------------|---|-------------|------|--------|--------|------|--------------|------|-----------|
| | | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I_{DD} | 5 | $V_{IN} = V_{SS}$ or V_{DD} All valid input combinations | — | 0.05 | — | 0.0005 | 0.05 | — | 1.5 | μ Adc |
| | | 10 | | — | 0.10 | — | 0.001 | 0.10 | — | 3.0 | |
| | | 15 | | — | 0.20 | — | 0.002 | 0.20 | — | 6.0 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".² T_{LOW} = - 55°C for C, D, F, H device.
= - 40°C for E device. T_{HIGH} = + 125°C for C, D, F, H device.
= + 85°C for E device.SWITCHING CHARACTERISTICS* ($T_A = 25^\circ\text{C}$)

| CHARACTERISTIC | SYMBOL | V_{DD} | Min. | Typ. All Types | Max. | Unit |
|---|-------------|----------|------|-------------------|----------|------|
| Output Transition Time ($C_L = 15\text{pF}$) | t_r | 5.0 | — | 100 | 200 | ns |
| | t_{TLH} | 10 | — | 50 | 100 | |
| | t_{THL} | 15 | — | 40 | 80 | |
| Propagation Delay Time ($C_L = 15\text{pF}$) | t_{PLH} | 5.0 | — | 200 | 400 | ns |
| | t_{PHL} | 10 | — | 110 | 220 | |
| | | 15 | — | 90 | 180 | |
| Minimum Clock Pulse Width | PW_C | 5.0 | — | 170 | 250 | ns |
| | | 10 | — | 75 | 100 | |
| | | 15 | — | 60 | 75 | |
| Maximum Clock Pulse Frequency | PRF | 5.0 | 2.0 | 3.0 | — | MHz |
| | | 10 | 5.0 | 6.7 | — | |
| | | 15 | 6.7 | 8.3 | — | |
| Maximum Clock Pulse Rise and Fall Time | t_r, t_f | 5.0 | — | — | No Limit | — |
| | | 10 | — | — | ** | |
| | | 15 | — | — | | |
| Data to Clock Setup Time | t_{setup} | 5.0 | — | - 40 | - 10 | ns |
| | | 10 | — | - 15 | 0 | |
| | | 15 | — | 0 | 5 | |
| Data to Clock Hold Time | t_{hold} | 5.0 | — | 75 | 120 | ns |
| | | 10 | — | 25 | 50 | |
| | | 15 | — | 10 | 25 | |
| Write Enable to Clock Setup Time | t_{setup} | 5.0 | — | 170 | 300 | ns |
| | | 10 | — | 65 | 130 | |
| | | 15 | — | 50 | 80 | |
| Write Enable to Clock Release Time | t_{rel} | 5.0 | — | 160 | 280 | ns |
| | | 10 | — | 55 | 120 | |
| | | 15 | — | 40 | 70 | |

*The formula given is for the typical characteristics only.

**When shift register sections are cascaded, the maximum rise and fall time of the clock input should be equal to or less than the rise and fall time of the data outputs, driving data inputs, plus the propagation of the output driving stage for the output capacitance load.

AC TEST WAVEFORMS






FIGURE 1 - POWER DISSIPATION TEST CIRCUIT AND WAVEFORM

EXPANDED BLOCK DIAGRAM
(1/2 OF DEVICE SHOWN)

CMOS DUAL UP COUNTERS

FEATURES

- ◆ Two Independent 4-Bit Counters
- ◆ Internally Synchronous for High Speed
- ◆ Dual BCD (4518B) and Dual Binary (4520B) Configurations
- ◆ Direct Reset
- ◆ Logic Edge-Clocked Design
- ◆ Trigger from either Edge of Clock Signal
- ◆ Static Operation— DC to 5MHz @ 10Vdc

DESCRIPTION


The 4518B Dual BCD Counter and the 4520B Dual Binary Counter are constructed with MOS P-channel and N-channel enhancement-mode devices in a single monolithic structure. Each consists of two identical, independent, internally synchronous 4-stage counters. The counter stages are type-D flip-flops, with interchangeable Clock and Enable lines for incrementing on either the positive-going or negative-going transition as required when cascading multiple stages. Each counter can be cleared by applying a high level on the Reset line. In addition, the 4518B will count out of all undefined states within two clock periods. These complementary MOS up counters find primary use in multi-stage synchronous or ripple counting applications requiring low power dissipation and/or high noise immunity.

TRUTH TABLE


| CLOCK | ENABLE | RESET | ACTION |
|-------|--------|-------|-------------------|
| | 1 | 0 | Increment Counter |
| 0 | | 0 | Increment Counter |
| | X | 0 | No Change |
| X | | 0 | No Change |
| | 0 | 0 | No Change |
| 1 | | 0 | No Change |
| X | X | 1 | Q0 thru Q3 = 0 |

X = Don't Care

TIMING DIAGRAM



CONNECTION DIAGRAM (all packages)



Add suffix for package:


- C 16-pin Cerdip
- D 16-pin Ceramic
- E 16-pin Epoxy
- F 16-pin Flat
- H Chip

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | -55 to +125 | °C |
| C, D, F, H Device | | -40 to +85 | °C |
| E Device | | | |

BLOCK DIAGRAM



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|--|-------------------------------|------|-------|------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | V _{IN} = V _{SS} or V _{DD} All valid input combinations | — | 5 | — | 0.05 | 5 | — | 150 | μAdc |
| | | | — | 10 | — | 0.1 | 10 | — | 300 | |
| | | | — | 20 | — | 0.2 | 20 | — | 600 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.

= -40°C for E device.


T_{HIGH} = +125°C for C, D, F, H device.

= +85°C for E device.


DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETER | | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|--|-------------------------------------|--------------------------|-------------------|-------------------|-------------------|-------|
| CLOCKED OPERATION | | | | | | |
| PROPAGATION DELAY TIME From Clock or Clock Enable | t _{PLH} , t _{PHL} | 5 10 15 | — — — | 225 100 80 | 450 200 160 | ns |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 10 15 | — — — | 100 50 40 | 200 100 80 | ns |
| MINIMUM CLOCK PULSE WIDTH | PW _{CL} | 5 10 15 | — — — | 100 50 35 | 200 100 70 | ns |
| MINIMUM CLOCK ENABLE PULSE WIDTH | PW _{CE} | 5 10 15 | — — — | 200 100 70 | 400 200 140 | ns |
| MAXIMUM CLOCK FREQUENCY | f _{CL} | 5 10 15 | 1.5 3.0 4.0 | 3.0 6.0 8.0 | — — — | MHz |
| MAXIMUM CLOCK OR CLOCK ENABLE RISE & FALL TIME ¹ | t _{rCL} , t _{fCL} | 5 10 15 | 15 5 5 | — — — | — — — | μs |
| RESET OPERATION | | | | | | |
| PROPAGATION DELAY TIME | t _{PHL} | 5 10 15 | — — — | 225 100 80 | 450 200 160 | ns |
| MINIMUM RESET PULSE WIDTH | PW _R | 5 10 15 | — — — | 120 50 40 | 240 100 80 | ns |
| RESET REMOVAL TIME | t _{rem} | 5 10 15 | — — — | 100 50 40 | 200 100 80 | ns |

¹ When units are cascaded, the maximum rise and fall times of the clock input should be equal to or less than the transition times of the data outputs driving data inputs, plus the propagation delay of the output driving stage for the output capacitive load.




Typical P-Channel
Source Current Characteristics




Typical N-Channel
Sink Current Characteristics


LOGIC DIAGRAMS



APPLICATIONS INFORMATION



Ripple cascading of four counters with positive-edge triggering.



Synchronous cascading of four binary counters with negative-edge triggering.

CMOS PROGRAMMABLE DOWN COUNTERS

FEATURES

- ◆ Internally Synchronous for High Speed
- ◆ BCD Decade (4522B) or 4-Bit Binary (4526B) Down Counters
- ◆ Asynchronous Preset Enable
- ◆ Asynchronous Reset
- ◆ Cascadable
- ◆ Logic Edge-Clocked Design
- ◆ Static Operation – DC to 5MHz @ 10Vdc
- ◆ Trigger from Either Edge of Clock Input


DESCRIPTION

The 4522B BCD Counter and the 4526B Binary Counter are constructed with MOS P-channel and N-channel enhancement-mode devices in a single monolithic structure.

These devices are programmable, cascadable down counters with a decoded "0" state output for divide-by-N applications. In single stage applications the "0" output is applied to the Preset Enable input. The Cascade Feedback input allows cascade divide-by-N operation with no additional gates required. The Master Reset function provides synchronous initiation of divide-by-N cycles. The Clock Inhibit input allows disabling of the pulse counting function.

These complementary MOS counters can be used in frequency synthesizers, phase-locked loops, and other frequency division applications requiring low power dissipation and/or high noise immunity.

CONNECTION DIAGRAM (all packages)



Add suffix for package:

- C 16-pin Cerdip
- D 16-pin Ceramic
- E 16-pin Epoxy
- F 16-pin Flat
- H Chip

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | -55 to +125 | °C |
| C, D, F, H Device | | -40 to +85 | °C |
| E Device | | | |

TRUTH TABLES

Both Types

| Clock | Inhibit | Preset Enable | Master Reset | Action |
|-------|---------|---------------|--------------|----------|
| 0 | 0 | 0 | 0 | No Count |
| 1 | 0 | 0 | 0 | Count 1 |
| 0 | 1 | 0 | 0 | No Count |
| 1 | 1 | 0 | 0 | Count 1 |
| 0 | X | 1 | 0 | Preset |
| 1 | X | 1 | 1 | Reset |


4522B

| Count | Output | | | |
|-------|--------|----|----|----|
| | Q4 | Q3 | Q2 | Q1 |
| 9 | 1 | 0 | 0 | 1 |
| 8 | 1 | 0 | 0 | 0 |
| 7 | 0 | 1 | 1 | 1 |
| 6 | 0 | 1 | 1 | 0 |
| 5 | 0 | 1 | 0 | 1 |
| 4 | 0 | 1 | 0 | 0 |
| 3 | 0 | 0 | 1 | 1 |
| 2 | 0 | 0 | 1 | 0 |
| 1 | 0 | 0 | 0 | 1 |
| 0 | 0 | 0 | 0 | 0 |

4526B

| Count | Output | | | |
|-------|--------|----|----|----|
| | Q4 | Q3 | Q2 | Q1 |
| 15 | 1 | 1 | 1 | 1 |
| 14 | 1 | 1 | 1 | 0 |
| 13 | 1 | 1 | 0 | 1 |
| 12 | 1 | 1 | 0 | 0 |
| 11 | 1 | 0 | 1 | 1 |
| 10 | 1 | 0 | 1 | 0 |
| 9 | 1 | 0 | 0 | 1 |
| 8 | 1 | 0 | 0 | 0 |
| 7 | 0 | 1 | 1 | 1 |
| 6 | 0 | 1 | 1 | 0 |
| 5 | 0 | 1 | 0 | 1 |
| 4 | 0 | 1 | 0 | 0 |
| 3 | 0 | 0 | 1 | 1 |
| 2 | 0 | 0 | 1 | 0 |
| 1 | 0 | 0 | 0 | 1 |
| 0 | 0 | 0 | 0 | 0 |

BLOCK DIAGRAM



V_{DD} = Pin 16
 V_{SS} = Pin 8

ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (V _{dc}) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|---------------------------------------|--|-------------------------------|------|-------|------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | V _{IN} = V _{SS} or V _{DD} All valid input combinations | — | 5 | — | 0.05 | 5 | — | 150 | μAdc |
| | | | — | 10 | — | 0.1 | 10 | — | 300 | |
| | | | — | 20 | — | 0.2 | 20 | — | 600 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.

= -40°C for E device.


T_{HIGH} = +125°C for C, D, F, H device.

= + 85°C for E device.


DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETER | | V _{DD} (V dc) | Min. | Typ. | Max. | Units | |
|--|-------------------------------------|---------------------------|------|------|------|-------|----|
| CLOCKED OPERATION | | | | | | | |
| PROPAGATION DELAY TIME Clock or Inhibit to Q | t _{PLH} , t _{PHL} | 5 | — | 415 | 830 | ns | |
| | | 10 | — | 160 | 320 | | |
| | | 15 | — | 120 | 240 | | |
| | Clock or Inhibit to "O" | 5 | — | 175 | 350 | ns | |
| | | 10 | — | 125 | 250 | | |
| | | 15 | — | 100 | 200 | | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | — | 100 | 200 | ns | |
| 10 | — | 50 | 100 | | | | |
| 15 | — | 40 | 80 | | | | |
| MINIMUM CLOCK PULSE WIDTH | PW _{CL} | 5 | — | 125 | 250 | ns | |
| 10 | — | 50 | 100 | | | | |
| 15 | — | 40 | 80 | | | | |
| MAXIMUM CLOCK FREQUENCY | f _{CL} | 5 | 1.5 | 2.0 | — | MHz | |
| 10 | 3.0 | 5.0 | — | | | | |
| 15 | 4.0 | 6.6 | — | | | | |
| MAXIMUM CLOCK OR INHIBIT RISE AND FALL TIME ¹ | t _{rCL} , t _{fCL} | 5 | 15 | — | — | μs | |
| 10 | 15 | — | — | | | | |
| 15 | 15 | — | — | | | | |
| PRESET OPERATION | | | | | | | |
| PROPAGATION DELAY TIME PE to Q | t _{PLH} , t _{PHL} | 5 | — | 415 | 830 | ns | |
| | | 10 | — | 160 | 320 | | |
| | | 15 | — | 120 | 240 | | |
| | PE to "O" | 5 | — | 175 | 350 | ns | |
| | | 10 | — | 125 | 250 | | |
| | | 15 | — | 100 | 200 | | |
| MINIMUM PRESET ENABLE PULSE WIDTH | PW _{PE} | 5 | — | 125 | 250 | ns | |
| 10 | — | 50 | 100 | | | | |
| 15 | — | 40 | 80 | | | | |
| MINIMUM DATA INPUT HOLD TIME | t _{hold} | 5 | — | 75 | 125 | ns | |
| 10 | — | 25 | 50 | | | | |
| 15 | — | 20 | 40 | | | | |
| RESET OPERATION | | | | | | | |
| PROPAGATION DELAY TIME MR to Q | t _{PHL} | 5 | — | 415 | 830 | ns | |
| | | 10 | — | 160 | 320 | | |
| | | 15 | — | 120 | 240 | | |
| | MR to "O" | t _{PLH} | 5 | — | 175 | 350 | ns |
| | | | 10 | — | 125 | 250 | |
| | | | 15 | — | 100 | 200 | |
| MINIMUM MASTER RESET PULSE WIDTH | PW _{MR} | 5 | — | 150 | 300 | ns | |
| 10 | — | 125 | 250 | | | | |
| 15 | — | 100 | 200 | | | | |

¹ When units are cascaded, the maximum rise and fall times of the clock input should be equal to or less than the transition times of the data outputs driving data inputs, plus the propagation delay of the output driving stage for the output capacitive load.




Typical P-Channel
Source Current Characteristics




Typical N-Channel
Sink Current Characteristics


4522B LOGIC DIAGRAM (BCD Divide-by-N Counter)




4526B LOGIC DIAGRAM (Binary Divide-by-N Counter)



APPLICATIONS INFORMATION



2-Stage Programmable Down Counter (One Cycle)



2-Stage Programmable Frequency Divider

CMOS BCD RATE MULTIPLIER


FEATURES

- ◆ Internally Synchronous for High Speed
- ◆ Strobe for Enabling or Inhibiting Outputs
- ◆ Enable and Cascade Inputs
- ◆ "9" Output Available for Cascading
- ◆ Complementary Outputs
- ◆ Clear and Set-To-Nine Inputs

DESCRIPTION

The 4527B is a BCD Digital Rate Multiplier (DRM) which provides an output pulse rate of the clock input pulse rate multiplied by 1/10 of the BCD input. For example, when the BCD input is 8, there will be 8 output pulses for every 10 input pulses. The output is clocked on the negative-going edge of the input clock. This device may be used to perform arithmetic operations, solve algebraic and differential equations, generate logarithms and trigonometric functions, A/D and D/A conversion, and frequency division.

CONNECTION DIAGRAM (all packages)



Add suffix for package:

- C 16-pin Cerdip
- D 16-pin Ceramic
- E 16-pin Epoxy
- F 16-pin Flat
- H Chip

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:


| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | -55 to +125 | °C |
| C, D, F, H Device | | -40 to +85 | °C |
| E Device | | | |

TRUTH TABLE

| Inputs | | | | | | | | | | Number of Pulses or Output Logic Level (H or L) | | | |
|--------------------------------------|---|---|---|---------------------|----------|--------|---------|-------|-----|---|-----------|------------|-----------|
| D | C | B | A | No. of Clock Pulses | E_{in} | Strobe | Cascade | Clear | Set | Pin 6 OUT | Pin 5 OUT | Pin 7 EOUT | Pin 1 "9" |
| 0 | 0 | 0 | 0 | 10 | 0 | 0 | 0 | 0 | 0 | L | H | 1 | 1 |
| 0 | 0 | 0 | 1 | 10 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 |
| 0 | 0 | 1 | 0 | 10 | 0 | 0 | 0 | 0 | 0 | 2 | 2 | 1 | 1 |
| 0 | 0 | 1 | 1 | 10 | 0 | 0 | 0 | 0 | 0 | 3 | 3 | 1 | 1 |
| 0 | 1 | 0 | 0 | 10 | 0 | 0 | 0 | 0 | 0 | 4 | 4 | 1 | 1 |
| 0 | 1 | 0 | 1 | 10 | 0 | 0 | 0 | 0 | 0 | 5 | 5 | 1 | 1 |
| 0 | 1 | 1 | 0 | 10 | 0 | 0 | 0 | 0 | 0 | 6 | 6 | 1 | 1 |
| 0 | 1 | 1 | 1 | 10 | 0 | 0 | 0 | 0 | 0 | 7 | 7 | 1 | 1 |
| 1 | 0 | 0 | 0 | 10 | 0 | 0 | 0 | 0 | 0 | 8 | 8 | 1 | 1 |
| 1 | 0 | 0 | 1 | 10 | 0 | 0 | 0 | 0 | 0 | 9 | 9 | 1 | 1 |
| 1 | 0 | 1 | 0 | 10 | 0 | 0 | 0 | 0 | 0 | 8 | 8 | 1 | 1 |
| 1 | 0 | 1 | 1 | 10 | 0 | 0 | 0 | 0 | 0 | 9 | 9 | 1 | 1 |
| 1 | 1 | 0 | 0 | 10 | 0 | 0 | 0 | 0 | 0 | 8 | 8 | 1 | 1 |
| 1 | 1 | 0 | 1 | 10 | 0 | 0 | 0 | 0 | 0 | 9 | 9 | 1 | 1 |
| 1 | 1 | 1 | 0 | 10 | 0 | 0 | 0 | 0 | 0 | 8 | 8 | 1 | 1 |
| 1 | 1 | 1 | 1 | 10 | 0 | 0 | 0 | 0 | 0 | 9 | 9 | 1 | 1 |
| Depends on internal state of counter | | | | | | | | | | L | H | 1 | 1 |
| X | X | X | X | 10 | 0 | 1 | 0 | 0 | 0 | H | 0 | 1 | 1 |
| X | X | X | X | 10 | 0 | 0 | 1 | 0 | 0 | H | 0 | 1 | 1 |
| 1 | X | X | X | 10 | 0 | 0 | 0 | 1 | 0 | L | H | H | L |
| 0 | X | X | X | 10 | 0 | 0 | 0 | 0 | 1 | L | H | H | L |
| X | X | X | X | 10 | 0 | 0 | 0 | 0 | 1 | L | H | L | H |


* Output same as the first 16 lines of this truth table (depending on values of A, B, C, D).

BLOCK DIAGRAM




V_{DD} = Pin 16
 V_{SS} = Pin 8

LOGIC DIAGRAM



TIMING DIAGRAM




APPLICATIONS INFORMATION


Cascading Connections

For words of more than one digit, 4527B devices may be cascaded in two different modes: an Add mode and a Multiply mode.

In the Add mode, some of the gaps left by the more significant unit at the count of 9 are filled in by the less significant units. Output Rate = Clock Rate X (0.1 BCD₁ + 0.01 BCD₂ + ...)



Two 4527B's cascaded in the "Multiply" mode with a preset number of 36.



Two 4527B's cascaded in the "Add" mode with a preset number of 94.

In the Multiply mode, the fraction programmed into the first DRM is multiplied by the fraction programmed into the second one.

$$\text{Output Rate} = \text{Clock Rate} \times \frac{\text{BCD}_1}{10} \times \frac{\text{BCD}_2}{10} \times \dots$$

ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|------------|-------------------------------|------|-------|------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | 5 | — | 5 | — | 0.05 | 5 | — | 150 | μAdc |
| | | 10 | — | 10 | — | 0.1 | 10 | — | 300 | |
| | | 15 | — | 20 | — | 0.2 | 20 | — | 600 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.

= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.

= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETER | | V _{DD} (V _{dc}) | Min. | Typ. | Max. | Units |
|---|-------------------------------------|---------------------------------------|------|-------|------|-------|
| CLOCKED OPERATION | | | | | | |
| PROPAGATION DELAY TIME Clock to Out | t _{PLH} , t _{PHL} | 5 | — | 150 | 300 | ns |
| Clock to Out | | 10 | — | 75 | 150 | |
| | | 15 | — | 60 | 120 | |
| | | 5 | — | 95 | 190 | ns |
| Clock to E _{out} | | 10 | — | 50 | 100 | |
| | | 15 | — | 35 | 70 | |
| | | 5 | — | 250 | 500 | ns |
| Clock to "9" | 10 | — | 100 | 200 | | |
| | 15 | — | 75 | 150 | | |
| | 5 | — | 300 | 600 | ns | |
| Cascade to Out | 10 | — | 125 | 250 | | |
| | 15 | — | 100 | 200 | | |
| | 5 | — | 95 | 190 | ns | |
| Strobe to Out | 10 | — | 50 | 100 | | |
| | 15 | — | 35 | 70 | | |
| | 5 | — | 175 | 350 | ns | |
| | 10 | — | 80 | 160 | | |
| | 15 | — | 60 | 120 | | |
| | 5 | — | 130 | 260 | ns | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | — | 65 | 130 | |
| | | 10 | — | 50 | 100 | |
| | | 15 | — | 65 | 130 | |
| MINIMUM CLOCK PULSE WIDTH | PW _{CL} | 5 | — | 165 | 330 | ns |
| | | 10 | — | 85 | 170 | |
| | | 15 | — | 65 | 130 | |
| MAXIMUM CLOCK FREQUENCY | f _{CL} | 5 | 1.5 | 3.0 | — | MHz |
| | | 10 | 3.0 | 6.0 | — | |
| | | 15 | 4.0 | 8 | — | |
| MAXIMUM CLOCK RISE AND FALL TIME ¹ | t _{rCL} , t _{fCL} | 5 | 15 | — | — | μs |
| | | 10 | 15 | — | — | |
| | | 15 | 15 | — | — | |
| MINIMUM ENABLE IN SETUP TIME | t _{setup} | 5 | — | 175 | 350 | ns |
| | | 10 | — | 60 | 120 | |
| | | 15 | — | 45 | 90 | |
| SET OR CLEAR OPERATION | | | | | | |
| PROPAGATION DELAY TIME | t _{PLH} , t _{PHL} | 5 | — | 350 | 700 | ns |
| | | 10 | — | 150 | 300 | |
| | | 15 | — | 115 | 230 | |
| MINIMUM SET OR CLEAR PULSE WIDTH | PW _S , PW _C | 5 | — | 90 | 180 | ns |
| | | 10 | — | 35 | 70 | |
| | | 15 | — | 30 | 60 | |
| SET OR CLEAR REMOVAL TIME | t _{rem} | 5 | — | -20 | 0 | ns |
| | | 10 | — | -10 | 0 | |
| | | 15 | — | - 7.5 | 0 | |

¹ When units are cascaded, the maximum rise and fall times of the clock input should be equal to or less than the transition times of the data outputs driving data inputs, plus the propagation delay of the output driving stage for the output capacitive load.

APPLICATIONS INFORMATION

Multiplication of Two Variables

$$R_1 = f_{CLK} \left(\frac{A}{10} \right)$$

$$R_2 = f_{\text{CLK}} \left(\frac{A}{10} \right) \left(\frac{B}{10} \right) = f_{\text{CLK}} \left(\frac{AB}{100} \right)$$

$$R_3 = f_{CLK} \left(\frac{N}{10} \right)$$


R₂ addresses "up" count, R₃ addresses "down" count. The interface circuit converts to a single clock with mode control. When loop stabilizes,

$$R_2 = R_3$$

$$f_{\text{CLK}} \left(\frac{AB}{100} \right) = f_{\text{CLK}} \left(\frac{N}{10} \right)$$

$$\text{or } N = \frac{AB}{10}$$

Note: To prevent simultaneous "up" and "down" commands, a multiphase clock input must be used.



Generation of A^{2/3}

$$R_1 = f_{CLK} \left(\frac{A^2}{100} \right) \left(\frac{1}{10} \right) = f_{CLK} \left(\frac{A^2}{1000} \right)$$

$$R_2 = f_{CLK} \left(\frac{N^3}{1000} \right)$$


At equilibrium,

$$R_1 = R_2$$

$$N^3 = A^2$$

or $N = A^{2/3}$

Note: To prevent simultaneous "up" and "down" commands, a multiphase clock input must be used.



Frequency Ratios

$$R_1 = f_1/10^n$$


$R_2 = f_2 N / 10^n$ where n = number of stages

At equilibrium,

$$R_1 = R_2$$

$$N = f_1/f_2$$

Note: To prevent simultaneous commands (overlap), f_1 and f_2 may require preconditioning.



CMOS DUAL MONOSTABLE MULTIVIBRATOR

FEATURES

- ◆ Two Independent Multivibrators on One Chip
- ◆ Triggerable from Leading- or Trailing-Edge Pulse
- ◆ Retriggerable
- ◆ Resettable
- ◆ Q and \bar{Q} Buffered Outputs Available
- ◆ Wide Range of Output Pulse Widths

DESCRIPTION

The 4528B Dual Multivibrator provides stable retriggerable/resettable one-shot operation for any fixed-voltage timing application. Timing for the circuit is controlled by an external resistor-capacitor combination (R_X - C_X). Adjustment of these components permits generation of output pulse widths from nanoseconds to minutes. Leading-edge and trailing-edge Trigger inputs are provided, and both positive-going and negative-going pulses are available from complementary outputs.


Timing pulses may be terminated at any time by applying a low logic level to the Reset input C_D .

FUNCTION TABLE

| INPUTS | | | OUTPUTS | |
|--------|---|---|---------|-----------|
| C_D | A | B | Q | \bar{Q} |
| L | X | X | L | H |
| X | H | X | L | H |
| X | X | L | L | H |
| H | ↑ | H | ⌊ | ⌋ |
| H | L | ↓ | ⌋ | ⌊ |

H = High Level (Steady State)
 L = Low Level (Steady State)
 ↑ = Transition, Low-to-High
 ↓ = Transition, High-to-Low
 X = Irrelevant (Inc. Transitions)
 ⌊ = One High-Level Pulse
 ⌋ = One Low-Level Pulse

CONNECTION DIAGRAM (all packages)




RECOMMENDED OPERATING CONDITIONS


For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | -55 to +125 | °C |
| C, D, F, H Device | | -55 to +125 | °C |
| E Device | | -40 to +85 | °C |



BLOCK DIAGRAM (one of two devices)



R_X and C_X are external components.

4528B PULSE WIDTH VS. R_X , C_X , V_{DD} 

LOGIC DIAGRAM



Normalized Pulse Width versus Temperature

Notes:

There is no effective maximum limit on R_X ; recommended minimum value for R_X is 1K Ω . There are no restrictions on the value of C_X .

For proper operation all unused inputs should be tied to a logic level. The mode point (T2) of a unused half of device should be tied high through an external resistor to V_{DD} .

ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|------------|-------------------------------|------|-------|------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | 5 | — | 5 | — | 0.05 | 5 | — | 150 | μAdc |
| | | 10 | — | 10 | — | 0.1 | 10 | — | 300 | |
| | | 20 | — | 20 | — | 0.2 | 20 | — | 600 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.


= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.


= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETER | C _x (pF) | R _x (kΩ) | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|--|--|------------------------|--------------------------|------|-------|------|-------|
| PROPAGATION DELAY TIME From A or B | t _{PLH} , t _{PHL} | 15 5 | 5 | — | 270 | 540 | ns |
| | | | 10 | — | 90 | 180 | |
| | | | 15 | — | 70 | 140 | |
| | 1000 10 | 10 | 5 | — | 510 | 1020 | ns |
| | | | 10 | — | 170 | 340 | |
| | | | 15 | — | 120 | 240 | |
| From C _D | 15 5 | 5 | 5 | — | 270 | 540 | ns |
| | | | 10 | — | 90 | 180 | |
| | | | 15 | — | 70 | 140 | |
| | 1000 10 | 10 | 5 | — | 550 | 1100 | ns |
| | | | 10 | — | 300 | 600 | |
| | | | 15 | — | 250 | 500 | |
| OUTPUT TRANSITION TIME Note: \bar{Q} Output | t _{TLH} , t _{THL} | — — | 5 | — | 130 | 260 | ns |
| | | | 10 | — | 65 | 130 | |
| | | | 15 | — | 50 | 100 | |
| | t _{TLH} | 15 5 | 5 | — | 130 | 260 | ns |
| | | | 10 | — | 65 | 130 | |
| | | | 15 | — | 50 | 100 | |
| MINIMUM INPUT PULSE WIDTH A or B Input | PW _{in} | — — | 5 | — | 70 | 140 | ns |
| | | | 10 | — | 30 | 60 | |
| | | | 15 | — | 25 | 50 | |
| OUTPUT PULSE WIDTH MATCH Same package | ΔPW _{out} | 1000 10 | 5 | — | ± 7.5 | ±15 | % |
| | | | 10 | — | ±10 | ±20 | |
| | | | 15 | — | ±10 | ±20 | |
| Different packages | 1000 10 | 10 | 5 | — | — | ±50 | % |
| | | | 10 | — | — | ±50 | |
| | | | 15 | — | — | ±50 | |




Typical P-Channel
Source Current Characteristics




Typical N-Channel
Sink Current Characteristics


AC TEST WAVEFORMS




APPLICATIONS INFORMATION



Astable Operation



Connection for Non-Retriggerable Operation



Astable Multivibrator with Adjustable Period and Duty Cycle

CMOS 12-BIT PARITY TREE


FEATURES

- ◆ Variable Word Length
- ◆ Buffered Output
- ◆ Parity Selection Input

DESCRIPTION

The 4531B 12-Bit Parity Tree is constructed with MOS P-channel and N-channel enhancement-mode devices in a single monolithic structure. The circuit consists of 12 Data-bit inputs (D0 thru D11), an even or odd Parity Selection input (W), and an output (Q). The Parity Selection input can be considered as an additional bit. Words of less than 13 bits can generate an even or odd parity output if the remaining inputs are selected to contain an even number of 1's. Words of greater than 12 bits can be accommodated by cascading other 4531B devices by using the W input. Applications include checking or including a redundant (parity) bit to a word for error detection/correction systems, controller for remote digital sensors or switches (digital event detection/correction), or as a multiple-input summer without carries.

CONNECTION DIAGRAM (all packages)



Add suffix for package:

- C 16-pin Cerdip
- D 16-pin Ceramic
- E 16-pin Epoxy
- F 16-pin Flat
- H Chip

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | -55 to +125 | °C |
| C, D, F, H Device | | -55 to +125 | °C |
| E Device | | -40 to +85 | °C |


TRUTH TABLE

| INPUTS | | | | | | | | | | OUTPUT |
|--------|-----|-----|----|----|----|----|----|----|----|--------|
| W | D11 | D10 | D9 | D8 | D7 | D6 | D5 | D4 | D3 | Q* |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 1 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 1 | 0 |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 1 |
| 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 |
| 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 |
| 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 0 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 1 | 1 |
| 1 | 1 | 1 | 1 | 0 | 0 | 1 | 0 | 0 | 0 | 0 |
| 1 | 1 | 1 | 1 | 0 | 1 | 0 | 0 | 0 | 0 | 0 |
| 1 | 1 | 1 | 1 | 0 | 1 | 1 | 0 | 0 | 0 | 0 |
| 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 |
| 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 1 | 0 | 1 |
| 1 | 1 | 1 | 1 | 1 | 0 | 0 | 1 | 0 | 0 | 0 |
| 1 | 1 | 1 | 1 | 1 | 0 | 1 | 0 | 0 | 0 | 0 |
| 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 |
| 1 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 |
| 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 |
| 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 |
| 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |

*Q = Even Parity
1 = Odd Parity

Note: May redefine to suit application by manipulating W and/or other available D's

LOGIC DIAGRAM



$$Q = D0 \oplus D1 \oplus D2 \oplus \dots \oplus D11 \oplus W$$

ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|-----------------------------|--------------------------|---|-------------------------------|------|-------|------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | V _{IN} = V _{SS} or V _{DD} All valid input combinations | — | 5 | — | 0.05 | 5 | — | 150 | μAdc |
| | | | — | 10 | — | 0.1 | 10 | — | 300 | |
| | | | — | 20 | — | 0.2 | 20 | — | 600 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.


= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.


= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETER | | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|---|-------------------------------------|--------------------------|------|------|------|-------|
| PROPAGATION DELAY TIME From D Inputs | t _{PLH} , t _{PHL} | 5 | — | 420 | 840 | ns |
| | | 10 | — | 175 | 350 | |
| | | 15 | — | 120 | 240 | |
| | From W Input | 5 | — | 250 | 500 | ns |
| | | 10 | — | 100 | 200 | |
| | | 15 | — | 70 | 140 | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | — | 130 | 260 | ns |
| | | 10 | — | 65 | 130 | |
| | | 15 | — | 50 | 100 | |
| | | 15 | — | 50 | 100 | |



Typical P-Channel
Source Current Characteristics



Typical N-Channel
Sink Current Characteristics

FEATURES

- Converts from 1 of 8 binary
- Provides cascading features to handle any number of inputs
- group select indicates one or more priority inputs
- Standardized, symmetrical output characteristics
- Noise margin (full package-temperature range):
 1V at $V_{DD} = 5V$
 2V at $V_{DD} = 10V$
 2.5V at $V_{DD} = 15V$
- 5V, 10V, and 15V parametric ratings


APPLICATIONS

- Priority encoder
- Binary or BCD encoder (keyboard encoding)
- Floating point arithmetic

DESCRIPTION

The 4532B consists of combinational logic that encodes the highest priority input (D7-D0) to a 3-bit binary code. The eight inputs, D7 through D0, each have an assigned priority; D7 is the highest priority and D0 is the lowest. The priority encoder is inhibited when the chip-enable input E_1 is low. Then E_1 is high, the binary representation of the highest-priority input appears on output lines Q2-Q0, and the group select line GS is high to indicate that priority inputs are present. The enable-out (E_0) is high when no priority inputs are present. If any one input is high, E_0 is low and all cascaded lower-order stages are disabled.

CMOS 8-BIT PRIORITY ENCODER




RECOMMENDED OPERATING CONDITIONS

For maximum reliability, nominal operating conditions should be selected so that operation is always within the following ranges.

| Characteristic | Min. | Max. | Units |
|---|------|------|-------|
| Supply Voltage Range (for $T_A =$ Full Package Temp. Range) | 3 | 15 | V |

FUNCTIONAL DIAGRAM





TRUTH TABLE

| Input | | | | | | | | | Output | | | | |
|-------|----|----|----|----|----|----|----|----|--------|----|----|----|-------|
| E_1 | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 | GS | Q2 | Q1 | Q0 | E_0 |
| 0 | X | X | X | X | X | X | X | X | 0 | 0 | 0 | 0 | 0 |
| 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 |
| 1 | 1 | X | X | X | X | X | X | X | 1 | 1 | 1 | 1 | 0 |
| 1 | 0 | 1 | X | X | X | X | X | X | 1 | 1 | 1 | 0 | 0 |
| 1 | 0 | 0 | 1 | X | X | X | X | X | 1 | 1 | 0 | 1 | 0 |
| 1 | 0 | 0 | 0 | 1 | X | X | X | X | 1 | 1 | 0 | 0 | 0 |
| 1 | 0 | 0 | 0 | 0 | 1 | X | X | X | 1 | 0 | 1 | 1 | 0 |
| 1 | 0 | 0 | 0 | 0 | 0 | 1 | X | X | 1 | 0 | 1 | 0 | 0 |
| 1 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | X | 1 | 0 | 0 | 1 | 0 |
| 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 0 | 0 | 0 | 0 |

X = Don't Care


Logic 1 \equiv High

Logic 0 \equiv Low




*ALL INPUTS PROTECTED BY COS/MOS PROTECTION NETWORK


4532 logic diagram.



Quiescent device current test circuit.



Input voltage test circuit.



Input current test circuit.

ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | + 25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|--|-------------------------------|------|--------|------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | V _{IN} = V _{SS} or V _{DD} All Valid input combinations | — | 5 | — | 0.05 | 5 | — | 150 | μAdc |
| | | | — | 10 | — | 0.1 | 10 | — | 300 | |
| | | | — | 20 | — | 0.2 | 20 | — | 600 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications"

² T_{LOW} = -55°C for C, D, F, H device.

= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device

= +85°C for E device.

DYNAMIC ELECTRICAL CHARACTERISTICS at T_A = 25°C; C_L = 50 pF.

| CHARACTERISTIC | TEST CONDITONS V _{DD} VOLTS | LIMITS ALL TYPES | | UNITS |
|---|--|---------------------|------|-------|
| | | TYP. | MAX. | |
| PROPAGATION DELAY TIME t _{PHL} , t _{PLH} E _I to E _O , E _I to GS | 5 | 110 | 220 | ns |
| | 10 | 55 | 110 | |
| | 15 | 45 | 85 | |
| E _I to Qm, Dn to GS | 5 | 170 | 340 | |
| | 10 | 85 | 170 | |
| | 15 | 65 | 125 | |
| Dn to QM | 5 | 220 | 440 | |
| | 10 | 110 | 220 | |
| | 15 | 85 | 160 | |
| TRANSITION TIME t _{THL} , t _{TLH} | 5 | 100 | 200 | ns |
| | 10 | 50 | 100 | |
| | 15 | 40 | 80 | |
| INPUT CAPACITANCE C _{IN} | Any Input | 5 | 75 | pF |

AC TEST WAVEFORMS






FIGURE 1 - POWER DISSIPATION TEST CIRCUIT AND WAVEFORM



**EXPANDED BLOCK DIAGRAM
(1/2 OF DEVICE SHOWN)**



BCD-TO-SEVEN SEGMENT LATCH/DECODER/DRIVER

FEATURES

- ◆ Phase Input Signal Reproduced on Outputs for Liquid Crystal Display
- ◆ Latched Storage of Input Code
- ◆ Blanking Input for Display Intensity Modulation
- ◆ Readout Blanking for Illegal Input Combinations
- ◆ Pin Compatible with CD4056A (with Pin 7 Tied to V_{SS})

DESCRIPTION

The 4543B BCD-to-7 Segment Latch/Decoder/Driver is designed for use with liquid crystal readouts and is constructed with complementary MOS (CMOS) enhancement-mode devices. The circuit provides the functions of a 4-bit storage latch and a 8421 BCD-to-seven segment decoder and driver. The device has the capability to invert the logic levels of the output combinations. The Phase (Ph), Blanking (BI), and Latch Disable (LD) inputs are used to reverse the truth-table phase, blank the display, and store a BCD code, respectively. For liquid crystal readouts, a square wave is applied to the Ph input of the circuit and the electrically common backplane of the display. The outputs of the circuit are connected directly to the segments of the readout. For other types of readouts, such as light-emitting diode (LED), incandescent, gas discharge, and fluorescent readouts, connection diagrams are given on this data sheet.

Applications include instrument (e.g., counter,

TRUTH TABLE

| INPUTS | | | | OUTPUTS | | | | | | | |
|--------|----|-----|---------|--------------------------------------|---|---|---|---|---|------------------|---------|
| LD | BI | Ph* | D C B A | a | b | c | d | e | f | g | Display |
| X | 1 | 0 | X X X X | 0 | 0 | 0 | 0 | 0 | 0 | 0 | Blank |
| 1 | 0 | 0 | 0 0 0 0 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 |
| 1 | 0 | 0 | 0 0 0 1 | 0 | 1 | 1 | 0 | 0 | 0 | 0 | 1 |
| 1 | 0 | 0 | 0 0 1 0 | 0 | 1 | 1 | 1 | 0 | 1 | 1 | 2 |
| 1 | 0 | 0 | 0 0 1 1 | 1 | 1 | 1 | 1 | 0 | 0 | 1 | 3 |
| 1 | 0 | 0 | 0 1 0 0 | 0 | 1 | 0 | 0 | 1 | 0 | 1 | 4 |
| 1 | 0 | 0 | 0 1 0 1 | 1 | 0 | 1 | 0 | 1 | 1 | 1 | 5 |
| 1 | 0 | 0 | 0 1 1 0 | 1 | 0 | 1 | 1 | 1 | 1 | 1 | 6 |
| 1 | 0 | 0 | 0 1 1 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 7 |
| 1 | 0 | 0 | 1 0 0 0 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 8 |
| 1 | 0 | 0 | 1 0 0 1 | 1 | 1 | 1 | 1 | 0 | 1 | 1 | 9 |
| 1 | 0 | 0 | 1 0 1 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | Blank |
| 1 | 0 | 0 | 1 0 1 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | Blank |
| 1 | 0 | 0 | 1 1 0 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | Blank |
| 1 | 0 | 0 | 1 1 0 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | Blank |
| 1 | 0 | 0 | 1 1 1 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | Blank |
| 1 | 0 | 0 | 1 1 1 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | Blank |
| 0 | 0 | 0 | X X X X | ** | | | | | | ** | |
| 1 | 1 | 1 | 1 | Inverse of Output Combinations Above | | | | | | Display as above | |

X - Don't care

1 - Above Combinations


* - For liquid crystal readouts, apply a square wave to Ph

For common cathode LED readouts, select Ph = 0.

For common anode LED readouts, select Ph = 1.

** - Depends upon the BCD code previously applied when LD = 1

CONNECTION DIAGRAM (all packages)



Add suffix for package:

- C 16-pin Cerdip
- D 16-pin Ceramic
- E 16-pin Epoxy
- F 16-pin Flat
- H Chip


RECOMMENDED OPERATING CONDITIONS

For maximum reliability:


| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | -55 to +125 | °C |
| C, D, F, H Device | | -40 to +85 | °C |
| E Device | | | |

DVM, etc.) display driver, computer/calculator display driver, cockpit display driver, and various clock, watch, and timer uses.

BLOCK DIAGRAM



DISPLAY



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|---|-------------------------------|------|-------|------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | V _{IN} =V _{SS} or V _{DD} All valid input combinations | — | 5 | — | 0.05 | 5 | — | 150 | μAdc |
| | | | — | 10 | — | 0.1 | 10 | — | 300 | |
| | | | — | 20 | — | 0.2 | 20 | — | 600 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.


= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.


= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETER | | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|-------------------------------|-------------------------------------|--------------------------|------|------|------|-------|
| PROPAGATION DELAY TIME | t _{PLH} , t _{PHL} | 5 | — | 550 | 1100 | ns |
| | | 10 | — | 210 | 420 | |
| | | 15 | — | 160 | 320 | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | — | 100 | 200 | ns |
| | | 10 | — | 50 | 100 | |
| | | 15 | — | 40 | 80 | |
| MINIMUM DATA INPUT SETUP TIME | t _{setup} | 5 | — | -40 | 0 | ns |
| | | 10 | — | -15 | 0 | |
| | | 15 | — | -10 | 0 | |
| MINIMUM DATA INPUT HOLD TIME | t _{hold} | 5 | — | 40 | 80 | ns |
| | | 10 | — | 15 | 30 | |
| | | 15 | — | 10 | 20 | |
| MINIMUM LD PULSE WIDTH | PW _{LD} | 5 | — | 125 | 250 | ns |
| | | 10 | — | 50 | 100 | |
| | | 15 | — | 40 | 80 | |




Typical P-Channel
Source Current Characteristics



Typical N-Channel
Sink Current Characteristics


LOGIC DIAGRAM




APPLICATIONS INFORMATION

CONNECTIONS TO VARIOUS DISPLAY READOUTS

LIQUID CRYSTAL (LC) READOUT




LIGHT EMITTING DIODE (LED) READOUT




Note: Bipolar transistors may be added for gain (for $V_{DD} \leq 10V$ or $I_{out} \geq 10\text{ mA}$).


FLUORESCENT READOUT



INCANDESCENT READOUT



GAS DISCHARGE READOUT



CMOS DUAL 2-TO-4 LINE DECODERS

FEATURES

- ◆ Buffered Outputs
- ◆ Selected Output Active High (4555B) or Active Low (4556B)
- ◆ Expandable

DESCRIPTION

The 4555B and 4556B are constructed with complementary MOS (CMOS) enhancement-mode devices. Each decoder/demultiplexer has two Select inputs (A and B), an active-low Enable input (E), and four mutually-exclusive outputs (Q0, Q1, Q2, Q3). The 4555B has the selected output go to the "high" state, and the 4556B has the selected output go to the "low" state. Expanded decoding such as binary-to-hexadecimal (1-of-16), etc., can be achieved by using other 4555B or 4556B devices.


Applications include code conversion, address decoding, memory selection control, and demultiplexing (using the Enable input as a data input) in digital data transmission systems.

TRUTH TABLE

| Inputs | | | Outputs 4555B | | | | Outputs 4556B | | | |
|-----------|--------|---|---------------|----|----|----|---------------|------------|------------|------------|
| Enable | Select | | | | | | | | | |
| \bar{E} | B | A | Q3 | Q2 | Q1 | Q0 | $\bar{Q}3$ | $\bar{Q}2$ | $\bar{Q}1$ | $\bar{Q}0$ |
| 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 0 |
| 0 | 0 | 1 | 0 | 0 | 1 | 0 | 1 | 1 | 0 | 1 |
| 0 | 1 | 0 | 0 | 1 | 0 | 0 | 1 | 0 | 1 | 1 |
| 0 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 1 | 1 | 1 |
| 1 | X | X | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 |

X = Don't Care

CONNECTION DIAGRAM
(all packages)



*Inverted for 4556B

Add suffix for package:


- C 16-pin Cerdip
- D 16-pin Ceramic
- E 16-pin Epoxy
- F 16-pin Flat
- H Chip

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | -55 to +125 | °C |
| C, D, F, H Device | | -40 to +85 | °C |
| E Device | | | |

BLOCK DIAGRAMS



V_{DD} = Pin 16
 V_{SS} = Pin 8

ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|---|-------------------------------|------|-------|------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | V _{IN} = V _{SS} or V _{DD} All valid inputs combinations | — | 5 | — | 0.05 | 5 | — | 150 | μAdc |
| | | | — | 10 | — | 0.1 | 10 | — | 300 | |
| | | | — | 20 | — | 0.2 | 20 | — | 600 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.


= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.


= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETER | | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|---------------------------------|-------------------------------------|--------------------------|------|------|------|-------|
| PROPAGATION DELAY TIME 4555B | t _{PLH} , t _{PHL} | 5 | — | 140 | 280 | ns |
| | | 10 | — | 65 | 130 | |
| | | 15 | — | 50 | 100 | |
| 4556B | t _{PLH} , t _{PHL} | 5 | — | 160 | 320 | ns |
| | | 10 | — | 75 | 150 | |
| | | 15 | — | 50 | 100 | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | — | 100 | 200 | ns |
| | | 10 | — | 50 | 100 | |
| | | 15 | — | 40 | 80 | |




Typical P-Channel
Source Current Characteristics




Typical N-Channel
Sink Current Characteristics


LOGIC DIAGRAM (½ of Dual)




APPLICATIONS INFORMATION



1-of-4 Line Data Demultiplexer Using 4555B



1-of-8 Decoder Using 4555B



1-of-16 Decoder Using 4555B/ 4556B

CMOS 4-BIT ARITHMETIC LOGIC UNIT

FEATURES

- ◆ Function and Pinout Equivalent to 74181
- ◆ Provides 16 Logic Functions and 16 Arithmetic Functions
- ◆ Comparator Function
- ◆ Positive or Negative Logic
- ◆ Full Look-Ahead for High-Speed Operations on Long Words

DESCRIPTION


The 4581B is a CMOS 4-Bit Arithmetic Logic Unit (ALU) capable of providing 16 functions of two Boolean variables and 16 binary arithmetic operations on two 4-bit words. The level of the Mode Control input determines whether the output function is logic or arithmetic. The desired logic function is selected by applying the appropriate binary word to the Select inputs (S0 thru S3) with the Mode Control input high, while the desired arithmetic operation is selected by applying a low voltage to the Mode Control input, the required level to Carry in, and the appropriate word to the Select inputs. The Word inputs and Function outputs can be operated with either active-high or active-low data.

Carry propagate (P) and Carry generate (G) outputs are provided to allow a full look-ahead carry scheme for fast simultaneous carry generation for the four bits in the package. Fast arithmetic operations on long words are obtainable by using the 4582B as a second-order look-ahead block. An inverted Ripple-Carry input (C_n) and a Ripple-Carry output (C_{n+4}) are included for ripple-through operation.

ALU SIGNAL DESIGNATIONS

| Designation | Pin Nos. | Function |
|----------------|---------------|------------------------|
| A3, A2, A1, A0 | 19, 21, 23, 2 | Word A Inputs |
| B3, B2, B1, B0 | 18, 20, 22, 1 | Word B Inputs |
| S3, S2, S1, S0 | 3, 4, 5, 6 | Function-Select Inputs |
| C_n | 7 | Inv. Carry Input |
| MC | 8 | Mode Control Input |
| F3, F2, F1, F0 | 13, 11, 10, 9 | Function Outputs |
| A = B | 14 | Comparator Output |
| P | 15 | Carry Propagate Output |
| C_{n+4} | 16 | Inv. Carry Output |
| G | 17 | Carry Generate Output |

CONNECTION DIAGRAM (all packages)



Add suffix for package:


- D 24-pin Ceramic
- E 24-pin Epoxy
- H Chip

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | | |
| D, H Device | | -55 to +125 | °C |
| E Device | | -40 to +85 | °C |

BLOCK DIAGRAM



ALU FUNCTION GENERATION

The 4581B can be used with the signal designations of either Figure 1 or Figure 2.

The logic functions and arithmetic operations obtained with signal designations as in Figure 1 are given in Table 1; those obtained with the signal designations of Figure 2 are given in Table 2.




FIGURE 1
(Use with Table 1 for Positive logic,
with Table 2 for negative logic)




FIGURE 2
(Use with Table 2 for positive logic,
with Table 1 for negative logic)

TABLE 1

| SELECTION S3 S2 S1 S0 | MC = H LOGIC FUNCTIONS | ACTIVE-LOW DATA MC = L: ARITHMETIC OPERATIONS | |
|--------------------------|------------------------------|--|--|
| | | MC = L (no carry) | C _n = H (with carry) |
| L L L L | F = \bar{A} | F = A MINUS 1 | F = A |
| L L L H | F = $\bar{A}\bar{B}$ | F = AB MINUS 1 | F = AB |
| L L H L | F = $\bar{A} + B$ | F = $\bar{A}\bar{B}$ MINUS 1 | F = $\bar{A}\bar{B}$ |
| L L H H | F = 1 | F = MINUS 1 (2's COMPL) | F = ZERO |
| L H L L | F = $\bar{A} \oplus \bar{B}$ | F = A PLUS (A + \bar{B}) | F = A PLUS (A + \bar{B}) PLUS 1 |
| L H L H | F = \bar{B} | F = AB PLUS (A + \bar{B}) | F = AB PLUS (A + \bar{B}) PLUS 1 |
| L H H L | F = A \oplus B | F = A MINUS B MINUS 1 | F = A MINUS B |
| L H H H | F = A + \bar{B} | F = A + \bar{B} | F = (A + \bar{B}) PLUS 1 |
| H L L L | F = $\bar{A}\bar{B}$ | F = A PLUS (A + B) | F = A PLUS (A + B) PLUS 1 |
| H L L H | F = A \oplus B | F = A PLUS B | F = A PLUS B PLUS 1 |
| H L H L | F = B | F = $\bar{A}\bar{B}$ PLUS (A + B) | F = $\bar{A}\bar{B}$ PLUS (A + B) PLUS 1 |
| H L H H | F = A + B | F = (A + B) | F = (A + B) PLUS 1 |
| H H L L | F = 0 | F = A PLUS A* | F = A PLUS A PLUS 1 |
| H H L H | F = $\bar{A}\bar{B}$ | F = AB PLUS A | F = AB PLUS A PLUS 1 |
| H H H L | F = AB | F = $\bar{A}\bar{B}$ PLUS A | F = $\bar{A}\bar{B}$ PLUS A PLUS 1 |
| H H H H | F = A | F = A | F = A PLUS 1 |

TABLE 2

| SELECTION S3 S2 S1 S0 | MC = H LOGIC FUNCTIONS | ACTIVE-HIGH DATA MC = L: ARITHMETIC OPERATIONS | |
|--------------------------|------------------------------|---|--|
| | | C _n = H (no carry) | C _n = L (with carry) |
| L L L L | F = \bar{A} | F = A | F = A PLUS 1 |
| L L L H | F = $\bar{A} \oplus \bar{B}$ | F = A + B | F = (A + B) PLUS 1 |
| L L H L | F = $\bar{A}\bar{B}$ | F = A + \bar{B} | F = (A + \bar{B}) PLUS 1 |
| L L H H | F = 0 | F = MINUS 1 (2's COMPL) | F = ZERO |
| L H L L | F = $\bar{A}\bar{B}$ | F = A PLUS $\bar{A}\bar{B}$ | F = A PLUS $\bar{A}\bar{B}$ PLUS 1 |
| L H L H | F = \bar{B} | F = (A + B) PLUS $\bar{A}\bar{B}$ | F = (A + B) PLUS $\bar{A}\bar{B}$ PLUS 1 |
| L H H L | F = A \oplus B | F = A MINUS B MINUS 1 | F = A MINUS B |
| L H H H | F = $\bar{A}\bar{B}$ | F = $\bar{A}\bar{B}$ MINUS 1 | F = $\bar{A}\bar{B}$ |
| H L L L | F = $\bar{A} + B$ | F = A PLUS AB | F = A PLUS AB PLUS 1 |
| H L L H | F = A \oplus B | F = A PLUS B | F = A PLUS B PLUS 1 |
| H L H L | F = B | F = (A + \bar{B}) PLUS AB | F = (A + \bar{B}) PLUS AB PLUS 1 |
| H L H H | F = AB | F = AB MINUS 1 | F = AB |
| H H L L | F = 1 | F = A PLUS A* | F = A PLUS A PLUS 1 |
| H H L H | F = A + \bar{B} | F = (A + B) PLUS A | F = (A + B) PLUS A PLUS 1 |
| H H H L | F = A + B | F = (A + \bar{B}) PLUS A | F = (A + \bar{B}) PLUS A PLUS 1 |
| H H H H | F = A | F = A MINUS 1 | F = A |

* Each bit is shifted to the next more significant position.

When the device is in the subtract mode (LHHL), comparison of two 4-bit words present at the A and B inputs is provided using the A=B output. It assumes a high-level state when indicating equality. Also, when the ALU is in the subtract mode the C_{n+4} output can be used to indicate relative magnitude as shown in this table:

| Data Level | C _n | C _{n+4} | Magnitude |
|-------------|----------------|------------------|-----------|
| Active High | H | H | A ≤ B |
| | L | L | A < B |
| | H | L | A > B |
| Active Low | L | L | A ≤ B |
| | H | L | A < B |
| | L | H | A > B |

ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|--|-------------------------------|------|-------|------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | V _{IN} = V _{SS} or V _{DD} All valid input combinations | — | 5 | — | 0.05 | 5 | — | 150 | μAdc |
| | | | — | 10 | — | 0.1 | 10 | — | 300 | |
| | | | — | 20 | — | 0.2 | 20 | — | 600 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for D, H device.

= -40°C for E device.

T_{HIGH} = +125°C for D, H device.


= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)


| PARAMETER | | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|---|-------------------------------------|--------------------------|------|------|------|-------|
| PROPAGATION DELAY TIME Sum In to Sum Out | t _{PLH} , t _{PHL} | 5 | — | 400 | 800 | ns |
| | | 10 | — | 160 | 320 | |
| | | 15 | — | 120 | 240 | |
| | | 5 | — | 380 | 760 | ns |
| | | 10 | — | 190 | 380 | |
| | | 15 | — | 160 | 320 | |
| | | 5 | — | 450 | 900 | ns |
| | | 10 | — | 275 | 550 | |
| | | 15 | — | 225 | 450 | |
| Sum In to A = B | | 5 | — | 300 | 600 | ns |
| | | 10 | — | 150 | 300 | |
| | | 15 | — | 125 | 250 | |
| Sum In to \bar{P} or \bar{G} | | 5 | — | 300 | 600 | ns |
| | | 10 | — | 150 | 300 | |
| | | 15 | — | 125 | 250 | |
| Sum In to C _{N+4} | | 5 | — | 300 | 600 | ns |
| | | 10 | — | 150 | 300 | |
| | | 15 | — | 125 | 250 | |
| Carry In to Sum Out | | 5 | — | 200 | 400 | ns |
| | | 10 | — | 100 | 50 | |
| | | 15 | — | 70 | 35 | |
| Carry In to C _{N+4} | | 5 | — | 200 | 400 | ns |
| | | 10 | — | 100 | 50 | |
| | | 15 | — | 70 | 35 | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | — | 100 | 200 | ns |
| | | 10 | — | 50 | 100 | |
| | | 15 | — | 40 | 80 | |

AC Test Setup Reference Table

| TEST | AC PATHS | | DC DATA INPUTS | | MODE |
|---|----------------|------------------|---------------------------------|--------------------|--------------|
| | INPUTS | OUTPUTS | TO V _{SS} | TO V _{DD} | |
| Sum _{IN} to Sum _{OUT} Delay Time | A0 | Any \bar{F} | Remaining A's C _N | All B's | Add |
| Sum _{IN} to \bar{P} Delay Time | A0 | P | Remaining A's C _N | All B's | Add |
| Sum _{IN} to \bar{G} Delay Time | B0 | C _{N+Y} | All A's C _N | Remaining B's | Add |
| Sum _{IN} to C _{N+4} Delay Time | B0 | \bar{G} | All A's C _N | Remaining B's | Add |
| C _N to Sum _{OUT} Delay Time | C _N | Any \bar{F} | All A's | All B's | Add |
| C _N to C _{N+4} Delay Time | C _N | C _{N+4} | All A's | All B's | Add |
| Sum _{IN} to A = B Delay Time | A0 | A = B | All B's Remaining A's | C _N | Sub |
| Sum _{IN} to Sum _{OUT} Delay Time (Logic Mode) | All B's | Any \bar{F} | All A's | M | Exclusive OR |



Typical P-Channel
Source Current Characteristics








Typical N-Channel
Sink Current Characteristics

APPLICATIONS INFORMATION

ADDITION REQUIREMENTS

| Number of Bits | Package Count | | Carry Method Between ALU's |
|----------------|------------------------|-----------------------------|----------------------------|
| | Arithmetic/Logic Units | Look-Ahead Carry Generators | |
| 1 to 4 | 1 | | None |
| 5 to 8 | 2 | | Ripple |
| 9 to 16 | 3 or 4 | 1 | Full Look-Ahead |
| 17 to 64 | 5 to 16 | 2 to 5 | Full Look-Ahead |

EXPANSION TECHNIQUES



A and B Inputs and F Outputs are not shown (4581B).

CMOS LOOK-AHEAD CARRY BLOCK

FEATURES

- ◆ Expandable to any Number of Bits
- ◆ High-Speed Operation
- ◆ Directly Compatible with 4581B ALU

DESCRIPTION

The 4582B is a high-speed, Look-Ahead Carry Generator capable of anticipating a carry across four binary adders or group of adders. It is cascable to perform full look-ahead across n-bit adders. Carry, generate-carry, and propagate-carry functions are provided.

When used in conjunction with the 4581B Arithmetic Logic Unit (ALU), these generators provide high-speed carry look-ahead capability for any word length. Each 4582B generates the look-ahead (anticipated carry) across a group of four ALU's and, in addition, other carry look-ahead circuits may be employed to anticipate carry across sections of four look-ahead packages up to n-bits.

Carry input and output of the 4581B ALU are in their true form and the carry propagate (P) and carry generate (G) are in negated form; therefore, the carry functions (inputs, outputs, generate, and propagate) of the look-ahead generators are implemented in the compatible forms for direct connections to the ALU. Reinterpretations of carry functions as explained on the 4581B data sheet are also applicable to and compatible with the look-ahead generator.


PIN DESIGNATIONS

| DESIGNATION | PIN NO.'s | FUNCTION |
|--|-------------|--|
| $\bar{G}_0, \bar{G}_1, \bar{G}_2, \bar{G}_3$ | 3, 1, 14, 5 | Active-Low Carry-Generate Inputs |
| $\bar{P}_0, \bar{P}_1, \bar{P}_2, \bar{P}_3$ | 4, 2, 15, 6 | Active-Low Carry-Propagate Inputs |
| C_n | 13 | Carry Input |
| $C_{n+x}, C_{n+y}, C_{n+z}$ | 12, 11, 9 | Carry Outputs |
| \bar{G} | 10 | Active-Low Group Carry-Generate Output |
| \bar{P} | 7 | Active-Low Group Carry-Propagate Output |

LOGIC EQUATIONS

$$\begin{aligned}
 C_{n+x} &= G_0 + P_0 \cdot C_n \\
 C_{n+y} &= G_1 + P_1 \cdot G_0 + P_1 \cdot P_0 \cdot C_n \\
 C_{n+z} &= G_2 + P_2 \cdot G_1 + P_2 \cdot P_1 \cdot G_0 + P_2 \cdot P_1 \cdot P_0 \cdot C_n \\
 \bar{G} &= G_3 + P_3 \cdot G_2 + P_3 \cdot P_2 \cdot G_1 + P_3 \cdot P_2 \cdot P_1 \cdot G_0 \\
 \bar{P} &= P_3 \cdot P_2 \cdot P_1 \cdot P_0
 \end{aligned}$$

CONNECTION DIAGRAM (all packages)



Add suffix for package:


- C 16-pin Cerdip
- D 16-pin Ceramic
- E 16-pin Epoxy
- F 16-pin Flat
- H Chip

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | | |
| C, D, F, H Device | | -55 to +125 | °C |
| E Device | | -40 to +85 | °C |

BLOCK DIAGRAM



V_{DD} = Pin 16
 V_{SS} = Pin 8

ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|--|-------------------------------|------|-------|------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | V _{IN} = V _{SS} or V _{DD} All valid input combinations | — | 5 | — | 0.05 | 5 | — | 150 | μAdc |
| | | | — | 10 | — | 0.1 | 10 | — | 300 | |
| | | | — | 20 | — | 0.2 | 20 | — | 600 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.


= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.


= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETER | | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|------------------------|-------------------------------------|--------------------------|------|------|------|-------|
| PROPAGATION DELAY TIME | t _{PLH} , t _{PHL} | 5 | — | 200 | 400 | ns |
| | | 10 | — | 100 | 200 | |
| | | 15 | — | 85 | 160 | |
| | | | | | | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | — | 100 | 200 | ns |
| | | 10 | — | 50 | 100 | |
| | | 15 | — | 40 | 80 | |
| | | | | | | |




Typical P-Channel
Source Current Characteristics



Typical N-Channel
Sink Current Characteristics

APPLICATIONS INFORMATION



64-BIT ALU, FULL-CARRY LOOK-AHEAD IN THREE LEVELS

CMOS HEX INVERTING SCHMITT TRIGGER


FEATURES:

- Schmitt Trigger Action on each Input with no External Components
- Noise Immunity Greater than 30%
- No Limit on Input Rise and Fall Times
- Pin for Pin Replacement for CD40106B, MM74C14 and MCI4584B
- Also Pin Compatible with 74C04 and 4069 Hex Inverters


DESCRIPTION:

The 4584B consists of six Schmitt Trigger circuits, constructed with MOS P-channel and N-channel enhancement mode devices in a single monolithic structure. These devices find primary use where low power dissipation and/or high noise immunity is desired. The 4584B may be used in place of the MCI4069B hex inverter for enhanced noise immunity or to square up slowly changing waveforms.

LOGIC DIAGRAMS



CONNECTION DIAGRAM (all packages)



Add suffix for package:

- C 14-pin Cerdip
- D 14-pin Ceramic
- E 14-pin Epoxy
- F 14-pin Flat
- H Chip

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:

| | | | |
|-----------------------|-------------------|-------------|----------|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | V_{dc} |
| Operating Temperature | T_A | | |
| C, D, F, H Device | | -55 to +125 | °C |
| E Device | | -40 to +85 | °C |

ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--|-----------------|--------------------------|---|-------------------------------|------|-------|------|------|--------------------------------|------|-------|
| | | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | 5 | V _{IN} = V _{SS} or V _{DD} All valid input combinations | — | 1.0 | — | .005 | 1.0 | — | 30 | μA |
| | | 10 | | — | 2.0 | — | .01 | 2.0 | — | 60 | |
| | | 15 | | — | 4.0 | — | .02 | 4.0 | — | 120 | |
| POSITIVE TRIGGER THRESHOLD VOLTAGE | V _{TP} | 5 | | 2.3 | 3.5 | 2.3 | 2.9 | 3.5 | 2.3 | 3.5 | V |
| | | 10 | | 4.5 | 7.0 | 4.5 | 5.3 | 7.0 | 4.5 | 7.0 | |
| | | 15 | | 6.8 | 11.0 | 6.8 | 7.7 | 11.0 | 6.8 | 11.0 | |
| NEGATIVE TRIGGER THRESHOLD VOLTAGE | V _{TN} | 5 | | 1.5 | 2.7 | 1.5 | 2.15 | 2.7 | 1.5 | 2.7 | V |
| | | 10 | | 3.0 | 5.5 | 3.0 | 4.4 | 5.5 | 3.0 | 5.5 | |
| | | 15 | | 4.0 | 8.2 | 4.0 | 6.5 | 8.2 | 4.0 | 8.2 | |
| HYSTERESIS VOLTAGE | V _H | 5 | | .4 | 2.0 | .4 | .75 | 2.0 | .4 | 2.0 | V |
| | | 10 | | .7 | 3.0 | .7 | .95 | 3.0 | .7 | 3.0 | |
| | | 15 | | .85 | 4.0 | .85 | 1.2 | 4.0 | .85 | 4.0 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H devices.

= -40°C for E Devices.

T_{HIGH} = +125°C for E, D, F, H devices.

= +85°C for E devices.

DYNAMIC CHARACTERISTICS ($C_L = 50pF$, $T_A = 25^\circ C$)

| PARAMETER | | V_{DD} (Vdc) | Min. | Typ. | Max. | Units |
|---------------------------|-----------|-------------------|------|------|------|-------|
| PROPAGATION DELAY TIME | t_{PLH} | 5 | 86 | 107 | 150 | ns |
| | t_{PHL} | 10 | 42 | 48 | 60 | |
| | | 15 | 30 | 35 | 40 | |
| OUTPUT TRANSITION TIME | t_{TLH} | 5 | 44 | 62 | 200 | ns |
| | t_{THL} | 10 | 24 | 29 | 100 | |
| | | 15 | 19 | 23 | 80 | |

CMOS 4-BIT MAGNITUDE COMPARATOR


FEATURES

- ◆ Binary or BCD Comparison
- ◆ Expandable
- ◆ $A < B$, $A = B$, $A > B$ Outputs Available

DESCRIPTION

This 4-Bit Magnitude Comparator performs comparison of straight binary and straight BCD (8-4-2-1) codes. Three decisions about two 4-bit words (A, B) are made and are externally available at three outputs. These devices are fully expandable to any number of bits without external gates. Words of greater length may be compared by connecting comparators in cascade. The $A < B$ and $A = B$ outputs of a stage handling less-significant bits are connected to the corresponding $A < B$ and $A = B$ inputs of the next stage handling more-significant bits. The $A > B$ cascading input is connected to a high level. The stage handling the least-significant bits must have a high-level voltage applied to the $A = B$ and $A > B$ inputs. An alternate method of cascading which reduces the comparison time is shown under Applications Information.

CONNECTION DIAGRAM (all packages)



Add suffix for package:

- C 16-pin Cerdip
- D 16-pin Ceramic
- E 16-pin Epoxy
- F 16-pin Flat
- H Chip

RECOMMENDED OPERATING CONDITIONS

For maximum reliability:


| | | | |
|-----------------------|-------------------|-------------|-----|
| DC Supply Voltage | $V_{DD} - V_{SS}$ | 3 to 15 | Vdc |
| Operating Temperature | T_A | | |
| C, D, F, H Device | | -55 to +125 | °C |
| E Device | | -40 to +85 | °C |

TRUTH TABLE

| Inputs | | | | Outputs | | | | | | |
|-----------|--------|--------|--------|-----------|-----|-----|-----|-----|-----|--|
| Comparing | | | | Cascading | | | | | | |
| A3, B3 | A2, B2 | A1, B1 | A0, B0 | A<B | A=B | A>B | A<B | A=B | A>B | |
| A3>B3 | X | X | X | X | X | 1 | 0 | 0 | 1 | |
| A3=B3 | A2>B2 | X | X | X | X | 1 | 0 | 0 | 1 | |
| A3=B3 | A2=B2 | A1>B1 | X | X | X | 1 | 0 | 0 | 1 | |
| A3=B3 | A2=B2 | A1=B1 | A0>B0 | X | X | 1 | 0 | 0 | 1 | |
| A3=B3 | A2=B2 | A1=B1 | A0=B0 | 0 | 0 | 1 | 0 | 0 | 1 | |
| A3=B3 | A2=B2 | A1=B1 | A0=B0 | 0 | 1 | X | 0 | 1 | 0 | |
| A3=B3 | A2=B2 | A1=B1 | A0=B0 | 1 | 0 | X | 1 | 0 | 0 | |
| A3=B3 | A2=B2 | A1=B1 | A0<B0 | X | X | X | 1 | 0 | 0 | |
| A3=B3 | A2=B2 | A1<B1 | X | X | X | X | 1 | 0 | 0 | |
| A3=B3 | A2<B2 | X | X | X | X | X | 1 | 0 | 0 | |
| A3<B3 | X | X | X | X | X | X | 1 | 0 | 0 | |
| X | X | X | X | X | X | 0 | - | - | 0 | |

X = Don't Care

BLOCK DIAGRAM



ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS¹

| PARAMETER | V _{DD} (Vdc) | CONDITIONS | T _{LOW} ² | | +25°C | | | T _{HIGH} ² | | Units |
|--------------------------|--------------------------|--|-------------------------------|------|-------|------|------|--------------------------------|------|-------|
| | | | Min. | Max. | Min. | Typ. | Max. | Min. | Max. | |
| QUIESCENT DEVICE CURRENT | I _{DD} | V _{IN} = V _{SS} or V _{DD} All valid input combinations | — | 5 | — | 0.05 | 5 | — | 150 | μAdc |
| | | | — | 10 | — | 0.1 | 10 | — | 300 | |
| | | | — | 20 | — | 0.2 | 20 | — | 600 | |

NOTES: ¹ Remaining Static Electrical Characteristics are listed under "4000B Series Family Specifications".

² T_{LOW} = -55°C for C, D, F, H device.


= -40°C for E device.

T_{HIGH} = +125°C for C, D, F, H device.


= + 85°C for E device.

DYNAMIC CHARACTERISTICS (C_L = 50pF, T_A = 25°C)

| PARAMETER | V _{DD} (Vdc) | Min. | Typ. | Max. | Units |
|------------------------|-------------------------------------|------|------|------|-------|
| PROPAGATION DELAY TIME | t _{PLH} , t _{PHL} | 5 | — | 300 | ns |
| | | 10 | — | 125 | |
| | | 15 | — | 80 | |
| OUTPUT TRANSITION TIME | t _{TLH} , t _{THL} | 5 | — | 100 | ns |
| | | 10 | — | 50 | |
| | | 15 | — | 40 | |




Typical P-Channel
Source Current Characteristics





Typical N-Channel
Sink Current Characteristics

LOGIC DIAGRAM



APPLICATIONS INFORMATION


COMPARISON OF TWO N-BIT WORDS



This application demonstrates how these magnitude comparators can be cascaded to compare longer words. The example illustrated shows the comparison of two 20-bit words; however, the scheme is expandable to n-bits. As an example, one comparator can be used with five of the 20-bit comparators illustrated to expand the word length to 100-bits.

| WORD LENGTH | NUMBER OF PKGS |
|-------------|----------------|
| 1-4 bits | 1 |
| 5-20 bits | 2-6 |
| 21-100 bits | 8-31 |

JEDEC Standard Specifications



JEDEC STANDARD SPECIFICATIONS FOR DESCRIPTION OF "B" SERIES CMOS DEVICES

MAY 1976

Formulated by
JEDEC Solid State Products Council

NOTE: Solid State Scientific has taken part in the activities of the JEDEC Committee since its inception, and fully supports the following specifications. All part types manufactured by Solid State Scientific and marked with the designation "B" meet or exceed the industry standard CMOS specifications described herein.

1. PURPOSE AND SCOPE

1.1 Purpose

To develop a standard of "B" Series CMOS Specifications to provide for uniformity, multiplicity of sources, elimination of confusion, and ease of device specification and system design by users.

1.2 Scope

This Standard covers standard specifications for description of "B" Series CMOS devices.

2. DEFINITIONS

2.1 "B" Series

"B" Series CMOS includes both buffered and unbuffered devices.

2.2 "Buffered"

A buffered output is one that has the characteristic that the output "on" impedance is independent of any and all valid input logic conditions, both preceding and present.

3. STANDARD SPECIFICATIONS

3.1 Listing of Standard Specifications. Table 1 lists the standard specifications for "B" Series CMOS devices.

3.2 Absolute Maximum Ratings. In the maximum ratings listed below voltages are referenced to V_{SS} .

ABSOLUTE MAXIMUM RATINGS

| | | | |
|-------------------------------------|----------|------------------------|------|
| DC Supply Voltage | V_{DD} | -0.5 to + 18 | Vdc |
| Input Voltage | V_{IN} | -0.5 to $V_{DD} + 0.5$ | Vdc |
| DC Input Current (any one input) | I_{IN} | ± 10 | mAdc |
| Storage Temperature Range | T_S | -65 to + 150 | °C |

3.3 Recommended Operating Conditions. Recommended operating conditions are listed below.

RECOMMENDED OPERATING CONDITIONS

| | | | |
|-----------------------------|----------|--------------|-----|
| DC Supply Voltage | V_{DD} | +3 to + 15 | Vdc |
| Operating Temperature Range | T_A | | |
| Military-Range Devices | | -55 to + 125 | °C |
| Commercial-Range Devices | | -40 to + 85 | °C |

3.4 Designation of "B" Series CMOS Devices

Those parts which have analog inputs and/or outputs shall be included in the "B" Series providing those parts' maximum ratings and logical input and output parameters conform to the "B" Series, such as (including, but not limited to):

| | |
|-------|-------|
| 4051B | 4053B |
| 4052B | 4066B |

Products that meet "B" Series specifications except that the logical outputs are not buffered and the V_{IL} and V_{IH} specifications are 20% and 80% of V_{DD} , respectively, shall be marked with the UB designation, such as (including, but not limited to):

| | | | | | |
|--------|--------|--------|--------|--------|--------|
| 4000UB | 4002UB | 4011UB | 4023UB | 4041UB | 4069UB |
| 4001UB | 4007UB | 4012UB | 4025UB | 4049UB | |

STATIC CHARACTERISTICS

| PARAMETER | | TEMP. RANGE | V _{DD} (V _{dc}) | CONDITIONS | LIMITS | | | | | | UNITS | | |
|-----------------|---------------------------------|---------------------------|------------------------------------|--|------------------------------|------|-------|------|------|---------------------|-------|------------------|------------------|
| | | | | | T _{LOW} * | | +25°C | | | T _{HIGH} * | | | |
| | | | | | Min. | Max. | Min. | Typ. | Max. | Min. | | Max. | |
| I _{DD} | Quiescent Device Current | Mil | 5 | V _{IN} =V _{SS} or V _{DD} | — | 0.25 | — | — | 0.25 | — | 7.5 | μA _{dc} | |
| | | | 10 | | — | 0.5 | — | — | 0.5 | — | 15 | | |
| | | | 15 | | — | 1.0 | — | — | 1.0 | — | 30 | | |
| | | GATES | Comm | 5 | All valid input combinations | — | 1.0 | — | — | 1.0 | — | 7.5 | μA _{dc} |
| | | | | 10 | | — | 2.0 | — | — | 2.0 | — | 15 | |
| | | | | 15 | | — | 4.0 | — | — | 4.0 | — | 30 | |
| | BUFFERS, FLIP-FLOPS | Mil | 5 | V _{IN} =V _{SS} or V _{DD} | — | 1.0 | — | — | 1.0 | — | 30 | μA _{dc} | |
| | | | 10 | | — | 2.0 | — | — | 2.0 | — | 60 | | |
| | | | 15 | | — | 4.0 | — | — | 4.0 | — | 120 | | |
| | | Comm | 5 | All valid input combinations | — | 4.0 | — | — | 4.0 | — | 30 | μA _{dc} | |
| | | | 10 | | — | 8.0 | — | — | 8.0 | — | 60 | | |
| | | | 15 | | — | 16.0 | — | — | 16.0 | — | 120 | | |
| | MSI | Mil | 5 | V _{IN} =V _{SS} or V _{DD} | — | 5 | — | — | 5 | — | 150 | μA _{dc} | |
| | | | 10 | | — | 10 | — | — | 10 | — | 300 | | |
| | | | 15 | | — | 20 | — | — | 20 | — | 600 | | |
| | | Comm | 5 | All valid input combinations | — | 20 | — | — | 20 | — | 150 | μA _{dc} | |
| | | | 10 | | — | 40 | — | — | 40 | — | 300 | | |
| | | | 15 | | — | 80 | — | — | 80 | — | 600 | | |
| V _{OL} | Low-Level Output Voltage | All | 5 | V _{IN} =V _{SS} or V _{DD} I _O ≤1μA | — | 0.05 | — | — | 0.05 | — | 0.05 | V _{dc} | |
| 10 | — | 0.05 | — | | — | 0.05 | — | 0.05 | | | | | |
| 15 | — | 0.05 | — | | — | 0.05 | — | 0.05 | | | | | |
| V _{OH} | High-Level Output Voltage | All | 5 | V _{IN} =V _{SS} or V _{DD} I _O ≤1μA | 4.95 | — | 4.95 | — | — | 4.95 | — | V _{dc} | |
| 10 | 9.95 | — | 9.95 | | — | — | 9.95 | — | | | | | |
| 15 | 14.95 | — | 14.95 | | — | — | 14.95 | — | | | | | |
| V _{IL} | Input Low Voltage | All | 5 | V _O = 0.5V or 4.5V 1.0V or 9.0V 1.5V or 13.5V I _O ≤1μA | — | 1.5 | — | — | 1.5 | — | 1.5 | V _{dc} | |
| 10 | — | 3.0 | — | | — | 3.0 | — | 3.0 | | | | | |
| 15 | — | 4.0 | — | | — | 4.0 | — | 4.0 | | | | | |
| V _{IH} | Input High Voltage | All | 5 | V _O = 0.5V or 4.5V 1.0V or 9.0V 1.5V or 13.5V I _O ≤1μA | 3.5 | — | 3.5 | — | — | 3.5 | — | V _{dc} | |
| 10 | 7.0 | — | 7.0 | | — | — | 7.0 | — | | | | | |
| 15 | 11.0 | — | 11.0 | | — | — | 11.0 | — | | | | | |
| I _{OL} | Output Low (Sink) Current | Mil | 5 | V _O =0.4V, V _{IN} =0 or 5V V _O =0.5V, V _{IN} =0 or 10V V _O =1.5V, V _{IN} =0 or 15V | 0.64 | — | 0.51 | — | — | 0.36 | — | mA _{dc} | |
| | | | 10 | | 1.6 | — | 1.3 | — | — | 0.9 | — | | |
| | | | 15 | | 4.2 | — | 3.4 | — | — | 2.4 | — | | |
| | | Comm | 5 | V _O =0.4V, V _{IN} =0 or 5V V _O =0.5V, V _{IN} =0 or 10V V _O =1.5V, V _{IN} =0 or 15V | 0.52 | — | 0.44 | — | — | 0.36 | — | mA _{dc} | |
| | | | 10 | | 1.3 | — | 1.1 | — | — | 0.9 | — | | |
| | | | 15 | | 3.6 | — | 3.0 | — | — | 2.4 | — | | |
| I _{OH} | Output High (Source) Current | Mil | 5 | V _O =4.6V, V _{IN} =0 or 5V V _O =9.5V, V _{IN} =0 or 10V V _O =13.5V, V _{IN} =0 or 15V | -0.25 | — | -0.2 | — | — | -0.14 | — | mA _{dc} | |
| | | | 10 | | -0.62 | — | -0.5 | — | — | -0.35 | — | | |
| | | | 15 | | -1.8 | — | -1.5 | — | — | -1.1 | — | | |
| | | Comm | 5 | V _O =4.6V, V _{IN} =0 or 5V V _O =9.5V, V _{IN} =0 or 10V V _O =13.5V, V _{IN} =0 or 15V | -0.2 | — | -0.16 | — | — | -0.12 | — | mA _{dc} | |
| | | | 10 | | -0.5 | — | -0.4 | — | — | -0.3 | — | | |
| | | | 15 | | -1.4 | — | -1.2 | — | — | -1.0 | — | | |
| I _{IN} | Input Current | Mil | 15 | V _{IN} =0 or 15V | — | ±0.1 | — | — | ±0.1 | — | ±1.0 | μA _{dc} | |
| Comm | 15 | V _{IN} =0 or 15V | — | ±0.3 | — | — | ±0.3 | — | ±1.0 | μA _{dc} | | | |
| C _{IN} | Input Capacitance per Unit Load | All | — | Any Input | — | — | — | — | 7.5 | — | — | pF | |

*T_{LOW} = -55°C for Military Temp. Range device, -40°C for Commercial Temp. Range device.

*T_{HIGH} = +125°C for Military Temp. Range device, +85°C for Commercial Temp. Range device.

CMOS Fundamentals



CMOS FUNDAMENTALS

MOS DEVICES

Complementary MOS (CMOS) logic, memory, and switching circuits are constructed with P-channel and N-channel enhancement-mode MOS transistors diffused on a monolithic silicon chip. Field-effect transistors are unipolar devices; that is, their operation is based on a function of only one type of charge carrier—holes in P-channel types, and electrons in N-channel types.

A simplified cross-section of an N-channel enhancement-mode MOS transistor is shown in Figure 1. This transistor is a four-terminal device. In CMOS logic applications, the substrate and the source are usually connected to a common point, which in the N-channel transistor is the most negative potential or V_{SS} . With no voltage applied between gate and source, the two N+ diffusions are electrically isolated from each other and no conduction occurs. As an increasingly positive voltage is applied to the gate, an N-type inversion layer begins to form at the surface between source

and drain. When a threshold voltage V_{TN} is reached, the inversion layer just begins to connect source and drain, allowing some conduction. As the gate voltage increases further, the inversion layer is driven deeper, resulting in greater conductivity from source to drain. A saturation point is reached when $+V_{DS}$ is forced higher than $V_G - V_{TN}$; the device, therefore, is self-current-limiting. Figure 2 shows typical drain characteristics for an N-channel MOS transistor. Note the similarity to equivalent vacuum tube characteristics.

Operation of the P-channel device (Figure 3) is similar, except that the source and substrate are connected to the most positive potential, V_{DD} . A P-type inversion layer, or channel, is formed when a negative voltage is applied to the gate with respect to the source. The threshold voltage V_{TP} is defined as that value of V_G which causes a specified minimum conductivity between source and drain. Saturation occurs when the drain-to-source voltage V_{DS} is forced more negative than $V_G - V_{TN}$. Figure 4 shows typical drain characteristics for a P-channel MOS transistor.




Figure 1




Figure 2




Figure 3




Figure 4




Figure 5

A major feature of the metal oxide semiconductor is the very high input resistance resulting from the dielectric oxide isolation between the gate and the channel. The input resistance is virtually unaffected by the polarity of the gate bias. Also, whatever leakage current does exist between gate and source is relatively independent of ambient temperature variations.

CMOS DEVICES

Complementary MOS logic circuits employ both P-channel and N-channel enhancement-mode MOS transistors. They have opposite, or complementary, switching characteristics and can therefore be used as virtually ideal switching components. Consider the implementation shown in Figure 5. The circuit consists of one P-channel device and one N-channel device. Note that to form the N-channel device, a P-doped "tub" must be created into which the device is placed. "Channel stops" must also be placed between the P-tub and the P-drain to prevent parasitic channeling effects.

When a positive voltage V_{DD} is applied at the input, the P-channel switches off and the N-channel switches on. Thus, the output is connected to V_{SS} through the low on-resistance of the N-channel device. Alternatively, applying V_{SS} to the input turns off the N-channel and turns on the P-channel. In this state, the output is connected to V_{DD} through the equivalent on-resistance of the P-channel device. Therefore, an input voltage of V_{DD} results in an output voltage of V_{SS} , and an input voltage of V_{SS} results in an output voltage of V_{DD} . The circuit is a simple digital inverter.

Gates

Any logic function capable of being constructed with ideal switches can be implemented in CMOS. Adding a parallel P-channel device and a series N-channel device to the basic inverter transforms the circuit into a positive-logic 2-input NAND gate (Figure 6). Adding a parallel N-channel and a series P-channel device instead transforms the inverter into a 2-input NOR gate.




Figure 6




Figure 7

Note that in each circuit there exists no DC path from V_{DD} to V_{SS} ; if a connection is made to V_{SS} through the N-channels, a corresponding P-channel blocks the connection to V_{DD} ; alternatively, if the P-channels are on, then a corresponding N-channel is off. Therefore, very low power dissipation results without sacrificing low output impedance.

Combinational Logic

Numerous functional logic combinations are easily implemented in CMOS. A rule of thumb is series N-channel devices for AND/NAND functions, and parallel N-channel devices for OR/NOR functions. The P-channel devices are then configured in the circuit dual of the N-channel devices. Figure 7 shows the common AND/OR/INVERT (AOI) construction.

Transmission Gates (Analog Switches)

The CMOS transmission gate, or analog switch, is a single-pole single-throw (SPST) switch formed by the parallel connection of a P-channel and an N-channel




Figure 8


device (Figure 8). The inverter is required to apply the correct polarity gate voltage to both transistors simultaneously. The switch is purely ohmic, with an ON-resistance of about 200 - 400 Ω and OFF-resistance typically about $10^{11}\Omega$. There is no offset voltage across the switch. These characteristics approach those of the ideal switch ($R_{ON} = 0$, $R_{OFF} = \infty$). A single-transistor switch results in a source-follower circuit in which gate cut-off occurs and limits the load to charge only to within one threshold of the gate. When two complementary devices are operated in parallel, one of the two channels is always being operated as a drain-loaded stage, permitting a low-impedance path for all switched signal voltages.

The transmission gate is useful in digital applications as well. Combinational logic functions can be implemented, and the device provides a simple method for constructing 3-state (bussed) systems.

4000 SERIES DEVICES

Using basic CMOS techniques, Solid State Scientific has developed the SCL4000 Series Family of building block elements and complex functions. Devices numbered 40xx and 45xx are equivalents to industry 40xx and 45xx types. The designation 44xx indicates proprietary devices; they are usually variations on standard 40xx devices, making them more suitable for specific applications.

Design Information



CMOS DESIGN CONSIDERATIONS

This section is presented as an aid to the systems designer in proper application and use of CMOS devices. Areas such as power supply techniques and dissipation characteristics, thermal factors, operating considerations, interfacing parameters, and ac fan-out are covered in some detail.

POWER SUPPLY CONSIDERATIONS

CMOS offers the designer several important advantages over other technologies:

1. wide operating voltage range
2. very low power dissipation
3. constant switching threshold voltage ratio

These advantages permit operation from unregulated supplies, simplify filtering requirements, and eliminate the need for cooling equipment. In addition, battery-operated systems, either stand-alone or back-up, are feasible.

OPERATING VOLTAGE RANGE

Minimum and maximum operating voltages for all Solid State Scientific CMOS devices are specified as 3 and 15 Vdc, respectively, with an absolute limitation of -0.5 and 18 Vdc, applied at the V_{DD} terminal relative to V_{SS} . The minimum value of 3 Vdc represents the maximum expected value of either P-channel or N-channel transistor threshold voltages. Operation at lower voltages may, therefore, prevent half of the device from turning on. The absolute limitation of -0.5 Vdc merely prevents the internal device junctions from becoming forward-biased; the circuit is obviously non-operational under this condition.

The maximum value prevents avalanche of these internal junctions. While the 18 Vdc restriction on low-current avalanche is somewhat conservative, there is the possibility of on-chip current transients turning on the parasitic bipolar transistors inherent in CMOS construction. The chip can enter secondary breakdown because these transients can easily exceed the 10 - 50 mA sustaining current required. The result is a short circuit reflected at the supply and catastrophic device failure (see Figure 1).




Fig. 1 — Secondary breakdown characteristics

POWER DISSIPATION

The quiescent, or DC, power dissipation component consists normally of only leakage currents across reverse-biased diode junctions. This is true because, in the quiescent state, there exists no direct path between V_{DD} and V_{SS} other than these leakages, which are typically in the nanoampere region. In reality, certain surface effects will contribute to the quiescent dissipation. These factors have been taken into account in specifying the worst-case values given in the individual device data sheets; these values should be used by the designer in determining the necessary capacity of standby battery or other back-up supplies.

Dynamic, or ac, dissipation consists of two factors associated with switching: the power delivered from the supply to the load, and the current which momentarily flows between the supplies during switching. The first of these represents the energy required to charge and discharge the load capacitance (plus the small internal capacitances). The energy stored by a capacitor is given by:

$$E_s = \frac{1}{2} C V^2$$

Since CMOS outputs switch from supply to supply, and the load capacitance is both charged and discharged once each cycle of the output frequency f , this component of power dissipation is given by:

$$P_n = \frac{2E_s}{t} = C_L V_{DD}^2 f \quad (V_{SS} = 0 \text{ Vdc})$$

Note that this component increases linearly with load capacitance C_L , operating frequency f , and the square of the operating voltage V_{DD} . Figure 2 shows this functional dependence for a typical CMOS gate.

The Figure assumes input rise and fall times of 20ns. As these transition times increase, however, cur-




Fig. 2 — Typical gate power dissipation characteristics




Fig. 3 — Typical current and voltage transfer characteristics

rent flows between the supplies because both P-channel and N-channel transistors are biased on momentarily. This through-current is a complex function of fabrication parameters, device geometries, operating voltage, temperature, rise and fall times, and operating frequency. A typical waveform of through-current I_{TC} in relation to voltage transfer characteristics is shown in Figure 3.

Power dissipation due to through-current can be shown to be proportional to the factors described above in the following way:

$$P_{TC} \propto f(t_r + t_f)V_{DD}$$

where the constant of proportionality is dependent upon device parameters.

The relationship between supply current I_{DD} and I_{SS} , load capacitance, and input rise and fall time is illustrated in Figure 4.

The waveforms (a) show I_{DD} , I_{SS} , and the through-current I_{TC} for a load capacitance of 15pF and t_r , t_f of 10μs. The smaller of the I_{DD} and I_{SS} pulses represents the maximum through-current of the device. The slight amplitude differences between pulses represent the current delivered to the load. The magnitude of the through-current pulses in (a) is used as the standard for (b) and (c).

The input rise and fall times are decreased to 400ns in (b). Here again, the smaller current pulses represent through-current, which has somewhat decreased from (a). Note that since the width of the current pulse has also decreased, the magnitude of the current delivered to the 15pF load has increased (to deliver the same charge).

Load capacitance in (c) is increased to 65pF, and input transition times decreased to 40ns. Through-current pulses have virtually disappeared, except for the current charging and discharging internal capacitance. The magnitude of the load current, however, has increased due to the increased load and narrower current pulse width.

All complex CMOS functional devices employ buffered inputs to minimize the through-current effects described here. Caution is urged when using high-current buffers and unbuffered gates in conjunction with large loads and high operating voltages; long input rise and fall times may cause the device power dissipation restriction to be exceeded.

REGULATION AND BATTERY OPERATION

The wide operating voltage range and constant switching voltage ratio of CMOS permit use of simple unregulated supplies, as shown in Figure 5.




Fig. 4 — Switching current waveforms




Fig. 5 — CMOS unregulated power supply




Fig. 6 — CMOS battery back-up power supply

The primary considerations with a supply of this type are:

1. The resulting voltage must at all times fall within the specified limits of the system. This is the purpose of the zener diode.
2. The lowest instantaneous voltage must permit the system to operate at the worst-case system speed parameters.
3. The filter capacitor must be able to furnish the worst-case system switching current. R_S is selected to supply the peak transient current of the system plus the necessary zener current when diode D_1 is forward biased (high portion of V_S cycle). The capacitor is selected to supply the system switching current and quiescent current when D_1 is reverse biased (low portion of V_S cycle).

Replacing the filter capacitor with a rechargeable battery provides an easy method of implementing a back-up supply (see Figure 6). Here, R_S supplies also the charging current for the battery. The zener diode has a breakdown voltage between the battery voltage and the maximum device rating. It prevents power line transients from developing damaging voltage spikes due to the characteristic impedance of the battery. Systems may be kept operating over long periods of time on such a supply.

CMOS power supplies may also be derived from higher-voltage dc supplies as shown in Figure 7. The zener diode regulates the CMOS supply voltage; resistor R_S supplies the load and zener currents, while the filter capacitor maintains the voltage during switching transients.

FILTERING

Most CMOS systems require less filtering on supply busses than other logic families. While V_{DD} and V_{SS} line drops are generally small due to the small currents involved, a few capacitors per board are recommended to prevent switching transients from causing excessive voltage variations. This is especially true with devices which have long rise and fall time input signals. As described in the discussion of through-current, large supply currents can result under these conditions. An extra $0.1 \mu F$ capacitor may be required to supply the current surge without causing excessive supply voltage drops. Similarly, devices which operate synchronously, such as counters and shift registers, supply large charging currents to several loads during switching. Here again, $0.1 \mu F$ bypass capacitors may be indicated in such cases.




Fig. 7 — Deriving CMOS power from high voltage DC source

THERMAL FACTORS

Transfer characteristics of CMOS devices exhibit excellent stability over temperature. This feature allows the ambient temperature range of CMOS devices to be a function of package type. This section discusses techniques of thermal management and the variation of device characteristics with temperature.

THERMAL MANAGEMENT

Circuit performance and long-term reliability are maximized at low junction temperatures. Power dissipation is the common source of heat in any system; the negligible power consumed in the quiescent state in CMOS circuits is a major factor in maintaining performance and reliability. In general, operation at moderate speeds and voltages does not require consideration of the package dissipation restriction of 300 mW. In high-frequency, high-voltage, large-load, or analog applications, however, these considerations become important.

The average junction temperature is a function of device power dissipation and the ability of the packaging system to remove the generated heat. This is expressed in the following formula:

$$T_J = T_A + P_D (\Theta_{JA})$$

where T_J = junction temperature

T_A = ambient temperature

P_D = calculated power dissipation

Θ_{JA} = thermal resistance, junction-to-ambient

Worst-case and typical values of Θ_{JA} for common IC package types in still air and without heat sinking are shown in the table:

| Package Type | $\Theta_{JA} (^{\circ}\text{C}/\text{watt})$ | |
|--|--|-----|
| | Typ | Max |
| Epoxy B Dual-in-line 14- or 16-lead | 135 | 200 |
| Cerdip Dual-in-line 14- or 16-lead | 100 | 155 |
| Epoxy B Dual-in-line 24-lead | 95 | 140 |
| Ceramic Dual-in-line 24-lead | 70 | 100 |

These figures should be consulted in cases where there is reason to believe that device dissipation may be excessive.




Fig. 8 — Typical inverter voltage transfer characteristics as a function of temperature

PARAMETRIC THERMAL VARIATION

All operational parameters vary to some degree with temperature. Since CMOS devices may be used over very wide temperature ranges, the designer should be familiar with the effects of these thermal variations. They fall into three categories: transfer characteristics, leakage current, and channel resistance effects.

1. Transfer Characteristics

Figure 8 illustrates the negligible variation in transfer voltage over the entire military temperature range. This results from the tendency of P-channel and N-channel transistor threshold voltages to track together. Under similar conditions, a bipolar device threshold may vary more than 40%. This feature makes threshold-dependent circuits such as oscillators and multi-vibrators feasible in systems with a wide range of operating temperature.

2. Leakage Current

As expected, since device leakage current is normally leakage across reverse-biased silicon junctions, temperature variation of this parameter follows the traditional diode leakage characteristic, i.e., approximately doubling with each 11°C rise in temperature.

3. Channel Resistance

Such parameters as output drive current (I_{OH} , I_{OL}), switching through-current (I_{TC}), propagation delays (t_{PLH} , t_{PHL}), and output transition times (t_{TLH} , t_{THL}) are direct effects of channel resistance. These parameters vary as channel resistance varies—0.3%/°C. Current characteristics decrease with increasing temperature at this rate; this factor is employed in specifying low- and high-temperature limits for these parameters on device data sheets. Switching parameters increase at this rate with temperature; this dependence must be considered by the designer in order to guarantee system dynamic performance over temperature.

INPUT RATINGS

The high impedance of a CMOS input results from the insulating oxide between the gate and the channel. This high impedance coupled with the 5pF input capacitance make CMOS inputs excellent energy storage nodes, allowing buildup of large voltages. Input diode protection networks are used, therefore, to conduct excess energy to the supply rails, thus protecting the gate regions from damage. These diodes affect certain device operations, as described in the following discussion of general input characteristics.




Fig. 9 — Typical multiple-input switching transfer characteristics for conventional 4-input NAND gate

INPUT VOLTAGE RANGE

Input signals should never exceed the range from 0.5 Vdc more negative than V_{SS} to 0.5 Vdc more positive than V_{DD} . This prevents forward biasing the input diodes, with the attendant possibility of entering a latch-up mode due to high-current transients. Further details may be found in the preceding discussion of "Power Supply Considerations" and later on in this section.

NOISE IMMUNITY

Noise immunity as specified in CMOS data sheets refers to the worst-case input voltage levels which will maintain guaranteed output conditions and will not produce a change in logic state. Specifically, the data sheets specify the minimum input high-level voltage (V_{IH}) and maximum input low-level voltage (V_{IL}) which guarantee an output voltage of no lower than 90% of V_{DD} or no higher than 10% of V_{DD} under no-load conditions ($|I_a| < 1\mu A$). Since the switching threshold voltage of a CMOS inverter is typically 50% of the supply and fairly sharp, and output voltages are close to the supplies, these input voltages tend to be symmetric and close to the ideal situation of 50% noise immunity. In fact, V_{IH} is typically 55% of V_{DD} , and V_{IL} is 45% of V_{DD} . (Note: the older designations of V_{NH} and V_{NL} can be related to V_{IH} and V_{IL} by the following:

$$V_{NH} = V_{DD} - V_{IH} (\min)$$

$$V_{NL} = V_{IL} (\max) - V_{SS}$$

Worst-case specifications under these output voltage requirements are 20% of V_{DD} for the conventional SSI devices (Note: the older 30% noise immunity specification allowed much greater output voltage variations). This specification can be greatly improved by making the transfer voltage characteristic sharper, i.e., increasing device gain. In 1970, Solid State Scientific developed the technique of buffering gate outputs for increased gain; since that time, all CMOS gates in the 4000 series have been buffered. The industry began to realize the superiority of this structure for digital logic applications only with the recent agreement on "B" series CMOS.

Buffered outputs become even more important in maintaining noise immunity with the variation in transfer voltage with input pattern on multiple input gates. Figure 9 shows the typical range in switching voltage for a conventional 4-input NAND gate. Observe that $V_{IH} (\min)$ degrades as a function of the number of inputs switching. This pattern sensitivity is reversed for NOR




Fig. 10 — Typical signal-line noise-immunity

gate types. Buffering the device outputs, although the variations in switching voltage are unaffected, maintains greater noise immunity over all input conditions resulting from the much more nearly ideal transfer characteristic. Further improvement is attained by the requirement that CMOS gate structures consist of no more than three inputs per section; this decreases the variation in switching voltage, as compared with the 4-input gate in Figure 9. There are many other advantages to the buffered-gate concept. Each one is fully discussed in following sections.

Note that Solid State Scientific specifies and measures noise immunity under worst-case input combinations. This factor gives the designer a more realistic description of device operation, in view of the above discussion.

Noise immunity specifications refer to input signals; however, a similar discussion applies to noise introduced on power and ground lines. CMOS devices are sensitive only to negative power line transients and positive ground line transients. The magnitude of power- and ground-line noise immunity approaches that of signal-line noise immunity because of the close tracking of output voltage with supply in either state.

The relatively slow response times of CMOS devices tend to act as a noise filter: extremely short spikes of greater magnitude than the dc noise immunity limits are prevented from propagating through the device. A typical example of dc noise immunity is shown in Figure 10.

Another source of noise introduction into CMOS devices is crosstalk from high noise voltages coupled through small capacitances. Since CMOS devices have much higher output impedance than equivalent TTL types, they are much more sensitive than TTL to such capacitively-coupled noise. The designer should consult the individual device data sheets to determine the magnitude of current which will pull a CMOS output into the threshold region of the driven CMOS inputs, and use good interconnection techniques to prevent this type of crosstalk from interfering with system operation.

INPUT CURRENT

The high input impedance of CMOS results in an input current of typically 10pA_{dc}. Worst-case specifica-

tions provide allowance for surface effects, and guarantee no higher than 100nA_{dc} at room temperature.

These characteristics apply for input voltages within the permitted range, as described above. There are a certain class of applications, however, such as oscillators and multivibrators, for which input voltages normally exceed the supplies by large margins. In these instances, the input protection diodes can be utilized as clamps if the input current is restricted to 10mA_{dc} or less. This is usually accomplished by adding a series resistor at the affected input. The minimum value of this resistor is calculated from the worst-case input voltage and the input current limitation; the maximum value should be determined by the effect which the combination of this resistor and the 5pF input capacitance has on operating speed and frequency.

UNUSED INPUTS

If a CMOS input is left unterminated, it can acquire unpredictable voltages through coupling with stray external capacitances and internal crosstalk. Since these voltages are normally within the supply range, the input protection diodes cannot conduct away this accumulated energy. Since both P- and N-channel transistors spend significant time in their "on" states, both power dissipation and device noise immunity degrade. Even catastrophic failure can result from these conditions. Therefore, all inputs should be connected to an appropriate supply voltage, or to another driven CMOS input. If a portion of a device is not loaded, its inputs must also be properly terminated.

INPUT WAVEFORMS

The maximum input rise and fall time specification for sequential circuits is typically in the 3 μ s to 15 μ s range, depending on supply voltage. This prevents ambiguous logic states and false clocking due to switching voltage variations and skew problems. Power dissipation also increases as logic elements spend more time in the switching region.

When sequential circuits are cascaded, the maximum rise and fall times of the clock input should be equal to or less than the transition times of the data outputs driving data inputs, plus the propagation delay of the output driving stage for the output capacitive load. If setup and hold times are specified on device data sheets, they must also be taken into account.

Schmitt trigger constructions may be indicated to bring rise and fall times within indicated bounds.

INPUT PROTECTION NETWORKS

Because the gate oxide of a CMOS transistor has extremely high resistance, even a very-low-energy source (such as a static charge) is capable of developing the breakdown voltage of approximately 100V. This results in permanent damage to the device. Therefore, gate protection structures are employed to conduct excess energy away from the gate region. These structures, however, are only capable of protecting from overvoltages of less than 1000V. While this is normally sufficient for in-system transients, device handling can produce overvoltages of one or two orders of magnitude greater. Handling precautions are recommended when using CMOS devices. Some suggested procedures appear in the section entitled "Handling Precautions for CMOS Devices".

The input protection structure utilized on 4000 Series devices is shown in the diagram of a typical




Fig. 11 — Gate-oxide protection circuit used in 4000 Series integrated circuits

CMOS device in Figure 11. The circuit consists of diodes D1 and D2, which clamp the input voltage to V_{SS} and V_{DD} , respectively, and series resistor R, whose nominal value is 1.5K Ω . Avalanche voltages of the diodes are well below the breakdown voltage of the gate oxide. The resistor provides a small delay with the 5pF input capacitance which allows excess energy to be conducted away before reaching the gate region.

When the diodes are used as clamps for oscillators, multivibrators, etc., input current must be limited to less than 10mA to protect against both possible latchup and long-term degradation due to metal migration.

In a system power-up or power-down sequence, power must be applied to the device before the introduction of low-impedance driving signals. This sequence must also be maintained while troubleshooting systems where devices or modules must be removed from or inserted into a system.

OUTPUT CHARACTERISTICS

The amount of current which a CMOS output is capable of sinking or sourcing is a function of the channel impedance of the driving structure. These characteristics vary with voltage and temperature; these variations were discussed previously. Transistor characteristics are illustrated on most device data sheets.

BUFFERED OUTPUTS

Consider the conventional CMOS 2-input NAND gate structure of Figure 12. Since the N-channel devices are in series, their on-resistance must be decreased (larger chip area) to hold the output low impedance (or sink current parameter) within specification. As the number of gate inputs increases, even larger N-channel transistors are required. Also, since the P-channel de-

vices are connected in parallel, the output high impedance (and, therefore source current) is a function of input pattern, i.e., the number of devices turned on. Solid State Scientific gates have buffered outputs: small geometry logic transistors are used to generate the required function, while only one large P-channel and one large N-channel device form the output. This technique reduces chip size; in addition, output impedance is no longer a function of input pattern. This means that dc and ac fanout are constant, and the user need not concern himself with several sets of loading requirements for each device.

OUTPUT LOADING

Since CMOS outputs driving CMOS inputs switch essentially from supply to supply while the driven inputs draw very little current (typically 10 pAdc), dc fanout can usually be ignored, except in bus-oriented systems. Of much greater importance is ac fanout, discussed below. However, several precautions are necessary to prevent damaging the output structure.

The outputs of most CMOS devices consist of a complementary pair. This structure prohibits the connection of outputs in a "wire-OR" configuration. Three-state output devices should be used to achieve this configuration. It is possible, however, to parallel inputs and outputs of devices to provide increased drive. This practice should be restricted to devices within the same package to avoid current hogging.

Note that because of the negative temperature coefficient of MOS transistors, there is built-in short-term burn-out protection. In general, devices with standard output characteristics may be shorted to the supply rails at low operating voltages. Precautions are necessary with higher voltages and/or high-current buffers, in which saturation currents can cause the maximum dissipation limitation to be exceeded.

CMOS drive capability is limited if the outputs are required to maintain a specified logic level. However, if the output is used to drive a discrete device such as a transistor or LED, large currents (within maximum ratings) can be achieved by operating the device in the saturated region.

The output impedance of a CMOS device can be employed as an effective means of providing delay and integrator functions when loaded with a capacitor. However, in any application which places a sizable capacitive load on a CMOS output, care must be taken to prevent damaging transient currents when power is removed. If the capacitive load is charged when the power supply is removed, the diode from the output to the supply (output D2 in Figure 11) forms the discharge path as it becomes forward biased. Series resistance should be added to the output in order to prevent discharge currents above 1mA.




Figure 12

INTERFACE PARAMETERS

Table I provides interface parameters between CMOS and other logic families under the following conditions:

1. The power-supply voltage level and tolerances are chosen to accommodate the interfaced elements, since CMOS devices will operate over a much wider range.
2. The logic levels at the interface will meet or exceed the specified worst-case logic levels of the other elements.
3. Fan-out rules at the interface are derived from the current sourcing or sinking capability of the driving element.

TABLE I. CMOS INTERFACE PARAMETERS

| INTERFACE | INTERFACE NOISE MARGIN | | INTERFACE LOGIC LEVELS | | INTERFACE MAXIMUM FAN OUT | REMARKS |
|--------------|------------------------|--------|------------------------|--------|---------------------------|--|
| | "1" | "0" | "1" | "0" | | |
| CMOS-CMOS | 1.5V | 1.5V | 3.5V | 1.5V | > 50 | 5-volt system |
| | 3.0V | 3.0V | 7.0V | 3.0V | > 50 | 10-volt system |
| | 4.0V | 4.0V | 11.0V | 4.0V | > 50 | 15-volt system |
| CMOS-TTL/DTL | 2.5V | 0.4V | 2.0V | 0.8V | 2 | Buffers only |
| TTL/DTL-CMOS | 1.1V | 1.1V | 3.5V | 1.5V | See Remarks | 2K Ω pull-up resistor for TTL or open-collector DTL. Fan-out determined by dynamic requirements |
| CMOS-LTTL | 2.5V | 0.5V | 2.0V | 0.7V | 2 | Standard "B" Series Output Drive |
| LTTL-CMOS | 1.1V | 1.2V | 3.5V | 1.5V | See Remarks | 3K Ω pull-up resistor. Fan-out determined by dynamic requirements |
| CMOS-LSTTL | 2.5V | 0.4V | 2.0V | 0.8V | 1 | Standard "B" Series Output Drive |
| LSTTL-CMOS | 1.1V | 1.1V | 3.5V | 1.5V | See Remarks | 3K Ω pull-up resistor. Fan-out determined by dynamic requirements. |
| CMOS-HTL | 5.0V | 5.0V | 8.5V | 6.5V | 1 | |
| HTL-CMOS | 2.5V | 2.5V | 11.0V | 4.0V | > 50 | Active pull-up HTL |
| | 3.5V | 3.5V | | | > 50 | Passive pull-up HTL with 2K Ω to 5K Ω pull-up resistor. |
| CMOS-MOS | 3.0V | 4.0V | -3.0V | -9.0V | > 50 | High threshold PMOS: $V_{SS}-V_{DD}=13V$ |
| | 2.5V | 6.0V | 2.5V | 1.0V | > 50 | Low threshold PMOS: $V_{SS}-V_{DD}=10V$ |
| MOS-CMOS | 3.9V | 3.9V | -3.9V | -9.1V | > 50 | High threshold PMOS: $V_{SS}-V_{DD}=13V$ |
| | 3.0V | 3.0V | 2.0V | -2.0V | > 50 | Low threshold PMOS: $V_{SS}-V_{DD}=10V$ |
| CMOS-ECL | 0.225V | 4.325V | -1.105 | -1.475 | 2 | $V_{DD}=\text{ground}$ $V_{SS}=-5.2V$ |
| ECL-CMOS | 0.66V* | 1.56V* | -1.56V | -3.64V | > 50 | $V_{DD}=\text{ground}$ $V_{SS}=-5.2V$ |

* typical with transistor driver

NOTES: 1. Interface Noise Margin

For "1" Column — difference between output high level of one device and input high level of next device.

For "0" Column — difference between output low level of one device and input low level of next device.

2. Interface Logic Level Worst-case threshold level going from one device to the input of another.

DYNAMIC CONSIDERATIONS

The operating speed of a CMOS logic system is dependent upon signal propagation delays, output transition times, and associated characteristics. These parameters vary as a function of output load capacitance (ac fanout), operating voltage, and device temperature.

All device data sheets give dynamic characteristics at V_{DD} 5, 10, and 15 Vdc, 50pF load capacitance, and 25°C ambient temperature.

CAPACITIVE LOADING

The higher output impedance of CMOS devices, in comparison to TTL, make them more sensitive to capacitive loading (ac fan-out). A linear relationship exists between dynamic parameters and load capacitance, which is to be expected: loads are charged and discharged by the resistance of the driving transistor channel.

The buffered gate output structure pioneered by Solid State Scientific in 1970 provides significantly better performance than conventional CMOS gate structures. The single stage output makes delays and transition times independent of input pattern and less sensitive to capacitive loading. In addition, the extra gain stages provide significant pulse shaping of slow transition inputs — when input rise and fall times increase, the conventional gate exhibits an increase in output transition time, while the buffered gate transition times remain unchanged. This feature eliminates progressive deterioration of pulse characteristics in a system. These buffered outputs are designed for symmetric transition times, as opposed to the conventional types.

Special considerations must be given to output transition times and propagation delays when driving synchronous systems with edge triggered inputs. Consult the section on "Input Waveforms".

It should be noted that the extra gain stages in a buffered-output gate exhibit very sharp transfer characteristics. In certain applications, notably oscillators, multivibrators, or poor input transitions, this may result in ringing or even oscillation at the switching point. For this reason, Solid State Scientific manufactures several simple unbuffered inverters (4007UB, 4069UB, 4449UB) and unbuffered 2-input gates (4001UB, 4011UB). Since these types exhibit none of the features of buffered outputs, it is recommended that some pulse shaping be employed to permit use of the buffered structures wherever possible.

VOLTAGE EFFECTS

Increasing the supply voltage from 5Vdc to 10Vdc at least doubles the operating speed of CMOS devices. Increasing to 15V results in another increase, usually far less, at a substantial penalty in power dissipation. The increase in speed is a direct effect of the lower channel resistance; the increase in power dissipation is a symptom of higher charging currents to load capacitances.

Dynamic characteristics at voltages not given on device data sheets may be interpolated from specified data.

TEMPERATURE VARIATIONS

As the temperature of a CMOS device increases, carrier mobility decreases, resulting in an increase in channel impedance. Therefore, dynamic parameters change in proportion to the factor given previously: -0.3%/°C for operating frequency, +0.3%/°C for all other parameters. Consequently, this factor must be considered in designing a system which must operate at a given frequency over a wide temperature range.

THREE STATE LOGIC

Devices such as the 4016 and 4066 provide a means for constructing bus-oriented systems. Several devices in the 4000 Series employ variations in this structure to provide their own high-impedance output state. Leakage currents and capacitances are specified on individual data sheets, to allow the user to determine fan-out and system speed.

ANALOG SIGNAL SWITCHING

When using the analog switch device types, care must be taken to prevent the input signal from exceeding the supply voltage. Latch-up conditions may result if this precaution is not observed.

The ON-resistance characteristics of the switch are specified on the device data sheets. This enables the user to calculate power dissipation for high-current-drive requirements.

All CMOS switches are make-before-break. Therefore, in multiplexing applications, the low-impedance path between signal drivers which occurs during the overlap must be considered when generating control input signals.

Further information is contained on individual data sheets.

HANDLING CMOS DEVICES

Care must be exercised in handling any CMOS device. Although all SSS CMOS devices have a built-in protective diode network which protects the device against damage due to static electric discharge, additional precautions should be followed to assure trouble-free performance after assembly. The following guidelines for handling CMOS devices are suggested:

A. GENERAL

- Use a conductive, grounded work surface.
- Keep operators at ground potential (use conductive wrist bands and a 1 megohm resistor to ground)
- Don't use nylon smocks.
- Repack devices in conductive or anti-static containers; keep devices at a common potential.
- Use conductive or anti-static envelopes for storing and shipping devices — never use untreated plastic.

B. CLEANING

- Use static neutralizing ion blower when manually cleaning with brushes.

- Ground all automatic equipment.
- Ground cleaning baskets.

C. ASSEMBLY

- Insert CMOS devices last to avoid overhandling.
- Use conductive handling trays.
- Use conductive material between edge connections.
- Ground all automatic insertion equipment.
- Ground solder machines and metallic parts of conveyor systems.
- Ground soldering irons.

D. TESTING

- Use grounded metallic fixtures where possible.
- Use static neutralizing ion air blower when using automatic handlers.
- Use conductive handling trays.
- Don't insert or remove boards with power turned ON.

CMOS CHIPS

Solid State Scientific CMOS integrated circuits are provided in chip form to permit customer design of special or hybrid circuits to suit individual needs. CMOS chips are electrically identical to (temperature range -55°C to $+125^{\circ}\text{C}$) and offer the features of their packaged counterparts. For maximum ratings, electrical characteristics, schematics, and features, see the individual data sheets in this catalog.

CHIP PREPARATION

- All chips are glass passivated.
- All chips have been electrically tested for all static and functional parameters.
- Chip inspection and packaging is performed under laminar flow hoods in a temperature- and humidity-controlled dust-free atmosphere.

CHIP HANDLING



- Chips should be stored in a clean, dry atmosphere preferably below 40°C and 50% relative humidity.
- The user should exercise proper care when handling chips to prevent even the slightest mechanical damage to the chip.
- Individual handling should be done with nonmetallic vacuum pick-ups.

- Proper mounting and lead bonding techniques must be used to obtain optimum electrical, mechanical and thermal performance.
- The back surface of the chip is electrically connected to the P-channel substrates which should be the most positive potential (V_{int}). Care must be taken to keep the active substrate isolated from ground or other circuit elements in the assembly. It is recommended that the $+V_{\text{int}}$ pad on the front of the chip be wire bonded to the chip substrate mount for optimum performance.
- After mounting and bonding, necessary procedures must be followed to insure that the chips are not subjected to mechanical abuse or to moist or contaminated atmosphere which might permit electrical conductive paths across the relatively small insulating surfaces.
- Bonders, pick-up tools, table tops, sealing and die attach equipment, and other apparatus used in chip handling should be properly grounded.
- The operator should be properly grounded.
- Assemblies or sub-assemblies of chips should be transported and stored in conductive carriers.
- All external leads of assemblies should be shorted together.

Typical Package Outlines





14 Lead Cerdip*



| | MIN. | MAX. |
|----------------|-----------|------|
| A | — | .200 |
| A ₁ | .020 | — |
| B | .015 | .023 |
| B ₁ | .030 | .070 |
| C | .008 | .015 |
| D | .660 | .785 |
| E ₁ | .220 | .280 |
| e ₁ | .100 Typ. | — |
| e _A | .300 Typ. | — |
| L | .100 | — |
| α | 0° | 15° |
| Q ₁ | — | — |
| S | — | — |

*JEDEC drawing
#MO-001AA




16 Lead Cerdip*



| | MIN. | MAX. |
|----------------|-----------|------|
| A | .165 | .210 |
| A ₁ | .015 | .045 |
| B | .015 | .020 |
| B ₁ | .045 | .070 |
| C | .009 | .011 |
| D | .750 | .795 |
| E ₁ | .245 | .300 |
| e ₁ | .100 Typ. | — |
| e _A | .300 Typ. | — |
| L | .120 | .160 |
| α | 2° | 15° |
| Q ₁ | .050 | .080 |
| S | .010 | .060 |




*JEDEC drawing
#MO-001AG

18 Lead Cerdip



| | MIN. | MAX. |
|----------------|-----------|------|
| A | .165 | .202 |
| A ₁ | .015 | .040 |
| B | .015 | .020 |
| B ₁ | .053 | .065 |
| C | .008 | .012 |
| D | .870 | .923 |
| E ₁ | .258 | .306 |
| e ₁ | .100 Typ. | |
| e _A | .300 Typ. | |
| L | .120 | .155 |
| α | 4° | 15° |
| Q ₁ | — | — |
| S | .020 | .060 |



22 Lead Cerdip*



| | MIN. | MAX. |
|----------------|-----------|-------|
| A | .090 | .150 |
| A ₁ | .020 | .065 |
| B | .014 | .020 |
| B ₁ | .035 | .065 |
| C | .008 | .012 |
| D | 1.050 | 1.110 |
| E ₁ | .370 | .390 |
| e ₁ | .100 Typ. | |
| e _A | .400 Typ. | |
| L | .120 | .160 |
| α | 0° | 15° |
| Q ₁ | .010 | .050 |
| S | .035 | .060 |

*JEDEC drawing
#MO-026AA



24 Lead Cerdip*



| | MIN. | MAX. |
|----------------|-----------|-------|
| A | .120 | .250 |
| A ₁ | .020 | .070 |
| B | .016 | .020 |
| B ₁ | .028 | .070 |
| C | .008 | .012 |
| D | 1.200 | 1.290 |
| E ₁ | .515 | .580 |
| e ₁ | .100 Typ. | |
| e _A | .600 Typ | |
| L | .100 | .200 |
| α | 0° | 15° |
| Q ₁ | .040 | .075 |
| S | .040 | .100 |




*JEDEC drawing
#MO-015AA

28 Lead Cerdip



| | MIN. | MAX. |
|----------------|-------|-------|
| A | .164 | .219 |
| A ₁ | .020 | .070 |
| B | .016 | .020 |
| B ₁ | .050 | .060 |
| C | .008 | .012 |
| D | 1.430 | 1.485 |
| E ₁ | .510 | .541 |
| e ₁ | .090 | .110 |
| e _A | .600 | .620 |
| L | .120 | .155 |
| α | 4° | 20° |
| Q ₁ | — | — |
| S | .060 | .090 |




40 Lead Cerdip*



| | MIN. | MAX. |
|----------------|-----------|-------|
| A | .160 | .220 |
| A ₁ | .000 | .070 |
| B | .015 | .020 |
| B ₁ | .015 | .055 |
| C | .008 | .012 |
| D | 2.020 | 2.070 |
| E ₁ | .485 | .580 |
| e ₁ | .100 Typ. | |
| e _A | .600 Typ. | |
| L | .100 | .200 |
| α | 0° | 15° |
| Q ₁ | .070 | .120 |
| S | .060 | .090 |

*JEDEC drawing
MO-015AJ




14 Lead Plastic*



| | MIN. | MAX. |
|----------------|-----------|------|
| A | .140 | .180 |
| A ₁ | .015 | .040 |
| B | .014 | .020 |
| B ₁ | .044 | .070 |
| C | .008 | .012 |
| D | .730 | .770 |
| E ₁ | .240 | .260 |
| e ₁ | .100 Typ. | |
| e _A | .300 Typ. | |
| L | .115 | .155 |
| α | 0° | 15° |
| Q ₁ | .050 | .085 |
| S | .055 | .095 |

*JEDEC drawing
#MO-001AH




16 Lead Plastic*



| | MIN. | MAX. |
|----------------|-----------|------|
| A | .120 | .160 |
| A ₁ | .020 | .065 |
| B | .014 | .020 |
| B ₁ | .035 | .065 |
| C | .008 | .012 |
| D | .745 | .785 |
| E ₁ | .240 | .260 |
| e ₁ | .100 Typ. | |
| e _A | .300 Typ. | |
| L | .125 | .150 |
| α | 0° | 15° |
| Q ₁ | .050 | .085 |
| S | .015 | .060 |



*JEDEC drawing
#MO-001AE

18 Lead Plastic



| | MIN. | MAX. |
|----------------|------|------|
| A | .136 | .175 |
| A ₁ | .008 | .040 |
| B | .015 | .021 |
| B ₁ | .055 | .065 |
| C | .008 | .013 |
| D | .890 | .910 |
| E ₁ | .245 | .255 |
| e ₁ | .090 | .110 |
| e _A | .285 | .315 |
| L | .115 | .145 |
| α | 2° | 12° |
| Q ₁ | .060 | .079 |
| S | .040 | .070 |



22 Lead Plastic*



| | MIN. | MAX. |
|----------------|-----------|-------|
| A | .090 | .150 |
| A ₁ | .020 | .065 |
| B | .014 | .020 |
| B ₁ | .035 | .065 |
| C | .008 | .012 |
| D | 1.050 | 1.110 |
| E ₁ | .370 | .390 |
| e ₁ | .100 Typ. | |
| e _A | .400 Typ. | |
| L | .120 | .160 |
| α | 0° | 15° |
| Q ₁ | .010 | .050 |
| S | .035 | .060 |

*JEDEC drawing
#MO-026AA



24 Lead Plastic*



| | MIN. | MAX. |
|----------------|-----------|-------|
| A | .120 | .250 |
| A ₁ | .020 | .070 |
| B | .016 | .020 |
| B ₁ | .028 | .070 |
| C | .008 | .012 |
| D | 1.200 | 1.290 |
| E ₁ | .515 | .580 |
| e ₁ | .100 Typ. | |
| e _A | .600 Typ. | |
| L | .100 | .200 |
| α | 0° | 15° |
| Q ₁ | .040 | .075 |
| S | .040 | .100 |



*JEDEC drawing
#MO-015AA

28 Lead Plastic



| | MIN. | MAX. |
|----------------|-------|-------|
| A | .157 | .187 |
| A ₁ | — | .040 |
| B | .015 | .021 |
| B ₁ | .055 | .065 |
| C | .008 | .013 |
| D | 1.440 | 1.460 |
| E ₁ | .535 | .545 |
| e ₁ | .090 | .110 |
| e _A | .585 | .615 |
| L | .115 | .145 |
| α | 4° | 12° |
| Q ₁ | .070 | .084 |
| S | .060 | .090 |

40 Lead Plastic*




| | MIN. | MAX. |
|----------------|-----------|-------|
| A | .160 | .220 |
| A ₁ | .000 | .070 |
| B | .015 | .020 |
| B ₁ | .015 | .055 |
| C | .008 | .012 |
| D | 2.020 | 2.070 |
| E ₁ | .485 | .580 |
| e ₁ | .100 Typ. | |
| e _A | .600 Typ. | |
| L | .100 | .200 |
| α | 0° | 15° |
| Q ₁ | .070 | .120 |
| S | .060 | .090 |

*JEDEC drawing
#MO-015AJ

Ordering Information



ORDERING INFORMATION




PACKAGING INFORMATION


Devices in the 4000 Series are available in a variety of package types and temperature ranges. The single-letter package designator appears as a suffix to the device type.

| Designator SCL | Type | Style | No. of Pins | Temperature Range |
|-------------------|--|-----------------------|-------------|-------------------|
| C | Cerdip (Frit-Seal) | Dual-in-Line (DIP) | 14, 16, 24 | -55° C to +125° C |
| D | Ceramic (Welded-Seal or Side-Brazed) | Dual-in-Line (DIP) | 14, 16, 24 | -55° C to +125° C |
| E | Epoxy (Plastic) | Dual-in-Line (DIP) | 14, 16, 24 | -40° C to +85° C |
| H | Dice | — | — | -55° C to +125° C |

DEVICE MARKING



4000 Series High Reliability



Built-In Reliability

Reliability in MOS integrated circuits does not just happen—it must be built in. Built in through conservative designs, advanced wafer fabrication technology, and controlled by stringent in-process quality controls, inspections and tests. But there is more. Reliability is built in by people. At Solid State Scientific, dedicated people work with the latest technology producing MOS devices that meet the highest quality and reliability standards in the industry. SSS has proven its dedication to these high standards since 1968 when it was founded.


Solid State Scientific is a high volume manufacturer of MOS integrated circuits and offers a variety of high reliability options to meet customer requirements. Our facilities in Willow Grove, Pennsylvania have been certified by the Defense Electronics Supply Center for the production of Class B devices in accordance with MIL-M-38510.

In addition, regardless of product grade, Solid State Scientific has established definite minimum quality and reliability standards which apply across all product lines. All products are manufactured identically from incoming inspection through wafer probe of the die. Pre-seal visual inspection is performed in accordance with MIL-STD-883 level B. This same philosophy of ensuring the reliability of our products applies to environmental screening, final electrical testing and lot acceptance for packaged parts.

Integrated Circuit Reliability

CMOS integrated circuits exhibit the same basic reliability characteristics as other semi-

conductor devices in that the failure rate has three distinct phases. Within a relatively short time, certain failure mechanisms appear under moderate levels of stress. Failures which occur during this phase are called infant mortality failures. During infant mortality, the failure rate decreases dramatically. Then for a long period of time, infrequent random failures occur. Finally, device packages can actually wear out and the failure rate will increase again. For CMOS integrated circuits, there are only two significant wear-out mechanisms; electromigration and corrosion in plastic devices. Electromigration is a function of temperature and current density in the metallization and is influenced by the type of metal, grain structure and surface sealing. This phenomenon occurs in all package types. The other major wear-out mechanism is electrolytic corrosion of the die metallization which occurs in plastic packages. This



is a function of the package/passivation system and is influenced by the type of epoxy, the protective molding compound and chip glassivation materials. When the failure rate is plotted as a function of time, the result is the basic bathtub curve characteristic of all semiconductor devices. While the bathtub curve is universal throughout the IC industry, actual values can vary greatly from one manufacturer to another. Solid State Scientific has many years of experience in the manu-

facturing of CMOS integrated circuits, and our design rules and processing techniques have been developed to:

- minimize the infant mortality failure mechanisms.
- detect potential failures before they reach the customer.
- control wear-out so that operating life far exceeds the lifetime required by the customer.
- prevent defects from occurring at the earliest possible stage.

State-of-the-Art Device Development

Conservative Design Rules

At Solid State Scientific, rules for mask lay-out extend the operating life of the product far beyond normal usage. This reliability is a result of the following design considerations:

- Metal width and spacing controls in conjunction with stringent in-process controls eliminate electro-migration. MIL-M-38510 Level B specifications call for a maximum current density in glassivated pure aluminum stripes of 5×10^5 amps/cm². Solid State Scientific demands no more than 1.5×10^5 amps/cm². Also, an absolute minimum design width for any metal line is maintained for standard industrial devices.
- Strictly controlled element spacings and sizes are specified for:
 - all diffusion widths
 - distances between pad and scribe line for leakage protection
 - spacings between elements to prevent inversion
 - spacing between the boundary of a diffusion and the contact cut for the diffusion to prevent leakage.

- metal-to-metal and pad-to-pad spacings
- pad size to insure room for a good bond
- High voltage reverse biased diodes to both V_{SS} and V_{DD} in conjunction with series resistors to protect inputs from voltage transients and ESD.

Each wafer contains its own process control test cells. This special device measures all process and design parameters that have a significant effect on yield and reliability.

Controlled Wafer Processing

Reliability Assured Through Stringent Controls

At Solid State Scientific we have one of the most highly controlled wafer processing facilities in the industry. All MOS products are manufactured in the same fabrication facility using identical materials, technology, and MIL-M-38510 procedures and controls. All SSS products are processed on a fully approved MIL-M-38510

wafer line, whether destined for the commercial or military market.

Reliability is assured through:

- a special tapered oxide process that controls the edges of all cuts in the oxide to obtain a nominal 45° angle.
- planetary rotation during metal evaporation. This technique results in a controlled oxide step with uniform metal thickness. Failure due to electron migration is eliminated.

Product Assurance Program

Table 1—Processing and Screening requirements for MIL-STD-883, MIL-M-38510 and Standard products.

| | MIL-STD-883B Method In accordance with 5004 & 5005 | 883C4 XXX DESC Drawing MIL-STD-883B Class B | MIL-M-38510 Class B |
|--|---|--|---------------------------|
| Assembly | | | |
| Precap Visual (Cond. B) | 2010B | X | X |
| Preconditioning | | | |
| Seal & Lot Identification | | X | X |
| Stabilization Bake 24 hrs @ 150°C | 1008C | X | X |
| Temperature Cycle | 1010C | X | X |
| Centrifuge Y1 | 2001E | X | X |
| Fine Leak | 1014B | X | X |
| Gross Leak | 1014C | X | X |
| Test and Burn-In | | | |
| Initial Test | | X | X |
| Static Burn-In, 160 Hr. Min. or Equiv. | 1015 | X | X |
| Final Electrical 25°C, DC and Functional (A-1, A-7) | | X | X |
| Final Electrical AC 25°C (A-4, A-9) | | X | X |
| Final Electrical – 55°C DC and Functional (A-3, A-8) | | X | X** |
| Final Electrical AC – 55°C (A-6, A-11) | | — | X** |
| Final Electrical + 125°C DC and Functional (A-2, A-8b) | | X | X** |
| Final Electrical AC + 125°C (A-5, A-10) | | — | X** |
| External Visual | 2009 | X | X |

X = 100% Testing — = Not Required "(A-X)" are Subgroups

** + " product has 168 hours of static burn-in or equivalent.

**Subgroups A-5, A-6, A-8, A-8b, A-10 and A-11 are only performed when required by the detailed specification.

- an ion-implant operation to increase the P-channel thick field inversion voltage. This allows SSS to offer the cost effectiveness of a smaller chip while maintaining the same low leakage and high voltage characteristics found in guard ring construction.
- precision phosphorous doping of the glass passivation that prevents surface inversion during the life of the device. Passivation layer thickness is carefully chosen to provide full coverage over the tapered oxide steps. This means superior long term stability and added moisture protection at the die level.

- test cells and test transistors on every wafer are probed for twelve parameters prior to metal alloying and fourteen parameters at final wafer probe. Trends are monitored continuously and variations are detected immediately. Typical parameters measured are:

- threshold voltages of transistors
- breakdown voltages of transistors
- gate breakdown voltages
- transistor contact resistance
- metal strip fusing current

Our process controls are some of the most stringent in the

industry. Every lot undergoes 100% inspection after each and every mask level operation.

Sampling Inspection

Tables 2, 3, 4 and 5 illustrate the sample criteria used to insure an LTPD requirement for military product. Sample sizes are based on the Poisson exponential binominal limit in accordance with MIL-S-19500. The tables of subgroup tests demonstrate the level of quality conformance of Hi-Rel Military and Standard products.

Table 2—Group A Electrical Sampling Inspection for Class B High-Reliability CMOS Integrated Circuits per MIL-STD-883, Method 5005

| Subgroup | Test | Condition | LTPD Class B | 883C4 XXX DESC Drawing | |
|----------|-----------------------|------------------------------|--------------|---------------------------|---------------------|
| | | | | MIL-STD-883B Class B | MIL-M-38510 Class B |
| 1 | DC Static Parameters | $T_A = +25^{\circ}\text{C}$ | 2 | ✓ | ✓ |
| 2 | DC Static Parameters | $T_A = +125^{\circ}\text{C}$ | 3 | ✓ | ✓ |
| 3 | DC Static Parameters | $T_A = -55^{\circ}\text{C}$ | 5 | ✓ | ✓ |
| 4 | Dynamic Parameters | $T_A = +25^{\circ}\text{C}$ | 2 | ✓ | ✓ |
| 7 | Functional Parameters | $T_A = +25^{\circ}\text{C}$ | 2 | ✓ | ✓ |
| 9 | AC Parameters | $T_A = +25^{\circ}\text{C}$ | 2 | ✓ | ✓ |

Note: Performed on each inspection lot.

Table 3—Group B Sampling Inspection for Class B High-Reliability CMOS Integrated Circuits per MIL-STD-883, Method 5005

| Subgroup | Test | MIL-STD-883 Method & Condition | 883C4 XXX DESC Drawing | |
|----------|--------------------------------|---|---------------------------|---------------------|
| | | | MIL-STD-883B Class B | MIL-M-38510 Class B |
| 1 | Physical Dimension | 2016 — | ✓ | ✓ |
| 2 | Resistance to Solvents | 2015 — | ✓ | ✓ |
| 3 | Solderability | 2003 Soldering Temperature $245^{\circ}\text{C} \pm 5^{\circ}\text{C}$ | ✓ | ✓ |
| 4 | Internal Visual and Mechanical | 2014 — | ✓ | ✓ |
| 5 | Bond Strength | 2011 | ✓ | ✓ |
| 6 | Internal Water Vapor Content | 1018 — | ✓ | ✓ |
| 7 | Fine and Gross Leak | 1014B, 1014C — | ✓ | ✓ |
| 9 | V_{ZAP} | Per Detailed Specification | ✓ | ✓ |

Note: Performed on each package type and lead finish for each week of seal (date code).

Table 4—Group C Die-Related Tests for Class B High-Reliability CMOS Integrated Circuits per MIL-STD-883, Method 5005

| Subgroup | Test | MIL-STD-883 Method & Condition | 883C4 XXX DESC Drawing | |
|----------|-----------------------|--|---------------------------|------------------------|
| | | | MIL-STD-883B Class B | MIL-M-38510 Class B |
| 1 | Operating Life | 1005, $T_A = 125^\circ\text{C}$, 1000 hrs. or equiv. | ✓ | ✓ |
| | Electrical Parameters | As Specified | ✓ | ✓ |
| 2 | Temperature Cycling | 1010 Test Condition C | ✓ | ✓ |
| | Constant Acceleration | 2001 Test Condition E | ✓ | ✓ |
| | Fine Leak | 1014B — | ✓ | ✓ |
| | Gross Leak | 1014C — | ✓ | ✓ |
| | Visual Examination | 1010 or 1011 | ✓ | ✓ |
| | Electrical Parameters | As Specified | ✓ | ✓ |

Note: Performed every 13 weeks for each microcircuit group or as specified in the detailed drawing.

Table 5—Group D Package-Related Tests for High-Reliability CMOS Integrated Circuits per MIL-STD-883, Method 5005

| Subgroup | Test | MIL-STD-883 Method & Condition | 883C4 XXX DESC Drawing | |
|----------|---|---------------------------------------|---------------------------|------------------------|
| | | | MIL-STD-883B Class B | MIL-M-38510 Class B |
| 1 | Physical Dimensions | 2016 — | ✓ | ✓ |
| 2 | Lead Integrity | 2004 — | ✓ | ✓ |
| | Fine Leak | 1014B — | ✓ | ✓ |
| | Gross Leak | 1014C — | ✓ | ✓ |
| 3 | Thermal Shock | 1011 Test Condition B Min. | ✓ | ✓ |
| | Temperature Cycling | 1010 Test Condition C 100 cycles | ✓ | ✓ |
| | Moisture Resistance | 1004 — | ✓ | ✓ |
| | Fine Leak | 1014 Test Condition B | ✓ | ✓ |
| | Gross Leak | 1014 Test Condition C | ✓ | ✓ |
| | Visual Examination | Per Visual of Method 1004 and 1010 | ✓ | ✓ |
| | Electrical Parameters | As Specified | ✓ | ✓ |
| 4 | Mechanical Shock | 2002 Test Condition B | ✓ | ✓ |
| | Vibration, var. freq. Constant Acceleration, Y1 plane | 2007 Test Condition A | ✓ | ✓ |
| | Fine Leak | 2001 Test Condition E | ✓ | ✓ |
| | Gross Leak | 1014 Test Condition B | ✓ | ✓ |
| | Visual Examination | 1014 Test Condition C | ✓ | ✓ |
| | Electrical Parameters | 1010 or 1011 As Specified | ✓ | ✓ |
| 5 | Salt Atmosphere | 1009 Test Condition A | ✓ | ✓ |
| | Fine Leak | 1014B — | ✓ | ✓ |
| | Gross Leak | 1014C — | ✓ | ✓ |
| | Visual Examination | Per Visual of Method 1009 | ✓ | ✓ |
| 6 | Internal Water Vapor Content | 1018 5000ppm Max. | ✓ | ✓ |
| 7 | Adhesion of Lead Finish | 2025 As Applicable | ✓ | ✓ |
| 8 | Lid Torque | 2024 As Applicable | ✓ | ✓ |

Note: Performed every 26 weeks or as specified in the detailed drawing.

Summary

Solid State Scientific has extensive experience in all aspects of CMOS integrated circuit technology. This expertise dates back to 1968 with the design and development of custom CMOS devices for space applications. In 1970 SSS began manufacturing the 4000 Series standard circuits. Today, with more than a decade of CMOS experience, SSS is respected as a major supplier of a wide variety of CMOS products.

Over the years, our products have established a reputation for outstanding reliability in applications as varied as data processing, military and space systems, automotive, and timekeeping products. This quality and reliability results from a combination of:

- conservative design rules
- advanced wafer fabrication capabilities
- stringent in-process controls and inspection procedures


In addition, Solid State Scientific adds one more ingredient to every device; a company-wide dedication to customer satisfaction.

QPL Products

MIL-STD-883C Class B CMOS 4000 Series Products

CMOS 4000 Series devices are available in Cerdip (Frit-Seal) (C), Ceramic (Side-Brazed) (D) packages, and Dice (H).

Figure 1
MIL-STD-883C—Device Nomenclature




MIL-M-38510 Class B CMOS 4000 Series, QPL Accepted Product

Contact SSS Regional Sales Offices for the current listing of MIL-M-38510 Class B, QPL Accepted Products.

MIL-M-38510 CMOS 4000 Series devices are available in Ceramic (Side-Brazed) and Cerdip (Frit-Seal) packages.

Figure 2
MIL-M-38510—Device Nomenclature



MIL-M-38510 Package Type

| | |
|---|------------------------------------|
| C | 14-lead 1/4 x 3/4 DIP ¹ |
| E | 16-lead 1/4 x 7/8 DIP ¹ |

MIL-M-38510 Lead Finish¹

| | | | |
|---|----------------|---|------------|
| A | Hot Solder Dip | C | Gold Plate |
| B | Tin Plate | X | Optional |

1. Note: Hot Solder Dip and Tin Plate lead finishes are available in Cerdip (Frit-Seal) packages. Tin plate and gold lead finishes are available in Ceramic (Side-Brazed) packages. When ordering tin plate lead finishes, specify package preferred.

Notes

Notes

Notes

Solid State Scientific

Sales Offices

NORTH AMERICA

2444 Moorpark Avenue
San Jose, CA 95128
(408) 241-7111
TWX-910-997-0074

15010 Ventura Blvd.
Sherman Oaks, CA 91403
(213) 995-6666
TWX-910-495-1746

3395L N. Arlington Heights Rd.
Arlington Heights, IL 60004
(312) 255-3883
TWX-910-687-0270

12703 A. Research Blvd.
Austin, TX 78759
(512) 331-0778
TWX-910-997-6560

10 Dale Street
Waltham, MA 02154
(617) 891-7530
TWX-710-324-0321

3900 Welsh Road
Willow Grove, PA 19090
(215) 657-8400
TWX-510-661-7267

8001 N. Dale Mabry Hwy.
Building 501, Suite T
Tampa, FL 33614
(813) 935-8203
TWX-810-876-9120

EUROPE

3900 Welsh Road
Willow Grove, PA 19090
(215) 657-8400
TWX-510-661-7267
Telex-476-1101


FAR EAST

G.P.O.B. 4289
Hong Kong
Tel: 0-283188
Telex-43395 SPRAG HX

Solid State Scientific, Inc.

3900 Welsh Road Willow Grove, PA 19090
(215) 657-8400

TWX-510-661-7267 Telex-476-1101



Printed in U.S.A. 4SCL108425